

init

free

Accessing the font setFont:

font

Setting the delegate setDelegate:

Displaying and editing drawFieldAt::inside:inView:withAttributes::

usePositions::

editFieldAt::inside:inView:withAttributes::

usePositions::onEvent:

endEditing

abortEditing

Archiving read:

write:

abortEditing

Forces an end to editing, discarding any changes the user may have made. Returns self.

endEditing

drawFieldAt:(unsigned int)rowIndex
:(unsigned int)columnIndex
inside:(NXRect *)frameRect
inView:aView
withAttributes:(id <NXTableVectors>)rowAttributes
:(id <NXTableVectors>)columnAttributes
usePositions:(BOOL)rowPosFlag
:(BOOL)columnPosFlag

:(unsigned int)columnIndex
inside:(NXRect *)frameRect
inView:aView
withAttributes:(id <NXTableVectors>)rowAttributes
:(id <NXTableVectors>)columnAttributes
usePositions:(BOOL)rowPosFlag
:(BOOL)columnPosFlag
onEvent:(NXEvent *)theEvent

Begins an editing session for the field of aView identified by rowIndex and columnIndex. You never directly invoke this method; it's invoked automatically by the NXTableView when a field needs to be edited. When editing ends, the receiver sends formatterDidEndEditing: to aView (this method is described in the NXFormatter class specification).

Returns YES if the field is successfully edited, NO otherwise (for example, if aView can't be made editable).

endEditing, abortEditing, drawFieldAt::inside:inView:withAttributes::usePositions::

(BOOL)endEditing

Finishes editing in the field indicated by an editFieldAt::... message, typically when the user presses the return key or clicks in another field (thereby indicating that editing in the receiver is complete). Returns YES if successful, NO otherwise.

abortEditing

font

Returns the Font object used for drawing text.

free

Releases the storage for the NXEditableFormatter and returns nil.

init

Initializes a newly allocated NXEditableFormatter, setting the font to the user's default font at a designated initializer for the NXEditableFormatter class. Returns self.

read:(NXTypedStream *)stream

Reads the NXEditableFormatter from the typed stream stream. Returns self.

messages for formatters are described in the NXFormatterValidation informal protocol specification
delegate (NXFormatter)

write:(NXTypedStream *)stream

Writes the NXTextFormatter to the typed stream stream.