

formatterWillChangeValueFor::sender:

formatterWillChangeValueFor::to:sender:

formatterDidChangeValueFor::to:sender:

Notification by position formatterWillChangeValueFor:at:sender:

formatterWillChangeValueFor:at:to:sender:

formatterDidChangeValueFor:at:to:sender:

formatterDidChangeValueFor:rowIdentifier
:columnIdentifier
to:aValue
sender:sender

Notifies the receiver that sender, an editable NXFormatter, has changed the value identified by rowIdentifier and columnIdentifier to aValue (an NXTableValue object). Returns self.

This method is only invoked when the field to be edited was specified by identifier only (that is, when both axes of the NXTableView are static). A delegate that implements this method should also implement formatterDidChangeValueFor:at:to:sender: to be notified when a field is specified by position.

formatterDidChangeValueFor:identifier
at:(unsigned int)position
to:aValue
sender:sender

Notifies the receiver that sender, an editable NXFormatter, has changed the value at position in the static axis identified by identifier to aValue (an NXTableValue object). Returns self.

This method is only invoked when the field to be edited was specified by position. A delegate that implements this method should also implement formatterDidChangeValueFor::to:sender: to be notified when a field is specified by identifier.

(BOOL)formatterWillChangeValueFor:rowIdentifier
:columnIdentifier
sender:sender

Notifies the receiver that sender, an editable NXFormatter, is about to edit the value at rowIdentifier and columnIdentifier

at:(unsigned int)position
sender:sender

Informs the receiver that sender, an editable NXFormatter, is about to edit the value at position in t by identifier (an NXTableValue object). If the delegate returns YES the formatter goes on to edit t returns NO the formatter disallows editing.

This method is only invoked when the field to be edited was specified by position. A delegate that method should also implement formatterWillChangeValueFor::sender: to be notified when a field identifier.

(BOOL)formatterWillChangeValueFor:identifier
at:(unsigned int)position
to:aValue
sender:sender

Informs the receiver that sender, an editable NXFormatter, is about to change the value at position identified by identifier to aValue (an NXTableValue object). If the delegate returns YES the change formatter ends editing if the delegate returns NO the formatter doesn't end editing, requiring the user value.

This method is only invoked when the field to be edited was specified by position. A delegate that method should also implement formatterWillChangeValueFor::to:sender: to be notified when a field identifier.

(BOOL)formatterWillChangeValueFor:rowIdentifier
:columnIdentifier
to:aValue
sender:sender

Informs the receiver that sender, an editable NXFormatter, is about to change the value identified by columnIdentifier to aValue (an NXTableValue object). If the delegate returns YES the change is made ends editing if the delegate returns NO the formatter doesn't end editing, requiring the user to enter

This method is only invoked when the field to be edited was specified by identifier only. A delegate that method should also implement formatterWillChangeValueFor:at:to:sender: to be notified when a field position.