

getValueFor:identifier at:(unsigned int)position into:aValue

rowCount

columnCount

Getting/setting data
getValueFor:at:into:
getValueFor::into:
setValueFor:at:from:
setValueFor::from:

(unsigned int)columnCount

Returns the number of columns in the data source. If the data source is set up for a static column this is 1 if it's set up for a static row, this is the number of records in the data source.

rowCount

getValueFor:rowIdentifier
:columnIdentifier
into:aValue

Copies the value of an attribute from the data source into the object aValue (an object conforming to the NXTableValue protocol). The record value to retrieve is specified by the property identifiers rowIdentifier and columnIdentifier, and not by position. Returns self.

Specifying record values by identifier and not position is useful when you don't want to depend on an array-like ordering

Copies the value of an attribute from the data source into the object aValue (an object conforming to NXTableValue protocol). The record value to retrieve is specified by the property identifier identifier and by aPosition within the data source for the value. Returns self.

getValueFor::into:

(unsigned int)rowCount

Returns the number of rows in the data source. If the data source is set up for a static row this is 1. If the data source is set up for a dynamic row, this is the number of records in the data source.

columnCount

setValueFor:rowIdentifier
:columnIdentifier
from:aValue

Sets the value of a record's attribute in the data source to the value contained in aValue (an object conforming to NXTableValue protocol). The record value to modify is specified by the property identifiers rowIdentifier and columnIdentifier, which gives the index within the data source for the value. Returns self.

Specifying record values by identifier and not position is useful when you don't want to depend on the order of records. For example, a data source can use rowIdentifier as a primary key for its records and columnIdentifier as a property identifier.

setValueFor:at:from:

setValueFor:identifier
at:(unsigned int)aPosition
from:aValue

Sets the value of a record's attribute in the data source to the value contained in aValue (an object conforming to NXTableValue protocol). The record value to modify is specified by the property identifier identifier and aPosition, which gives the index within the data source for the value. Returns self.

setValueFor::from: