


```

initWithEntity:qualifierFormat:
Combining qualifiers conjoinWithQualifier:
disjoinWithQualifier:
negate
Getting the entity entity
Checking the definition isEmpty
Setting distinct selection setUsesDistinct:
usesDistinct

```

destinationEntity (EORelationship)

destinationEntity (EORelationship)

```
(void)conjoinWithQualifier:(EOQualifier *)aQualifier
```

Replaces the contents of the receiver with the conjunction (logical AND) of the existing contents and the new qualifier. For example, this code excerpt creates a qualifier that selects employees whose salaries are between 40,000 and 50,000:

departments:

(EOEntity *)entity

Returns the entity that defines the context for attributes and relationships. Any attribute named in the format string must belong to this entity, and data paths must begin with a relationship defined in this entity.

initWithEntity:(EOEntity *)anEntity qualifierFormat:(NSString *)format, ...

Initializes a newly allocated EOQualifier to be rooted in anEntity and to build itself from a format string using a printf()-style format string as presented in the class description. This is the designated initializer for the class. Returns self if format is successfully parsed, nil otherwise.

(BOOL)isEmpty

Returns YES if the receiver selects all rows for its entity (that is, if it has no qualifying information). Returns NO otherwise.

(void)negate

Negates the receiver's qualifying information.

(void)setUsesDistinct:(BOOL)flag

Sets according to flag whether the receiver eliminates duplicates from the results of a select operation. If the flag is YES, a qualifier that uses distinct results eliminates all but one row. If the flag is NO, one row is retrieved.

