

Addresses;¬Addresses

converse-addr.tiff ¬

The "**Addresses**" window controls a list of user information. This list is used to send messages to specific user's on a given machine. This window can be brought up from the Tools menu or with command-A.

UserAddresses;¬The **User Addresses** browser contains a list of machines to send messages. The list can be saved and loaded from the Address Menu or with command keys. Entries are added from the **machine name** field with the **add** button, and removed by selecting an entry and using the **remove** button.

MachineName;¬The **machine name** field is where you type in the HostMachine Name that you will want to add to the Address List. Press "enter" to add the machine to the Address List. When a message is received, the sender's machine name will be placed into the **machine name** field. This simplifies adding new users and responding to messages.

The **add** button will take the text entered into machine name and add it to the list of "User Addresses".

The **remove** button will remove the entry that is selected within the "User Addresses" browser.

UpdateSend;¬Checking the "**Update Addresses when Send**" box will cause the User's address information to be retrieved when a message is sent to them. Otherwise, the information is not retrieved.

Unique;¬Checking the "**Only Add Unique Machine Addresses**" box will ensure that only unique machine name addresses are added to the UserAddress list. Otherwise, duplicate machine name addresses can be added.

Add;¬Adding an Address

Enter the user's machine address into the machine field, then press the "enter" key.

Remove;¬Removing an Address

Select the user address to remove, then click on the **remove** button.

This can be done in one step by double-clicking on the user address.

See Also:

;LogInput.rtf;LogInput;↵	Message Log/Input
;Preferences.rtf;Preferences;↵	Preferences
;SendMsg.rtf;SendMsg;↵	Sending Messages