Name

mmove - move or rename an MSDOS file or subdirectory

Note

This manpage has been automatically generated from mtools's texinfo documentation. However, this process is only approximative, and some items, such as crossreferences, footnotes and indices are lost in this translation process. Indeed, this items have no appropriate representation in the manpage format. Moreover, only the items specific to each command have been translated, and the general information about mtools has been dropped in the manpage version. Thus I strongly advise you to use the original texinfo doc.

* To generate a printable copy from the texinfo doc, run the following commands:

  ./configure; make dvi; dvips mtools.dvi

* To generate a html copy, run:

  ./configure; make html

  A premade html can be found at: `'http://linux.wauug.org/pub/knaff/mtools'`

* To generate an info copy (browsable using emacs' info mode), run:

  ./configure; make info

The texinfo doc looks most pretty when printed or as html. Indeed, in the info version certain examples are difficult to read due to the quoting conventions used in info.

Description

The `mmove` command is used to moves or renames an existing MS-DOS file or subdirectory. `mmove` [`-voOsSrRA`] *sourcefile targetfile* `mmove` [`-voOsSrRA`] *sourcefile* [*sourcefiles...*] *targetdirectory*

`Mmove` moves or renames an existing MS-DOS file or subdirectory. Unlike the MS-DOS version of `MOVE`, `mmove` is able to move subdirectories.

See Also

Mtools' texinfo doc