

---

## List of Examples

<b>Example 1-1</b>	Using systune to Check Address Space Limits	7
<b>Example 1-2</b>	Function to Lock Maximum Stack Size	25
<b>Example 2-1</b>	Initializing a Shared Memory Arena	37
<b>Example 2-2</b>	Setting Up an Arena with uscasinfo()	41
<b>Example 2-3</b>	Resigning From an Arena	44
<b>Example 2-4</b>	msgget() System Call Example	58
<b>Example 2-5</b>	msgctl() System Call Example	62
<b>Example 2-6</b>	msgsnd() and msgrcv() System Call Example	71
<b>Example 2-7</b>	semget() System Call Example	84
<b>Example 2-8</b>	semctl() System Call Example	91
<b>Example 2-9</b>	semop() System Call Example	98
<b>Example 2-10</b>	shmget() System Call Example	108
<b>Example 2-11</b>	shmctl() System Call Example	113
<b>Example 2-12</b>	shmat() and shmdt() System Call Example	118
<b>Example 3-1</b>	Partial Code to Manage a Pool of Processes	139
<b>Example 4-1</b>	Opening a File for Locked Use	151
<b>Example 4-2</b>	Setting a Whole-File Lock With fcntl()	152
<b>Example 4-3</b>	Setting a Whole-File Lock With lockf()	153
<b>Example 4-4</b>	Record Locking With Promotion Using fcntl()	155
<b>Example 4-5</b>	Record Locking Using lockf()	157
<b>Example 4-6</b>	Detecting Contending Locks Using fcntl()	159
<b>Example 4-7</b>	Testing for Contending Lock Using lockf()	160
<b>Example 4-8</b>	Setting Mandatory Locking Permission Bits	162

<b>Example 6-1</b>	Find Number of Bytes in an MB Character	208
<b>Example 6-2</b>	Counting MB Characters Without Conversion	209
<b>Example 6-3</b>	Reading an XPG/4 Catalog	230
<b>Example 6-4</b>	Internationalized Code	239
<b>Example 6-5</b>	Initializing Xlib for a Locale	242
<b>Example 6-6</b>	Creating a Fontset	244
<b>Example 6-7</b>	Opening an IM	253
<b>Example 6-8</b>	Finding What a Client Can Do	258
<b>Example 6-9</b>	Setting the Desired IM Style	258
<b>Example 6-10</b>	Creating an Input Context With XCreateIC()	261
<b>Example 6-11</b>	Using the IC	261
<b>Example 6-12</b>	Event Loop	262
<b>Example 6-13</b>	<i>KeyPress</i> Event	264