# List of Examples


**Example 1-1** Using systune to Check Address Space Limits 7
**Example 1-2** Function to Lock Maximum Stack Size 25
**Example 2-1** Initializing a Shared Memory Arena 37
**Example 2-2** Setting Up an Arena with uscasinfo() 41
**Example 2-3** Resigning From an Arena 44
**Example 2-4** msgget() System Call Example 58
**Example 2-5** msgctl() System Call Example 62
**Example 2-6** msgsnd() and msgrcv() System Call Example 71
**Example 2-7** semget() System Call Example 84
**Example 2-8** semctl() System Call Example 91
**Example 2-9** semop() System Call Example 98
**Example 2-10** shmget() System Call Example 108
**Example 2-11** shmctl() System Call Example 113
**Example 2-12** shmat() and shmdt() System Call Example 118
**Example 3-1** Partial Code to Manage a Pool of Processes 139
**Example 4-1** Opening a File for Locked Use 151
**Example 4-2** Setting a Whole-File Lock With fcntl() 152
**Example 4-3** Setting a Whole-File Lock With lockf() 153
**Example 4-4** Record Locking With Promotion Using fcntl() 155
**Example 4-5** Record Locking Using lockf() 157
**Example 4-6** Detecting Contending Locks Using fcntl() 159
**Example 4-7** Testing for Contending Lock Using lockf() 160
**Example 4-8** Setting Mandatory Locking Permission Bits 162

**Example 6-1** Find Number of Bytes in an MB Character 208
**Example 6-2** Counting MB Characters Without Conversion 209
**Example 6-3** Reading an XPG/4 Catalog 230
**Example 6-4** Internationalized Code 239
**Example 6-5** Initializing Xlib for a Locale 242
**Example 6-6** Creating a Fontset 244
**Example 6-7** Opening an IM 253
**Example 6-8** Finding What a Client Can Do 258
**Example 6-9** Setting the Desired IM Style 258
**Example 6-10** Creating an Input Context With XCreateIC() 261
**Example 6-11** Using the IC 261
**Example 6-12** Event Loop 262
**Example 6-13** *KeyPress* Event 264