



NWS Linux Implementation

Barry C. West Chief Information Officer



Internet/Web



- Apache is used on all webfarms
- Most webfarm administrators use linux workstations and many open source tools to manage the webfarms
- MRTG is used to monitor system and network status
- NWS operates six linux based webfarms capable of handling 100 million hits per day



Internet/Web



- OpenSSL and ssh are widely used to manage the NWS webfarms and support secure communication between them
- Rsync is widely used to move data between servers and the webfarms
- Linux virtual server is used to handle failover of data servers and load balancing between web servers



AWIPS Linux Migration



- Objectives
 - Replace approximately 300 HP Communications Processors with Linux Servers (complete)
 - Add approximately 140 High Availability Linux Clusters to NWS field forecast offices (complete)
 - Drastically improve AWIPS system performance
 - Replace nearly 900 HP-UX graphics workstations with Linux workstations (nearly complete)
 - Replace approximately 900 HP X-Terminals
 - Replace 550 aging HP-UX High Availability Servers
 - Institute a 3 yr. Hardware replacement cycle -- Take advantage of Moore's Law



Motivation for Linux Evolution



- Workstation (WS) performance problems at individual sites during severe weather
- High resolution IFPS/GFE operations
- Data Server (DS) performance problems
- Projected increases in the volume and resolution of data and information the system must receive, process, display, and transmit
- Some hardware components are approaching End of Life (EOL) thresholds
- AWIPS Hardware Maintenance Costs (>5M/yr.)
- Intel platforms running Linux are cost effective



PHASE I LINUX PERFORMANCE METRIC IMPROVEMENT



| | (Old Baseline) HP WS (100 Mbps) | Linux WS (10 Mbps LAN) | Linux WS (100 Mbps LAN) | (Phase II step 1) ** Linux WS, PP, & CP |
|------------|------------------------------------|---------------------------|----------------------------|---|
| T (secs) * | 247 Sec. | 174 Sec. | 127 Sec. | 62 Sec. |
| CPU | 71.6 %. | 13.2 % | 16.1 % | 13.1 % |

* "T" above is the total time required to run a series of scripted "Autotests" which perform meteorological actions such as loading various loops of model, satellite, radar, and observational data, in multiple panes simulating severe WX workstation ops.

** From Testing on the NHDA system conducted on 9/9/03 after Linux WS Mod Kit installation






- Develop Target Architecture that builds on investments made in Phase I
- Look at projected demand for computing resources, and bandwidth required for AWIPS over the next 10 years
- Add system resources (MFLOPS, MBPS, etc) to architecture to meet projected demand
- Change AWIPS Maintenance Philosophy to support a 3 year refresh cycle partially funded by hardware maintenance savings reaching \$5M/Yr in FY-08
- With a 3 year refresh cycle, Moore's Law will assure an exponential growth in site computer power to keep up with exponential growth in data volume



AWIPS Linux Workstation Architecture







AWIPS Linux Pre-Processor Architecture



