

## HTTP State Management Mechanism (Errata)

### Status of this Memo

This document is an Internet-Draft. Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

To learn the current status of any Internet-Draft, please check the "lid-abstracts.txt" listing contained in the Internet-Drafts Shadow Directories on ftp.is.co.za (Africa), nic.nordu.net (Europe), munnari.oz.au (Pacific Rim), ds.internic.net (US East Coast), or ftp.isi.edu (US West Coast).

This is author's draft 1.9.

### 1. ABSTRACT

This document contains miscellaneous small wording changes and clarifications to draft-ietf-http-state-mgmt-05, the HTTP State Management Mechanism draft.

### 2. PROPOSED CHANGES

Changes are referenced to the sections in the original document. New or changed text is shown in []'s.

#### 4.2.2 Set-Cookie Syntax

Under the heading: `Comment=comment`:

"Optional. Because cookies can contain private information about a user, the [Comment] attribute allows an origin server to document its intended use of a cookie...."

Under the heading: `Secure`:

"Optional. The `Secure` attribute (with no value) directs the user agent to use only (unspecified) secure means to contact the origin server whenever it sends back this cookie[, to protect the confidentiality and authenticity of the information in the cookie]."

#### 4.2.3 Controlling Caching

The directive `max-age=0` is necessary in the `Cache-Control` header to force revalidation. Therefore, two example headers must change.

The example header in the second bullet should read `Cache-Control: must-revalidate[, max-age=0]`.

The example header in the third bullet should read `Cache-Control: proxy-revalidate[, max-age=0]`.

#### 4.3.2 Rejecting Cookies

"To prevent possible security or privacy violations, a user agent rejects a cookie (shall not store its information) if any of the following is true [of the attributes explicitly present in the Set-Cookie response header]:..."

## 10.2 Compatibility with Microsoft's Implementation

[Insert new section between current sections 10.1 and 10.2.]

“Microsoft Internet Explorer (MSIE) Version 3 and earlier will fail to handle some cookies that use this specification. For example, if a server sends the following response header to MSIE V3 (omitting the line breaks):

```
Set-cookie: xx="1=2&3-4";  
            Comment="blah";  
            Version=1; Max-Age=15552000; Path=/  
            Expires=Sun, 27 Apr 1997 01:16:23 GMT
```

then MSIE V3 will send something like the following request header next time:

```
Cookie: Max-Age=15552000
```

instead of the correct

```
Cookie: xx="1=2&3-4"
```

In other words, MSIE sends back the wrong cookie name and value.”

### 3. ACKNOWLEDGEMENTS

The following people identified problems and/or suggested improvements in draft-ietf-http-state-mgmt-05: Anselm Baird Smith (reported by Koen Holtman), Jason Catlett, Martijn Koster (reported by Koen Holtman), Raymie Stata.

### 4. AUTHOR'S ADDRESS

David M. Kristol  
Bell Laboratories, Lucent Technologies  
600 Mountain Ave. Room 2A-227  
Murray Hill, NJ 07974

Phone: (908) 582-2250  
FAX: (908) 582-5809  
Email: dmk@bell-labs.com

Expires August 3, 1997