

Representing IP Information in the X.500 Directory

Thomas Johannsen (Dresden University)
Glenn Mansfield (AIC Systems Lab.)
Mark Kosters (Network Solutions)
Srinivas Sataluri (AT&T Bell Laboratories)

September 1993

Draft document OSI-DS-38-02

Status of this Memo

This document is an Internet Draft. Internet Drafts are working documents of the Internet Engineering Task Force (IETF), its Areas, and its Working Groups. Note that other groups may also distribute working documents as Internet Drafts.

Internet Drafts are draft documents valid for a maximum of six months. Internet Drafts may be updated, replaced, or obsoleted by other documents at any time. It is not appropriate to use Internet Drafts as reference material or to cite them other than as a "working draft" or "work in progress."

To learn the current status of any Internet-Draft, please check the `lid-abstracts.txt` listing contained in the Internet-Drafts Shadow Directories on `ds.internic.net`, `nic.nordu.net`, `ftp.nisc.sri.com`, or `munari.oz.au`.

Abstract

This document describes the objects necessary to include information about IP networks and IP numbers in the X.500 Directory. It extends the work "Charting networks in the Directory" [ND] where a general framework is presented for representing networks in the Directory by applying it to IP networks. This application of the Directory is intended to support the work of IP network assigning authorities, NICs, as well as other applications looking for a mapping of IP numbers to data of related networks. Furthermore, Autonomous Systems and related routing policy

information can be represented in the Directory along with their relationship to networks and organizations.

Contents

1	Introduction	5
2	IP images of networks	6
2.1	IP network image	6
2.2	IP node image	8
2.3	IP network interface image	9
2.4	Autonomous Systems	10
3	Number assignment information	11
3.1	Delegated Block object	12
3.2	IP Group object	12
3.3	IP Reference object	13
3.4	AS block object	14
3.5	AS reference object	14
4	Directory tree	15
4.1	IP image objects	15
4.2	AS objects	15
4.3	Namespace objects	15
4.4	Relationship to organizational entries	17
5	Security Considerations	18
6	Author's Addresses	19
	References	19

1 Introduction

Information related to the Internet Network Infrastructure is created and stored by a number of different organizations, such as the Internet Assigned Numbers Authority (IANA), Internet Registry (IR), Network Information Centers (NICs), and the NSFNET Network Operations Center (NOC). This information is generally "mastered" (stored and maintained) by these organizations on a centralized basis, i.e. there is a single place to look for a definitive list of entries for these categories. This has worked well in the past but given the tremendous growth of the Internet and its number of users and networks, it is essential that a distributed schema be used.

The X.500 Directory offers the appropriate technology for implementing this distributed method of managing network infrastructure information.

The following goals are addressed in this document:

1. Provision of IP specific images of network elements
2. Mapping from Network Number to network, owner, provider etc.
3. Support of delegation of IP address blocks
4. Storage of high-level routing policies and AS information
5. Support of "classless" network address formats
6. Provision of several organizational images of a network

It may be noted that the document basically consists of two parts. In the first part, an IP specific extension of the general framework "Charting networks in the Directory" [ND] is given. Objects defined by the application of this framework are related to IP numbers. An IP namespace is defined in the second part of this paper, referring to IP network elements defined at the beginning.

2 IP images of networks

As defined in [ND], networks are modelled as a set of subnetworks and nodes, called network elements in the remainder. To obtain a particular view of a network element, images were introduced. Below, images of network elements for an IP specific view are defined. Please note that images contain references to underlying physical information about elements.

In the remainder, `ipStringSyntax` is used as attribute type for all attributes that are to hold an IP number. Currently, there are two definitions for a syntax like this:

1. `IpAddress` as of RFC1155
2. `ip` as of RFC1278

It is suggested to use `CaseIgnoreStringSyntax` for implementations for the time being with the convention to use the ordinary IP syntax. Nevertheless, an OID has been reserved for `ipStringSyntax` (see appendix).

2.1 IP network image

IP network image is one application of network images and therefore inherits the `networkImageClass`. This class is given below for reference only, its definition can be found in [ND].

```
networkImage OBJECT CLASS
  SUBCLASS of ImageCommunicationObject
  MAY CONTAIN {
    externalGateway :: distinguishedNameSyntax,
                      /* points to one or more nodes that act
                       as gateway for the protocol application
                       this image refers to */
  }
```

An IP network combines all network elements that have a common IP network number. Presently, IP network numbers fall into one of the classes A, B, or C. However, sub- and supernetworking is already done broadly, and classless networks numbers are expected to be assigned soon. [RFC 1466] proposes to assign bitwise contiguous blocks of class-C-addresses to all networks with more than 255 nodes. The definition of IP network, therefore, is always related to common network number and network mask.

IP networks have a very close relationship to the Domain Name System. Several attributes are introduced to take care of these relations. Though we do not intend to abolish the existing DNS service, the schema defined here is able to provide the mapping IP number to domain name and vice versa.

An IP network image object as defined below is intended to provide technical and administrative data for one IP network. Attributes hold information that a NIC-WHOIS server would reveal for the network, and more.

```
ipNetworkImage OBJECT CLASS
  SUBCLASS of NetworkImage
  MUST CONTAIN {
    ipNetworkImageName :: CaseIgnoreString,
      /* common name */
    ipNwNumber :: IPStringSyntax,
      /* the IP network number for
      this (sub)network */
    ipNwMask :: IPStringSyntax
      /* mask that applies to ipNwNumber
      in order to define classless
      network number; also used for routing */
  }
  MAY CONTAIN {
    /* DNS related info ; e.g. - */
    associatedDomain :: CaseIgnoreStringSyntax,
      /* the domain name associated to this IP network;
      As there is not always a 1:1 mapping between traditional
      IP numbers and domain names, the name given here
      should contain the "closest match".
      1) (sub)network does not have a domain name
      of its own, but is part of a bigger domain:
      take name of that domain
      2) network is divided into several domains,
      therefore having more than one domain name:
      list all of them.
      Note: a reverse mapping of domain names to
      networks/nodes can be achieved by a modified
      implementation of RFC1279 */
    inAddrServer :: DistinguishedNameSyntax,
      /* refers to the ipNodeImageObject of the
      inaddr Server that holds information about
      this network */
    /* routing policy; e.g. - */
    asNumber :: integerStringSyntax,
      /* number of Autonomous System this network belongs to */
    acceptedUsagePolicy :: caseIgnoreStringSyntax,
      /* semantics to be defined */
    /* Any other - */
  }
```

```

provider :: DistinguishedNameSyntax,
          /* points to network provider */
onlineDate :: uTCTimeSyntax
          /* date when network got connected to the Internet */
}

```

2.2 IP node image

If a node in the network is running the IP protocol, an `ipNodeImageObject` should be created for this node. This image is a subclass of `nodeImageClass` and holds IP specific information. The `nodeImageClass` is given below for reference only, its definition can be found in [ND].

```

nodeImage OBJECT CLASS
  SUBCLASS of ImageCommunicationObject
          /* no attributes common for all nodeImages have been
          defined yet */

```

An `ipNodeImage` is used to obtain technical and administrative information on a host. The object is defined as follows:

```

ipNodeImage OBJECT CLASS
  SUBCLASS of NodeImage
  MUST CONTAIN {
    ipNodeName :: CaseIgnoreString
                /* common name, it is advised to use
                the hostname for this purpose */
  MAY CONTAIN {
    protocol :: CaseIgnoreString,
              /* name and version of IP protocol running */
    domainName :: CaseIgnoreString,
              /* the complete domain name of this node;
              CNAMEs can be stored additionally to the
              DNS A record name;
              further relationships, like MX record entries,
              should be taken care of by the domain name tree
              according to RFC 1279 */
  }
}

```


2.3 IP network interface image

The most important IP related information of a node (its IP addresses) is registered with `ipNetworkInterfaceImageObjects`. This picture is accurate as a node can have several IP addresses, but at most one per interface. Furthermore, it shows clearly the relationship between interface and neighboring IP network.

`IpNetworkInterfaceImage` is a subclass of `networkInterfaceImageClass`. The `networkInterfaceImageClass` is given below for reference only, its definition can be found in [ND]. Note that for `ipNetworkInterfaceImage` all references are drawn in the context of IP, i.e. `networkInterfaceAddress` becomes an IP address and `connectedNetwork` points to an `ipNetworkImageObject`.

```
networkInterfaceImage OBJECT CLASS
  SUBCLASS of ImageCommunicationObject
  MAY CONTAIN {
    networkInterfaceAddress :: caseIgnoreStringSyntax,
      /* this interfaces address in the context the
      image referes to, e.g. IP number, NSAP */
    connectedNetwork :: distinguishedNameSyntax
      /* pointer to networkImageObject that describes
      the network this interface is attached to in terms
      of the protocol or application the images
      indicates */
  }
```

Additionally, `ipNetworkInterfaceImageObject` has the following properties:

```
ipNetworkInterfaceImage OBJECT CLASS
  SUBCLASS of NetworkInterfaceImage
  MUST CONTAIN {
    ipNetworkInterfaceName :: CaseIgnoreStringSyntax
      /* It is suggested that the interface name
      is derived from the name of the logical
      device this interface represents for the
      operating system, e.g. le0, COM1 */
  MAY CONTAIN {
    ipNwMask :: IPStringSyntax
      /* mask that applies to networkInterfaceAddress for
      routing of packets to nodes on the connected
      (broadcast) network;
      Note: This is only a fraction
      of the routing table information
      for this interface, namely for one hop. */
```

```
}

```

2.4 Autonomous Systems

Autonomous Systems (AS) are defined in `asObject` which is a subclass of `imageCommunicationObject`. It provides technical and administrative information of an AS. Furthermore, routing policies can be stored with the AS object. The definition of the AS object is aligned with the corresponding database object defined in [RIPE-81].

```
as OBJECT CLASS
  SUBCLASS of ImageCommunicationObject
  MUST CONTAIN {
    asNumber :: IntegerStringSyntax
  }
  MAY CONTAIN {
    asName :: CaseIgnoreStringSyntax,
      /* if there is a name different from AS XXXXX */
    asIn :: CaseIgnoreStringSyntax,
      /* accepted routes from other AS */
      /* for syntax and semantics refer [RIPE-81] */
    asOut :: CaseIgnoreStringSyntax,
      /* generated routes announced to others */
      /* for syntax and semantics refer [RIPE-81] */
    asDefault :: CaseIgnoreStringSyntax,
      /* how default routing is handled */
      /* for syntax and semantics refer [RIPE-81] */
    asGuardian :: DistinguishedNameSyntax, /*
      /* DN of guardian of this AS */
    lastModifiedTime :: UTCtimeSyntax /*
      /* important as routes change frequently */
  }

```

Note that routing policies for an Autonomous System are represented by the `{asIn, asOut}` attributes of `asObject`. Due to performance constraints of present X.500 technology, it will probably not be used directly by routers for dynamic routing. However, it certainly can be used in network management systems to determine the allowed paths [i.e. in accordance with published policies] between two networks. This will be useful in finding alternate paths, and evaluating the connectivity of networks.

3 Number assignment information

In the following, Directory objects have been defined to represent IP and AS (Autonomous System) namespace in the Directory. Their purpose is to provide

1. mapping from IP number to IP network element (network or node)
2. mapping from IP number to AS number and vice versa
3. assignment and delegation information

The need for a global, distributed database supporting the objectives arises mainly from distributed IP- and AS-number assignment.

Describing all IP numbers with one of the new objects `delegatedBlock`, `ipGroup` and `ipReference` leads to the desired information. AS number information is stored with the objects `asBlock` and `asReference`. Furthermore, all assigned numbers have some properties in common. Therefore, an objectclass `assignedNumberClass` is introduced. This class exports attributes to `delegatedBlock`, `ipGroup`, `ipReference`, `asBlock`, and `asReference`.

`AssignedNumberClass` is defined as follows (“number” always refers to IP number of `delegatedBlock`, network, host, and AS number, resp.):

```
assignedNumberClass OBJECT CLASS
  SUBCLASS of top
  MAY CONTAIN {
    assBy :: DistinguishedNameSyntax,
            /* refers to an organization or organizationalRole
            that assigned the number to assTo (see below) */
    assTo :: DistinguishedNameSyntax,
            /* refers to organization or organizationalRole
            that the number was assigned to. This does not
            imply that assTo "owns" this number now. */
    assDate :: uTCTimeSyntax,
            /* date of assignment for this number */
    nicHandle :: CaseIgnoreStringSyntax,
            /* gives the unique ID for a description
            related to this number.
            format: "handle : nic-domain-name"
            example: MAK21 : rs.internic.net */
    relNwElement :: DistinguishedNameSyntax,
            /* the network element related to this number
            (network or node) */
  }
```

3.1 Delegated Block object

This object provides information on a block of IP addresses delegated to some local-authority or service provider. Only contiguous blocks can be represented with the following schema. If an organization (say, a NIC) has been assigned several IP network numbers which do not form a contiguous block, it might want to use a different form of representing that fact (e.g. using `imageNetworks`). The `delegatedBlock` object holds lower and upper bounds of the block.

Note that the above does not make any assumption about the network masks being constrained by byte boundaries. We can thus represent subnetting within a "network (number)" that often happens within an organization in the same framework.

This schema does lead to some granularity in the otherwise flat IP-number space. Further, the granularity is significant as it may be used to identify the administrator of the block - a service provider or a domain manager. E.g. it fits well into the schema of aggregating networks for routing purposes as has been proposed in [RFC 1338].

The object `delegatedBlock` is of the form:

```
delegatedBlock OBJECT CLASS
  SUBCLASS of AssignedNumberClass
  MUST CONTAIN {
    delegatedBlockName :: caseIgnoreStringSyntax,
    lowerBound :: IPStringSyntax,
      /* smallest IP address belonging to the
      block, e.g. 195.100.0.0 */
    upperBound :: IPStringSyntax
      /* highest IP address belonging to the
      block, e.g. 195.103.255.255 */
  }
```

The attribute `relNwElement` (inherited from `AssignedNumberClass`) can point to a `networkImage` covering all networks within the block if this makes sense.

3.2 IP Group object

This object provides information for an IP network number. Its purpose is basically only to

1. show that the number has been assigned, and

2. provide a reference to the descriptive ipNetworkObject for this network.

Regardless of the actual value of x, IP group objects may exist for IP numbers x.0.0.0, x.y.0.0 and x.y.z.0. This approach includes "classical" class-A, -B and -C network addresses as well as any kind of super- and subnetworking.

The IP group object is a subclass of assignedNumberClass. The attribute relNwElement points to an ipNetworkImage as defined above.

```
ipGroup OBJECT CLASS
  SUBCLASS of AssignedNumberClass
  MUST CONTAIN {
    ipGroupName :: IPStringSyntax,
      /* IP number; x.0.0.0 or x.y.0.0 or x.y.z.0
       where x, y, z in {1..255} */
    ipNwMask :: IPStringSyntax
      /* mask that applies to all numbers
       within the group; used to define
       classless networking; */
  }
```

3.3 IP Reference object

There is one IP reference object for each IP host address. The purpose of this object is to

1. tell that this IP number is already assigned to a node
2. give a pointer to the related ipNodeImageObject

The IP reference object is a subclass of assignedNumberClass. The attribute relNwElement points to an ipNodeImage.

```
ipReference OBJECT CLASS
  SUBCLASS of AssignedNumberClass
  MUST CONTAIN {
    ipReferenceName :: IPString
      /* value is always IP address */
  }
```

3.4 AS block object

The AS block object is used to show delegation of blocks of AS numbers to regional registries. This is similar to `delegatedBlock` of `ipNetwork` numbers.

```
asBlock OBJECT CLASS
  SUBCLASS of AssignedNumberClass
  MUST CONTAIN {
    asBlockName :: caseIgnoreStringSyntax,
    asLowerBound :: integerStringSyntax,
    asUpperBound :: integerStringSyntax
  }
```

An AS block will comprise several consecutive AS numbers. Objects to describe these numbers may be stored in `asObjects`.

3.5 AS reference object

An AS reference object is used to show that an Autonomous System number has been assigned (and thus can not be given to somebody else). Similar to `ipGroup`, `asReference` does not contain technical details about an autonomous system itself but rather points (with `relNwElement`) to a descriptive `asObject`.

```
asReference OBJECT CLASS
  SUBCLASS of AssignedNumberClass
  MUST CONTAIN {
    asNumber :: integerStringSyntax
  }
```

4 Directory tree




Figure 1: Overall relationship of objects.

4.1 IP image objects

According to [ND], IP image entries will be stored underneath the organization / organizationalUnit entry of the entity responsible for that network. The case that such an entry does not yet exist in the white-pages pilot is discussed in 4.4 below.

4.2 AS objects

The technical and administrative description of an AS is basically maintained by NICs, network providers, or other special organizations. It is suggested that these organizations build a subtree for information on AS which they are responsible for.

4.3 Namespace objects

The new IP namespace objects build a single tree in the Directory. It is suggested that this tree will have a root of type organizationalUnit within @o=Internet@ou=Network Information.

```

objectClass= organizationalUnit
organizationalUnitName= IP networks
description= root of IP number tree
  
```

The tree is built under an administrative and an implementational view. Nowadays, network numbers usually are assigned to organizations by (national) Network Information Centers (NIC) which themselves have got a block of IP network numbers assigned from another authority (e.g. IR at top level). This concept of delegated blocks falling apart in smaller delegated blocks and IP network numbers is used to model the Directory tree. Thus, an ipGroup object is always subordinate of a delegated block object (namely the delegated block including this IP number). Network numbers that were directly assigned by a top-level authority, i.e. have not been object of a delegation to a local assigning authority, will all be at one level in the Directory. Already today, however, we find many delegations within the traditional class A-, B- and C-addresses. Such a delegation is represented by a delegated block object, having the assigned IP network numbers as subordinates. Also, part of the block can be further delegated to another authority, leading to another delegated block object within the parent delegated block's tree. Usually, subordinates of ip-Group objects are ipReferences, i.e. single IP addresses as assigned to nodes. To support subnetting, it is also allowed to divide ipGroups into several subnetwork ipGroups, each representing an IP subnetwork. In such cases, subnetwork numbers are given as subordinates to the assigned IP network number. Network masks clarify what the subnetwork addresses are.




Figure 2: Example population of IP namespace tree according to delegation and subnetting.

For some applications, the separation of ipImage (description of the network) and ipGroup (description of the namespace element) will bear disadvantages in the look-up procedure. In that case one might think of combining both object classes with the aim to provide one object describing administrative and technical data for an

IP network.

As Autonomous Systems are an additional namespace to the existing IP number space, they should go into a separate subtree. It is suggested that this is an organizationalUnit within @o=Internet@ou=Network Information.

```
objectClass= organizationalUnit
organizationalUnitName= AS numbers
description= root of Autonomous System number space
```

Similar to blocks of IP network numbers, blocks of AS numbers are sometimes delegated to another registry. This is expressed by asBlock objects. These objects come below the root of the AS number space. All AS numbers falling into such a block are stored as subordinates of the block. An AS block may have smaller AS blocks underneath if delegation is extended.

4.4 Relationship to organizational entries

Organizational information (i.e. white-pages-like information about an organization, its departments and employees) occurs at several places in the network DIT - [org of IP-Number, org of AS-Number, org of Admin-contact, ...]. However, it will be basically mastered [administered, maintained] by the organization itself in the Directory Management Domain (DMD) over which the organization has the authority. This gives rise to some tricky problems - a typical example is that of a NIC which holds the AS, DNS, IP, ... subtrees of the DIT.

A good strategy would avoid explicit duplication of information. By explicit duplication of information we understand information being duplicated outside the directory framework, e.g. by having several master entries for one and the same piece of information. The only way to avoid duplication would be to have relevant entries point to the pertinent organizational entry for organizational information. But since

- most organizations do not, as yet, have an entry in the DIT and
- the reliability of the access to an organizations DIT when stored in a remote DSA cannot be taken for granted,

the following framework is adopted to accomodate the conflicting requirements /conditions.

1. A copy of all the *necessary* organization-info is retained at the NICs DSA. Since only the necessary info will be kept the NIC will not be burdened to

act as the repository of the organizations DIT. These objects may be kept in a separate subtree of affiliated-organizations [organizations affiliated to the NIC]. Though the affiliated organizations node does not really represent a locality, it is suggested to define the node as objectClass locality. This does not break the Directory schema when entries of organizations shall become subordinate to the NIC's organization's entry.

2. The problem of information duplication/consistency will arise when organizational DITs/DSAs do come into existence. At that stage a *shadowing mechanism* which will attempt to maintain the data consistency may be resorted to. The X.500/ISO 9594(1993) implementations are expected to provide appropriate shadowing mechanisms along X.525.

It may be noted that what is suggested is not a duplication of an entire white-pages-like structure at the NIC. It suggests an "affiliated organizations node". The entries under this node will be organization objects with a limited number of attributes, i.e. the attributes to hold the organization info necessary for the NIC: nothing more, nothing less. Operationally, and content wise the NIC DSA will hold exactly the amount of info that is desired by the NIC. When an organization sets up its DSA and when the organization informs the NIC about it, the NIC will set up the shadowing arrangement to obtain info on changes of interest [and forget about it].

It may be emphasized that the entries under affiliated organizations are physical entities [replicated and refined from the Master entries, if and when they exist...] rather than alias entries. If a NIC dislikes the idea of users poring over the entries in the affiliated organizations - appropriate access control can be applied. Though duplication is unavoidable, the proposal attempts to make it transparent, by delegating the responsibility of maintaining the integrity to the Directory.

This issue is discussed in greater detail in a separate document [DEP].

5 Security Considerations

Security Considerations are not discussed in this Draft.

6 Author's Addresses

Thomas Johannsen
Dresden University of Technology
Institute of Communication Technology
D-01062 Dresden, GERMANY
Phone: +49-351-463-4621
EMail: Thomas.Johannsen@ifn.et.tu-dresden.de

Glenn Mansfield
AIC Systems Laboratories
6-6-3 Minami Yoshinari, Aoba-ku
Sendai 989-32, JAPAN
Phone: +81-22-279-3310
EMail: glenn@aic.co.jp

Mark Kusters
Network Solutions
EMail: markk@internic.net

Srinivas Sataluri
AT&T Bell Laboratories
EMail: sri@qsun.att.com

References

- [DEP] Mansfield, G., Th. Johannsen, J. Murai:
Deployment Strategy for the Directory in the Internet;
Work in Progress, July 1993.
- [InNIC] Kusters, M., S. Sataluri:
Representing Registration Information in the X.500 Directory
Draft proposal, March 1993.
- [ND] Mansfield, G., Th. Johannsen, M. Knopper:
Charting Networks in the Directory
Draft proposal OSI-DS-37, February 1993.
- [OSI-DS 19] Weider, C., M. Knopper, R. Lang:
Interim Directory Tree Structure for Network Infrastructure Infor-
mation;
OSI-Directory Services Working Group Document osi-ds-19, April
1991.

- [OSI-DS 25] Hardcastle-Kille, S.E.:
Representing the Real World in the OSI Directory;
Document osi-ds-25, February 1992.
- [RFC 1155] Rose, M.T., K. McCloghrie:
Structure and identification of managementg information for
TCP/IP-based internets;
RFC 1155, May 1990.
- [RFC 1274] Barker, P., S. Kille:
The COSINE and Internet X.500 Schema
RFC 1274, November 1991.
- [RFC 1278] Hardcastle-Kille, S.E.:
A string encoding of Presentation Address;
RFC 1278, November 1991.
- [RFC 1287] Clark, D., L. Chapin, V. Cerf, R. Braden, R. Hobby:
Towards the Future Internet Architecture;
RFC 1287, December 1991.
- [RFC 1338] Fuller, V., T. Li, J.Y. Yu, K. Varadhan:
Supernetting: An address assignment and aggregation strategy.
RFC 1338, June 1992.
- [RFC 1466] Gerich, E.:
Guidelines for Management of IP Address Space;
RFC 1466, May 1993.
- [RIPE-81] Bates, T., J.-M. Jouanigot, D. Karrenberg, P. Lothberg, M. Terp-
stra:
Representation of IP Routing Policies in the RIPE Database;
ripe-81, February 1993.
- [SPP] Johannsen, Th., G. Mansfield:
The Soft Pages Project;
Draft proposal OSI-DS-39, February 1993.
- [X.500-88] CCITT:
The Directory - Overview of Concepts, Models and Services
Recommendations X.500 - X.521

Appendix: OID tables

This appendix lists object identifiers for object classes and attributes type defined in [ND] and this document.

OIDs are given in quipu-oidtable format to make it easy for people to include them into their pilots. We would like to thank the ISODE Consortium for providing us with a node OID. Please note that definitions given below have no connection to the ISODE Consortium though.

```
IMPORT from oidtable.gen:
```

```
iso:                1
identifiedOrganization: iso.3
dod:                identifiedOrganization.6
internet:          dod.1
private:           internet.4
enterprises:       private.1
isode-consortium:  enterprises.453
```

```
-- localoidtable.gen
```

```
network-objects:   isode-consortium.11
id-nw-oc:          network-objects.1
id-nw-at:          network-objects.2
id-nw-as:          network-objects.3
ipStringSyntax:    ip-nw-as.1
```

```
-- localoidtable.oc
```

```
# general class definitions
```

```
CommunicationObject: id-nw-oc.1 : top : \
    : \
    adminContact, technContact, description
```

```
PhysicalCommunicationObject: id-nw-oc.2 : CommunicationObject : \
    : \
    owner, localityName, IC0
```

```
ImageCommunicationObject: id-nw-oc.3 : CommunicationObject : \
    : \
    imageType, imageOf
```

```
# physical communication elements
```

```
network: id-nw-oc.4 : PhysicalCommunicationObject : \  
    networkName : \  
    externalGateway, nwType, media, speed, traffic, \  
    configurationDate, configurationHistory  
  
node: id-nw-oc.5 : PhysicalCommunicationObject : \  
    nodeName : \  
    typeOfMachine, OS  
  
networkInterface: id-nw-oc.6 : PhysicalCommunicationObject : \  
    networkInterfaceName : \  
    networkInterfaceAddress, connectedNetwork  
  
# image communication elements  
  
networkImage: id-nw-oc.7 : ImageCommunicationObject : \  
    : \  
    externalGateway, speed, traffic, charge  
  
nodeImage: id-nw-oc.8 : ImageCommunicationObject : \  
    :  
  
networkInterfaceImage: id-nw-oc.9 : ImageCommunicationObject : \  
    : \  
    networkInterfaceAddress, connectedNetwork  
  
# IP image elements  
  
ipNetworkImage: id-nw-oc.10 : networkImage : \  
    ipNetworkImageName, ipNwNumber, ipNwMask : \  
    associatedDomain, inAddrServer, asNumber, \  
    provider, onlineDate  
  
ipNodeImage: id-nw-oc.11 : nodeImage : \  
    ipNodeName : \  
    protocol, domainName  
  
ipNetworkInterfaceImage: id-nw-oc.12 : networkInterfaceImage : \  
    ipNetworkInterfaceName : \  
    ipNwMask  
  
as: id-nw-oc.13 : ImageCommunicationObject : \  
    asNumber : \  
    asName, asIn, asOut, asDefault, asGuardian, \  
    lastModifiedDate  
  
# number assignement objects  
  
assignedNumberClass: id-nw-oc.14 : top : \  

```

```

: \
  assBy, assTo, assDate, nicHandle, relNwElement, \
description

```

```

delegatedBlock: id-nw-oc.15 : AssignedNumberClass : \
  delegatedBlockName, lowerBound, upperBound :

```

```

ipGroup: id-nw-oc.16 : AssignedNumberClass : \
  ipGroupName, ipNwMask :

```

```

ipReference: id-nw-oc.17 : AssignedNumberClass : \
  ipReferenceName :

```

```

asBlock: id-nw-oc.18 : AssignedNumberClass : \
  asBlockName, asLowerBound, asUpperBound :

```

```

asReference: id-nw-oc.19 : AssignedNumberClass : \
  asNumber :

```

```
-- localoidtable.at
```

```

adminContact:          id-nw-at.1      :DN
technContact:         id-nw-at.2      :DN
owner:                 id-nw-at.3      :DN
IC0:                   id-nw-at.4      :DN
imageType:             id-nw-at.5      :caseIgnoreString
imageOf:               id-nw-at.6      :DN
networkName:          id-nw-at.7      :caseIgnoreString
externalGateway:      id-nw-at.8      :DN
nwType:                id-nw-at.9      :caseIgnoreString
media:                 id-nw-at.10     :caseIgnoreString
speed:                 id-nw-at.11     :numericString
traffic:               id-nw-at.12     :numericString
configurationDate:    id-nw-at.13     :utcTime
configurationHistory: id-nw-at.14     :caseIgnoreString
nodeName:              id-nw-at.15     :caseIgnoreString
typeOfMachine:        id-nw-at.16     :caseIgnoreString
OS:                    id-nw-at.17     :caseIgnoreString
networkInterfaceName: id-nw-at.18     :caseIgnoreString
networkInterfaceAddress: id-nw-at.19 :caseIgnoreString
connectedNetwork:     id-nw-at.20     :DN
charge:                id-nw-at.21     :numericString
ipNetworkImageName:   id-nw-at.22     :caseIgnoreString
ipNwNumber:           id-nw-at.23     :caseIgnoreString
ipNwMask:              id-nw-at.24     :caseIgnoreString
associatedDomain:     id-nw-at.25     :caseIgnoreString
inAddrServer:         id-nw-at.26     :DN
asNumber:              id-nw-at.27     :integerString
provider:              id-nw-at.28     :DN

```

```
onlineDate:          id-nw-at.29   :utcTime
protocol:           id-nw-at.30   :caseIgnoreString
domainName:         id-nw-at.31   :caseIgnoreString
ipNetworkInterfaceName: id-nw-at.32 :caseIgnoreString
asName:             id-nw-at.33   :caseIgnoreString
asIn:               id-nw-at.34   :caseIgnoreString
asOut:              id-nw-at.35   :caseIgnoreString
asDefault:         id-nw-at.36   :caseIgnoreString
asGuardian:        id-nw-at.37   :DN
assBy:              id-nw-at.38   :DN
assTo:              id-nw-at.39   :DN
assDate:           id-nw-at.40   :utcTime
nicHandle:         id-nw-at.41   :caseIgnoreString
relNwElement:      id-nw-at.42   :DN
delegatedBlockName: id-nw-at.43   :caseIgnoreString
lowerBound:        id-nw-at.44   :caseIgnoreString
upperBound:        id-nw-at.45   :caseIgnoreString
ipGroupName:       id-nw-at.46   :caseIgnoreString
ipReferenceName:   id-nw-at.47   :caseIgnoreString
asBlockName:       id-nw-at.48   :caseIgnoreString
asLowerBound:      id-nw-at.49   :integerString
asUpperBound:      id-nw-at.50   :integerString
```

--