

#¹ \$² +³ **Windows Sockets**
An Open Interface for
Network Programming under
Microsoft® Windows™

Version 1.0
18 April, 2021

Authors and Copyright

Introduction

Programming with Sockets

Socket Library Overview

Socket Library Reference

Appendices

Error Codes and Header Files

Error Codes

Header Files

Notes for Windows Sockets Suppliers

Background Information

Origins of Windows Sockets

Roadmap

1# WinSock_Index

2\$ Windows Sockets Index

3+ WinSock:0005

2 Appendix C: Background Information

#4Martin Hall	JSB Corporation
Mark Towfiq	FTP Software, Inc.
Geoff Arnold	Sun Microsystems, Inc.
David Treadwell	Microsoft Corporation
Henry Sanders	Microsoft Corporation

Copyright © 1992 by Martin Hall, Mark Towfiq
Geoff Arnold, David Treadwell and Henry Sanders

All rights reserved.

This document may be freely redistributed in any form, electronic or otherwise, provided that it is distributed in its entirety and that the copyright and this notice are included. Comments or questions may be submitted via electronic mail to **winsock@ftp.com**. Requests to be added to the Windows Sockets mailing list should be addressed to **winsock-request@ftp.com**. Questions about products conforming to this specification should be addressed to the vendors of the products.

#₅ \$₆ +₇ K₈ **Windows Sockets**

Introduction

What is Windows Sockets

Berkeley Sockets

Microsoft Windows and Windows-specific extensions

The Status of this Specification

5# WinSock_Intro

6\$ Introduction

7+ WinSock:0010

8^K Introduction

4 Appendix C: Background Information

#⁹ \$¹⁰ +¹¹ Introduction

What is Windows Sockets

The Windows Sockets specification defines a network programming interface for Microsoft Windows which is based on the "socket" paradigm popularized in the Berkeley Software Distribution (BSD) from the University of California at Berkeley. It encompasses both familiar Berkeley socket style routines and a set of Windows-specific extensions designed to allow the programmer to take advantage of the message-driven nature of Windows.

The Windows Sockets Specification is intended to provide a single API to which application developers can program and multiple network software vendors can conform. Furthermore, in the context of a particular version of Microsoft Windows, it defines a binary interface (ABI) such that an application written to the Windows Sockets API can work with a conformant protocol implementation from any network software vendor. This specification thus defines the library calls and associated semantics to which an application developer can program and which a network software vendor can implement.

Network software which conforms to this Windows Sockets specification will be considered "Windows Sockets Compliant". Suppliers of interfaces which are "Windows Sockets Compliant" shall be referred to as "Windows Sockets Suppliers". To be Windows Sockets Compliant, a vendor must implement 100% of this Windows Sockets specification.

Applications which are capable of operating with any "Windows Sockets Compliant" protocol implementation will be considered as having a "Windows Sockets Interface" and will be referred to as "Windows Sockets Applications".

This version of the Windows Sockets specification defines and documents the use of the API in conjunction with the Internet Protocol Suite (IPS, generally referred to as TCP/IP). Specifically, all Windows Sockets implementations support both stream (TCP) and datagram (UDP) sockets.

While the use of this API with alternative protocol stacks is not precluded (and is expected to be the subject of future revisions of the specification), such usage is beyond the scope of this version of the specification.

9# WinSock_WhatIs

10\$ What is Windows Socket

11+ WinSockIntro:0010

#¹² \$¹³ +¹⁴ K¹⁵ **Introduction**

Berkeley Sockets

The Windows Sockets Specification has been built upon the Berkeley Sockets programming model which is the de facto standard for TCP/IP networking. It is intended to provide a high degree of familiarity for programmers who are used to programming with sockets in UNIX and other environments, and to simplify the task of porting existing sockets-based source code. The Windows Sockets API is consistent with release 4.3 of the Berkeley Software Distribution (4.3BSD).

Portions of the Windows Sockets specification are derived from material which is Copyright (c) 1982-1986 by the Regents of the University of California. All rights are reserved. The Berkeley Software License Agreement specifies the terms and conditions for redistribution.

12# WinSock_Berkeley
13\$ Berkeley Socket
14+ WinSockIntro:0020
15^K Berkeley Sockets

6 Appendix C: Background Information

#¹⁶ \$¹⁷ +¹⁸ Introduction

Microsoft Windows and Windows-specific extensions

This API is intended to be usable within all implementations and versions of Microsoft Windows from Microsoft Windows Version 3.0 onwards. It thus provides for Windows Sockets implementations and Windows Sockets applications in both 16 and 32 bit operating environments.

Windows Sockets makes provisions for multithreaded Windows processes. A process contains one or more threads of execution. In the Win16 non-multithreaded world, a task corresponds to a process with a single thread. All references to threads in this document refer to actual "threads" in multithreaded Windows environments. In non multithreaded environments (such as Windows 3.0), use of the term thread refers to a Windows process.

The Microsoft Windows extensions included in Windows Sockets are provided to allow application developers to create software which conforms to the Windows programming model. It is expected that this will facilitate the creation of robust and high-performance applications, and will improve the cooperative multitasking of applications within non-preemptive versions of Windows. With the exception of WSAStartup() and WSACleanup() their use is not mandatory.

16# WinSock_Windows

17\$ Microsoft Windows and Windows-specific extension

18+ WinSockIntro:0030

#19 \$20 +21 K22 Introduction

The Status of this Specification

This document is version 1.0 of the Windows Sockets Specification. It represents the results of considerable work within the vendor and user community, as described in Appendix C. This version of the specification has been released in order that network software suppliers and applications developers can begin to construct implementations and applications which conform to the standard. As with any specification, we anticipate that changes will be necessary, as the users of the standard gain experience with it, and Appendix C describes the way in which this change is expected to occur.

19# WinSock_Status

20\$ The Status of this Specificatio

21+ WinSockIntro:0040

22K Status of the Spec

8 Appendix C: Background Information

#²³ \$²⁴ +²⁵ **Windows Sockets**

Programming with Sockets

Windows Sockets Stack Installation Checking

Sockets

Byte Ordering

Socket Options

Database Files

Deviation from Berkeley Sockets

23# WinSock_ProgrammingWithSockets

24\$ Programming with Sockets

25+ WinSock:0020

#²⁶ \$²⁷ +²⁸ K²⁹ **Programming with Sockets**

Windows Sockets Stack Installation Checking

To detect the presence of one (or many) Windows Sockets implementations on a system, an application which has been linked with the Windows Sockets Import Library may simply call the **WSAStartup()** routine. If an application wishes to be a little more sophisticated it can examine the \$PATH environment variable and search for instances of Windows Sockets implementations (WINSOCK.DLL). For each instance it can issue a **LoadLibrary()** call and use the **WSAStartup()** routine to discover implementation specific data.

This version of the Windows Sockets specification does not attempt to address explicitly the issue of multiple concurrent Windows Sockets implementations. Nothing in the specification should be interpreted as restricting multiple Windows Sockets DLLs from being present and used concurrently by one or more Windows Sockets applications.

26# WinSockProg_StackInstall

27\$ Windows Sockets Stack Installation Checking

28+ WinSockProg:0010

29K Installation Check

10 Appendix C: Background Information

#³⁰ \$³¹ +³² K³³ K³⁴ Programming with Sockets

Sockets

The following material is derived from the document "An Advanced 4.3BSD Interprocess Communication Tutorial" by Samuel J. Leffler, Robert S. Fabry, William N. Joy, Phil Lapsley, Steve Miller, and Chris Torek.

Basic concepts

Client-server model

Out-of-band data

Broadcasting

30# WinSockProg_Sockets

31\$ Sockets

32+ WinSockProg:0020

33^K Sockets

34^K Berkeley Sockets

#³⁵ \$³⁶ +³⁷ K³⁸ Sockets

Basic concepts

The basic building block for communication is the socket. A socket is an endpoint of communication to which a name may be bound. Each socket in use has a type and an associated process. Sockets exist within communication domains. A communication domain is an abstraction introduced to bundle common properties of threads communicating through sockets. Sockets normally exchange data only with sockets in the same domain (it may be possible to cross domain boundaries, but only if some translation process is performed). The Windows Sockets facilities support a single communication domain: the Internet domain, which is used by processes which communicate using the Internet Protocol Suite. (Future versions of this specification may include additional domains.)

Sockets are typed according to the communication properties visible to a user. Applications are presumed to communicate only between sockets of the same type, although there is nothing that prevents communication between sockets of different types should the underlying communication protocols support this.

Two types of sockets currently are available to a user. A stream socket provides for the bi-directional, reliable, sequenced, and unduplicated flow of data without record boundaries.

A datagram socket supports bi-directional flow of data which is not promised to be sequenced, reliable, or unduplicated. That is, a process receiving messages on a datagram socket may find messages duplicated, and, possibly, in an order different from the order in which it was sent. An important characteristic of a datagram socket is that record boundaries in data are preserved. Datagram sockets closely model the facilities found in many contemporary packet switched networks such as Ethernet.

35# WinSockSockets_BasicConcepts

36\$ Basic concepts

37+ WinSockSock:0010

38^K Sockets

12 Appendix C: Background Information

#³⁹ \$⁴⁰ +⁴¹ K⁴² **Sockets**

Client-server model

The most commonly used paradigm in constructing distributed applications is the client/server model. In this scheme client applications request services from a server application. This implies an asymmetry in establishing communication between the client and server.

The client and server require a well-known set of conventions before service may be rendered (and accepted). This set of conventions comprises a protocol which must be implemented at both ends of a connection. Depending on the situation, the protocol may be symmetric or asymmetric. In a symmetric protocol, either side may play the master or slave roles. In an asymmetric protocol, one side is immutably recognized as the master, with the other as the slave. An example of a symmetric protocol is the TELNET protocol used in the Internet for remote terminal emulation. An example of an asymmetric protocol is the Internet file transfer protocol, FTP. No matter whether the specific protocol used in obtaining a service is symmetric or asymmetric, when accessing a service there is a "client process" and a "server process".

A server application normally listens at a well-known address for service requests. That is, the server process remains dormant until a connection is requested by a client's connection to the server's address. At such a time the server process "wakes up" and services the client, performing whatever appropriate actions the client requests of it. While connection-based services are the norm, some services are based on the use of datagram sockets.

39# WinSockSockets_ClientServer

40\$ Client-server model

41+ WinSockSock:0020

42^K Sockets

#⁴³ \$⁴⁴ +⁴⁵ K⁴⁶ **Sockets**

Out-of-band data

Note: The following discussion of out-of-band data, also referred to as TCP Urgent data, follows the model used in the Berkeley software distribution. Users and implementors should be aware of the fact that there are at present two conflicting interpretations of RFC 793 (in which the concept is introduced), and that the implementation of out-of-band data in the Berkeley Software Distribution does not conform to the Host Requirements laid down in RFC 1122. To minimize interoperability problems, applications writers are advised not to use out-of-band data unless this is required in order to interoperate with an existing service. Windows Sockets suppliers are urged to document the out-of-band semantics (BSD or RFC 1122) which their product implements. It is beyond the scope of this specification to mandate a particular set of semantics for out-of-band data handling.

The stream socket abstraction includes the notion of "out of band" data. Out-of-band data is a logically independent transmission channel associated with each pair of connected stream sockets. Out-of-band data is delivered to the user independently of normal data. The abstraction defines that the out-of-band data facilities must support the reliable delivery of at least one out-of-band message at a time. This message may contain at least one byte of data, and at least one message may be pending delivery to the user at any one time. For communications protocols which support only in-band signaling (i.e. the urgent data is delivered in sequence with the normal data), the system normally extracts the data from the normal data stream and stores it separately. This allows users to choose between receiving the urgent data in order and receiving it out of sequence without having to buffer all the intervening data. It is possible to "peek" at out-of-band data.

An application may prefer to process out-of-band data "in-line", as part of the normal data stream. This is achieved by setting the socket option SO_OOBINLINE (see [**setsockopt\(\)**](#)). In this case, the application may wish to determine whether any of the unread data is "urgent" (the term usually applied to in-line out-of-band data). To facilitate this, the Windows Sockets implementation will maintain a logical "mark" in the data stream indicate the point at which the out-of-band data was sent. An application can use the SIOCATMARK [**ioctlsocket\(\)**](#) command to determine whether there is any unread data preceding the mark. For example, it might use this to resynchronize with its peer by ensuring that all data up to the mark in the data stream is discarded when appropriate.

The [**WSAAsyncSelect\(\)**](#) routine is particularly well suited to handling notification of the presence of out-of-band-data.

- 43# WinSockSockets_OutOfBand
- 44\$ Out-of-band data
- 45+ WinSockSock:0030
- 46^K Sockets

14 Appendix C: Background Information

#⁴⁷ \$⁴⁸ +⁴⁹ K⁵⁰ **Sockets**

Broadcasting

By using a datagram socket, it is possible to send broadcast packets on many networks supported by the system. The network itself must support broadcast: the system provides no simulation of broadcast in software. Broadcast messages can place a high load on a network, since they force every host on the network to service them. Consequently, the ability to send broadcast packets has been limited to sockets which are explicitly marked as allowing broadcasting. Broadcast is typically used for one of two reasons: it is desired to find a resource on a local network without prior knowledge of its address, or important functions such as routing require that information be sent to all accessible neighbors.

The destination address of the message to be broadcast depends on the network(s) on which the message is to be broadcast. The Internet domain supports a shorthand notation for broadcast on the local network, the address INADDR_BROADCAST. Received broadcast messages contain the senders address and port, as datagram sockets must be bound before use.

Some types of network support the notion of different types of broadcast. For example, the IEEE 802.5 token ring architecture supports the use of link-level broadcast indicators, which control whether broadcasts are forwarded by bridges. The Windows Sockets specification does not provide any mechanism whereby an application can determine the type of underlying network, nor any way to control the semantics of broadcasting.

47# WinSockSockets_Broadcasting

48\$ Broadcasting

49+ WinSockSock:0040

50^K Sockets

#⁵¹ \$⁵² +⁵³ K⁵⁴ **Programming with Sockets**

Byte Ordering

The Intel byte ordering is like that of the DEC VAX, and therefore differs from the Internet and 68000-type processor byte ordering. Thus care must be taken to ensure correct orientation.

Consider an application which normally contacts a server on the TCP port corresponding to the "time" service, but which provides a mechanism for the user to specify that an alternative port is to be used. The port number returned by getservbyname() is already in network order, which is the format required constructing an address, so no translation is required. However if the user elects to use a different port, entered as an integer, the application must convert this from host to network order (using the htons() function) before using it to construct an address. Conversely, if the application wishes to display the number of the port within an address (returned via, e.g., getpeername()), the port number must be converted from network to host order (using ntohs()) before it can be displayed.

Since the Intel and Internet byte orders are different, the conversions described above are unavoidable. Application writers are cautioned that they should use the standard conversion functions provided as part of the Windows Sockets API rather than writing their own conversion code, since future implementations of Windows Sockets are likely to run on systems for which the host order is identical to the network byte order. Only applications which use the standard conversion functions are likely to be portable.

51# WinSockProg_ByteOrdering
52\$ Byte Ordering
53+ WinSockProg:0030
54^K Sockets

16 Appendix C: Background Information

#⁵⁵ \$⁵⁶ +⁵⁷ K⁵⁸ Programming with Sockets

Socket Options

The socket options supported by Windows Sockets are listed in the pages describing [setsockopt\(\)](#) and [getsockopt\(\)](#). A Windows Sockets implementation must recognize all of these options, and (for [getsockopt\(\)](#)) return plausible values for each. The default value for each option is shown in the following table.

<u>Value</u>	<u>Type</u>	<u>Meaning</u>	<u>Default</u>	<u>Note</u>
SO_ACCEPTCON	BOOL	Socket is <u>listen()</u> ing.	FALSE unless a <u>listen()</u> has been performed	
SO_BROADCAST	BOOL	Socket is configured for the transmission of broadcast messages.	FALSE	
SO_DEBUG	BOOL	Debugging is enabled.		FALSE (i)
SO_DONTLINGER	BOOL	If true, the SO_LINGER option is disabled..	TRUE	
SO_DONTROUTE	BOOL	Routing is disabled.	FALSE	(i)
SO_ERROR	int	Retrieve error status and clear.	0	
SO_KEEPAIVE	BOOL	Keepalives are being sent.	FALSE	
SO_LINGER	struct linger	Returns the current linger options.	<i>l_onoff</i> is 0	
SO_OOINLINE	BOOL	Out-of-band data is being received in the normal data stream.	FALSE	
SO_RCVBUF	int	Buffer size for receives	none	(i)
SO_REUSEADDR	BOOL	The address to which this socket is bound can be used by others.	FALSE	
SO_SNDBUF	int	Buffer size for sends	none	(i)
SO_TYPE	int	The type of the socket (e.g. SOCK_STREAM). via <u>socket()</u>	As created	

Notes:

- (i) An implementation may silently ignore this option on [setsockopt\(\)](#) and return a constant value for [getsockopt\(\)](#), or it may accept a value for [setsockopt\(\)](#) and return the corresponding value in [getsockopt\(\)](#) without using the value in any way.

55# WinSockProg_SocketOptions

56\$ Socket Options

57+ WinSockProg:0040

58^K Sockets

#⁵⁹ \$⁶⁰ +⁶¹ K⁶² K⁶³ **Programming with Sockets**

Database Files

The **getXbyY()** and **WSAAsyncGetXByY()** classes of routines are provided for retrieving network specific information. The **getXbyY()** routines were originally designed (in the first Berkeley UNIX releases) as mechanisms for looking up information in text databases. Although the information may be retrieved by the Windows Sockets implementation in different ways, a Windows Sockets application requests such information in a consistent manner through either the **getXbyY()** or the **WSAAsyncGetXByY()** class of routines.

59# WinSockProg_DatabaseFiles

60\$ Database Files

61+ WinSockProg:0050

62^K Sockets

63^K Database Routines

18 Appendix C: Background Information

#⁶⁴ \$⁶⁵ +⁶⁶ K⁶⁷ Programming with Sockets

Deviation from Berkeley Sockets

There are a few limited instances where the Windows Sockets API has had to divert from strict adherence to the Berkeley conventions, usually because of difficulties of implementation in a Windows environment.

socket data type and error values

select() and FD *

Error codes - errno, h_errno & WSAGetLastError()

Pointers

Renamed functions

Blocking routines & EINPROGRESS

Maximum number of sockets supported

Include files

Return values on API failure

64# WinSockProg_Deviation

65\$ Deviation from Berkeley Sockets

66+ WinSockProg:0060

67^K Sockets

#⁶⁸ \$⁶⁹ +⁷⁰ K⁷¹ **Deviation from Berkeley Sockets****socket data type and error values**

A new data type, SOCKET, has been defined. The definition of this type was necessary for future enhancements to the Windows Sockets specification, such as being able to use sockets as file handles in Windows/NT. Definition of this type also facilitates porting of applications to a Win/32 environment, as the type will automatically be promoted from 16 to 32 bits.

Because the SOCKET type is unsigned, compiling existing source code from, for example, a UNIX environment may lead to compiler warnings about signed/unsigned data type mismatches.

This means, for example, that checking for errors when the **socket()** and **accept()** routines return should not be done by comparing the return value with -1, or seeing if the value is negative (both common, and legal, approaches in BSD). Instead, an application should use the manifest constant INVALID_SOCKET as defined in **winsock.h**. For example:

TYPICAL BSD STYLE:

```
s = socket(...);
if (s == -1)      /* or s < 0 */
    {...}
```

PREFERRED STYLE:

```
s = socket(...);
if (s == INVALID_SOCKET)
    {...}
```

68# WinSockDeviation_DataType
 69\$ socket data type and error values
 70+ WinSockDev:0010
 71^K Sockets

20 Appendix C: Background Information

#⁷² \$⁷³ +⁷⁴ K⁷⁵ **Deviation from Berkeley Sockets**

select() and FD_*

Because a SOCKET is no longer represented by the UNIX-style "small non-negative integer", the implementation of the **select()** function was changed in the Windows Sockets API. Each set of descriptors is still represented by the fd_set type, but instead of being stored as a bitmask the set is implemented as an array of SOCKETS.. To avoid potential problems, applications must adhere to the use of the FD_XXX macros to set, initialize, clear, and check the fd_set structures.

72# WinSockDeviation_Select

73\$ select() and FD_*

74+ WinSockDev:0020

75^K Sockets

#76 \$77 +78 K79 **Deviation from Berkeley Sockets****Error codes - errno, h_errno & WSAGetLastError()**

Error codes set by the Windows Sockets implementation are NOT made available via the `errno` variable. Additionally, for the `getXbyY()` class of functions, error codes are NOT made available via the `h_errno` variable. Instead, error codes are accessed by using the **WSAGetLastError()** API. This function is provided in Windows Sockets as a precursor (and eventually an alias) for the Win32 function **GetLastError()**. This is intended to provide a reliable way for a thread in a multi-threaded process to obtain per-thread error information.

For compatibility with BSD, an application may choose to include a line of the form:

```
#define errno WSAGetLastError()
```

This will allow networking code which was written to use the global `errno` to work correctly in a single-threaded environment. There are, obviously, some drawbacks. If a source file includes code which inspects `errno` for both socket and non-socket functions, this mechanism cannot be used. Furthermore, it is not possible for an application to assign a new value to `errno`. (In Windows Sockets the function **WSASetLastError()** may be used for this purpose.)

TYPICAL BSD STYLE:

```
r = recv(...);
if (r == -1
    && errno == EWOULDBLOCK)
    {...}
```

PREFERRED STYLE:

```
r = recv(...);
if (r == -1 /* (but see below) */
    && WSAGetLastError() == EWOULDBLOCK)
    {...}
```

Although error constants consistent with 4.3 Berkeley Sockets are provided for compatibility purposes, applications should, where possible, use the "WSA" error code definitions. For example, a more accurate version of the above source code fragment is:

```
r = recv(...);
if (r == -1
    && WSAGetLastError() == WSAEWOULDBLOCK)
    {...}
```

76# WinSockDeviation_ErrorCodes
 77\$ Error codes - errno, h_errno & WSAGetLastError()
 78+ WinSockDev:0030
 79^K Sockets

22 Appendix C: Background Information

#⁸⁰ \$⁸¹ +⁸² K⁸³ **Deviation from Berkeley Sockets**

Pointers

All pointers used by applications with Windows Sockets should be FAR. To facilitate this, data type definitions such as LPHOSTENT are provided.

80# WinSockDeviation_Pointers

81\$ Pointers

82+ WinSockDev:0040

83^K Sockets

#⁸⁴ \$⁸⁵ +⁸⁶ K⁸⁷ **Deviation from Berkeley Sockets**

Renamed functions

In two cases it was necessary to rename functions which are used in Berkeley Sockets in order to avoid clashes with other APIs.

close() & closesocket()

In Berkeley Sockets, sockets are represented by standard file descriptors, and so the **close()** function can be used to close sockets as well as regular files. While nothing in the Windows Sockets API prevents an implementation from using regular file handles to identify sockets, nothing requires it either. Socket descriptors are not presumed to correspond to regular file handles, and file operations such as **read()**, **write()**, and **close()** cannot be assumed to work correctly when applied to socket descriptors.. Sockets must be closed by using the **closesocket()** routine. Using the **close()** routine to close a socket is incorrect and the effects of doing so are undefined by this specification.

ioctl() & ioctlsocket()

Various C language run-time systems use the **ioctl()** routine for purposes unrelated to Windows Sockets. For this reason we have defined the routine **ioctlsocket()** which is used to handle socket functions which in the Berkeley Software Distribution are performed using **ioctl()** and **fcntl()**.

84# WinSockDeviation_RenamedFunctions

85\$ Renamed functions

86+ WinSockDev:0050

87^K Sockets

24 Appendix C: Background Information

#⁸⁸ \$⁸⁹ +⁹⁰ K⁹¹ **Deviation from Berkeley Sockets**

Blocking routines & EINPROGRESS

Although blocking operations on sockets are supported under Windows Sockets, their use is strongly discouraged. Programmers who are constrained to use blocking mode - for example, as part of an existing application which is to be ported - should be aware of the semantics of blocking operations in Windows Sockets. See [Blocking/Non blocking & Data Volatility](#) for more details.

88# WinSockDeviation_BlockingRoutines

89\$ Blocking routines & EINPROGRESS

90+ WinSockDev:0060

91^K Sockets

#⁹² \$⁹³ +⁹⁴ K⁹⁵ **Deviation from Berkeley Sockets**

Maximum number of sockets supported

The maximum number of sockets supported by a particular Windows Sockets supplier is implementation specific. An application should make no assumptions about the availability of a certain number of sockets. This topic is addressed further in section 4.3.15, `WSAStartup()`. However, independent of the number of sockets supported by a particular implementation is the issue of the maximum number of sockets which an application can actually make use of.

The maximum number of sockets which a Windows Sockets application can make use of is determined at compile time by the manifest constant `FD_SETSIZE`. This value is used in constructing the `fd_set` structures used in `select()`. The default value in `winsock.h` is 64. If an application is designed to be capable of working with more than 64 sockets, the implementor should define the manifest `FD_SETSIZE` in every source file before including `winsock.h`. One way of doing this may be to include the definition within the compiler options in the makefile. It must be emphasized that defining `FD_SETSIZE` as a particular value has no effect on the actual number of sockets provided by a Windows Sockets implementation.

92# WinSockDeviation_MaxSockets

93\$ Maximum number of sockets supported

94+ WinSockDev:0070

95^K Sockets

26 Appendix C: Background Information

#⁹⁶ \$⁹⁷ +⁹⁸ K⁹⁹ **Deviation from Berkeley Sockets**

Include files

For ease of portability of existing Berkeley sockets based source code, a number of standard Berkeley include files are supported. However, these Berkeley header files merely include the **winsock.h** include file, and it is therefore sufficient (and recommended) that Windows Sockets application source files should simply include **winsock.h**.

96# WinSockDeviation_IncludeFiles

97\$ Include files

98+ WinSockDev:0080

99K Sockets

#₁₀₀ \$₁₀₁ +₁₀₂ K₁₀₃ **Deviation from Berkeley Sockets****Return values on API failure**

The manifest constant `SOCKET_ERROR` is provided for checking API failure. Although use of this constant is not mandatory, it is recommended. The following example illustrates the use of the `SOCKET_ERROR` constant:

TYPICAL BSD STYLE:

```
r = recv(...);
if (r == -1          /* or r < 0 */
    && errno == EWOULDBLOCK)
    {...}
```

PREFERRED STYLE:

```
r = recv(...);
if (r == SOCKET_ERROR
    && WSAGetLastError() == WSAEWOULDBLOCK)
    {...}
```

100# WinSockDeviation_ReturnValues

101\$ Return values on API failure

102+ WinSockDev:0090

103^K Sockets

28 Appendix C: Background Information

#¹⁰⁴ \$¹⁰⁵ +¹⁰⁶ **Windows Sockets**

Socket Library Overview

Socket Functions

Blocking/Non blocking & Data Volatility

Database Functions

Microsoft Windows-specific Extension Functions

104# WinSock_SocketLibraryOverview

105\$ SOCKET LIBRARY OVERVIEW

106+ WinSock:0030

#¹⁰⁷ \$¹⁰⁸ +¹⁰⁹ K¹¹⁰ **Socket Library Overview**

Socket Functions

The Windows Sockets specification includes the following Berkeley-style socket routines:

<u>accept()</u>	An incoming connection is acknowledged and associated with an immediately created socket. The original socket is returned to the listening state.
<u>bind()</u>	Assign a local name to an unnamed socket.
<u>closesocket()</u>	Remove a socket descriptor from the per-process object reference table.
<u>connect()</u>	Initiate a connection on the specified socket.
<u>getpeername()</u>	Retrieve the name of the peer connected to the specified socket descriptor.
<u>getsockname()</u>	Retrieve the current name for the specified socket
<u>getsockopt()</u>	Retrieve options associated with the specified socket descriptor.
<u>htonl()</u>	Convert a 32-bit quantity from host byte order to network byte order.
<u>htons()</u>	Convert a 16-bit quantity from host byte order to network byte order.
<u>inet_addr()</u>	Converts a character string representing a number in the Internet standard "." notation to an Internet address value.
<u>inet_ntoa()</u>	Converts an Internet address value to an ASCII string in "." notation i.e. "a.b.c.d".
<u>ioctlsocket()</u>	Provide control for descriptors.
<u>listen()</u>	Listen for incoming connections on a specified socket.
<u>ntohl()</u>	Convert a 32-bit quantity from network byte order to host byte order.
<u>ntohs()</u>	Convert a 16-bit quantity from network byte order to host byte order.
<u>recv()</u>	Receive data from a connected socket.
<u>recvfrom()</u>	Receive data from either a connected or unconnected socket.
<u>select()</u>	Perform synchronous I/O multiplexing.
<u>send()</u>	Send data to a connected socket.
<u>sendto()</u>	Send data to either a connected or unconnected socket.
<u>setsockopt()</u>	Store options associated with the specified socket descriptor.
<u>shutdown()</u>	Shut down part of a full-duplex connection.
<u>socket()</u>	Create an endpoint for communication and return a socket descriptor.

107# WinSockOverview_SocketFunctions

108\$ Socket Functions

109+ WinSockOver:0010

110^K Socket Functions

30 Appendix C: Background Information

#¹¹¹ \$¹¹² +¹¹³ K¹¹⁴ **Socket Library Overview**

Blocking/Non blocking & Data Volatility

One major issue in porting applications from a Berkeley sockets environment to a Windows environment involves "blocking"; that is, invoking a function which does not return until the associated operation is completed. The problem arises when the operation may take an arbitrarily long time to complete: an obvious example is a **recv()** which may block until data has been received from the peer system. The default behavior within the Berkeley sockets model is for a socket to operate in a blocking mode unless the programmer explicitly requests that operations be treated as non-blocking.

Even on a blocking socket, some operations (e.g. **bind()**, **getsockopt()**, **getpeername()**) can be completed immediately. For such operations there is no difference between blocking and non-blocking operation. Other operations (e.g. **recv()**) may be completed immediately or may take an arbitrary time to complete, depending on various transport conditions. When applied to a blocking socket, these operations are referred to as blocking operations.

Within a Windows Sockets implementation, a blocking operation which cannot be completed immediately is handled as follows. The DLL initiates the operation, and then enters a loop in which it dispatches any Windows messages (yielding the processor to another thread if necessary) and then checks for the completion of the Windows Sockets function. If the function has completed, or if **WSACancelBlockingCall()** has been invoked, the blocking function completes with an appropriate result. Refer to **WSASetBlockingHook()**, for a complete description of this mechanism, including pseudocode for the various functions.

If a Windows message is received for a process for which a blocking operation is in progress, there is a risk that the application will attempt to issue another Windows Sockets call. Because of the difficulty of managing this condition safely, the Windows Sockets specification does not support such application behavior. Two functions are provided to assist the programmer in this situation. **WSAIsBlocking()** may be called to determine whether or not a blocking Windows Sockets call is in progress. **WSACancelBlockingCall()** may be called to cancel an in-progress blocking call, if any. **Any other Windows Sockets function which is called in this situation will fail with the error WSAEINPROGRESS.** It should be emphasized that this restriction applies to both blocking and non-blocking operations.

Although this mechanism is sufficient for simple applications, it cannot support the complex message-dispatching requirements of more advanced applications (for example, those using the MDI model). For such applications, the Windows Sockets API includes the function **WSASetBlockingHook()**, which allows the programmer to define a special routine which will be called instead of the default message dispatch routine described above.

If an application invokes an asynchronous or non-blocking operation which takes a pointer to a memory object (e.g. a buffer, or a global variable) as an argument, it is the responsibility of the application to ensure that the object is available to the Windows Sockets implementation throughout the operation. The application must not invoke any Windows function which might affect the mapping or addressability of the memory involved. In a multithreaded system, the application is also responsible for coordinating access to the object using appropriate

111# WinSockOverview_BlockingNonBlocking

112\$ Blocking/Non blocking & Data Volatility

113+ WinSockOver:0020

114^K Sockets

Appendix C: Background Information 31

synchronization mechanisms. A Windows Sockets implementation cannot, and will not, address these issues. The possible consequences of failing to observe these rules are beyond the scope of this specification.

32 Appendix C: Background Information

#¹¹⁵ \$¹¹⁶ +¹¹⁷ K¹¹⁸ K¹¹⁹ **Socket Library Overview**

Database Functions

The Windows Sockets specification defines the following "database" routines. As noted earlier, a Windows Sockets supplier may choose to implement these in a manner which does not depend on local database files. The pointer returned by certain database routines such as **gethostbyname()** points to a structure which is allocated by the Windows Sockets library. The data which is pointed to is volatile and is good only until the next Windows Sockets API call from that thread. Additionally, the application must never attempt to modify this structure or to free any of its components. Only one copy of this structure is allocated for a thread, and so the application should copy any information which it needs before issuing any other Windows Sockets API calls.

<u>gethostbyaddr()</u>	Retrieve the name(s) and address corresponding to a network address.
<u>gethostbyname()</u>	Retrieve the name(s) and address corresponding to a host name.
<u>getprotobyname()</u>	Retrieve the protocol name and number corresponding to a protocol name.
<u>getprotobynumber()</u>	Retrieve the protocol name and number corresponding to a protocol number.
<u>getservbyname()</u>	Retrieve the service name and port corresponding to a service name.
<u>getservbyport()</u>	Retrieve the service name and port corresponding to a port.

115# WinSockOverview_DatabaseFunctions

116\$ Database Functions

117+ WinSockOver:0030

118^K Socket Functions

119^K Database Functions

#¹²⁰ \$¹²¹ +¹²² K¹²³ K¹²⁴ **Socket Library Overview**

Microsoft Windows-specific Extension Functions

The Windows Sockets specification provides a number of extensions to the standard set of Berkeley Sockets routines. Principally, these extended APIs allow message-based, asynchronous access to network events. While use of this extended API set is not mandatory for socket-based programming, it is recommended for conformance with the Microsoft Windows programming paradigm.

- Asynchronous select() Mechanism**
- Asynchronous Support Routines**
- Hooking Blocking Methods**
- Error Handling**

- WSAAsyncGetHostByAddr()**
- WSAAsyncGetHostByName()**
- WSAAsyncGetProtoByName()**
- WSAAsyncGetProtoByNumber()**

- WSAAsyncGetServByName()**
- WSAAsyncGetServByPort()**
- WSAAsyncSelect()**
- WSACancelAsyncRequest()**

- WSACancelBlockingCall()**
- WSACleanup()**

- WSAGetLastError()**
- WSAIsBlocking()**

- WSASetBlockingHook()**

- WSASetLastError()**

- WSAStartup()**
- WSAUnhookBlockingHook()**

A set of functions which provide asynchronous versions of the standard Berkeley **getXbyY()** functions. For example, the **WSAAsyncGetHostByName()** function provides an asynchronous message based implementation of the standard Berkeley **gethostbyname()** function.

Perform asynchronous version of **select()**

Cancel an outstanding instance of a **WSAAsyncGetXByY()** function.

Cancel an outstanding "blocking" API call

Sign off from the underlying Windows Sockets DLL.

Obtain details of last Windows Sockets API error

Determine if the underlying Windows Sockets DLL is already blocking an existing call for this thread

"Hook" the blocking method used by the underlying Windows Sockets implementation

Set the error to be returned by a subsequent **WSAGetLastError()**

Initialize the underlying Windows Sockets DLL.

Restore the original blocking function

120# WinSockOverview_WindowsSpecific
 121\$ Microsoft Windows-specific Extension Functions
 122+ WinSockOver:0040
 123^K Socket Functions
 124^K Windows Extensions

34 Appendix C: Background Information

#¹²⁵ \$¹²⁶ +¹²⁷ K¹²⁸ K¹²⁹ Microsoft Windows Extension Functions

Asynchronous select() Mechanism

The WSAAsyncSelect() API allows an application to register an interest in one or many network events. This API is provided to supersede the need to do polled network I/O. Any situation in which select() or non-blocking I/O routines (such as send() and recv()) are either already used or are being considered is usually a candidate for the WSAAsyncSelect() API. When declaring interest in such condition(s), you supply a window handle to be used for notification. The corresponding window then receives message-based notification of the conditions in which you declared an interest.

WSAAsyncSelect() allows interest to be declared in the following conditions for a particular socket:

- Socket readiness for reading
- Socket readiness for writing
- Out-of-band data ready for reading
- Socket readiness for accepting incoming connection
- Completion of non-blocking connect()
- Connection closure

- 125# WinSockWindows_AsyncSelect
- 126\$ Asynchronous select() Mechanism
- 127+ WinSockWin:0010
- 128^K Socket Functions
- 129^K Windows Extensions

#¹³⁰ \$¹³¹ +¹³² K¹³³ K¹³⁴ **Microsoft Windows Extension Functions**

Asynchronous Support Routines

The asynchronous "database" functions allow applications to request information in an asynchronous manner. Some network implementations and/or configurations perform network based operations to resolve such requests. The **WSAAsyncGetXByY()** functions allow application developers to request services which would otherwise block the operation of the whole Windows environment if the standard Berkeley function were used. The **WSACancelAsyncRequest()** function allows an application to cancel any outstanding asynchronous request.

130# WinSockWindows_AsyncSupport
131\$ Asynchronous Support Routines
132+ WinSockWin:0020
133^K Socket Functions
134^K Windows Extensions

36 Appendix C: Background Information

#¹³⁵ \$¹³⁶ +¹³⁷ K¹³⁸ Microsoft Windows Extension Functions

Hooking Blocking Methods

As noted in [Blocking/Non blocking & Data Volatility](#), Windows Sockets implements blocking operations in such a way that Windows message processing can continue, which may result in the application which issued the call receiving a Windows message. In certain situations an application may want to influence or change the way in which this pseudo-blocking process is implemented. The [WSASetBlockingHook\(\)](#) provides the ability to substitute a named routine which the Windows Sockets implementation is to use when relinquishing the processor during a "blocking" operation.

135# WinSockWindows_HookingBlocking

136\$ Hooking Blocking Methods

137+ WinSockWin:0030

138^K Windows Extensions

#¹³⁹ \$¹⁴⁰ +¹⁴¹ K¹⁴² **Microsoft Windows Extension Functions**

Error Handling

For compatibility with thread-based environments, details of API errors are obtained through the **WSAGetLastError()** API. Although the accepted "Berkeley-Style" mechanism for obtaining socket-based network errors is via "errno", this mechanism cannot guarantee the integrity of an error ID in a multi-threaded environment. **WSAGetLastError()** allows you to retrieve an error code on a per thread basis.

WSAGetLastError() returns error codes which avoid conflict with standard Microsoft C error codes. Certain error codes returned by certain Windows Sockets routines fall into the standard range of error codes as defined by Microsoft C. If you are NOT using an application development environment which defines error codes consistent with Microsoft C, you are advised to use the Windows Sockets error codes prefixed by "WSA" to ensure accurate error code detection.

Note that this specification defines a recommended set of error codes, and lists the possible errors which may be returned as a result of each function. It may be the case in some implementations that other Windows Sockets error codes will be returned in addition to those listed, and applications should be prepared to handle errors other than those enumerated under each API description. However a Windows Sockets implementation must not return any value which is not enumerated in the table of legal Windows Sockets errors given in Appendix A.1.

- 139# WinSockWindows_ErrorHandling
- 140\$ Error Handling
- 141+ WinSockWin:0040
- 142^K Windows Extensions

38 Appendix C: Background Information

#¹⁴³ \$¹⁴⁴ +¹⁴⁵ K¹⁴⁶ Windows Sockets

Socket Library Reference

Socket Routines

Database Routines

Microsoft Windows-specific Extensions

143# WinSock_SocketLibraryReference

144\$ Socket Library Reference

145+ WinSock:0040

146^K Socket Library Reference

#¹⁴⁷ \$¹⁴⁸ +¹⁴⁹ **Socket Library Reference****Socket Routines**

This chapter presents the socket library routines in alphabetical order, and describes each routine in detail.

In each routine it is indicated that the header file **winsoc.h** must be included. Appendix [Header Files](#) lists the Berkeley-compatible header files which are supported. These are provided for compatibility purposes only, and each of them will simply include **winsoc.h**. The Windows header file **windows.h** is also needed, but **winsoc.h** will include it if necessary.

[accept\(\)](#)
[bind\(\)](#)
[closesocket\(\)](#)
[connect\(\)](#)
[getpeername\(\)](#)
[getsockname\(\)](#)
[getsockopt\(\)](#)
[htonl\(\)](#)
[htons\(\)](#)
[inet_addr\(\)](#)
[inet_ntoa\(\)](#)
[ioctlsocket\(\)](#)
[listen\(\)](#)
[ntohl\(\)](#)
[ntohs\(\)](#)
[recv\(\)](#)
[recvfrom\(\)](#)
[select\(\)](#)
[send\(\)](#)
[sendto\(\)](#)
[setsockopt\(\)](#)
[shutdown\(\)](#)
[socket\(\)](#)

147# WinSockRef_SocketRoutines

148\$ Socket Routines

149+ WinSockRef:0010

40 Appendix C: Background Information

#₁₅₀ \$₁₅₁ +₁₅₂ K₁₅₃ Windows Sockets - Socket Routines

accept()

Description Accept a connection on a socket.

```
#include <winsock.h>
```

```
SOCKET accept ( SOCKET s, struct sockaddr FAR * addr, int FAR * addrlen );
```

s A descriptor identifying a socket which is listening for connections after a **listen()**.

addr The address of the connecting entity, as known to the communications layer. The exact format of the *addr* argument is determined by the address family established when the socket was created.

addrlen A pointer to an integer which contains the length of the address *addr*.

Remarks This routine extracts the first connection on the queue of pending connections on *s*, creates a new socket with the same properties as *s* and returns a handle to the new socket. If no pending connections are present on the queue, and the socket is not marked as non-blocking, **accept()** blocks the caller until a connection is present. If the socket is marked non-blocking and no pending connections are present on the queue, **accept()** returns an error as described below. The accepted socket may not be used to accept more connections. The original socket remains open.

The argument *addr* is a result parameter that is filled in with the address of the connecting entity, as known to the communications layer. The exact format of the *addr* parameter is determined by the address family in which the communication is occurring. The *addrlen* is a value-result parameter; it should initially contain the amount of space pointed to by *addr*; on return it will contain the actual length (in bytes) of the address returned. This call is used with connection-based socket types such as SOCK_STREAM.

Return Value If no error occurs, **accept()** returns a value of type SOCKET which is a descriptor for the accepted packet. Otherwise, a value of INVALID_SOCKET is returned, and a specific error code may be retrieved by calling **WSAGetLastError()**.

The integer referred to by *addrlen* initially contains the amount of space pointed to by *addr*. On return it will contain the actual length in bytes of the address returned.

150# WinSock_Accept
151\$ accept()
152+ WinSockSR:0010
153K accept()

Appendix C: Background Information 41

Error Codes	WSANOTINITIALISED	A successful <u>WSAStartup()</u> must occur before using this API.
	WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
	WSAEFAULT	The address in the <code>addr</code> argument is the wrong size.
	WSAEINTR	The (blocking) call was canceled via <u>WSACancelBlockingCall()</u>
	WSAEINPROGRESS	A blocking Windows Sockets call is in progress.
	WSAEINVAL	<u>listen()</u> was not invoked prior to <code>accept()</code> .
	WSAEMFILE	The queue is empty upon entry to <code>accept()</code> and there are no descriptors available.
	WSAENOBUFS	No buffer space is available.
	WSAENOTSOCK	The descriptor is not a socket.
	WSAEOPNOTSUPP	The referenced socket is not a type that supports connection-oriented service.
	WSAEWOULDBLOCK	The socket is marked as non-blocking and no connections are present to be accepted.
See Also	<u>bind()</u>, <u>connect()</u>, <u>listen()</u>, <u>select()</u>, <u>socket()</u>, <u>WSAAsyncSelect()</u>	

42 Appendix C: Background Information

#154 \$155 +156 K157 Windows Sockets - Socket Routines

bind()

Description Associate a local address with a socket.

```
#include <winsock.h>
```

```
int bind ( SOCKET s, struct sockaddr FAR * name, int namelen );
```

s A descriptor identifying an unbound socket.

name The address to assign to the socket. The sockaddr structure is defined as follows:

```
struct sockaddr {  
    u_short sa_family;  
    char sa_data[14];  
};
```

namelen The length of the *name*.

Remarks This routine is used on an unconnected datagram or stream socket, before subsequent **connect()**s or **listen()**s. When a socket is created with **socket()**, it exists in a name space (address family), but it has no name assigned. **bind()** establishes the local association (host address/port number) of the socket by assigning a local name to an unnamed socket.

If an application does not care what address is assigned to it, it may specify an Internet address and port equal to 0. If this is the case, the Windows Sockets implementation will assign a unique address to the application. The application may use **getsockname()** after **bind()** to learn the address that has been assigned to it.

In the Internet address family, a name consists of several components. For SOCK_DGRAM and SOCK_STREAM, the name consists of three parts: a host address, the protocol number (set implicitly to UDP or TCP, respectively), and a port number which identifies the application.

Return Value If no error occurs, **bind()** returns 0. Otherwise, it returns SOCKET_ERROR, and a specific error code may be retrieved by calling **WSAGetLastError()**.

Error Codes WSANOTINITIALISED A successful **WSAStartup()** must occur before using this API.

154# WinSock_Bind

155\$ bind()

156+ WinSockSR:0020

157K bind()

Appendix C: Background Information 43

WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
WSAEADDRINUSE	The specified address is already in use. (See the SO_REUSEADDR socket option under <u>setsockopt()</u> .)
WSAEFAULT	The <i>namelen</i> argument is too small (less than the size of a struct sockaddr).
WSAEINTR	The (blocking) call was canceled via <u>WSACancelBlockingCall()</u>
WSAEINPROGRESS	A blocking Windows Sockets call is in progress.
WSAEAFNOSUPPORT	The specified address family is not supported by this protocol.
WSAEINVAL	The socket is already bound to an address.
WSAENOBUFS	Not enough buffers available, too many connections.
WSAENOTSOCK	The descriptor is not a socket.

See Also

[connect\(\)](#), [listen\(\)](#), [getsockname\(\)](#), [setsockopt\(\)](#), [socket\(\)](#), [WSACancelBlockingCall\(\)](#).

44 Appendix C: Background Information

#158 \$159 +160 K161 Windows Sockets - Socket Routines

closesocket()

Description Close a socket.

```
#include <winsock.h>
```

```
int closesocket ( SOCKET s );
```

s _____ A descriptor identifying a socket.

Remarks This function closes a socket. More precisely, it releases the socket descriptor *s*, so that further references to *s* will fail with the error WSAENOTSOCK. If this is the last reference to the underlying socket, the associated naming information and queued data are discarded.

The semantics of **closesocket()** are affected by the socket options SO_LINGER and SO_DONTLINGER as follows:

Option	Interval	Type of close	Wait for close?
SO_DONTLINGER	Don't care	Graceful	No
SO_LINGER	Zero	Hard	No
SO_LINGER	Non-zero	Graceful	Yes

If SO_LINGER is set (i.e. the *L_onoff* field of the linger structure is non-zero; see sections 2.4, 4.1.8 and 4.1.20) with a zero timeout interval (*L_linger* is zero), **closesocket()** is not blocked even if queued data has not yet been sent or acknowledged. This is called a "hard" close, because the socket is closed immediately, and any unsent data is lost.

If SO_LINGER is set with a non-zero timeout interval, the **closesocket()** call blocks until the remaining data has been sent or until the timeout expires. This is called a graceful disconnect.

If SO_DONTLINGER is set on a stream socket (i.e. the *L_onoff* field of the linger structure is zero; see sections 2.4, 4.1.8 and 4.1.20), the **closesocket()** call will return immediately. However, any data queued for transmission will be sent if possible before the underlying socket is closed. This is also called a graceful disconnect. Note that in this case the Windows Sockets implementation may not release the socket and other resources for an arbitrary period, which may affect applications which expect to use all available sockets.

Return Value If no error occurs, **closesocket()** returns 0. Otherwise, a value of SOCKET_ERROR is returned, and a specific error code may be retrieved by calling **WSAGetLastError()**.

158# WinSock_CloseSocket

159\$ closesocket()

160+ WinSockSR:0030

161^K closesocket()

Appendix C: Background Information 45

Error Codes	WSANOTINITIALISED	A successful <u>WSAStartup()</u> must occur before using this API.
	WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
	WSAENOTSOCK	The descriptor is not a socket.
	WSAEINPROGRESS	A blocking Windows Sockets call is in progress.
See Also	<u>accept()</u> , <u>socket()</u> , <u>ioctlsocket()</u> , <u>setsockopt()</u> , <u>WSAAsyncSelect()</u> .	

46 Appendix C: Background Information

#162 \$163 +164 K165 Windows Sockets - Socket Routines

connect()

Description Establish a connection to a peer.

```
#include <winsock.h>
```

```
int connect ( SOCKET s, struct sockaddr FAR * name, int namelen );
```

s _____ A descriptor identifying an unconnected socket.

name _____ The name of the peer to which the socket is to be connected.

namelen _____ The length of the *name*.

Remarks This function is used to create a connection to the specified foreign association. The parameter *s* specifies an unconnected datagram or stream socket. If the socket is unbound, unique values are assigned to the local association by the system, and the socket is marked as bound. Note that if the address field of the *name* structure is all zeroes, **connect()** will return the error WSAEADDRNOTAVAIL.

For stream sockets (type SOCK_STREAM), an active connection is initiated to the foreign host using *name* (an address in the name space of the socket). When the socket call completes successfully, the socket is ready to send/receive data.

For a datagram socket (type SOCK_DGRAM), a default destination is set, which will be used on subsequent **send()** and **recv()** calls.

Return Value If no error occurs, **connect()** returns 0. Otherwise, it returns SOCKET_ERROR, and a specific error code may be retrieved by calling **WSAGetLastError()**.

Error Codes	WSANOTINITIALISED	A successful WSAStartup() must occur before using this API.
	WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
	WSAEADDRINUSE	The specified address is already in use.
	WSAEINTR	The (blocking) call was canceled via WSACancelBlockingCall()
	WSAEINPROGRESS	A blocking Windows Sockets call is in progress.

162# WinSock_Connect

163\$ connect()

164+ WinSockSR:0040

165^K connect()

Appendix C: Background Information 47

WSAEADDRNOTAVAIL	The specified address is not available from the local machine.
WSAEAFNOSUPPORT	Addresses in the specified family cannot be used with this socket.
WSAECONNREFUSED	The attempt to connect was forcefully rejected.
WSAEDESTADDRREQ	A destination address is required.
WSAEFAULT	The <i>namelen</i> argument is incorrect.
WSAEINVAL	The socket is not already bound to an address.
WSAEISCONN	The socket is already connected.
WSAEMFILE	No more file descriptors are available.
WSAENETUNREACH	The network can't be reached from this host at this time.
WSAENOBUFS	No buffer space is available. The socket cannot be connected.
WSAENOTSOCK	The descriptor is not a socket.
WSAETIMEDOUT	Attempt to connect timed out without establishing a connection
WSAEINPROGRESS	The socket is marked as non-blocking and the connection cannot be completed immediately. It is possible to <u>select()</u> the socket while it is connecting by <u>select()</u> ing it for writing.

See Also [accept\(\)](#), [bind\(\)](#), [getsockname\(\)](#), [socket\(\)](#).

48 Appendix C: Background Information

#₁₆₆ \$₁₆₇ +₁₆₈ K₁₆₉ Windows Sockets - Socket Routines

getpeername()

Description Get the address of the peer to which a socket is connected.

#include <winsock.h>

int getpeername(SOCKET *s*, struct sockaddr FAR * *name*, int FAR * *namelen*);

s _____ A descriptor identifying a connected socket.

name _____ The structure which is to receive the name of the peer.

namelen _____ A pointer to the size of the *name* structure.

Remarks **getpeername()** retrieves the name of the peer connected to the socket *s* and stores it in the struct sockaddr identified by *name*. It is used on a connected datagram or stream socket.

On return, the *namelen* argument contains the actual size of the name returned in bytes.

Return Value If no error occurs, **getpeername()** returns 0. Otherwise, a value of SOCKET_ERROR is returned, and a specific error code may be retrieved by calling **WSAGetLastError()**.

Error Codes	WSANOTINITIALISED	A successful WSAStartup() must occur before using this API.
	WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
	WSAEFAULT	The <i>namelen</i> argument is not large enough.
	WSAEINPROGRESS	A blocking Windows Sockets call is in progress.
	WSAENOTCONN	The socket is not connected.
	WSAENOTSOCK	The descriptor is not a socket.

See Also [bind\(\)](#), [socket\(\)](#), [getsockname\(\)](#).

166# WinSock_GetPeerName

167\$ getpeername()

168+ WinSockSR:0050

169K getpeername()

#170 \$171 +172 K173 **Windows Sockets - Socket Routines**

getsockname()

Description Get the local name for a socket.

#include <winsock.h>

int getsockname(SOCKET s, struct sockaddr FAR * name, int FAR * namelen);

s _____ A descriptor identifying a bound socket.

name _____ The name of the socket.

namelen _____ The size of the *name* array.

Remarks **getsockname()** retrieves the current name for the specified socket descriptor in *name*. It is used on a bound and/or connected socket specified by the *s* parameter. The local association is returned. This call is especially useful when a **connect()** call has been made without doing a **bind()** first; this call provides the only means by which you can determine the local association which has been set by the system.

On return, the *namelen* argument contains the actual size of the name returned in bytes.

Return Value If no error occurs, **getsockname()** returns 0. Otherwise, a value of SOCKET_ERROR is returned, and a specific error code may be retrieved by calling **WSAGetLastError()**.

Error Codes	WSANOTINITIALISED	A successful WSAStartup() must occur before using this API.
	WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
	WSAEFAULT	The <i>namelen</i> argument is not large enough.
	WSAEINPROGRESS	A blocking Windows Sockets operation is in progress.
	WSAENOTSOCK	The descriptor is not a socket.

See Also [bind\(\)](#), [socket\(\)](#).

- 170# WinSock_GetSockName
- 171\$ getsockname()
- 172+ WinSockSR:0060
- 173K getsockname()

50 Appendix C: Background Information

#174 \$175 +176 K177 **Windows Sockets - Socket Routines**

getsockopt()

Description Retrieve a socket option.

#include <winsock.h>

int getsockopt (SOCKET s, int level, int optname, char FAR * optval, int FAR * optlen);

s _____ A descriptor identifying a socket.

level _____ The level at which the option is defined; the only supported *level* is SOL_SOCKET.

optname _____ The socket option for which the value is to be retrieved.

optval _____ A pointer to the buffer in which the value for the requested option is to be returned.

optlen _____ A pointer to the size of the *optval* buffer.

Remarks **getsockopt()** retrieves the current value for a socket option associated with a socket of any type, in any state, and stores the result in *optval*. Options may exist at multiple protocol levels, but they are always present at the uppermost "socket" level. Options affect socket operations, such as whether an operation blocks or not, the routing of packets, out-of-band data transfer, etc.

The value associated with the selected option is returned in the buffer *optval*. The integer pointed to by *optlen* should originally contain the size of this buffer; on return, it will be set to the size of the value returned. For SO_LINGER, this will be the size of a struct linger; for all other options it will be the size of an integer.

If the option was never set with **setsockopt()**, then **getsockopt()** returns the default value for the option.

The following options are supported for **getsockopt()**. The Type identifies the type of data addressed by *optval*.

Value	Type	Meaning
SO_ACCEPTCON	BOOL	Socket is listen() ing.
SO_BROADCAST	BOOL	Socket is configured for the transmission of broadcast messages.
SO_DEBUG	BOOL	Debugging is enabled.

174# WinSock_GetSockOpt

175\$ getsockopt()

176+ WinSockSR:0070

177K getsockopt()

52 Appendix C: Background Information

<u>SO_DONTLINGER</u>	<u>BOOL</u>	<u>If true, the SO_LINGER option is disabled..</u>
<u>SO_DONTRROUTE</u>	<u>BOOL</u>	<u>Routing is disabled.</u>
<u>SO_ERROR</u>	<u>int</u>	<u>Retrieve error status and clear.</u>
<u>SO_KEEPALIVE</u>	<u>BOOL</u>	<u>Keepalives are being sent.</u>
<u>SO_LINGER</u>	<u>struct linger FAR *</u>	<u>Returns the current linger options.</u>
<u>SO_OOINLINE</u>	<u>BOOL</u>	<u>Out-of-band data is being received in the normal data stream.</u>
<u>SO_RCVBUF</u>	<u>int</u>	<u>Buffer size for receives</u>
<u>SO_REUSEADDR</u>	<u>BOOL</u>	<u>The socket may be bound to an address which is already in use.</u>
<u>SO_SNDBUF</u>	<u>int</u>	<u>Buffer size for sends</u>
<u>SO_TYPE</u>	<u>int</u>	<u>The type of the socket (e.g. SOCK_STREAM).</u>

Options not supported for **getsockopt()** are:

Value	Type	Meaning
<u>SO_RCVLOWAT</u>	<u>int</u>	<u>Receive low water mark</u>
<u>SO_RCVTIMEO</u>	<u>int</u>	<u>Receive timeout</u>
<u>SO_SNDLOWAT</u>	<u>int</u>	<u>Send low water mark</u>
<u>SO_SNDTIMEO</u>	<u>int</u>	<u>Send timeout</u>

Calling **getsockopt()** with an unsupported option will result in an error code of **WSAENOPROTOOPT** being returned from **WSAGetLastError()**.

Return Value	If no error occurs, getsockopt() returns 0. Otherwise, a value of SOCKET_ERROR is returned, and a specific error code may be retrieved by calling WSAGetLastError() .	
Error Codes	WSANOTINITIALISED	A successful WSAStartup() must occur before using this API.
	WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
	WSAEFAULT	The <i>optlen</i> argument was invalid.
	WSAEINPROGRESS	A blocking Windows Sockets operation is in progress.
	WSAENOPROTOOPT	The option is unknown or unsupported. In particular, SO_BROADCAST is not supported on sockets of type SOCK_STREAM , while SO_ACCEPTCON , SO_DONTLINGER , SO_KEEPALIVE , SO_LINGER and SO_OOINLINE are not supported on sockets of type SOCK_DGRAM .
	WSAENOTSOCK	The descriptor is not a socket.

See Also [setsockopt\(\)](#), [WSAAsyncSelect\(\)](#), [socket\(\)](#).

54 Appendix C: Background Information

#¹⁷⁸ \$¹⁷⁹ +¹⁸⁰ K¹⁸¹ **Windows Sockets - Socket Routines**

htonl()

Description Convert a **u_long** from host to network byte order.

```
#include <winsock.h>
```

```
u_long htonl ( u_long hostlong );
```

hostlong _____ A 32-bit number in host byte order.

Remarks This routine takes a 32-bit number in host byte order and returns a 32-bit number in network byte order.

Return Value **htonl()** returns the value in network byte order.

See Also [htons\(\)](#), [ntohl\(\)](#), [ntohs\(\)](#).

178# WinSock_HtoNL

179\$ htonl()

180+ WinSockSR:0080

181^K htonl()

#¹⁸² \$¹⁸³ +¹⁸⁴ K¹⁸⁵ **Windows Sockets - Socket Routines**

htons()

Description Convert a **u_short** from host to network byte order.

#include <winsock.h>

u_short htons (**u_short** *hostshort*);

hostshort _____ A 16-bit number in host byte order.

Remarks This routine takes a 16-bit number in host byte order and returns a 16-bit number in network byte order.

Return Value **htons()** returns the value in network byte order.

See Also [htonl\(\)](#), [ntohl\(\)](#), [ntohs\(\)](#).

182# WinSock_HtoNS
183\$ htons()
184+ WinSockSR:0090
185K htons()

56 Appendix C: Background Information

#¹⁸⁶ \$¹⁸⁷ +¹⁸⁸ K¹⁸⁹ Windows Sockets - Socket Routines

inet_addr()

Description Convert a string containing a dotted address into an `in_addr`.

```
#include <winsock.h>
```

```
struct in_addr inet_addr ( char FAR * cp );
```

cp _____ A character string representing a number expressed in the Internet standard "." notation.

Remarks This function interprets the character string specified by the *cp* parameter. This string represents a numeric Internet address expressed in the Internet standard "." notation. The value returned is a number suitable for use as an Internet address. All Internet addresses are returned in network order (bytes ordered from left to right).

Internet Addresses

Values specified using the "." notation take one of the following forms:

a.b.c.d a.b.c a.b a

When four parts are specified, each is interpreted as a byte of data and assigned, from left to right, to the four bytes of an Internet address. Note that when an Internet address is viewed as a 32-bit integer quantity on the Intel architecture, the bytes referred to above appear as "d.c.b.a". That is, the bytes on an Intel processor are ordered from right to left.

Note: The following notations are only used by Berkeley, and nowhere else on the Internet. In the interests of compatibility with their software, they are supported as specified.

When a three part address is specified, the last part is interpreted as a 16-bit quantity and placed in the right most two bytes of the network address. This makes the three part address format convenient for specifying Class B network addresses as "128.net.host".

When a two part address is specified, the last part is interpreted as a 24-bit quantity and placed in the right most three bytes of the network address. This makes the two part address format convenient for specifying Class A network addresses as "net.host".

When only one part is given, the value is stored directly in the network address without any byte rearrangement.

186# WinSock_InetAddr

187\$ inet_addr()

188+ WinSockSR:0100

189^K inet_addr()

Appendix C: Background Information 57

Return Value If no error occurs, **inet_addr()** returns an `in_addr` structure containing a suitable binary representation of the Internet address given. Otherwise, it returns the value `INADDR_NONE`.

See Also [inet_ntoa\(\)](#)

58 Appendix C: Background Information

#¹⁹⁰ \$¹⁹¹ +¹⁹² K¹⁹³ **Windows Sockets - Socket Routines**

inet_ntoa()

Description Convert a network address into a string in dotted format.

```
#include <winsock.h>
```

```
char FAR * inet_ntoa ( struct in_addr in );
```

in _____ A structure which represents an Internet host address.

Remarks This function takes an Internet address structure specified by the *in* parameter. It returns an ASCII string representing the address in "." notation as "a.b.c.d". Note that the string returned by **inet_ntoa()** resides in memory which is allocated by the Windows Sockets implementation. The application should not make any assumptions about the way in which the memory is allocated. The data is guaranteed to be valid until the next Windows Sockets API call within the same thread, but no longer.

Return Value If no error occurs, **inet_ntoa()** returns a char pointer to a static buffer containing the text address in standard "." notation. Otherwise, it returns NULL. The data should be copied before another Windows Sockets call is made.

See Also [inet_addr\(\)](#).

190# WinSock_InetNtoA

191\$ inet_ntoa()

192+ WinSockSR:0110

193K inet_ntoa()

#₁₉₄ \$₁₉₅ +₁₉₆ K₁₉₇ **Windows Sockets - Socket Routines**

ioctlsocket()

Description Control the mode of a socket.

#include <winsock.h>

int ioctlsocket (SOCKET s, long cmd, u_long FAR * argp);

s _____ A descriptor identifying a socket.

cmd _____ The command to perform on the socket *s*.

argp _____ A pointer to a parameter for *cmd*.

Remarks This routine may be used on any socket in any state. It is used to get or retrieve operating parameters associated with the socket, independent of the protocol and communications subsystem. The following commands are supported:

Command	Semantics
FIONBIO	Enable or disable non-blocking mode on the socket <i>s</i> . <i>argp</i> points at an unsigned long , which is non-zero if non-blocking mode is to be enabled and zero if it is to be disabled. When a socket is created, it operates in blocking mode (i.e. non-blocking mode is disabled). This is consistent with BSD sockets.
FIONREAD	Determine the amount of data which can be read atomically from socket <i>s</i> . <i>argp</i> points at an unsigned long in which ioctlsocket() stores the result. If <i>s</i> is of type SOCK_STREAM, FIONREAD returns the total amount of data which may be read in a single recv() ; this is normally the same as the total amount of data queued on the socket. If <i>s</i> is of type SOCK_DGRAM, FIONREAD returns the size of the first datagram queued on the socket.
SIOCATMARK	Determine whether or not all out-of-band data has been read. This applies only to a socket of type SOCK_STREAM which has been configured for in-line reception of any out-of-band data (SO_OOBINLINE). If no out-of-band data is waiting to be read, the operation returns TRUE. Otherwise it returns FALSE, and the next recv() or recvfrom() performed on the socket will retrieve some or all of the data preceding the "mark"; the application should use the SIOCATMARK operation to determine whether any remains. If there is any normal data preceding the "urgent" (out of band) data, it will be received in order. (Note that a recv() or recvfrom() will never mix out-of-band and normal data in the same call.) <i>argp</i> points at a BOOL in which ioctlsocket() stores the result.

- 194# WinSock_IOCTLSocket
- 195\$ ioctlsocket()
- 196+ WinSockSR:0120
- 197K ioctlsocket()

60 Appendix C: Background Information

Compatibility This function is a subset of **ioctl()** as used in Berkeley sockets. In particular, there is no command which is equivalent to FIOASYNC, while SIOCATMARK is the only socket-level command which is supported.

Return Value Upon successful completion, the **ioctlsocket()** returns 0. Otherwise, a value of SOCKET_ERROR is returned, and a specific error code may be retrieved by calling **WSAGetLastError()**.

Error Codes	WSANOTINITIALISED	A successful WSAStartup() must occur before using this API.
	WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
	WSAEINVAL	<i>cmd</i> is not a valid command, or <i>arg</i> is not an acceptable parameter for <i>cmd</i> , or the command is not applicable to the type of socket supplied
	WSAEINPROGRESS	A blocking Windows Sockets operation is in progress.
	WSAENOTSOCK	The descriptor <i>s</i> is not a socket.

See Also [socket\(\)](#), [setsockopt\(\)](#), [getsockopt\(\)](#).

#198 \$199 +200 K201 **Windows Sockets - Socket Routines**

listen()

Description Establish a socket to listen for incoming connection.

#include <winsock.h>

int listen (SOCKET s, int backlog);

s _____ A descriptor identifying a bound, unconnected socket.

backlog _____ The maximum length to which the queue of pending connections may grow.

Remarks To accept connections, a socket is first created with **socket()**, a backlog for incoming connections is specified with **listen()**, and then the connections are accepted with **accept()**. **listen()** applies only to sockets that support connections, i.e. those of type SOCK_STREAM. The socket *s* is put into "passive" mode where incoming connections are acknowledged and queued pending acceptance by the process.

This function is typically used by servers that could have more than one connection request at a time: if a connection request arrives with the queue full, the client will receive an error with an indication of WSAECONNREFUSED.

listen() attempts to continue to function rationally when there are no available descriptors. It will accept connections until the queue is emptied. If descriptors become available, a later call to **listen()** or **accept()** will re-fill the queue to the current or most recent "backlog", if possible, and resume listening for incoming connections.

Compatibility *backlog* is currently limited (silently) to 5. As in 4.3BSD, illegal values (less than 1 or greater than 5) are replaced by the nearest legal value.

Return Value If no error occurs, **listen()** returns 0. Otherwise, a value of SOCKET_ERROR is returned, and a specific error code may be retrieved by calling **WSAGetLastError()**.

Error Codes	WSANOTINITIALISED	A successful WSAStartup() must occur before using this API.
	WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
	WSAEADDRINUSE	An attempt has been made to listen() on an address in use.

- 198# WinSock_Listen
- 199\$ listen()
- 200+ WinSockSR:0130
- 201K listen()

62 Appendix C: Background Information

WSAEINPROGRESS	A blocking Windows Sockets operation is in progress.
WSAEFAULT	An invalid argument was given.
WSAEINVAL	The socket has not been bound with <u>bind()</u> .
WSAEISCONN	The socket is already connected.
WSAEMFILE	No more file descriptors are available.
WSAENOBUFS	No buffer space is available.
WSAENOTSOCK	The descriptor is not a socket.
WSAEOPNOTSUPP	The referenced socket is not of a type that supports the listen() operation.

See Also [accept\(\)](#), [connect\(\)](#), [socket\(\)](#).

#²⁰² \$²⁰³ +²⁰⁴ K²⁰⁵ **Windows Sockets - Socket Routines**

ntohl()

Description Convert a **u_long** from network to host byte order.

#include <winsock.h>

u_long ntohl (**u_long** *netlong*);

netlong _____ A 32-bit number in network byte order.

Remarks This routine takes a 32-bit number in network byte order and returns a 32-bit number in host byte order.

Return Value **ntohl()** returns the value in host byte order.

See Also [htonl\(\)](#), [htons\(\)](#), [ntohs\(\)](#).

202# WinSock_NtoHL
203\$ ntohl()
204+ WinSockSR:0140
205K ntohl()

64 Appendix C: Background Information

#²⁰⁶ \$²⁰⁷ +²⁰⁸ K²⁰⁹ Windows Sockets - Socket Routines

ntohs()

Description Convert a `u_short` from network to host byte order.

```
#include <winsock.h>
```

```
u_short ntohs ( u_short netshort );
```

netshort _____ A 16-bit number in network byte order.

Remarks This routine takes a 16-bit number in network byte order and returns a 16-bit number in host byte order.

Return Value `ntohs()` returns the value in host byte order.

See Also [htonl\(\)](#), [htons\(\)](#), [ntohl\(\)](#).

206# WinSock_NtoHS
207\$ ntohs()
208+ WinSockSR:0150
209K ntohs()

#210 \$211 +212 K213 **Windows Sockets - Socket Routines**

recv()

Description Receive data from a socket.

#include <winsock.h>

int recv (int *s*, char FAR * *buf*, int *len*, int *flags*);

s _____ A descriptor identifying a connected socket.

buf _____ A buffer for the incoming data.

len _____ The length of *buf*.

flags _____ Specifies the way in which the call is made.

Remarks This function is used on connected datagram or stream sockets specified by the *s* parameter and is used to read incoming data.

For sockets of type SOCK_STREAM, as much information as is currently available up to the size of the buffer supplied is returned. If the socket has been configured for in-line reception of out-of-band data (socket option SO_OOBINLINE) and out-of-band data is unread, only out-of-band data will be returned. The application may use the **ioctlsocket()** SIOCATMARK to determine whether any more out-of-band data remains to be read.

For datagram sockets, data is extracted from the first enqueued datagram, up to the size of the size of the buffer supplied. If the datagram is larger than the buffer supplied, the excess data is lost.

If no incoming data is available at the socket, the **recv()** call waits for data to arrive unless the socket is non-blocking. In this case a value of SOCKET_ERROR is returned with the error code set to WSAEWOULDBLOCK. The **select()** or **WSAAsyncSelect()** calls may be used to determine when more data arrives.

Flags may be used to influence the behavior of the function invocation beyond the options specified for the associated socket. That is, the semantics of this function are determined by the socket options and the *flags* parameter. The latter is constructed by or-ing any of the following values:

Value	Meaning
MSG_PEEK	Peek at the incoming data. The data is copied into the buffer but is not removed from the input queue.

210# WinSock_Recv

211\$ recv()

212+ WinSockSR:0160

213K recv()

66 Appendix C: Background Information

MSG_OOB Process out-of-band data (See section 2.2.3 for a discussion of this topic.)

Return Value If no error occurs, **recv()** returns the number of bytes received. If the connection has been closed, it returns 0. Otherwise, a value of `SOCKET_ERROR` is returned, and a specific error code may be retrieved by calling **WSAGetLastError()**.

Error Codes	<code>WSANOTINITIALISED</code>	A successful <u>WSAStartup()</u> must occur before using this API.
	<code>WSAENETDOWN</code>	The Windows Sockets implementation has detected that the network subsystem has failed.
	<code>WSAENOTCONN</code>	The socket is not connected.
	<code>WSAEINTR</code>	The (blocking) call was canceled via <u>WSACancelBlockingCall()</u>
	<code>WSAEINPROGRESS</code>	A blocking Windows Sockets operation is in progress.
	<code>WSAENOTSOCK</code>	The descriptor is not a socket.
	<code>WSAEOPNOTSUPP</code>	<code>MSG_OOB</code> was specified, but the socket is not of type <code>SOCK_STREAM</code> .
	<code>WSAESHUTDOWN</code>	The socket has been shutdown; it is not possible to recv() on a socket after <u>shutdown()</u> has been invoked with <i>how</i> set to 0 or 2.
	<code>WSAEWOULDBLOCK</code>	The socket is marked as non-blocking and the receive operation would block.

See Also [recvfrom\(\)](#), [read\(\)](#), [send\(\)](#), [select\(\)](#), [WSAAsyncSelect\(\)](#), [socket\(\)](#)

#²¹⁴ \$²¹⁵ +²¹⁶ K²¹⁷ **Windows Sockets - Socket Routines**

recvfrom()

Description Receive a datagram and store the source address.

#include <winsock.h>

int recvfrom (int *s*, char FAR * *buf*, int *len*, int *flags*, struct sockaddr FAR * *from*, int FAR * *fromlen*);

- s* _____ A descriptor identifying a bound socket.
- buf* _____ A buffer for the incoming data.
- len* _____ The length of *buf*.
- flags* _____ Specifies the way in which the call is made.
- from* _____ Points to a buffer which will hold the source address upon return.
- fromlen* _____ A pointer to the size of the *from* buffer.

Remarks This function is used to read incoming data on a (possibly connected) socket and capture the address from which the data was sent.

For sockets of type SOCK_STREAM, as much information as is currently available up to the size of the buffer supplied is returned. If the socket has been configured for in-line reception of out-of-band data (socket option SO_OOBINLINE) and out-of-band data is unread, only out-of-band data will be returned. The application may use the **ioctlsocket()** SIOCATMARK to determine whether any more out-of-band data remains to be read.

For datagram sockets, data is extracted from the first enqueued datagram, up to the size of the size of the buffer supplied. If the datagram is larger than the buffer supplied, the excess data is lost.

If *from* is non-zero, and the socket is of type SOCK_DGRAM, the network address of the peer which sent the data is copied to the corresponding struct sockaddr. The value pointed to by *fromlen* is initialized to the size of this structure, and is modified on return to indicate the actual size of the address stored there.

If no incoming data is available at the socket, the **recvfrom()** call waits for data to arrive unless the socket is non-blocking. In this case a value of SOCKET_ERROR is returned with the error code set to WSAEWOULDBLOCK.

214# WinSock_RecvFrom
 215\$ recvfrom()
 216+ WinSockSR:0170
 217K recvfrom()

68 Appendix C: Background Information

The **select()** or **WSAAsyncSelect()** calls may be used to determine when more data arrives.

Flags may be used to influence the behavior of the function invocation beyond the options specified for the associated socket. That is, the semantics of this function are determined by the socket options and the *flags* parameter. The latter is constructed by or-ing any of the following values:

Value	Meaning
MSG_PEEK	<u>Peek at the incoming data. The data is copied into the buffer but is not removed from the input queue.</u>
MSG_OOB	<u>Process out-of-band data (See section 2.2.3 for a discussion of this topic.)</u>

Return Value	If no error occurs, recvfrom() returns the number of bytes received. If the connection has been closed, it returns 0. Otherwise, a value of SOCKET_ERROR is returned, and a specific error code may be retrieved by calling WSAGetLastError() .	
Error Codes	WSANOTINITIALISED	A successful WSAStartup() must occur before using this API.
	WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
	WSAEFAULT	The <i>fromlen</i> argument was invalid: the <i>from</i> buffer was too small to accommodate the peer address.
	WSAEINTR	The (blocking) call was canceled via WSACancelBlockingCall()
	WSAEINPROGRESS	A blocking Windows Sockets operation is in progress.
	WSAEINVAL	The socket has not been bound with bind() .
	WSAENOTCONN	The socket is not connected (SOCK_STREAM only).
	WSAENOTSOCK	The descriptor is not a socket.
	WSAEOPNOTSUPP	MSG_OOB was specified, but the socket is not of type SOCK_STREAM .
	WSAESHUTDOWN	The socket has been shutdown; it is not possible to recvfrom() on a socket after shutdown() has been invoked with <i>how</i> set to 0 or 2.
	WSAEWOULDBLOCK	The socket is marked as non-blocking and the recvfrom() operation would block.
See Also	<u>recv()</u> , <u>send()</u> , <u>socket()</u> , <u>WSAAsyncSelect()</u> .	

70 Appendix C: Background Information

#²¹⁸ \$²¹⁹ +²²⁰ K²²¹ Windows Sockets - Socket Routines

select()

Description Determine the status of one or more sockets, waiting if necessary.

```
#include <winsock.h>
```

```
long select ( int nfds, fd_set FAR * readfds, fd_set FAR * writefds,  
fd_set FAR * exceptfds, struct timeval FAR * timeout );
```

nfds _____ This argument is ignored and included only for the sake of compatibility.

readfds _____ A set of sockets to be checked for readability.

writefds _____ A set of sockets to be checked for writeability.

exceptfds _____ A set of sockets to be checked for errors.

timeout _____ The maximum time for **select()** to wait, or NULL for blocking operation.

Remarks This function is used to determine the status of one or more sockets. For each socket, the caller may request information on read, write or error status. The set of sockets for which a given status is requested is indicated by an fd_set structure. Upon return, the structure is updated to reflect the subset of these sockets which meet the specified condition, and **select()** returns the number of sockets meeting the conditions. A set of macros is provided for manipulating an fd_set. These macros are compatible with those used in the Berkeley software, but the underlying representation is completely different.

The parameter *readfds* identifies those sockets which are to be checked for readability. If the socket is currently **listen()**ing, it will be marked as readable if an incoming connection request has been received, so that an **accept()** is guaranteed to complete without blocking. For other sockets, readability means that queued data is available for reading, so that a **recv()** or **recvfrom()** is guaranteed to complete without blocking. The presence of out-of-band data will be checked if the socket option SO_OOBINLINE has been enabled (see **setsockopt()**).

The parameter *writefds* identifies those sockets which are to be checked for writeability. If a socket is **connect()**ing (non-blocking), writeability means that the connection establishment is complete. For other sockets, writeability means that a **send()** or **sendto()** will complete without blocking. [It is not specified how long this guarantee can be assumed to be valid, particularly in a multithreaded environment.]

218# WinSock_Select

219\$ select()

220+ WinSockSR:0180

221^K select()

Appendix C: Background Information 71

The parameter *exceptfds* identifies those sockets which are to be checked for the presence of out-of-band data or any exceptional error conditions. Note that out-of-band data will only be reported in this way if the option `SO_OOBINLINE` is `FALSE`. For a `SOCK_STREAM`, the breaking of the connection by the peer or due to `KEEPALIVE` failure will be indicated as an exception. This specification does not define which other errors will be included.

Any of *readfds*, *writfds*, or *exceptfds* may be given as `NULL` if no descriptors are of interest.

Four macros are defined in the header file **winsock.h** for manipulating the descriptor sets. The variable `FD_SETSIZE` determines the maximum number of descriptors in a set. (The default value of `FD_SETSIZE` is 64, which may be modified by #defining `FD_SETSIZE` to another value before #including **winsock.h**.) Internally, an *fd_set* is represented as an array of `SOCKETs`; the last valid entry is followed by an element set to `INVALID_SOCKET`. The macros are:

FD_CLR(s, *set) Removes the descriptor *s* from *set*.

FD_ISSET(s, *set) Nonzero if *s* is a member of the *set*, zero otherwise.

FD_SET(s, *set) Adds descriptor *s* to *set*.

FD_ZERO(*set) Initializes the *set* to the `NULL` set.

The parameter *timeout* controls how long the **select()** may take to complete. If *timeout* is a null pointer, **select()** will block indefinitely until at least one descriptor meets the specified criteria. Otherwise, *timeout* points to a struct `timeval` which specifies the maximum time that **select()** should wait before returning. If the `timeval` is initialized to `{0, 0}`, **select()** will return immediately; this is used to "poll" the state of the selected sockets.

Return Value **select()** returns the total number of descriptors which are ready and contained in the *fd_set* structures, or 0 if the time limit expired.

Error Codes	<code>WSANOTINITIALISED</code>	A successful <u>WSAStartup()</u> must occur before using this API.
	<code>WSAENETDOWN</code>	The Windows Sockets implementation has detected that the network subsystem has failed.
	<code>WSAEINVAL</code>	The <i>timeout</i> value is not valid.
	<code>WSAEINTR</code>	The (blocking) call was canceled via <u>WSACancelBlockingCall()</u>
	<code>WSAEINPROGRESS</code>	A blocking Windows Sockets operation is in progress.
	<code>WSAENOTSOCK</code>	One of the descriptor sets contains an entry which is not a socket.

See Also **WSAAsyncSelect()**, **accept()**, **connect()**, **read()**, **write()**, **recv()**, **recvfrom()**, **send()**.

72 Appendix C: Background Information

#222 \$223 +224 K225 **Windows Sockets - Socket Routines**

send()

Description Send data on a connected socket.

#include <winsock.h>

int send (SOCKET s, char FAR * buf, int len, int flags);

s _____ A descriptor identifying a connected socket.

buf _____ A buffer containing the data to be transmitted.

len _____ The length of the data in *buf*.

flags _____ Specifies the way in which the call is made.

Remarks **send()** is used on connected datagram or stream sockets and is used to write outgoing data on a socket. For datagram sockets, care must be taken not to exceed the maximum IP packet size of the underlying subnets, which is given by the *iMaxUdpDg* element in the *WSAData* structure returned by **WSAStartup()**. If the data is too long to pass atomically through the underlying protocol the error *WSAEMSGSIZE* is returned, and the (truncated) data is transmitted.

Note that the successful completion of a **send()** does not indicate that the data was successfully delivered.

If no buffer space is available within the transport system to hold the data to be transmitted, **send()** will block unless the socket has been placed in a non-blocking I/O mode. On non-blocking *SOCK_STREAM* sockets, the number of bytes written may be between 1 and the requested length, depending on buffer availability on both the local and foreign hosts. The **select()** call may be used to determine when it is possible to send more data.

Flags may be used to influence the behavior of the function invocation beyond the options specified for the associated socket. That is, the semantics of this function are determined by the socket options and the *flags* parameter. The latter is constructed by or-ing any of the following values:

<u>Value</u>	<u>Meaning</u>
<u>MSG_DONTROUTE</u>	<u>Specifies that the data should not be subject to routing. A Windows Sockets supplier may choose to ignore this flag; see also the discussion of the <i>SO_DONTROUTE</i> option in section 2.4.</u>

- 222# WinSock_Send
- 223\$ send()
- 224+ WinSockSR:0190
- 225^K send()

74 Appendix C: Background Information

MSG_OOB Send out-of-band data (SOCK_STREAM only; see also section 2.2.3)

Return Value If no error occurs, **send()** returns the total number of characters sent. (Note that this may be less than the number indicated by *len*.) Otherwise, a value of SOCKET_ERROR is returned, and a specific error code may be retrieved by calling **WSAGetLastError()**.

Error Codes	WSANOTINITIALISED	A successful WSAStartup() must occur before using this API.
	WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
	WSAEACCES	The requested address is a broadcast address, but the appropriate flag was not set.
	WSAEINTR	The (blocking) call was canceled via WSACancelBlockingCall()
	WSAEINPROGRESS	A blocking Windows Sockets operation is in progress.
	WSAEFAULT	The <i>buf</i> is not in a valid part of the user address space.
	WSAENETRESET	The connection must be reset because the Windows Sockets implementation dropped it.
	WSAENOBUFS	The Windows Sockets implementation reports a buffer deadlock.
	WSAENOTCONN	The socket is not connected.
	WSAENOTSOCK	The descriptor is not a socket.
	WSAEOPNOTSUPP	MSG_OOB was specified, but the socket is not of type SOCK_STREAM.
	WSAESHUTDOWN	The socket has been shutdown; it is not possible to send() on a socket after shutdown() has been invoked with how set to 1 or 2.
	WSAEWOULDBLOCK	The socket is marked as non-blocking and the requested operation would block.
	WSAEMSGSIZE	The socket is of type SOCK_DGRAM, and the datagram is larger than the maximum supported by the Windows Sockets implementation.

See Also recv(), recvfrom(), socket(), sendto(), WSAStartup().

#₂₂₆ \$₂₂₇ +₂₂₈ K₂₂₉ **Windows Sockets - Socket Routines**

sendto()

Description Send data to a specific destination.

#include <winsock.h>

int sendto (SOCKET s, char FAR * buf, int len, int flags, struct sockaddr FAR * to, int tolen);

s _____ A descriptor identifying a socket.

buf _____ A buffer containing the data to be transmitted.

len _____ The length of the data in *buf*.

flags _____ Specifies the way in which the call is made.

to _____ A pointer to the address of the target socket.

tolen _____ The size of the address in *to*.

Remarks

sendto() is used on datagram or stream sockets and is used to write outgoing data on a socket. For datagram sockets, care must be taken not to exceed the maximum IP packet size of the underlying subnets, which is given by the *iMaxUdpDg* element in the WSADATA structure returned by **WSAStartup()**. If the data is too long to pass atomically through the underlying protocol the error WSAEMSGSIZE is returned, and the (truncated) data is transmitted.

Note that the successful completion of a **sendto()** does not indicate that the data was successfully delivered.

sendto() is normally used on a SOCK_DGRAM socket to send a datagram to a specific peer socket identified by the *to* parameter. On a connection-oriented socket, the *to* parameter is ignored; in this case the **sendto()** is equivalent to **send()**.

To send a broadcast (on a SOCK_DGRAM only), the address in the *to* parameter should be constructed using the special IP address INADDR_BROADCAST (defined in **winsock.h**) together with the intended port number. It is generally inadvisable for a broadcast datagram to exceed the size at which fragmentation may occur, which implies that the data portion of the datagram (excluding headers) should not exceed 512 bytes.

If no buffer space is available within the transport system to hold the data to be transmitted, **sendto()** will block unless the socket has been placed in a non-

226# WinSock_SendTo

227\$ sendto()

228+ WinSockSR:0200

229K sendto()

76 Appendix C: Background Information

blocking I/O mode. On non-blocking SOCK_STREAM sockets, the number of bytes written may be between 1 and the requested length, depending on buffer availability on both the local and foreign hosts. The select() call may be used to determine when it is possible to send more data.

Flags may be used to influence the behavior of the function invocation beyond the options specified for the associated socket. That is, the semantics of this function are determined by the socket options and the *flags* parameter. The latter is constructed by or-ing any of the following values:

Value	Meaning
<u>MSG_DONTROUTE</u>	<u>Specifies that the data should not be subject to routing. A Windows Sockets supplier may choose to ignore this flag; see also the discussion of the SO_DONTROUTE option in section 2.4.</u>
<u>MSG_OOB</u>	<u>Send out-of-band data (SOCK_STREAM only; see also section 2.2.3)</u>

Return Value If no error occurs, **sendto()** returns the total number of characters sent. (Note that this may be less than the number indicated by *len*.) Otherwise, a value of SOCKET_ERROR is returned, and a specific error code may be retrieved by calling WSAGetLastError().

Error Codes	WSANOTINITIALISED	A successful <u>WSAStartup()</u> must occur before using this API.
	WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
	WSAEACCES	The requested address is a broadcast address, but the appropriate flag was not set.
	WSAEINTR	The (blocking) call was canceled via <u>WSACancelBlockingCall()</u>
	WSAEINPROGRESS	A blocking Windows Sockets operation is in progress.
	WSAEFAULT	The <i>buf</i> or <i>to</i> are not in a valid part of the user address space.
	WSAENETRESET	The connection must be reset because the Windows Sockets implementation dropped it.
	WSAENOBUFS	The Windows Sockets implementation reports a buffer deadlock.
	WSAENOTCONN	The socket is not connected (SOCK_STREAM only).
	WSAENOTSOCK	The descriptor is not a socket.

Appendix C: Background Information 77

WSAEOPNOTSUPP	MSG_OOB was specified, but the socket is not of type SOCK_STREAM.
WSAESHUTDOWN	The socket has been shutdown; it is not possible to sendto() on a socket after shutdown() has been invoked with how set to 1 or 2.
WSAEWOULDBLOCK	The socket is marked as non-blocking and the requested operation would block.
WSAEMSGSIZE	The socket is of type SOCK_DGRAM, and the datagram is larger than the maximum supported by the Windows Sockets implementation.

See Also [recv\(\)](#), [recvfrom\(\)](#), [socket\(\)](#), [send\(\)](#), [WSAStartup\(\)](#).

78 Appendix C: Background Information

#²³⁰ \$²³¹ +²³² K²³³ Windows Sockets - Socket Routines

setsockopt()

Description Set a socket option.

```
#include <winsock.h>
```

```
int setsockopt ( SOCKET s, int level, int optname, char FAR * optval, int optlen );
```

s _____ A descriptor identifying a socket.

level _____ The level at which the option is defined; the only supported *level* is SOL_SOCKET.

optname _____ The socket option for which the value is to be set.

optval _____ A pointer to the buffer in which the value for the requested option is supplied.

optlen _____ A pointer to the size of the *optval* buffer.

Remarks

setsockopt() sets the current value for a socket option associated with a socket of any type, in any state. Although options may exist at multiple protocol levels, this specification only defines options that exist at the uppermost "socket" level. Options affect socket operations, such as whether expedited data is received in the normal data stream, whether broadcast messages may be sent on the socket, etc.

There are two types of socket options: Boolean options that enable or disable a feature or behavior, and options which require an integer value or structure. To enable a Boolean option, *optval* points to a nonzero integer. To disable the option *optval* points to an integer equal to zero. *optlen* should be equal to sizeof(int) for Boolean options. For other options, *optval* points to the an integer or structure that contains the desired value for the option, and *optlen* is the length of the integer or structure.

SO_LINGER controls the action taken when unsent data is queued on a socket and a **closesocket()** is performed. See **closesocket()** for a description of the way in which the SO_LINGER settings affect the semantics of **closesocket()**. The application sets the desired behavior by creating a *struct linger* (pointed to by the *optval* argument) with the following elements:

```
struct linger {
    int    l_onoff;
    int    l_linger;
```

230# WinSock_SetSockOpt

231\$ setsockopt()

232+ WinSockSR:0210

233K setsockopt()

Appendix C: Background Information 79

}

To enable SO_LINGER, the application should set *l_onoff* to a non-zero value, set *l_linger* to 0 or the desired timeout (in seconds), and call **setsockopt()**. To enable SO_DONTLINGER (i.e. disable SO_LINGER) *l_onoff* should be set to zero and **setsockopt()** should be called.

By default, a socket may not be bound (see **bind()**) to a local address which is already in use. On occasions, however, it may be desirable to "re-use" an address in this way. Since every connection is uniquely identified by the combination of local and remote addresses, there is no problem with having two sockets bound to the same local address as long as the remote addresses are different. To inform the Windows Sockets implementation that a **bind()** on a socket should not be disallowed because of address re-use, the application should set the SO_REUSEADDR socket option for the socket before issuing the **bind()**. Note that the option is interpreted only at the time of the **bind()**: it is therefore unnecessary (but harmless) to set the option on a socket which is not to be bound to an existing address, and setting or resetting the option after the **bind()** has no effect on this or any other socket..

An application may request that the Windows Sockets implementation enable the use of "keep-alive" packets on TCP connections by turning on the SO_KEEPALIVE socket option. A Windows Sockets implementation need not support the use of keep-alives: if it does, the precise semantics are implementation-specific but should conform to section 4.2.3.6 of RFC 1122: *Requirements for Internet Hosts -- Communication Layers*. If a connection is dropped as the result of "keep-alives" the error code WSAENETRESET is returned to any calls in progress on the socket, and any subsequent calls will fail with WSAENOTCONN.

The following options are supported for **setsockopt()**. The Type identifies the type of data addressed by *optval*.

Value	Type	Meaning
SO_BROADCAST	BOOL	Allow transmission of broadcast messages on the socket.
SO_DEBUG	BOOL	Record debugging information.
SO_DONTLINGER	BOOL	Don't block close waiting for unsent data to be sent. Setting this option is equivalent to setting SO_LINGER with <i>l_onoff</i> set to zero.
SO_DONTROUTE	BOOL	Don't route: send directly to interface.
SO_KEEPALIVE	BOOL	Send keepalives
SO_LINGER	struct linger FAR *	Linger on close if unsent data is present
SO_OOINLINE	BOOL	Receive out-of-band data in the normal data stream.
SO_RCVBUF	int	Specify buffer size for receives
SO_REUSEADDR	BOOL	Allow the socket to be bound to an address which is already in use. (See bind() .)
SO_SNDBUF	int	Specify buffer size for sends

BSD options not supported for **setsockopt()** are:

80 Appendix C: Background Information

Value	Type	Meaning
SO_ACCEPTCON	BOOL	Socket is listening
SO_ERROR	int	Get error status and clear
SO_RCVLOWAT	int	Receive low water mark
SO_RCVTIMEO	int	Receive timeout
SO_SNDLOWAT	int	Send low water mark
SO_SNDTIMEO	int	Send timeout
SO_TYPE	int	Type of the socket

Return Value If no error occurs, **setsockopt()** returns 0. Otherwise, a value of SOCKET_ERROR is returned, and a specific error code may be retrieved by calling **WSAGetLastError()**.

Error Codes	WSANOTINITIALISED	A successful WSAStartup() must occur before using this API.
	WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
	WSAEFAULT	<i>optval</i> is not in a valid part of the process address space.
	WSAEINPROGRESS	A blocking Windows Sockets operation is in progress.
	WSAEINVAL	<i>level</i> is not valid.
	WSAENETRESET	Connection has timed out when SO_KEEPALIVE is set.
	WSAENOPROTOOPT	The option is unknown or unsupported. In particular, SO_BROADCAST is not supported on sockets of type SOCK_STREAM, while SO_DONTLINGER, SO_KEEPALIVE, SO_LINGER and SO_OOBINLINE are not supported on sockets of type SOCK_DGRAM.
	WSAENOTCONN	Connection has been reset when SO_KEEPALIVE is set.
	WSAENOTSOCK	The descriptor is not a socket.

See Also [bind\(\)](#), [getsockopt\(\)](#), [ioctlsocket\(\)](#), [socket\(\)](#), [WSAAsyncSelect\(\)](#).

#²³⁴ \$²³⁵ +²³⁶ K²³⁷ **Windows Sockets - Socket Routines**

shutdown()

Description Disable sends and/or receives on a socket.

#include <winsock.h>

int shutdown (SOCKET s, int how);

s _____ A descriptor identifying a socket.

how _____ A flag that describes what types of operation will no longer be allowed.

Remarks **shutdown()** is used on all types of sockets to disable reception, transmission, or both.

If *how* is 0, subsequent receives on the socket will be disallowed. This has no effect on the lower protocol layers. For TCP, the TCP window is not changed and incoming data will be accepted (but not acknowledged) until the window is exhausted. For UDP, incoming datagrams are accepted and queued. In no case will an ICMP error packet be generated.

If *how* is 1, subsequent sends are disallowed. For TCP sockets, a FIN will be sent.

Setting *how* to 2 disables both sends and receives as described above.

Note that **shutdown()** does not close the socket, and resources attached to the socket will not be freed until **closesocket()** is invoked.

Comments **shutdown()** does not block regardless of the SO_LINGER setting on the socket.

An application should not rely on being able to re-use a socket after it has been shut down. In particular, a Windows Sockets implementation is not required to support the use of **connect()** on such a socket.

Return Value If no error occurs, **shutdown()** returns 0. Otherwise, a value of SOCKET_ERROR is returned, and a specific error code may be retrieved by calling **WSAGetLastError()**.

Error Codes WSANOTINITIALISED A successful **WSAStartup()** must occur before using this API.

234# WinSock_ShutDown

235\$ shutdown()

236+ WinSockSR:0220

237K shutdown()

82 Appendix C: Background Information

WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
WSAEINVAL	how is not valid.
WSAEINTR	The (blocking) call was canceled via <u>WSACancelBlockingCall()</u>
WSAEINPROGRESS	A blocking Windows Sockets operation is in progress.
WSAENOTCONN	The socket is not connected (SOCK_STREAM only).
WSAENOTSOCK	The descriptor is not a socket.

See Also [connect\(\)](#), [socket\(\)](#).

#²³⁸ \$²³⁹ +²⁴⁰ K²⁴¹ **Windows Sockets - Socket Routines**

socket()

Description Create a socket.

#include <winsock.h>

SOCKET socket (int *af*, int *type*, int *protocol*);

af _____ An address format specification. The only format currently supported is PF_INET, which is the ARPA Internet address format.

type _____ A type specification for the new socket.

protocol _____ A particular protocol to be used with the socket.

Remarks **socket()** allocates a socket descriptor of the specified address family, data type and protocol, as well as related resources. If a protocol is not specified, the default for the specified connection mode is used.

Only a single protocol exists to support a particular socket type using a given address format. However, the address family may be given as AF_UNSPEC (unspecified), in which case the *protocol* parameter must be specified. The protocol number to use is particular to the "communication domain" in which communication is to take place.

The following *type* specifications are supported:

<u>Type</u>	<u>Explanation</u>
SOCK_STREAM	Provides sequenced, reliable, two-way, connection-based byte streams with an out-of-band data transmission mechanism. Uses TCP for the Internet address family.
SOCK_DGRAM	Supports datagrams, which are connectionless, unreliable buffers of a fixed (typically small) maximum length. Uses UDP for the Internet address family.

Sockets of type SOCK_STREAM are full-duplex byte streams. A stream socket must be in a connected state before any data may be sent or received on it. A connection to another socket is created with a **connect()** call. Once connected, data may be transferred using **send()** and **recv()** calls. When a session has

238# WinSock_Socket
 239\$ socket()
 240+ WinSockSR:0230
 241K socket()

84 Appendix C: Background Information

been completed, a **closesocket()** must be performed. Out-of-band data may also be transmitted as described in **send()** and received as described in **recv()**.

The communications protocols used to implement a SOCK_STREAM ensure that data is not lost or duplicated. If data for which the peer protocol has buffer space cannot be successfully transmitted within a reasonable length of time, the connection is considered broken and subsequent calls will fail with the error code set to WSAETIMEDOUT.

SOCK_DGRAM sockets allow sending and receiving of datagrams to and from arbitrary peers using **sendto()** and **recvfrom()**. If such a socket is **connect()**ed to a specific peer, datagrams may be send to that peer **send()** and may be received from (only) this peer using **recv()**.

Return Value If no error occurs, **socket()** returns a descriptor referencing the new socket. Otherwise, a value of INVALID_SOCKET is returned, and a specific error code may be retrieved by calling **WSAGetLastError()**.

Error Codes	WSANOTINITIALISED	A successful <u>WSAStartup()</u> must occur before using this API.
	WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
	WSAEAFNOSUPPORT	The specified address family is not supported..
	WSAEINPROGRESS	A blocking Windows Sockets operation is in progress.
	WSAEMFILE	No more file descriptors are available.
	WSAENOBUFS	No buffer space is available. The socket cannot be created.
	WSAEPROTONOSUPPORT	The specified protocol is not supported.
	WSAEPROTOTYPE	The specified protocol is the wrong type for this socket.
	WSAESOCKTNOSUPPORT	The specified socket type is not supported in this address family.

See Also [accept\(\)](#), [bind\(\)](#), [connect\(\)](#), [getsockname\(\)](#), [getsockopt\(\)](#), [setsockopt\(\)](#), [listen\(\)](#), [recv\(\)](#), [recvfrom\(\)](#), [select\(\)](#), [send\(\)](#), [sendto\(\)](#), [shutdown\(\)](#), [ioctlsocket\(\)](#).

#²⁴² \$²⁴³ +²⁴⁴ K²⁴⁵ **Socket Library Reference**

Database Routines

gethostbyaddr()
gethostbyname()
getprotobyname()
getprotobynumber()
getservbyname()
getservbyport()

242# WinSockRef_DatabaseRoutines

243\$ Database Routines

244+ WinSockRef:0020

245^K Database Functions

86 Appendix C: Background Information

#²⁴⁶ \$²⁴⁷ +²⁴⁸ K²⁴⁹ Database Routines

gethostbyaddr()

Description Get host information corresponding to an address.

```
#include <winsock.h>
```

```
struct hostent FAR * gethostbyaddr ( char FAR * addr, int len, int type );
```

addr A pointer to an address in network byte order.
len The length of the address, which must be 4 for PF_INET addresses.
type The type of the address, which must be PF_INET.

Remarks `gethostbyaddr()` returns a pointer to the following structure which contains the name(s) and address which correspond to the given address.

```
struct hostent {  
    char FAR * h_name;  
    char FAR * FAR * h_aliases;  
    int h_addrtype;  
    int h_length;  
    char FAR * FAR * h_addr_list;  
};
```

The members of this structure are:

Element	Usage
<u>h_name</u>	Official name of the host (PC).
<u>h_aliases</u>	A NULL-terminated array of alternate names.
<u>h_addrtype</u>	The type of address being returned; for Windows Sockets this is always PF_INET.
<u>h_length</u>	The length, in bytes, of each address; for PF_INET, this is always 4.
<u>h_addr_list</u>	A NULL-terminated list of addresses for the host. Addresses are returned in network byte order.

The macro `h_addr` is defined to be `h_addr_list[0]` for compatibility with older software.

The pointer which is returned points to a structure which is allocated by the Windows Sockets implementation. The application must never attempt to modify this structure or to free any of its components. Furthermore, only one copy of this structure is allocated per thread, and so the application should copy any information which it needs before issuing any other Windows Sockets API calls.

246# WinSock_GetHostByAddr

247\$ gethostbyaddr()

248+ WinSockDB:0010

249^K gethostbyaddr()

Appendix C: Background Information 87

Return Value	If no error occurs, gethostbyaddr() returns a pointer to the hostent structure described above. Otherwise it returns a NULL pointer and a specific error number may be retrieved by calling <u>WSAGetLastError()</u> .	
Error Codes	WSANOTINITIALISED	A successful <u>WSAStartup()</u> must occur before using this API.
	WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
	WSAHOST_NOT_FOUND	Authoritative Answer Host not found.
	WSATRY_AGAIN	Non-Authoritative Host not found, or SERVERFAIL.
	WSANO_RECOVERY	Non recoverable errors, FORMERR, REFUSED, NOTIMP.
	WSANO_DATA	Valid name, no data record of requested type.
	WSAEINPROGRESS	A blocking Windows Sockets operation is in progress.
	WSAEINTR	The (blocking) call was canceled via <u>WSACancelBlockingCall()</u>
See Also	<u>WSAAsyncGetHostByAddr()</u> , <u>gethostbyname()</u> ,	

88 Appendix C: Background Information

#₂₅₀ \$₂₅₁ +₂₅₂ K₂₅₃ Database Routines

gethostbyname()

Description Get host information corresponding to a hostname.

```
#include <winsock.h>
```

```
struct hostent FAR * gethostbyname ( char FAR * name );
```

name _____ A pointer to the name of the host.

Remarks **gethostbyname()** returns a pointer to a **hostent** structure as described under **gethostbyaddr()**. The contents of this structure correspond to the hostname *name*.

The pointer which is returned points to a structure which is allocated by the Windows Sockets implementation. The application must never attempt to modify this structure or to free any of its components. Furthermore, only one copy of this structure is allocated per thread, and so the application should copy any information which it needs before issuing any other Windows Sockets API calls.

Return Value If no error occurs, **gethostbyname()** returns a pointer to the **hostent** structure described above. Otherwise it returns a NULL pointer and a specific error number may be retrieved by calling **WSAGetLastError()**.

Error Codes	WSANOTINITIALISED	A successful WSAStartup() must occur before using this API.
	WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
	WSAHOST_NOT_FOUND	Authoritative Answer Host not found.
	WSATRY_AGAIN	Non-Authoritative Host not found, or SERVERFAIL.
	WSANO_RECOVERY	Non recoverable errors, FORMERR, REFUSED, NOTIMP.
	WSANO_DATA	Valid name, no data record of requested type.
	WSAEINPROGRESS	A blocking Windows Sockets operation is in progress.

250# WinSock_GetHostByName

251\$ gethostbyname()

252+ WinSockDB:0020

253K gethostbyname()

Appendix C: Background Information 89

WSAEINTR

The (blocking) call was canceled via
[WSACancelBlockingCall\(\)](#)

See Also [WSAAsyncGetHostByName\(\)](#), [gethostbyaddr\(\)](#)

90 Appendix C: Background Information

#²⁵⁴ \$²⁵⁵ +²⁵⁶ K²⁵⁷ Database Routines

getprotobyname()

Description Get protocol information corresponding to a protocol name.

```
#include <winsock.h>
```

```
struct protoent FAR * getprotobyname ( char FAR * name );
```

name _____ A pointer to a protocol name.

Remarks **getprotobyname()** returns a pointer to the following structure which contains the name(s) and protocol number which correspond to the given protocol *name*.

```
struct protoent {  
    char FAR * p_name;  
    char FAR * FAR * p_aliases;  
    int p_proto;  
};
```

The members of this structure are:

Element	Usage
<u>p_name</u>	Official name of the protocol.
<u>p_aliases</u>	A NULL-terminated array of alternate names.
<u>p_proto</u>	The protocol number, in host byte order.

The pointer which is returned points to a structure which is allocated by the Windows Sockets library. The application must never attempt to modify this structure or to free any of its components. Furthermore only one copy of this structure is allocated per thread, and so the application should copy any information which it needs before issuing any other Windows Sockets API calls.

Return Value If no error occurs, **getprotobyname()** returns a pointer to the protoent structure described above. Otherwise it returns a NULL pointer and a specific error number may be retrieved by calling **WSAGetLastError()**.

Error Codes	WSANOTINITIALISED	A successful WSAStartup() must occur before using this API.
	WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
	WSANO_RECOVERY	Non recoverable errors, FORMERR, REFUSED, NOTIMP.

254# WinSock_GetProtoByName

255\$ getprotobyname()

256+ WinSockDB:0030

257K getprotobyname()

Appendix C: Background Information 91

WSANO_DATA	Valid name, no data record of requested type.
WSAEINPROGRESS	A blocking Windows Sockets operation is in progress.
WSAEINTR	The (blocking) call was canceled via <u>WSACancelBlockingCall()</u>

See Also **WSAAsyncGetProtoByName(), getprotobynumber()**

92 Appendix C: Background Information

#²⁵⁸ \$²⁵⁹ +²⁶⁰ K²⁶¹ Database Routines

getprotobynumber()

Description Get protocol information corresponding to a protocol number.

```
#include <winsock.h>
```

```
struct protoent FAR * getprotobynumber ( int number );
```

number A protocol number, in host byte order.

Remarks This function returns a pointer to a protoent structure as described above in **getprotobyname()**. The contents of the structure correspond to the given protocol number.

The pointer which is returned points to a structure which is allocated by the Windows Sockets implementation. The application must never attempt to modify this structure or to free any of its components. Furthermore, only one copy of this structure is allocated per thread, and so the application should copy any information which it needs before issuing any other Windows Sockets API calls.

Return Value If no error occurs, **getprotobynumber()** returns a pointer to the protoent structure described above. Otherwise it returns a NULL pointer and a specific error number may be retrieved by calling **WSAGetLastError()**.

Error Codes	WSANOTINITIALISED	A successful WSAStartup() must occur before using this API.
	WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
	WSANO_RECOVERY	Non recoverable errors, FORMERR, REFUSED, NOTIMP.
	WSANO_DATA	Valid name, no data record of requested type.
	WSAEINPROGRESS	A blocking Windows Sockets operation is in progress.
	WSAEINTR	The (blocking) call was canceled via WSACancelBlockingCall()

See Also [WSAAsyncGetProtoByNumber\(\)](#), [getprotobyname\(\)](#)

258# WinSock_GetProtoByNumber

259\$ getprotobynumber()

260+ WinSockDB:0040

261^K getprotobynumber()

94 Appendix C: Background Information

#₂₆₂ \$₂₆₃ +₂₆₄ K₂₆₅ Database Routines

getservbyname()

Description Get service information corresponding to a service name and protocol.

```
#include <winsock.h>
```

```
struct servent FAR * getservbyname ( char FAR * name, char FAR * proto );
```

name A pointer to a service name.
proto A pointer to a protocol name. If this is NULL, **getservbyname()** returns the first service entry for which the *name* matches the *s_name* or one of the *s_aliases*. Otherwise **getservbyname()** matches both the *name* and the *proto*.

Remarks **getservbyname()** returns a pointer to the following structure which contains the name(s) and service number which correspond to the given service *name*.

```
struct servent {  
    char FAR * s_name;  
    char FAR * FAR * s_aliases;  
    int s_port;  
    char FAR * s_proto;  
};
```

The members of this structure are:

Element	Usage
<u><i>s_name</i></u>	Official name of the service.
<u><i>s_aliases</i></u>	A NULL-terminated array of alternate names.
<u><i>s_port</i></u>	The port number at which the service may be contacted. Port numbers are returned in network byte order.
<u><i>s_proto</i></u>	The name of the protocol to use when contacting the service.

The pointer which is returned points to a structure which is allocated by the Windows Sockets library. The application must never attempt to modify this structure or to free any of its components. Furthermore only one copy of this structure is allocated per thread, and so the application should copy any information which it needs before issuing any other Windows Sockets API calls.

Return Value If no error occurs, **getservbyname()** returns a pointer to the servent structure described above. Otherwise it returns a NULL pointer and a specific error number may be retrieved by calling **WSAGetLastError()**.

Error Codes WSA_NOT_INITIALIZED A successful **WSAStartup()** must occur before using this API.

262# WinSock_GetServByName

263\$ getservbyname()

264+ WinSockDB:0050

265^K getservbyname()

Appendix C: Background Information 95

WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
WSANO_RECOVERY	Non recoverable errors, FORMERR, REFUSED, NOTIMP.
WSANO_DATA	Valid name, no data record of requested type.
WSAEINPROGRESS	A blocking Windows Sockets operation is in progress.
WSAEINTR	The (blocking) call was canceled via <u>WSACancelBlockingCall()</u>

See Also **WSAAsyncGetServByName(), getservbyport()**

96 Appendix C: Background Information

#²⁶⁶ \$²⁶⁷ +²⁶⁸ K²⁶⁹ Database Routines

getservbyport()

Description Get service information corresponding to a port and protocol.

```
#include <winsock.h>
```

```
struct servent FAR * getservbyport ( int port, char FAR * proto );
```

port The port for a service, in network byte order.
proto A pointer to a protocol name. If this is NULL, **getservbyport()** returns the first service entry for which the *port* matches the *s_port*. Otherwise **getservbyport()** matches both the *port* and the *proto*.

Remarks **getservbyport()** returns a pointer a servent structure as described above for **getservbyname()**.

The pointer which is returned points to a structure which is allocated by the Windows Sockets implementation. The application must never attempt to modify this structure or to free any of its components. Furthermore, only one copy of this structure is allocated per thread, and so the application should copy any information which it needs before issuing any other Windows Sockets API calls.

Return Value If no error occurs, **getservbyport()** returns a pointer to the servent structure described above. Otherwise it returns a NULL pointer and a specific error number may be retrieved by calling **WSAGetLastError()**.

Error Codes	WSANOTINITIALISED	A successful WSAStartup() must occur before using this API.
	WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
	WSANO_RECOVERY	Non recoverable errors, FORMERR, REFUSED, NOTIMP.
	WSANO_DATA	Valid name, no data record of requested type.
	WSAEINPROGRESS	A blocking Windows Sockets operation is in progress.
	WSAEINTR	The (blocking) call was canceled via WSACancelBlockingCall()

266# WinSock_GetServByPort

267\$ getservbyport()

268+ WinSockDB:0060

269^K getservbyport

See Also [WSAAsyncGetServByPort\(\)](#), [getservbyname\(\)](#)

98 Appendix C: Background Information

#²⁷⁰ \$²⁷¹ +²⁷² K²⁷³ **Socket Library Reference**

Microsoft Windows-specific Extensions

WSAAsyncGetHostByAddr()

WSAAsyncGetHostByName()

WSAAsyncGetProtoByName()

WSAAsyncGetProtoByNumber()

WSAAsyncGetServByName()

WSAAsyncGetServByPort()

WSAAsyncSelect()

WSACancelAsyncRequest()

WSACancelBlockingCall()

WSACleanup()

WSAGetLastError()

WSAIsBlocking()

WSASetBlockingHook()

WSASetLastError()

WSAStartup()

WSAUnhookBlockingHook()

270# WinSockRef_WindowsExtensions

271\$ Microsoft Windows-specific Extensions

272+ WinSockRef:0030

273^K Windows Extensions

#²⁷⁴ \$²⁷⁵ +²⁷⁶ K²⁷⁷ **Microsoft Windows Specific Extensions**

WSAAsyncGetHostByAddr()

Description Get host information corresponding to an address - asynchronous version.

#include <winsock.h>

HANDLE WSAAsyncGetHostByAddr (HWND *hWnd*, unsigned int *wMsg*,
char FAR * *addr*, int *len*, int *type*, char FAR * *buf*, int *buflen*);

hWnd The handle of the window which should receive a message when the asynchronous request completes.

wMsg The message to be received when the asynchronous request completes.

addr A pointer to the network address for the host. Host addresses are stored in network byte order.

len The length of the address, which must be 4 for PF_INET.

type The type of the address, which must be PF_INET.

buf A pointer to the data area to receive the hostent data. Note that this must be larger than the size of a hostent structure. This is because the data area supplied is used by the Windows Sockets implementation to contain not only a hostent structure but any and all of the data which is referenced by members of the hostent structure. It is recommended that you supply a buffer of MAXGETHOSTSTRUCT bytes.

buflen The size of data area *buf* above.

Remarks This function is an asynchronous version of **gethostbyaddr()**, and is used to retrieve host name and address information corresponding to a network address. The Windows Sockets implementation initiates the operation and returns to the caller immediately, passing back an **asynchronous task handle** which the application may use to identify the operation. When the operation is completed, the results (if any) are copied into the buffer provided by the caller and a message is sent to the application's window.

When the asynchronous operation is complete the application's window *hWnd* receives message *wMsg*. The *wParam* argument contains the asynchronous task handle as returned by the original function call. The high 16 bits of *lParam* contain any error code. The error code may be any error as defined in **winsock.h**. An error code of zero indicates successful completion of the

274# WinSock_AsyncGetHostByAddr

275\$ WSAAsyncGetHostByAddr()

276+ WinSockWSE:0010

277K WSAAsyncGetHostByAddr()

100 Appendix C: Background Information

asynchronous operation. On successful completion, the buffer supplied to the original function call contains a hostent structure. To access the elements of this structure, the original buffer address should be cast to a hostent structure pointer and accessed as appropriate.

Note that if the error code is WSAENOBUFFS, it indicates that the size of the buffer specified by *buflen* in the original call was too small to contain all the resultant information. In this case, the low 16 bits of *IParam* contain the size of buffer required to supply ALL the requisite information. If the application decides that the partial data is inadequate, it may reissue the **WSAAsyncGetHostByAddr()** function call with a buffer large enough to receive all the desired information (i.e. no smaller than the low 16 bits of *IParam*).

The error code and buffer length should be extracted from the *IParam* using the macros WSAGETASYNCERROR and WSAGETASYNCBUFLLEN, defined in **winsock.h** as:

```
#define WSAGETASYNCERROR(IParam)          HIWORD(IParam)
#define WSAGETASYNCBUFLLEN(IParam)       LOWORD(IParam)
```

The use of these macros will maximize the portability of the source code for the application.

Return Value The return value specifies whether or not the asynchronous operation was successfully initiated. Note that it does not imply success or failure of the operation itself.

If the operation was successfully initiated, **WSAAsyncGetHostByAddr()** returns a nonzero value of type HANDLE which is the asynchronous task handle for the request. This value can be used in two ways. It can be used to cancel the operation using **WSACancelAsyncRequest()**. It can also be used to match up asynchronous operations and completion messages, by examining the *wParam* message argument.

If the asynchronous operation could not be initiated, **WSAAsyncGetHostByAddr()** returns a zero value, and a specific error number may be retrieved by calling **WSAGetLastError()**.

Comments The buffer supplied to this function is used by the Windows Sockets implementation to construct a hostent structure together with the contents of data areas referenced by members of the same hostent structure. To avoid the WSAENOBUFFS error noted above, the application should provide a buffer of at least MAXGETHOSTSTRUCT bytes (as defined in **winsock.h**).

Notes For Windows Sockets Suppliers

It is the responsibility of the Windows Sockets implementation to ensure that messages are successfully posted to the application. If a **PostMessage()** operation fails, the Windows Sockets implementation **must** re-post that message.

Windows Sockets suppliers should use the WSAMAKEASYNCREPLY macro when constructing the *IParam* in the message.

Appendix C: Background Information 101

Error Codes The following error codes may be set when an application window receives a message. As described above, they may be extracted from the *IPParam* in the reply message using the `WSAGETASYNCERROR` macro.

WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
WSAENOBUFS	No/insufficient buffer space is available
WSAHOST_NOT_FOUND	Authoritative Answer Host not found.
WSATRY_AGAIN	Non-Authoritative Host not found, or SERVERFAIL.
WSANO_RECOVERY	Non recoverable errors, FORMERR, REFUSED, NOTIMP.
WSANO_DATA	Valid name, no data record of requested type.

The following errors may occur at the time of the function call, and indicate that the asynchronous operation could not be initiated.

WSANOTINITIALISED	A successful <u>WSAStartup()</u> must occur before using this API.
WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
WSAEINPROGRESS	A blocking Windows Sockets operation is in progress.
WSAEWOULDBLOCK	The asynchronous operation cannot be scheduled at this time due to resource or other constraints within the Windows Sockets implementation.

See Also **gethostbyaddr()**, **WSACancelAsyncRequest()**

#²⁷⁸ \$²⁷⁹ +²⁸⁰ K²⁸¹ Microsoft Windows Specific Extensions

WSAAsyncGetHostByName()

Description Get host information corresponding to a hostname - asynchronous version.

```
#include <winsock.h>
```

```
HANDLE WSAAsyncGetHostByName ( HWND hWnd, unsigned int wMsg,  
char FAR * name, char FAR * buf, int buflen );
```

hWnd The handle of the window which should receive a message when the asynchronous request completes.

wMsg The message to be received when the asynchronous request completes.

name A pointer to the name of the host.

buf A pointer to the data area to receive the hostent data. Note that this must be larger than the size of a hostent structure. This is because the data area supplied is used by the Windows Sockets implementation to contain not only a hostent structure but any and all of the data which is referenced by members of the hostent structure. It is recommended that you supply a buffer of MAXGETHOSTSTRUCT bytes.

buflen The size of data area *buf* above.

Remarks This function is an asynchronous version of **gethostbyname()**, and is used to retrieve host name and address information corresponding to a hostname. The Windows Sockets implementation initiates the operation and returns to the caller immediately, passing back an **asynchronous task handle** which the application may use to identify the operation. When the operation is completed, the results (if any) are copied into the buffer provided by the caller and a message is sent to the application's window.

When the asynchronous operation is complete the application's window *hWnd* receives message *wMsg*. The *wParam* argument contains the asynchronous task handle as returned by the original function call. The high 16 bits of *lParam* contain any error code. The error code may be any error as defined in **winsock.h**. An error code of zero indicates successful completion of the asynchronous operation. On successful completion, the buffer supplied to the original function call contains a hostent structure. To access the elements of this structure, the original buffer address should be cast to a hostent structure pointer and accessed as appropriate.

278# WinSock_AsyncGetHostByName

279\$ WSAAsyncGetHostByName()

280+ WinSockWSE:0020

281^K WSAAsyncGetHostByName()

Appendix C: Background Information 103

Note that if the error code is WSAENOBUFS, it indicates that the size of the buffer specified by *bufLen* in the original call was too small to contain all the resultant information. In this case, the low 16 bits of *IPParam* contain the size of buffer required to supply ALL the requisite information. If the application decides that the partial data is inadequate, it may reissue the **WSAAsyncGetHostByName()** function call with a buffer large enough to receive all the desired information (i.e. no smaller than the low 16 bits of *IPParam*).

The error code and buffer length should be extracted from the *IPParam* using the macros WSAGETASYNCERROR and WSAGETASYNCBUFLen, defined in **winsock.h** as:

```
#define WSAGETASYNCERROR(IPParam) HIWORD(IPParam)
#define WSAGETASYNCBUFLen(IPParam) LOWORD(IPParam)
```

The use of these macros will maximize the portability of the source code for the application.

Return Value The return value specifies whether or not the asynchronous operation was successfully initiated. Note that it does not imply success or failure of the operation itself.

If the operation was successfully initiated, **WSAAsyncGetHostByName()** returns a nonzero value of type HANDLE which is the asynchronous task handle for the request. This value can be used in two ways. It can be used to cancel the operation using **WSACancelAsyncRequest()**. It can also be used to match up asynchronous operations and completion messages, by examining the *wParam* message argument.

If the asynchronous operation could not be initiated, **WSAAsyncGetHostByName()** returns a zero value, and a specific error number may be retrieved by calling **WSAGetLastError()**.

Comments The buffer supplied to this function is used by the Windows Sockets implementation to construct a hostent structure together with the contents of data areas referenced by members of the same hostent structure. To avoid the WSAENOBUFS error noted above, the application should provide a buffer of at least MAXGETHOSTSTRUCT bytes (as defined in **winsock.h**).

Notes For Windows Sockets

Suppliers It is the responsibility of the Windows Sockets implementation to ensure that messages are successfully posted to the application. If a **PostMessage()** operation fails, the Windows Sockets implementation **must** re-post that message.

Windows Sockets suppliers should use the WSAMAKEASYNCREPLY macro when constructing the *IPParam* in the message.

Error Codes The following error codes may be set when an application window receives a message. As described above, they may be extracted from the *IPParam* in the reply message using the WSAGETASYNCERROR macro.

WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
-------------	--

104 Appendix C: Background Information

WSAENOBUFS	No/insufficient buffer space is available
WSAHOST_NOT_FOUND	Authoritative Answer Host not found.
WSATRY_AGAIN	Non-Authoritative Host not found, or SERVERFAIL.
WSANO_RECOVERY	Non recoverable errors, FORMERR, REFUSED, NOTIMP.
WSANO_DATA	Valid name, no data record of requested type.

The following errors may occur at the time of the function call, and indicate that the asynchronous operation could not be initiated.

WSANOTINITIALISED	A successful <u>WSAStartup()</u> must occur before using this API.
WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
WSAEINPROGRESS	A blocking Windows Sockets operation is in progress.
WSAEWOULDBLOCK	The asynchronous operation cannot be scheduled at this time due to resource or other constraints within the Windows Sockets implementation.

See Also **gethostbyname(), WSACancelAsyncRequest()**

#₂₈₂ \$₂₈₃ +₂₈₄ K₂₈₅ Microsoft Windows Specific Extensions

WSAAsyncGetProtoByName()

Description Get protocol information corresponding to a protocol name - asynchronous version.

```
#include <winsock.h>
```

```
HANDLE WSAAsyncGetProtoByName ( HWND hWnd, unsigned int wMsg,
char FAR * name, char FAR * buf, int buflen );
```

hWnd The handle of the window which should receive a message when the asynchronous request completes.

wMsg The message to be received when the asynchronous request completes.

name A pointer to the protocol name to be resolved.

buf A pointer to the data area to receive the protoent data. Note that this must be larger than the size of a protoent structure. This is because the data area supplied is used by the Windows Sockets implementation to contain not only a protoent structure but any and all of the data which is referenced by members of the protoent structure. It is recommended that you supply a buffer of MAXGETHOSTSTRUCT bytes.

buflen The size of data area *buf* above.

Remarks This function is an asynchronous version of **getprotobyname()**, and is used to retrieve the protocol name and number corresponding to a protocol name. The Windows Sockets implementation initiates the operation and returns to the caller immediately, passing back an **asynchronous task handle** which the application may use to identify the operation. When the operation is completed, the results (if any) are copied into the buffer provided by the caller and a message is sent to the application's window.

When the asynchronous operation is complete the application's window *hWnd* receives message *wMsg*. The *wParam* argument contains the asynchronous task handle as returned by the original function call. The high 16 bits of *lParam* contain any error code. The error code may be any error as defined in **winsock.h**. An error code of zero indicates successful completion of the asynchronous operation. On successful completion, the buffer supplied to the original function call contains a protoent structure. To access the elements of this structure, the original buffer address should be cast to a protoent structure pointer and accessed as appropriate.

282# WinSock_AsyncGetProtoByName

283\$ WSAAsyncGetProtoByName()

284+ WinSockWSE:0030

285^K WSAAsyncGetProtoByName()

106 Appendix C: Background Information

Note that if the error code is WSAENOBUFFS, it indicates that the size of the buffer specified by *bufflen* in the original call was too small to contain all the resultant information. In this case, the low 16 bits of *IPParam* contain the size of buffer required to supply ALL the requisite information. If the application decides that the partial data is inadequate, it may reissue the **WSAAsyncGetProtoByName()** function call with a buffer large enough to receive all the desired information (i.e. no smaller than the low 16 bits of *IPParam*).

The error code and buffer length should be extracted from the *IPParam* using the macros WSAGETASYNCERROR and WSAGETASYNCBUFLLEN, defined in **winsock.h** as:

```
#define WSAGETASYNCERROR(IPParam)          HIWORD(IPParam)
#define WSAGETASYNCBUFLLEN(IPParam)       LOWORD(IPParam)
```

The use of these macros will maximize the portability of the source code for the application.

Return Value The return value specifies whether or not the asynchronous operation was successfully initiated. Note that it does not imply success or failure of the operation itself.

If the operation was successfully initiated, **WSAAsyncGetProtoByName()** returns a nonzero value of type HANDLE which is the asynchronous task handle for the request. This value can be used in two ways. It can be used to cancel the operation using **WSACancelAsyncRequest()**. It can also be used to match up asynchronous operations and completion messages, by examining the *wParam* message argument.

If the asynchronous operation could not be initiated, **WSAAsyncGetProtoByName()** returns a zero value, and a specific error number may be retrieved by calling **WSAGetLastError()**.

Comments The buffer supplied to this function is used by the Windows Sockets implementation to construct a protoent structure together with the contents of data areas referenced by members of the same protoent structure. To avoid the WSAENOBUFFS error noted above, the application should provide a buffer of at least MAXGETHOSTSTRUCT bytes (as defined in **winsock.h**).

Notes For Windows Sockets Suppliers

It is the responsibility of the Windows Sockets implementation to ensure that messages are successfully posted to the application. If a **PostMessage()** operation fails, the Windows Sockets implementation **must** re-post that message.

Windows Sockets suppliers should use the WSAMAKEASYNCREPLY macro when constructing the *IPParam* in the message.

Error Codes The following error codes may be set when an application window receives a message. As described above, they may be extracted from the *IPParam* in the reply message using the WSAGETASYNCERROR macro.

Appendix C: Background Information 107

WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
WSAENOBUFS	No/insufficient buffer space is available
WSAHOST_NOT_FOUND	Authoritative Answer Host not found.
WSATRY_AGAIN	Non-Authoritative Host not found, or SERVERFAIL.
WSANO_RECOVERY	Non recoverable errors, FORMERR, REFUSED, NOTIMP.
WSANO_DATA	Valid name, no data record of requested type.

The following errors may occur at the time of the function call, and indicate that the asynchronous operation could not be initiated.

WSANOTINITIALISED	A successful <u>WSAStartup()</u> must occur before using this API.
WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
WSAEINPROGRESS	A blocking Windows Sockets operation is in progress.
WSAEWOULDBLOCK	The asynchronous operation cannot be scheduled at this time due to resource or other constraints within the Windows Sockets implementation.

See Also [getprotobyname\(\)](#), [WSACancelAsyncRequest\(\)](#)

108 Appendix C: Background Information

#²⁸⁶ \$²⁸⁷ +²⁸⁸ K²⁸⁹ Microsoft Windows Specific Extensions

WSAAsyncGetProtoByNumber()

Description Get protocol information corresponding to a protocol number - asynchronous version.

```
#include <winsock.h>
```

```
HANDLE WSAAsyncGetProtoByNumber ( HWND hWnd, unsigned int wMsg,  
int number, char FAR * buf, int buflen );
```

hWnd The handle of the window which should receive a message when the asynchronous request completes.

wMsg The message to be received when the asynchronous request completes.

number The protocol number to be resolved, in host byte order.

buf A pointer to the data area to receive the protoent data. Note that this must be larger than the size of a protoent structure. This is because the data area supplied is used by the Windows Sockets implementation to contain not only a protoent structure but any and all of the data which is referenced by members of the protoent structure. It is recommended that you supply a buffer of MAXGETHOSTSTRUCT bytes.

buflen The size of data area *buf* above.

Remarks This function is an asynchronous version of **getprotobynumber()**, and is used to retrieve the protocol name and number corresponding to a protocol number. The Windows Sockets implementation initiates the operation and returns to the caller immediately, passing back an **asynchronous task handle** which the application may use to identify the operation. When the operation is completed, the results (if any) are copied into the buffer provided by the caller and a message is sent to the application's window.

When the asynchronous operation is complete the application's window *hWnd* receives message *wMsg*. The *wParam* argument contains the asynchronous task handle as returned by the original function call. The high 16 bits of *lParam* contain any error code. The error code may be any error as defined in **winsock.h**. An error code of zero indicates successful completion of the asynchronous operation. On successful completion, the buffer supplied to the original function call contains a protoent structure. To access the elements of this structure, the original buffer address should be cast to a protoent structure pointer and accessed as appropriate.

286# WinSock_AsyncGetProtoByNumber

287\$ WSAAsyncGetProtoByNumber()

288+ WinSockWSE:0040

289^K WSAAsyncGetProtoByNumber()

Appendix C: Background Information 109

Note that if the error code is WSAENOBUFFS, it indicates that the size of the buffer specified by *bufflen* in the original call was too small to contain all the resultant information. In this case, the low 16 bits of *IPParam* contain the size of buffer required to supply ALL the requisite information. If the application decides that the partial data is inadequate, it may reissue the **WSAAsyncGetProtoByNumber()** function call with a buffer large enough to receive all the desired information (i.e. no smaller than the low 16 bits of *IPParam*).

The error code and buffer length should be extracted from the *IPParam* using the macros WSAGETASYNCERROR and WSAGETASYNCBUFLen, defined in **winsock.h** as:

```
#define WSAGETASYNCERROR(IPParam)          HIWORD(IPParam)
#define WSAGETASYNCBUFLen(IPParam)       LOWORD(IPParam)
```

The use of these macros will maximize the portability of the source code for the application.

Return Value The return value specifies whether or not the asynchronous operation was successfully initiated. Note that it does not imply success or failure of the operation itself.

If the operation was successfully initiated, **WSAAsyncGetProtoByNumber()** returns a nonzero value of type HANDLE which is the asynchronous task handle for the request. This value can be used in two ways. It can be used to cancel the operation using **WSACancelAsyncRequest()**. It can also be used to match up asynchronous operations and completion messages, by examining the *wParam* message argument.

If the asynchronous operation could not be initiated, **WSAAsyncGetProtoByNumber()** returns a zero value, and a specific error number may be retrieved by calling **WSAGetLastError()**.

Comments The buffer supplied to this function is used by the Windows Sockets implementation to construct a protoent structure together with the contents of data areas referenced by members of the same protoent structure. To avoid the WSAENOBUFFS error noted above, the application should provide a buffer of at least MAXGETHOSTSTRUCT bytes (as defined in **winsock.h**).

Notes For Windows Sockets Suppliers

It is the responsibility of the Windows Sockets implementation to ensure that messages are successfully posted to the application. If a **PostMessage()** operation fails, the Windows Sockets implementation **must** re-post that message.

Windows Sockets suppliers should use the WSAMAKEASYNCREPLY macro when constructing the *IPParam* in the message.

Error Codes The following error codes may be set when an application window receives a message. As described above, they may be extracted from the *IPParam* in the reply message using the WSAGETASYNCERROR macro.

110 Appendix C: Background Information

WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
WSAENOBUFS	No/insufficient buffer space is available
WSAHOST_NOT_FOUND	Authoritative Answer Host not found.
WSATRY_AGAIN	Non-Authoritative Host not found, or SERVERFAIL.
WSANO_RECOVERY	Non recoverable errors, FORMERR, REFUSED, NOTIMP.
WSANO_DATA	Valid name, no data record of requested type.

The following errors may occur at the time of the function call, and indicate that the asynchronous operation could not be initiated.

WSANOTINITIALISED	A successful <u>WSAStartup()</u> must occur before using this API.
WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
WSAEINPROGRESS	A blocking Windows Sockets operation is in progress.
WSAEWOULDBLOCK	The asynchronous operation cannot be scheduled at this time due to resource or other constraints within the Windows Sockets implementation.

See Also **getprotobynumber()**, **WSACancelAsyncRequest()**

#²⁹⁰ \$²⁹¹ +²⁹² K²⁹³ **Microsoft Windows Specific Extensions****WSAAsyncGetServByName()**

Description Get service information corresponding to a service name and port - asynchronous version.

#include <winsock.h>

HANDLE WSAAsyncGetServByName (HWND *hWnd*, unsigned int *wMsg*, char FAR * *name*, char FAR * *proto*, char FAR * *buf*, int *buflen*);

hWnd The handle of the window which should receive a message when the asynchronous request completes.

wMsg The message to be received when the asynchronous request completes.

name A pointer to a service name.

proto A pointer to a protocol name. This may be NULL, in which case **WSAAsyncGetServByName()** will search for the first service entry for which *s_name* or one of the *s_aliases* matches the given *name*. Otherwise **WSAAsyncGetServByName()** matches both *name* and *proto*.

buf A pointer to the data area to receive the servent data. Note that this must be larger than the size of a servent structure. This is because the data area supplied is used by the Windows Sockets implementation to contain not only a servent structure but any and all of the data which is referenced by members of the servent structure. It is recommended that you supply a buffer of MAXGETHOSTSTRUCT bytes.

buflen The size of data area *buf* above.

Remarks This function is an asynchronous version of **getservbyname()**, and is used to retrieve service information corresponding to a service name. The Windows Sockets implementation initiates the operation and returns to the caller immediately, passing back an **asynchronous task handle** which the application may use to identify the operation. When the operation is completed, the results (if any) are copied into the buffer provided by the caller and a message is sent to the application's window.

When the asynchronous operation is complete the application's window *hWnd* receives message *wMsg*. The *wParam* argument contains the asynchronous task handle as returned by the original function call. The high 16 bits of *lParam*

290# WinSock_AsyncGetServByName

291\$ WSAAsyncGetServByName()

292+ WinSockWSE:0050

293K WSAAsyncGetServByName()

112 Appendix C: Background Information

contain any error code. The error code may be any error as defined in **winsock.h**. An error code of zero indicates successful completion of the asynchronous operation. On successful completion, the buffer supplied to the original function call contains a hostent structure. To access the elements of this structure, the original buffer address should be cast to a hostent structure pointer and accessed as appropriate.

Note that if the error code is WSAENOBUFFS, it indicates that the size of the buffer specified by *buflen* in the original call was too small to contain all the resultant information. In this case, the low 16 bits of *IParam* contain the size of buffer required to supply ALL the requisite information. If the application decides that the partial data is inadequate, it may reissue the **WSAAsyncGetServByName()** function call with a buffer large enough to receive all the desired information (i.e. no smaller than the low 16 bits of *IParam*).

The error code and buffer length should be extracted from the *IParam* using the macros WSAGETASYNCERROR and WSAGETASYNCBUFLLEN, defined in **winsock.h** as:

```
#define WSAGETASYNCERROR(IParam) HIWORD(IParam)
#define WSAGETASYNCBUFLLEN(IParam) LOWORD(IParam)
```

The use of these macros will maximize the portability of the source code for the application.

Return Value The return value specifies whether or not the asynchronous operation was successfully initiated. Note that it does **not** imply success or failure of the operation itself.

If the operation was successfully initiated, **WSAAsyncGetServByName()** returns a nonzero value of type HANDLE which is the asynchronous task handle for the request. This value can be used in two ways. It can be used to cancel the operation using **WSACancelAsyncRequest()**. It can also be used to match up asynchronous operations and completion messages, by examining the *wParam* message argument.

If the asynchronous operation could not be initiated, **WSAAsyncGetHostByAddr()** returns a zero value, and a specific error number may be retrieved by calling **WSAGetLastError()**.

Comments The buffer supplied to this function is used by the Windows Sockets implementation to construct a hostent structure together with the contents of data areas referenced by members of the same hostent structure. To avoid the WSAENOBUFFS error noted above, the application should provide a buffer of at least MAXGETHOSTSTRUCT bytes (as defined in **winsock.h**).

Notes For Windows Sockets Suppliers

It is the responsibility of the Windows Sockets implementation to ensure that messages are successfully posted to the application. If a **PostMessage()** operation fails, the Windows Sockets implementation **must** re-post that message.

Windows Sockets suppliers should use the WSAMAKEASYNCREPLY macro when constructing the *IParam* in the message.

Error Codes The following error codes may be set when an application window receives a message. As described above, they may be extracted from the *lParam* in the reply message using the `WSAGETASYNCERROR` macro.

WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
WSAENOBUFS	No/insufficient buffer space is available
WSAHOST_NOT_FOUND	Authoritative Answer Host not found.
WSATRY_AGAIN	Non-Authoritative Host not found, or SERVERFAIL.
WSANO_RECOVERY	Non recoverable errors, FORMERR, REFUSED, NOTIMP.
WSANO_DATA	Valid name, no data record of requested type.

The following errors may occur at the time of the function call, and indicate that the asynchronous operation could not be initiated.

WSANOTINITIALISED	A successful <u>WSAStartup()</u> must occur before using this API.
WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
WSAEINPROGRESS	A blocking Windows Sockets operation is in progress.
WSAEWOULDBLOCK	The asynchronous operation cannot be scheduled at this time due to resource or other constraints within the Windows Sockets implementation.

See Also [getservbyname\(\)](#), [WSACancelAsyncRequest\(\)](#)

#²⁹⁴ \$²⁹⁵ +²⁹⁶ K²⁹⁷ Microsoft Windows Specific Extensions**WSAAsyncGetServByPort()**

Description Get service information corresponding to a port and protocol - asynchronous version.

```
#include <winsock.h>
```

```
HANDLE WSAAsyncGetServByPort ( HWND hWnd, unsigned int wMsg,
int port, char FAR * proto, char FAR * buf, int buflen );
```

hWnd The handle of the window which should receive a message when the asynchronous request completes.

wMsg The message to be received when the asynchronous request completes.

port The port for the service, in network byte order.

proto A pointer to a protocol name. This may be NULL, in which case **WSAAsyncGetServByPort()** will search for the first service entry for which *s_port* match the given *port*. Otherwise **WSAAsyncGetServByPort()** matches both *port* and *proto*.

buf A pointer to the data area to receive the servent data. Note that this must be larger than the size of a servent structure. This is because the data area supplied is used by the Windows Sockets implementation to contain not only a servent structure but any and all of the data which is referenced by members of the servent structure. It is recommended that you supply a buffer of MAXGETHOSTSTRUCT bytes.

buflen The size of data area *buf* above.

Remarks This function is an asynchronous version of **getservbyport()**, and is used to retrieve service information corresponding to a port number. The Windows Sockets implementation initiates the operation and returns to the caller immediately, passing back an **asynchronous task handle** which the application may use to identify the operation. When the operation is completed, the results (if any) are copied into the buffer provided by the caller and a message is sent to the application's window.

When the asynchronous operation is complete the application's window *hWnd* receives message *wMsg*. The *wParam* argument contains the asynchronous task handle as returned by the original function call. The high 16 bits of *lParam* contain any error code. The error code may be any error as defined in

294# WinSock_AsyncGetServByPort

295\$ WSAAsyncGetServByPort()

296+ WinSockWSE:0060

297^K WSAAsyncGetServByPort()

Appendix C: Background Information 115

winsock.h. An error code of zero indicates successful completion of the asynchronous operation. On successful completion, the buffer supplied to the original function call contains a servent structure. To access the elements of this structure, the original buffer address should be cast to a servent structure pointer and accessed as appropriate.

Note that if the error code is WSAENOBUFFS, it indicates that the size of the buffer specified by *buflen* in the original call was too small to contain all the resultant information. In this case, the low 16 bits of *IPParam* contain the size of buffer required to supply ALL the requisite information. If the application decides that the partial data is inadequate, it may reissue the **WSAAsyncGetServByPort()** function call with a buffer large enough to receive all the desired information (i.e. no smaller than the low 16 bits of *IPParam*).

The error code and buffer length should be extracted from the *IPParam* using the macros WSAGETASYNCERROR and WSAGETASYNCBUFLLEN, defined in **winsock.h** as:

```
#define WSAGETASYNCERROR(IPParam) HIWORD(IPParam)
#define WSAGETASYNCBUFLLEN(IPParam) LOWORD(IPParam)
```

The use of these macros will maximize the portability of the source code for the application.

Return Value The return value specifies whether or not the asynchronous operation was successfully initiated. Note that it does **not** imply success or failure of the operation itself.

If the operation was successfully initiated, **WSAAsyncGetServByPort()** returns a nonzero value of type HANDLE which is the asynchronous task handle for the request. This value can be used in two ways. It can be used to cancel the operation using **WSACancelAsyncRequest()**. It can also be used to match up asynchronous operations and completion messages, by examining the *wParam* message argument.

If the asynchronous operation could not be initiated, **WSAAsyncGetServByPort()** returns a zero value, and a specific error number may be retrieved by calling **WSAGetLastError()**.

Comments The buffer supplied to this function is used by the Windows Sockets implementation to construct a servent structure together with the contents of data areas referenced by members of the same servent structure. To avoid the WSAENOBUFFS error noted above, the application should provide a buffer of at least MAXGETHOSTSTRUCT bytes (as defined in **winsock.h**).

Notes For Windows Sockets Suppliers

It is the responsibility of the Windows Sockets implementation to ensure that messages are successfully posted to the application. If a **PostMessage()** operation fails, the Windows Sockets implementation **must** re-post that message.

Windows Sockets suppliers should use the WSAMAKEASYNCREPLY macro when constructing the *IPParam* in the message.

116 Appendix C: Background Information

Error Codes The following error codes may be set when an application window receives a message. As described above, they may be extracted from the *lParam* in the reply message using the `WSAGETASYNCERROR` macro.

WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
WSAENOBUFS	No/insufficient buffer space is available
WSAHOST_NOT_FOUND	Authoritative Answer Host not found.
WSATRY_AGAIN	Non-Authoritative Host not found, or SERVERFAIL.
WSANO_RECOVERY	Non recoverable errors, FORMERR, REFUSED, NOTIMP.
WSANO_DATA	Valid name, no data record of requested type.

The following errors may occur at the time of the function call, and indicate that the asynchronous operation could not be initiated.

WSANOTINITIALISED	A successful <u>WSAStartup()</u> must occur before using this API.
WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
WSAEINPROGRESS	A blocking Windows Sockets operation is in progress.
WSAEWOULDBLOCK	The asynchronous operation cannot be scheduled at this time due to resource or other constraints within the Windows Sockets implementation.

See Also [getservbyport\(\)](#), [WSACancelAsyncRequest\(\)](#)

#²⁹⁸ \$²⁹⁹ +³⁰⁰ K³⁰¹ **Microsoft Windows Specific Extensions****WSAAsyncSelect()****Description** Request event notification for a socket.

#include <winsock.h>

int WSAAsyncSelect (SOCKET *s*, HWND *hWnd*, unsigned int *wMsg*, long *lEvent*);*s* _____ A descriptor identifying the socket for which event notification is required.*hWnd* _____ A handle identifying the window which should receive a message when a network event occurs.*wMsg* _____ The message to be received when a network event occurs.*lEvent* _____ A bitmask which specifies a combination of network events in which the application is interested.**Remarks** This function is used to request that the Windows Sockets DLL should send a message to the window *hWnd* whenever it detects any of the network events specified by the *lEvent* parameter. The message which should be sent is specified by the *wMsg* parameter. The socket for which notification is required is identified by *s*.The *lEvent* parameter is constructed by or'ing any of the values specified in the following list.

Value	Meaning
FD_READ	Want to receive notification of readiness for reading
FD_WRITE	Want to receive notification of readiness for writing
FD_OOB	Want to receive notification of the arrival of out-of-band data
FD_ACCEPT	Want to receive notification of incoming connections
FD_CONNECT	Want to receive notification of completed connection
FD_CLOSE	Want to receive notification of socket closure

Issuing a **WSAAsyncSelect()** for a socket cancels any previous **WSAAsyncSelect()** for the same socket. For example, to receive notification for both reading and writing, the application must call **WSAAsyncSelect()** with both FD_READ and FD_WRITE, as follows:

```
rc = WSAAsyncSelect(s, hWnd, wMsg, FD_READ|FD_WRITE);
```

298# WinSock_AsyncSelect

299\$ WSAAsyncSelect()

300+ WinSockWSE:0070

301^K WSAAsyncSelect()

118 Appendix C: Background Information

It is not possible to specify different messages for different events. The following code will **not** work; the second call will cancel the effects of the first, and only FD_WRITE events will be reported with message wMsg2:

```
rc = WSAAsyncSelect(s, hWnd, wMsg1, FD_READ);  
rc = WSAAsyncSelect(s, hWnd, wMsg2, FD_WRITE);
```

To cancel all notification - i.e., to indicate that the Windows Sockets implementation should send no further messages related to network events on the socket - *IEvent* should be set to zero.

```
rc = WSAAsyncSelect(s, hWnd, 0, 0);
```

Although the **WSAAsyncSelect()** takes effect immediately, it is possible that messages may be waiting in the application's message queue. The application must therefore be prepared to receive network event messages even after cancellation.

This function automatically sets socket *s* to non-blocking mode.

When one of the nominated network events occurs on the specified socket *s*, the application's window *hWnd* receives message *wMsg*. The *wParam* argument identifies the socket on which a network event has occurred. The low word of *IParam* specifies the network event that has occurred. The high word of *IParam* contains any error code. The error code be any error as defined in **winsock.h**.

The error and event codes may be extracted from the *IParam* using the macros WSAGETSELECTERROR and WSAGETSELECTEVENT, defined in **winsock.h** as:

```
#define WSAGETSELECTERROR(IParam) HIWORD(IParam)  
#define WSAGETSELECTEVENT(IParam) LOWORD(IParam)
```

The use of these macros will maximize the portability of the source code for the application.

The possible network event codes which may be returned are as follows:

Value	Meaning
FD_READ	Socket <i>s</i> ready for reading
FD_WRITE	Socket <i>s</i> ready for writing
FD_OOB	Out-of-band data ready for reading on socket <i>s</i> .
FD_ACCEPT	Socket <i>s</i> ready for accepting a new incoming connection
FD_CONNECT	Connection on socket <i>s</i> completed
FD_CLOSE	Connection identified by socket <i>s</i> has been closed

Return Value The return value is 0 if the application's declaration of interest in the network event set was successful. Otherwise the value SOCKET_ERROR is returned, and a specific error number may be retrieved by calling **WSAGetLastError()**.

Comments Although **WSAAsyncSelect()** can be called with interest in multiple events, the application window will receive a single message for each network event.

As in the case of the **select()** function, **WSAAsyncSelect()** will frequently be used to determine when a data transfer operation (**send()** or **recv()**) can be

Appendix C: Background Information 119

issued with the expectation of immediate success. Nevertheless, a robust application must be prepared for the possibility that it may receive a message and issue a Windows Sockets API call which returns WSAEWOULDBLOCK immediately. For example, the following sequence of events is possible:

- (i) data arrives on socket **s**; Windows Sockets posts **WSAAsyncSelect** message
- (ii) application processes some other message
- (iii) while processing, application issues an **ioctlsocket(s, FIONREAD...)** and notices that there is data ready to be read
- (iv) application issues a **recv(s,...)** to read the data
- (v) application loops to process next message, eventually reaching the **WSAAsyncSelect** message indicating that data is ready to read
- (vi) application issues **recv(s,...)**, which fails with the error WSAEWOULDBLOCK.

Other sequences are possible.

The Windows Sockets DLL will not continually flood an application with messages for a particular network event. Having successfully posted notification of a particular event to an application window, no further message(s) for that network event will be posted to the application window until the application makes the function call which implicitly re-enables notification of that network event.

Event	Re-enabling function
FD_READ	recv() or recvfrom()
FD_WRITE	send() or sendto()
FD_OOB	recv()
FD_ACCEPT	accept()
FD_CONNECT	NONE
FD_CLOSE	NONE

There is an intrinsic race condition in the message-based model that application developers should be aware of in their programming. Consider the following sequence:

- (i) Windows Sockets DLL receives 100 bytes of data on socket **s** and sends a message to the application
- (ii) application begins processing the message
- (iii) application issues **ioctlsocket(s, FIONREAD,...)** and learns that there are 100 bytes of data ready
- (iv) Windows Sockets DLL receives another 50 bytes of data. Since the application has not issued the re-enabling function (see below), no new message is sent
- (v) application performs a **recv(s, bufptr, 100, 0)** to read 100 bytes of data (as indicated by the FIONREAD)
- (vi) application yields, and unless more data is sent it never knows that there are 50 bytes of unread data

There are three obvious solutions to this. First, the application can issue another FIONREAD **ioctlsocket()** after the **recv()** to determine whether more data is available, Secondly, the application can perform repeated **recv()**'s until it encounters WSAEWOULDBLOCK. Finally, the application can issue a single **recv()** with a *len* which it can be certain is sufficient to gather all of the waiting

120 Appendix C: Background Information

data. (This last method is obviously risky unless the pattern of data transmission is well understood.)

The FD_OOB event is used only when a socket is configured to receive out-of-band data separately. If the socket is configured to receive out-of-band data in-line, the out-of-band (expedited) data is treated as normal data and the application should register an interest in, and will receive, FD_READ events, not FD_OOB events. An application may set or inspect the way in which out-of-band data is to be handled by using setsockopt() or getsockopt for the SO_OOBINLINE option.

Error Codes	WSANOTINITIALISED	A successful <u>WSAStartup()</u> must occur before using this API.
	WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
	WSAEINVAL	Indicates that one of the specified parameters was invalid
	WSAEINPROGRESS	A blocking Windows Sockets operation is in progress.

Additional error codes may be set when an application window receives a message. This error code is extracted from the *IParam* in the reply message using the WSAGETSELECTERROR macro. Possible error codes for each network event are:

Event: FD_CONNECT

Error Code

Meaning

WSAEADDRINUSE	The specified address is already in use.
WSAEADDRNOTAVAIL	The specified address is not available from the local machine.
WSAEAFNOSUPPORT	Addresses in the specified family cannot be used with this socket.
WSAECONNREFUSED	The attempt to connect was forcefully rejected.
WSAEDESTADDRREQ	A destination address is required.
WSAEFAULT	The namelen argument is incorrect.
WSAEINVAL	The socket is already bound to an address.
WSAEISCONN	The socket is already connected.
WSAEMFILE	No more file descriptors are available.
WSAENETUNREACH	The network can't be reached from this host at this time.
WSAENOBUFS	No buffer space is available. The socket cannot be connected.
WSAENOTCONN	The socket is not connected.

Appendix C: Background Information 121

WSAENOTSOCK	The descriptor is a file, not a socket.
WSAETIMEDOUT	Attempt to connect timed out without establishing a connection
Event: FD_CLOSE	
Event: FD_READ	
Event: FD_WRITE	
Event: FD_OOB	
Event: FD_ACCEPT	
<u>Error Code</u>	<u>Meaning</u>
WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.

Notes For Windows Sockets Suppliers

It is the responsibility of the Windows Sockets Supplier to ensure that messages are successfully posted to the application. If a **PostMessage()** operation fails, the Windows Sockets implementation **must** re-post that message.

Windows Sockets suppliers should use the WSAMAKESELECTREPLY macro when constructing the *IParam* in the message.

When a socket is closed, the Windows Sockets Supplier should purge any messages remaining for posting to the application window. However the application must be prepared to receive, and discard, any messages which may have been posted prior to the **closesocket()**.

See Also **select()**

122 Appendix C: Background Information

#₃₀₂ \$₃₀₃ +₃₀₄ K₃₀₅ Microsoft Windows Specific Extensions

WSACancelAsyncRequest()

Description Cancel an incomplete asynchronous operation.

```
#include <winsock.h>
```

```
int WSACancelAsyncRequest ( HANDLE hAsyncTaskHandle );
```

hAsyncTaskHandle Specifies the asynchronous operation to be canceled.

Remarks The **WSACancelAsyncRequest()** function is used to cancel an asynchronous operation which was initiated by one of the **WSAAsyncGetXByY()** functions such as **WSAAsyncGetHostByName()**. The operation to be canceled is identified by the *hAsyncTaskHandle* parameter, which should be set to the asynchronous task handle as returned by the initiating function.

Return Value The value returned by **WSACancelAsyncRequest()** is 0 if the operation was successfully canceled. Otherwise the value SOCKET_ERROR is returned, and a specific error number may be retrieved by calling **WSAGetLastError()**.

Comments An attempt to cancel an existing asynchronous **WSAAsyncGetXByY()** operation can fail with an error code of WSAEALREADY for two reasons. Firstly, the original operation has already completed and the application has dealt with the resultant message. Secondly, the original operation has already completed but the resultant message is still waiting in the application window queue.

Notes For Windows Sockets

Suppliers It is unclear whether the application can usefully distinguish between WSAEINVAL and WSAEALREADY, since in both cases the error indicates that there is no asynchronous operation in progress with the indicated handle. [Trivial exception: 0 is always an invalid asynchronous task handle.] The Windows Sockets specification does not prescribe how a conformant Windows Sockets implementation should distinguish between the two cases. For maximum portability, a Windows Sockets application should treat the two errors as equivalent.

Error Codes	WSANOTINITIALISED	A successful WSAStartup() must occur before using this API.
	WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.

302# WinSock_CancelAsyncRequest

303\$ WSACancelAsyncRequest()

304+ WinSockWSE:0080

305^K WSACancelAsyncRequest()

Appendix C: Background Information 123

WSAEINVAL	Indicates that the specified asynchronous task handle was invalid
WSAEINPROGRESS	A blocking Windows Sockets operation is in progress.
WSAEALREADY	The asynchronous routine being canceled has already completed.

See Also

[WSAAsyncGetHostByAddr\(\)](#), [WSAAsyncGetHostByName\(\)](#),
[WSAAsyncGetProtoByNumber\(\)](#), [WSAAsyncGetProtoByName\(\)](#),
[WSAAsyncGetHostByName\(\)](#), [WSAAsyncGetServByPort\(\)](#),
[WSAAsyncGetServByName\(\)](#)

#³⁰⁶ \$³⁰⁷ +³⁰⁸ K³⁰⁹ **Microsoft Windows Specific Extensions****WSACancelBlockingCall()**

Description Cancel a blocking call which is currently in progress.

```
#include <winsock.h>
```

```
int WSACancelBlockingCall ( void );
```

Remarks This function cancels any outstanding blocking operation for this task. It is normally used in two situations:

(1) An application is processing a message which has been received while a blocking call is in progress. In this case, **WSAIsBlocking()** will be true.

(2) A blocking call is in progress, and Windows Sockets has called back to the application's "blocking hook" function (as established by **WSASetBlockingHook()**).

In each case, the original blocking call will terminate as soon as possible with the error WSAEINTR. (In (1), the termination will not take place until Windows message scheduling has caused control to revert to the blocking routine in Windows Sockets. In (2), the blocking call will be terminated as soon as the blocking hook function completes.)

In the case of a blocking **connect()** operation, the Windows Sockets implementation will terminate the blocking call as soon as possible, but it may not be possible for the socket resources to be released until the connection has completed (and then been reset) or timed out. This is likely to be noticeable only if the application immediately tries to open a new socket (if no sockets are available), or to **connect()** to the same peer.

Return Value The value returned by **WSACancelBlockingCall()** is 0 if the operation was successfully canceled. Otherwise the value SOCKET_ERROR is returned, and a specific error number may be retrieved by calling **WSAGetLastError()**.

Error Codes	WSANOTINITIALISED	A successful WSAStartup() must occur before using this API.
	WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
	WSAEINVAL	Indicates that there is no outstanding blocking call.

306# WinSock_CancelBlockingCall

307\$ WSACancelBlockingCall()

308+ WinSockWSE:0090

309K WSACancelBlockingCall()

#³¹⁰ \$³¹¹ +³¹² K³¹³ **Microsoft Windows Specific Extensions****WSACleanup()****Description** Terminate use of the Windows Sockets DLL.**#include <winsock.h>****int WSACleanup (void);****Remarks** An application is required to perform a (successful) **WSAStartup()** call before it can use Windows Sockets services. When it has completed the use of Windows Sockets, the application may call **WSACleanup()** to deregister itself from a Windows Sockets implementation.**Return Value** The return value is 0 if the operation was successful. Otherwise the value SOCKET_ERROR is returned, and a specific error number may be retrieved by calling **WSAGetLastError()**.**Notes For
Windows Sockets
Suppliers**Well-behaved Windows Sockets applications will make a **WSACleanup()** call to indicate deregistration from a Windows Sockets implementation. This function can thus, for example, be utilized to free up resources allocated to the specific application.A Windows Sockets implementation must be prepared to deal with an application which terminates without invoking **WSACleanup()** - for example, as a result of an error.In a multithreaded environment, **WSACleanup()** terminates Windows Sockets operations for all threads.A Windows Sockets implementation must ensure that **WSACleanup()** leaves things in a state in which the application can invoke **WSAStartup()** to re-establish Windows Sockets usage.

Error Codes	WSANOTINITIALISED	A successful WSAStartup() must occur before using this API.
	WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
	WSAEINPROGRESS	A blocking Windows Sockets operation is in progress.

See Also **WSAStartup()**

310# WinSock_Cleanup

311\$ WSACleanup()

312+ WinSockWSE:0100

313K WSACleanup()

#³¹⁴ \$³¹⁵ +³¹⁶ K³¹⁷ **Microsoft Windows Specific Extensions****WSAGetLastError()**

Description Get the error status for the last operation which failed.

```
#include <winsock.h>
```

```
int WSAGetLastError ( void );
```

Remarks This function returns the last network error that occurred. When a particular Windows Sockets API function indicates that an error has occurred, this function should be called to retrieve the appropriate error code.

Return Value The return value indicates the error code for the last Windows Sockets API routine performed by this thread.

**Notes For
Windows Sockets**

Suppliers The use of the **WSAGetLastError()** function to retrieve the last error code, rather than relying on a global error variable (cf. *errno*), is required in order to provide compatibility with future multi-threaded environments.

Note that in a Win16 environment **WSAGetLastError()** is used to retrieve only Windows Sockets API errors. In a Win32 environment, **WSAGetLastError()** will invoke **GetLastError()**, which is used to retrieve the error status for all Win32 API functions on a per-thread basis. For portability, an application should use **WSAGetLastError()** immediately after the Windows Sockets API function which failed.

See Also [WSASetLastError\(\)](#)

314# WinSock_GetLastError

315\$ WSAGetLastError()

316+ WinSockWSE:0110

317K WSAGetLastError()

128 Appendix C: Background Information

#³¹⁸ \$³¹⁹ +³²⁰ K³²¹ Microsoft Windows Specific Extensions

WSAIsBlocking()

Description Determine if a blocking call is in progress.

```
#include <winsock.h>
```

```
BOOL WSAIsBlocking ( void );
```

Remarks This function allows a task to determine if it is executing while waiting for a previous blocking call to complete.

Return Value The return value is TRUE if there is an outstanding blocking function awaiting completion. Otherwise, it is FALSE.

Comments Although a call issued on a blocking socket appears to an application program as though it "blocks", the Windows Sockets DLL has to relinquish the processor to allow other applications to run. This means that it is possible for the application which issued the blocking call to be re-entered, depending on the message(s) it receives. In this instance, the **WSAIsBlocking()** function can be used to ascertain whether the task has been re-entered while waiting for an outstanding blocking call to complete. Note that Windows Sockets prohibits more than one outstanding call per thread.

Notes For Windows Sockets

Suppliers A Windows Sockets implementation must prohibit more than one outstanding blocking call per thread.

318# WinSock_IsBlocking
319\$ WSAIsBlocking()
320+ WinSockWSE:0120
321^K WSAIsBlcoking()

#₃₂₂ \$₃₂₃ +₃₂₄ K₃₂₅ **Microsoft Windows Specific Extensions**

WSASetBlockingHook()

Description Establish an application-specific blocking hook function.

#include <winsock.h>

FARPROC WSASetBlockingHook (FARPROC lpBlockFunc);

lpBlockFunc A pointer to the procedure instance address of the blocking function to be installed.

Remarks This function installs a new function which a Windows Sockets implementation should use to implement blocking socket function calls.

A Windows Sockets implementation includes a default mechanism by which blocking socket functions are implemented. The function **WSASetBlockingHook()** gives the application the ability to execute its own function at "blocking" time in place of the default function.

When an application invokes a blocking Windows Sockets API operation, the Windows Sockets implementation initiates the operation and then enters a loop which is equivalent to the following pseudocode:

```
for (;;) {
    /* flush messages for good user response */
    while (BlockingHook ())
        ;
    /* check for WSACancelBlockingCall() */
    if (operation_cancelled ())
        break;
    /* check to see if operation completed */
    if (operation_complete ())
        break; /* normal completion */
}
```

The default **BlockingHook()** function is equivalent to:

```
BOOL DefaultBlockingHook(void) {
    MSG msg;
    BOOL ret;
    /* get the next message if any */
    ret = (BOOL) PeekMessage (&msg, 0, 0, 0, PM_REMOVE);
    /* if we got one, process it */
    if (ret) {
        TranslateMessage (&msg);
```

322# WinSock_SetBlcokingHook

323\$ WSASetBlockingHook()

324+ WinSockWSE:0125

325^K WSASetBlockingHook()

130 Appendix C: Background Information

```
        DispatchMessage (&msg);
    }
    /* TRUE if we got a message */
    return ret;
}
```

The **WSASetBlockingHook()** function is provided to support those applications which require more complex message processing - for example, those employing the MDI (multiple document interface) model. It is not intended as a mechanism for performing general applications functions. In particular, the only Windows Sockets API function which may be issued from a custom blocking hook function is **WSACancelBlockingCall()**, which will cause the blocking loop to terminate.

Return Value The return value is a pointer to the procedure-instance of the previously installed blocking function. The application or library that calls the **WSASetBlockingHook ()** function should save this return value so that it can be restored if necessary. (If "nesting" is not important, the application may simply discard the value returned by **WSASetBlockingHook()** and eventually use **WSAUnsetBlockingHook()** to restore the default mechanism.) If the operation fails, a NULL pointer is returned, and a specific error number may be retrieved by calling **WSAGetLastError()**.

Notes For Windows Sockets

Suppliers This function must be implemented on a per-thread basis. It thus provides for a particular thread to replace the blocking mechanism without affecting other threads.

Error Codes	WSANOTINITIALISED	A successful <u>WSAStartup()</u> must occur before using this API.
	WSAENETDOWN	The Windows Sockets implementation has detected that the network subsystem has failed.
	WSAEINPROGRESS	A blocking Windows Sockets operation is in progress.

See Also **WSAUnhookBlockingHook()**

#³²⁶ \$³²⁷ +³²⁸ K³²⁹ **Microsoft Windows Specific Extensions****WSASetLastError()**

Description Set the error code which can be retrieved by **WSAGetLastError()**.

```
#include <winsock.h>
```

```
void WSASetLastError ( int iError );
```

Remarks This function allows an application to set the error code to be returned by a subsequent **WSAGetLastError()** call for the current thread. Note that any subsequent Windows Sockets routine called by the application will override the error code as set by this routine.

iError _____ Specifies the error code to be returned by a subsequent **WSAGetLastError()** call.

**Notes For
Windows Sockets**

Suppliers In a Win32 environment, this function will invoke **SetLastError()**.

Return Value None.

Error Codes WSANOTINITIALISED A successful **WSAStartup()** must occur before using this API.

See Also **WSAGetLastError()**

326# WinSock_SetLastError

327\$ WSASetLastError()

328+ WinSockWSE:0130

329K WSASetLastError()

132 Appendix C: Background Information

#³³⁰ \$³³¹ +³³² K³³³ Microsoft Windows Specific Extensions

WSAStartup()

Description

```
#include <winsock.h>
```

```
int WSAStartup ( WORD wVersionRequired, LPWSADATA lpWSADATA );
```

wVersionRequired The highest version of Windows Sockets API support required. The high order byte specifies the minor version (revision) number; the low-order byte specifies the major version number.

lpWSADATA A pointer to the **WSADATA** data structure that is to receive details of the Windows Sockets implementation.

Remarks

This function **must** be the first Windows Sockets function called by an application. It allows an application to specify the version of Windows Sockets API required and to retrieve details of the specific Windows Sockets implementation. The application may only issue further Windows Sockets API functions after a successful **WSAStartup()** invocation.

In order to support future Windows Sockets implementations and applications which may have functionality differences from Windows Sockets 1.0, a negotiation takes place in **WSAStartup()**. An application passes to **WSAStartup()** the highest Windows Sockets version that it can take advantage of. If this version is lower than the lowest version supported by the Windows Sockets DLL, the DLL cannot support the application and **WSAStartup()** returns WSAVERNOTSUPPORTED. Otherwise, the DLL will attempt to register the application as a client: if this fails, **WSAStartup()** fails and returns WSASYSNOTREADY. If the DLL can support the application and the registration process succeeds, the function stores the highest version of Windows Sockets supported by the DLL in the *wHighVersion* element of the *WSADATA* structure and returns 0. If *wHighVersion* is lower than the lowest version supported by the application, the application either fails its initialization or attempts to find another Windows Sockets DLL on the system.

This negotiation allows both a Windows Sockets DLL and a Windows Sockets application to support a range of Windows Sockets versions. An application can successfully utilize a DLL if there is any overlap in the versions. The following chart gives examples of how **WSAStartup()** works in conjunction with different application and DLL versions:

<u>App versions</u>	<u>DLL Versions</u>	<u><i>wVersionRequired</i></u>	<u><i>wHighVersion</i></u>	<u>Result</u>
1.0	1.0	1.0	1.0	use 1.0

330# WinSock_Startup

331\$ WSAStartup()

332+ WinSockWSE:0140

333^K WSAStartup()

Appendix C: Background Information 133

1.0 2.0	1.0	2.0	1.0	use 1.0
1.0	1.0 2.0	1.0	2.0	use 1.0
1.0	2.0 3.0	1.0	(failure)	fail
2.0 3.0	1.0	3.0	1.0	fail
1.0 2.0 3.0	1.0 2.0 3.0	3.0	3.0	use 3.0

Once an application has made a successful **WSAStartup()** call, it may proceed to make other Windows Sockets API calls as needed. When it has finished using the services of the Windows Sockets DLL, the application should call **WSACleanup()**.

Details of the actual Windows Sockets implementation are described in the WSADATA structure defined as follows:

```
struct WSADATA {
    WORD    wVersion;
    WORD    wHighVersion;
    char    szDescription[WSADESCRIPTION_LEN+1];
    char    szSystemStatus[WSASYSSTATUS_LEN+1];
    int     iMaxSockets;
    int     iMaxUdpDg;
    char FAR * lpVendorInfo
};
```

The members of this structure are:

Element	Usage
<u>wVersion</u>	The version of the Windows Sockets DLL, encoded as for <u>wVersionRequired</u> .
<u>wHighVersion</u>	The highest version of the Windows Sockets specification that this DLL can support (also encoded as above). Normally this will be the same as <u>wVersion</u> .
<u>szDescription</u>	A null-terminated ASCII string into which the Windows Sockets DLL copies a description of the Windows Sockets implementation, including vendor identification. The text (up to 256 characters in length) may contain any characters, but vendors are cautioned against including control and formatting characters: the most likely use that an application will put this to is to display it (possibly truncated) in a status message.
<u>szSystemStatus</u>	A null-terminated ASCII string into which the Windows Sockets DLL copies relevant status or configuration information. The Windows Sockets DLL should use this field only if the information might be useful to the user or support staff: it should not be considered as an extension of the <u>szDescription</u> field.
<u>iMaxSockets</u>	The maximum number of sockets which a single process can potentially open. A Windows Sockets implementation may provide a global pool of sockets for allocation to any process; alternatively it may allocate per-process resources for sockets. The number may well reflect the way in which the Windows Sockets DLL or the networking software was configured. Application writers may use this number as a crude indication of whether the Windows Sockets implementation is usable by the application. For example, an X Windows server might check <u>iMaxSockets</u> when first started: if it is less than 8, the application would display an error message instructing the user to reconfigure the networking software. (This is a situation in

134 Appendix C: Background Information

which the `szSystemStatus` text might be used.) Obviously there is no guarantee that a particular application can actually allocate `iMaxSockets` sockets, since there may be other Windows Sockets applications in use.

`iMaxUdpDg` The size in bytes of the largest UDP datagram that can be sent or received by a Windows Sockets application. If the implementation imposes no limit, `iMaxUdpDg` is zero. In many implementations of Berkeley sockets, there is an implicit limit of 8192 bytes on UDP datagrams (which are fragmented if necessary). A Windows Sockets implementation may impose a limit based, for instance, on the allocation of fragment reassembly buffers. The minimum value of `iMaxUdpDg` for a compliant Windows Sockets implementation is 512. Note that regardless of the value of `iMaxUdpDg`, it is inadvisable to attempt to send a broadcast datagram which is larger than the Maximum Transmission Unit (MTU) for the network. (The Windows Sockets API does not provide a mechanism to discover the MTU, but it must be no less than 512 bytes.)

`IpVendorInfo` A far pointer to a vendor-specific data structure. The definition of this structure (if supplied) is beyond the scope of this specification.

Return Value `WSAStartup()` returns zero if successful. Otherwise it returns one of the error codes listed below. Note that the normal mechanism whereby the application calls `WSAGetLastError()` to determine the error code cannot be used, since the Windows Sockets DLL may not have established the client data area where the "last error" information is stored.

Notes For Windows Sockets

Suppliers Each Windows Sockets application **must** make a `WSAStartup()` call before issuing any other Windows Sockets API calls. This function can thus be utilized for initialization purposes.

Further issues are discussed in the notes for `WSACleanup()`.

Error Codes `WSASYSNOTREADY` Indicates that the underlying network subsystem is not ready for network communication.

`WSAVERNOTSUPPORTED` The version of Windows Sockets API support requested is not provided by this particular Windows Sockets implementation.

`WSAEINVAL` The Windows Sockets version specified by the application is not supported by this DLL.

See Also `send()`, `sendto()`, `WSACleanup()`

#³³⁴ \$³³⁵ +³³⁶ K³³⁷ **Microsoft Windows Specific Extensions****WSAUnhookBlockingHook()**

Description Restore the default blocking hook function.

```
#include <winsock.h>
```

```
int WSAUnhookBlockingHook ( void );
```

Remarks This function removes any previous blocking hook that has been installed and reinstalls the default blocking mechanism.

WSAUnhookBlockingHook() will always install the **default** mechanism, not the **previous** mechanism. If an application wish to nest blocking hooks - i.e. to establish a temporary blocking hook function and then revert to the previous mechanism (whether the default or one established by an earlier **WSASetBlockingHook()**) - it must save and restore the value returned by **WSASetBlockingHook()**; it cannot use **WSAUnhookBlockingHook()**.

Return Value The return value is 0 if the operation was successful. Otherwise the value SOCKET_ERROR is returned, and a specific error number may be retrieved by calling **WSAGetLastError()**.

Error Codes WSANOTINITIALISED A successful **WSAStartup()** must occur before using this API.

See Also **WSASetBlockingHook()**

334# WinSock_UnhookBlockingHook

335\$ WSAUnhookBlockingHook()

336+ WinSockWSE:0150

337K WSAUnhookBlockingHook()

136 Appendix C: Background Information

#³³⁸ \$³³⁹ +³⁴⁰ K³⁴¹ Windows Sockets

Error Codes

The following is a list of possible error codes returned by the WSAGetLastError() call, along with their explanations. The error numbers are consistently set across all Windows Sockets-compliant implementations.

338# Winsock_ErrorCodes

339\$ Error Codes

340+ WinSock:0040

341^K Error Codes

Appendix C: Background Information 137

Windows Sockets code	Berkeley equivalent	Error	Interpretation
WSAEINTR	EINTR	10004	As in standard C
WSAEBADF	EBADF	10009	As in standard C
WSAEINVAL	EINVAL	10022	As in standard C
WSAEMFILE	EMFILE	10024	As in standard C
WSAEWOULDBLOCK	EWOULDBLOCK	10035	As in BSD
WSAEINPROGRESS	EINPROGRESS	10036	This error is returned if anyWindows Sockets API function is called while a blocking function is in progress.
WSAEALREADY	EALREADY	10037	As in BSD
WSAENOTSOCK	ENOTSOCK	10038	As in BSD
WSAEDESTADDRREQ	EDESTADDRREQ	10039	As in BSD
WSAEMSGSIZE	EMSGSIZE	10040	As in BSD
WSAEPROTOPT	EPROTOPT	10041	As in BSD
WSAENOPROTOPT	ENOPROTOPT	10042	As in BSD
WSAEPROTONOSUPPORT	EPROTONOSUPPORT	10043	As in BSD
WSAESOCKTNOSUPPORT	ESOCKTNOSUPPORT	10044	As in BSD
WSAEOPNOTSUPPORT	EOPNOTSUPPORT	10045	As in BSD
WSAEPFNOSUPPORT	EPFNOSUPPORT	10046	As in BSD
WSAEAFNOSUPPORT	EAFNOSUPPORT	10047	As in BSD
WSAEADDRINUSE	EADDRINUSE	10048	As in BSD
WSAEADDRNOTAVAIL	EADDRNOTAVAIL	10049	As in BSD
WSAENETDOWN	ENETDOWN	10050	As in BSD. This error may be reported at any time if the Windows Sockets implementation detects an underlying failure.
WSAENETUNREACH	ENETUNREACH	10051	As in BSD
WSAENETRESET	ENETRESET	10052	As in BSD
WSAECONNABORTED	ECONNABORTED	10053	As in BSD
WSAECONNRESET	ECONNRESET	10054	As in BSD
WSAENOBUFS	ENOBUFS	10055	As in BSD
WSAEISCONN	EISCONN	10056	As in BSD
WSAENOTCONN	ENOTCONN	10057	As in BSD
WSAESHUTDOWN	ESHUTDOWN	10058	As in BSD
WSAETOOMANYREFS	ETOOMANYREFS	10059	As in BSD
WSAETIMEDOUT	ETIMEDOUT	10060	As in BSD
WSAECONNREFUSED	ECONNREFUSED	10061	As in BSD
WSAELOOP	ELOOP	10062	As in BSD
WSAENAMETOOLONG	ENAMETOOLONG	10063	As in BSD
WSAEHOSTDOWN	EHOSTDOWN	10064	As in BSD
WSAEHOSTUNREACH	EHOSTUNREACH	10065	As in BSD
WSASYSNOTREADY		10091	Returned by WSAStartup() indicating that the network subsystem is unusable.
WSAVERNOTSUPPORTED		10092	Returned by WSAStartup() indicating that the Windows Sockets DLL cannot support this app.
WSANOTINITIALISED		10093	Returned by any function except WSAStartup() indicating that a successful WSAStartup() has not yet been performed.
WSAHOST_NOT_FOUND	HOST_NOT_FOUND	11001	As in BSD.
WSATRY_AGAIN	TRY_AGAIN	11002	As in BSD
WSANO_RECOVERY	NO_RECOVERY	11003	As in BSD
WSANO_DATA	NO_DATA	11004	As in BSD

The first set of definitions is present to resolve contentions between standard C error codes which may be defined inconsistently between various C compilers.

The second set of definitions provides Windows Sockets versions of regular Berkeley Sockets error codes.

The third set of definitions consists of extended Windows Sockets-specific error codes.

138 Appendix C: Background Information

The fourth set of errors are returned by Windows Sockets **getXbyY()** and **WSAAsyncGetXByY()** functions, and correspond to the errors which in Berkeley software would be returned in the *h_errno* variable. They correspond to various failures which may be returned by the Domain Name Service. If the Windows Sockets implementation does not use the DNS, it will use the most appropriate code. In general, a Windows Sockets application should interpret WSAHOST_NOT_FOUND and WSANO_DATA as indicating that the key (name, address, etc.) was not found,, while WSATRY_AGAIN and WSANO_RECOVERY suggest that the name service itself is non-operational.

The error numbers are derived from the [winsock.h](#) header file, and are based on the fact that Windows Sockets error numbers are computed by adding 10000 to the "normal" Berkeley error number.

Note that this table does not include all of the error codes defined in **winsock.h**. This is because it includes only errors which might reasonably be returned by a Windows Sockets implementation: **winsock.h**, on the other hand, includes a full set of BSD definitions to ensure compatibility with ported software.

#³⁴² \$³⁴³ +³⁴⁴ K³⁴⁵ **Windows Sockets**

Header Files

Berkeley Header Files

Windows Sockets Header File - winsock.h

342# Winsock_HeaderFiles

343\$ Header Files

344+ WinSock:0050

345K Header Files

140 Appendix C: Background Information

#³⁴⁶ \$³⁴⁷ +³⁴⁸ K³⁴⁹ Windows Sockets Header Files

Berkeley Header Files

A Windows Sockets supplier who provides a development kit to support the development of Windows Sockets applications must supply a set of vestigial header files with names that match a number of the header files in the Berkeley software distribution. These files are provided for source code compatibility only, and each consists of three lines:

```
#ifndef _WINSOCK_API_  
#include <winsock.h>  
#endif
```

The header files provided for compatibility are:

netdb.h
arpa/inet.h
sys/time.h
sys/socket.h
netinet/in.h

The file **winsock.h** contains all of the type and structure definitions, constants, macros, and function prototypes used by the Windows Sockets specification. An application writer may choose to ignore the compatibility headers and include **winsock.h** in each source file.

346# Winsock_BerkeleyHeaders
347\$ Berkeley Header Files
348+ WinsockH:0010
349K Header Files

#350 \$351 +352 K353 Windows Sockets Header Files

Windows Sockets Header File - winsock.h

The **winsock.h** header file includes a number of types and definitions from the standard Windows header file **windows.h**. The **windows.h** in the Windows 3.0 SDK (Software Developer's Kit) lacks a **#include** guard, so if you need to include **windows.h** as well as **winsock.h**, you should define the symbol **_INC_WINDOWS** before **#including winsock.h**, as follows:

```
#include <windows.h>
#define _INC_WINDOWS
#include <winsock.h>
```

Users of the SDK for Windows 3.1 and later need not do this.

```
/* WINSOCK.H--definitions to be used with the WINSOCK.DLL
 *
 * This file includes parts which are Copyright (c) 1982-1986 Regents
 * of the University of California. All rights reserved. The
 * Berkeley Software License Agreement specifies the terms and
 * conditions for redistribution.
 */

#ifndef _WINSOCKAPI_
#define _WINSOCKAPI_

/*
 * Pull in WINDOWS.H if necessary
 */
#ifndef _INC_WINDOWS
#include <windows.h>
#endif /* _INC_WINDOWS */

/*
 * Basic system type definitions, taken from the BSD file sys/types.h.
 */
typedef unsigned char u_char;
typedef unsigned short u_short;
typedef unsigned int u_int;
typedef unsigned long u_long;

/*
 * The new type to be used in all
 * instances which refer to sockets.
 */
typedef unsigned int SOCKET;

/*
 * Select uses arrays of SOCKETS. These macros manipulate such
 * arrays. FD_SETSIZE may be defined by the user before including
 * this file, but the default here should be >= 64.
 *
 * CAVEAT IMPLEMENTOR and USER: THESE MACROS AND TYPES MUST BE
 * INCLUDED IN WINSOCK.H EXACTLY AS SHOWN HERE.
 */
#ifndef FD_SETSIZE
#define FD_SETSIZE 64
#endif /* FD_SETSIZE */
```

350# Winsock_WinsockH

351\$ Windows Sockets Header File - winsock.h

352+ WinsockH:0020

353K Header Files

142 Appendix C: Background Information

```
typedef struct fd_set {
    u_short fd_count;          /* how many are SET? */
    SOCKET fd_array[FD_SETSIZE]; /* an array of SOCKETS */
} fd_set;

extern int PASCAL FAR __WSAFDIsSet(SOCKET, fd_set FAR *);

#define FD_CLR(fd, set) { \
    u_int __i; \
    for (__i = 0; __i < ((fd_set FAR *) (set))->fd_count; __i++) { \
        if (((fd_set FAR *) (set))->fd_array[__i] == fd) { \
            while (__i < ((fd_set FAR *) (set))->fd_count-1) { \
                ((fd_set FAR *) (set))->fd_array[__i] = \
                    ((fd_set FAR *) (set))->fd_array[__i+1]; \
                __i++; \
            } \
            ((fd_set FAR *) (set))->fd_count--; \
            break; \
        } \
    } \
}

#define FD_SET(fd, set) { \
    if (((fd_set FAR *) (set))->fd_count < FD_SETSIZE) \
        ((fd_set FAR *) (set))->fd_array[((fd_set FAR *) (set))->fd_count++] = fd; \
}

#define FD_ZERO(set) ((fd_set FAR *) (set))->fd_count=0

#define FD_ISSET(fd, set) __WSAFDIsSet((int)fd, (fd_set FAR *) set)

/*
 * Structure used in select() call, taken from the BSD file sys/time.h.
 */
struct timeval {
    long    tv_sec;          /* seconds */
    long    tv_usec;        /* and microseconds */
};

/*
 * Operations on timevals.
 *
 * NB: timercmp does not work for >= or <=.
 */
#define timerisset(tvp)      ((tvp)->tv_sec || (tvp)->tv_usec)
#define timercmp(tvp, uvp, cmp) \
    ((tvp)->tv_sec cmp (uvp)->tv_sec || \
     (tvp)->tv_sec == (uvp)->tv_sec && (tvp)->tv_usec cmp (uvp)->tv_usec)
#define timerclear(tvp)      (tvp)->tv_sec = (tvp)->tv_usec = 0

/*
 * Commands for ioctlsocket(),          taken from the BSD file fcntl.h.
 *
 *
 * Ioctl's have the command encoded in the lower word,
 * and the size of any in or out parameters in the upper
 * word.  The high 2 bits of the upper word are used
 * to encode the in/out status of the parameter; for now
 * we restrict parameters to at most 128 bytes.
 */
#define IOCPARM_MASK    0x7f          /* parameters must be < 128 bytes */
#define IOC_VOID        0x20000000    /* no parameters */
#define IOC_OUT          0x40000000    /* copy out parameters */
#define IOC_IN           0x80000000    /* copy in parameters */
#define IOC_INOUT        (IOC_IN|IOC_OUT)
/* 0x20000000 distinguishes new &
   old ioctl's */
#define _IO(x,y)        (IOC_VOID|('x'<<8)|y)
#define _IOR(x,y,t)     (IOC_OUT|((sizeof(t)&IOCPARM_MASK)<<16)|('x'<<8)|y)
```

Appendix C: Background Information 143

```
#define _IOW(x,y,t)      (IOC_IN|((sizeof(t)&IOCPARM_MASK)<<16)|('x'<<8)|y)

#define FIONREAD        _IOR(f, 127, int)      /* get # bytes to read */
#define FIONBIO         _IOW(f, 126, int) /* set/clear non-blocking i/o */
#define FIOASYNC        _IOW(f, 125, int)      /* set/clear async i/o */

/* Socket I/O Controls */
#define SIOCSHIWAT      _IOW(s,  0, int) /* set high watermark */
#define SIOCGHIWAT      _IOR(s,  1, int) /* get high watermark */
#define SIOCSLOWAT      _IOW(s,  2, int) /* set low watermark */
#define SIOCGLOWAT      _IOR(s,  3, int) /* get low watermark */
#define SIOCATMARK      _IOR(s,  7, int) /* at oob mark? */

/*
 * Structures returned by network data base library, taken from the
 * BSD file netdb.h.  All addresses are supplied in host order, and
 * returned in network order (suitable for use in system calls).
 */

struct hostent {
    char    FAR * h_name;          /* official name of host */
    char    FAR * FAR * h_aliases; /* alias list */
    int     h_addrtype;           /* host address type */
    int     h_length;             /* length of address */
    char    FAR * FAR * h_addr_list; /* list of addresses */
#define h_addr h_addr_list[0]      /* address, for backward compat */
};

/*
 * It is assumed here that a network number
 * fits in 32 bits.
 */
struct netent {
    char    FAR * n_name;          /* official name of net */
    char    FAR * FAR * n_aliases; /* alias list */
    int     n_addrtype;           /* net address type */
    u_long  n_net;                /* network # */
};

struct servent {
    char    FAR * s_name;          /* official service name */
    char    FAR * FAR * s_aliases; /* alias list */
    int     s_port;               /* port # */
    char    FAR * s_proto;         /* protocol to use */
};

struct protoent {
    char    FAR * p_name;          /* official protocol name */
    char    FAR * FAR * p_aliases; /* alias list */
    int     p_proto;              /* protocol # */
};

/*
 * Constants and structures defined by the internet system,
 * Per RFC 790, September 1981, taken from the BSD file netinet/in.h.
 */

/*
 * Protocols
 */
#define IPPROTO_IP      0          /* dummy for IP */
#define IPPROTO_ICMP    1          /* control message protocol */
#define IPPROTO_GGP     2          /* gateway^2 (deprecated) */
#define IPPROTO_TCP     6          /* tcp */
#define IPPROTO_PUP     12         /* pup */
#define IPPROTO_UDP     17         /* user datagram protocol */
#define IPPROTO_IDP     22         /* xns idp */
#define IPPROTO_ND      77         /* UNOFFICIAL net disk proto */

#define IPPROTO_RAW     255        /* raw IP packet */
```

144 Appendix C: Background Information

```
#define IPPROTO_MAX          256

/*
 * Port/socket numbers: network standard functions
 */
#define IPPORT_ECHO          7
#define IPPORT_DISCARD      9
#define IPPORT_SYSTAT       11
#define IPPORT_DAYTIME      13
#define IPPORT_NETSTAT      15
#define IPPORT_FTP           21
#define IPPORT_TELNET        23
#define IPPORT_SMTP          25
#define IPPORT_TIMESERVER    37
#define IPPORT_NAMESERVER    42
#define IPPORT_WHOIS         43
#define IPPORT_MTP           57

/*
 * Port/socket numbers: host specific functions
 */
#define IPPORT_TFTP          69
#define IPPORT_RJE           77
#define IPPORT_FINGER        79
#define IPPORT_TTYLINK       87
#define IPPORT_SUPDUP        95

/*
 * UNIX TCP sockets
 */
#define IPPORT_EXECSERVER    512
#define IPPORT_LOGINSERVER   513
#define IPPORT_CMDSERVER     514
#define IPPORT_EFSSERVER     520

/*
 * UNIX UDP sockets
 */
#define IPPORT_BIFFUDP       512
#define IPPORT_WHOSERVER     513
#define IPPORT_ROUTESEVER    520
/* 520+1 also used */

/*
 * Ports < IPPORT_RESERVED are reserved for
 * privileged processes (e.g. root).
 */
#define IPPORT_RESERVED      1024

/*
 * Link numbers
 */
#define IMPLINK_IP           155
#define IMPLINK_LOWEXPER     156
#define IMPLINK_HIGHEXPER    158

/*
 * Internet address (old style... should be updated)
 */
struct in_addr {
    union {
        struct { u_char s_b1,s_b2,s_b3,s_b4; } S_un_b;
        struct { u_short s_w1,s_w2; } S_un_w;
        u_long S_addr;
    } S_un;
#define s_addr S_un.S_addr
/* can be used for most tcp & ip code */
#define s_host S_un.S_un_b.s_b2
/* host on imp */
#define s_net S_un.S_un_b.s_b1
/* network */
```


Appendix C: Background Information 145

```
#define s_imp S_un.S_un_w.s_w2
/* imp */
#define s_impno S_un.S_un_b.s_b4
/* imp # */
#define s_lh S_un.S_un_b.s_b3
/* logical host */
};

/*
 * Definitions of bits in internet address integers.
 * On subnets, the decomposition of addresses to host and net parts
 * is done according to subnet mask, not the masks here.
 */
#define IN_CLASSA(i) ((long)(i) & 0x80000000) == 0)
#define IN_CLASSA_NET 0xff000000
#define IN_CLASSA_NSHIFT 24
#define IN_CLASSA_HOST 0x00ffffff
#define IN_CLASSA_MAX 128

#define IN_CLASSB(i) ((long)(i) & 0xc0000000) == 0x80000000)
#define IN_CLASSB_NET 0xffff0000
#define IN_CLASSB_NSHIFT 16
#define IN_CLASSB_HOST 0x0000ffff
#define IN_CLASSB_MAX 65536

#define IN_CLASSC(i) ((long)(i) & 0xc0000000) == 0xc0000000)
#define IN_CLASSC_NET 0xfffff000
#define IN_CLASSC_NSHIFT 8
#define IN_CLASSC_HOST 0x000000ff

#define INADDR_ANY (u_long)0x00000000
#define INADDR_LOOPBACK 0x7f000001
#define INADDR_BROADCAST (u_long)0xffffffff /* must be masked */
#define INADDR_NONE 0xffffffff /* -1 return */

/*
 * Socket address, internet style.
 */
struct sockaddr_in {
    short sin_family;
    u_short sin_port;
    struct in_addr sin_addr;
    char sin_zero[8];
};

#define WSADESCRIPTION_LEN 256
#define WSASYS_STATUS_LEN 128

typedef struct WSADATA {
    WORD wVersion;
    WORD wHighVersion;
    char szDescription[WSADESCRIPTION_LEN+1];
    char szSystemStatus[WSASYS_STATUS_LEN+1];
    int iMaxSockets;
    int iMaxUdpDg;
    char FAR * lpVendorInfo;
} WSADATA;

typedef WSADATA FAR *LPWSADATA;

/*
 * Options for use with [gs]etsockopt at the IP level.
 */
#define IP_OPTIONS 1 /* set/get IP per-packet options */

/*
 * Definitions related to sockets: types, address families, options,
 * taken from the BSD file sys/socket.h.
 */

/*
```

146 Appendix C: Background Information

```
* This is used instead of -1, since the
* SOCKET type is unsigned.
*/
#define INVALID_SOCKET (SOCKET) (~0)
#define SOCKET_ERROR   (-1)

/*
 * Types
 */
#define SOCK_STREAM 1 /* stream socket */
#define SOCK_DGRAM 2 /* datagram socket */
#define SOCK_RAW 3 /* raw-protocol interface */
#define SOCK_RDM 4 /* reliably-delivered message */
#define SOCK_SEQPACKET 5 /* sequenced packet stream */

/*
 * Option flags per-socket.
 */
#define SO_DEBUG 0x0001 /* turn on debugging info recording */
#define SO_ACCEPTCONN 0x0002 /* socket has had listen() */
#define SO_REUSEADDR 0x0004 /* allow local address reuse */
#define SO_KEEPAVAIL 0x0008 /* keep connections alive */
#define SO_DONTROUTE 0x0010 /* just use interface addresses */
#define SO_BROADCAST 0x0020 /* permit sending of broadcast msgs */
#define SO_USELOOPBACK 0x0040 /* bypass hardware when possible */
#define SO_LINGER 0x0080 /* linger on close if data present */
#define SO_OOBINLINE 0x0100 /* leave received OOB data in line */

#define SO_DONTLINGER (u_int) (~SO_LINGER)

/*
 * Additional options.
 */
#define SO_SNDBUF 0x1001 /* send buffer size */
#define SO_RCVBUF 0x1002 /* receive buffer size */
#define SO_SNDLOWAT 0x1003 /* send low-water mark */
#define SO_RCVLOWAT 0x1004 /* receive low-water mark */
#define SO_SNDTIMEO 0x1005 /* send timeout */
#define SO_RCVTIMEO 0x1006 /* receive timeout */
#define SO_ERROR 0x1007 /* get error status and clear */
#define SO_TYPE 0x1008 /* get socket type */

/*
 * Address families.
 */
#define AF_UNSPEC 0 /* unspecified */
#define AF_UNIX 1 /* local to host (pipes, portals) */
#define AF_INET 2 /* internet: UDP, TCP, etc. */
#define AF_IMPLINK 3 /* arpanet imp addresses */
#define AF_PUP 4 /* pup protocols: e.g. BSP */
#define AF_CHAOS 5 /* mit CHAOS protocols */
#define AF_NS 6 /* XEROX NS protocols */
#define AF_NBS 7 /* nbs protocols */
#define AF_ECMA 8 /* european computer manufacturers */
#define AF_DATAKIT 9 /* datakit protocols */
#define AF_CCITT 10 /* CCITT protocols, X.25 etc */
#define AF_SNA 11 /* IBM SNA */
#define AF_DECnet 12 /* DECnet */
#define AF_DLI 13 /* Direct data link interface */
#define AF_LAT 14 /* LAT */
#define AF_HYLINK 15 /* NSC Hyperchannel */
#define AF_APPLETALK 16 /* AppleTalk */

#define AF_MAX 17

/*
 * Structure used by kernel to store most
 * addresses.
 */
struct sockaddr {
    u_short sa_family; /* address family */
```

Appendix C: Background Information 147

```
    char    sa_data[14];          /* up to 14 bytes of direct address */
};

/*
 * Structure used by kernel to pass protocol
 * information in raw sockets.
 */
struct sockproto {
    u_short sp_family;           /* address family */
    u_short sp_protocol;        /* protocol */
};

/*
 * Protocol families, same as address families for now.
 */
#define PF_UNSPEC    AF_UNSPEC
#define PF_UNIX      AF_UNIX
#define PF_INET      AF_INET
#define PF_IMPLINK   AF_IMPLINK
#define PF_PUP       AF_PUP
#define PF_CHAOS     AF_CHAOS
#define PF_NS        AF_NS
#define PF_NBS       AF_NBS
#define PF_ECMA      AF_ECMA
#define PF_DATAKIT   AF_DATAKIT
#define PF_CCITT     AF_CCITT
#define PF_SNA       AF_SNA
#define PF_DECnet    AF_DECnet
#define PF_DLI       AF_DLI
#define PF_LAT       AF_LAT
#define PF_HYLINK   AF_HYLINK
#define PF_APPLETALK AF_APPLETALK

#define PF_MAX       AF_MAX

/*
 * Structure used for manipulating linger option.
 */
struct linger {
    u_short l_onoff;           /* option on/off */
    u_short l_linger;         /* linger time */
};

/*
 * Level number for (get/set)sockopt() to apply to socket itself.
 */
#define SOL_SOCKET    0xffff    /* options for socket level */

/*
 * Maximum queue length specifiable by listen.
 */
#define SOMAXCONN     5

#define MSG_OOB       0x1        /* process out-of-band data */
#define MSG_PEEK      0x2        /* peek at incoming message */
#define MSG_DONTROUTE 0x4        /* send without using routing tables */

#define MSG_MAXIOVLEN 16

/*
 * Define constant based on rfc883, used by gethostbyxxxx() calls.
 */
#define MAXGETHOSTSTRUCT 1024

/*
 * Define flags to be used with the WSAAsyncSelect() call.
 */
#define FD_READ       0x01
#define FD_WRITE      0x02
#define FD_OOB        0x04
```

148 Appendix C: Background Information

```
#define FD_ACCEPT      0x08
#define FD_CONNECT    0x16
#define FD_CLOSE      0x32

/*
 * All Windows Sockets error constants are biased by WSABASEERR from
 * the "normal"
 */
#define WSABASEERR      10000
/*
 * Windows Sockets definitions of regular Microsoft C error constants
 */
#define WSAEINTR        (WSABASEERR+4)
#define WSAEBADF        (WSABASEERR+9)
#define WSAEFAULT      (WSABASEERR+14)
#define WSAEINVAL      (WSABASEERR+22)
#define WSAEMFILE      (WSABASEERR+24)

/*
 * Windows Sockets definitions of regular Berkeley error constants
 */
#define WSAEWOULDBLOCK  (WSABASEERR+35)
#define WSAEINPROGRESS  (WSABASEERR+36)
#define WSAEALREADY     (WSABASEERR+37)
#define WSAENOTSOCK     (WSABASEERR+38)
#define WSAEDESTADDRREQ (WSABASEERR+39)
#define WSAEMSGSIZE     (WSABASEERR+40)
#define WSAEPROTOTYPE   (WSABASEERR+41)
#define WSAENOPROTOOPT  (WSABASEERR+42)
#define WSAEPROTONOSUPPORT (WSABASEERR+43)
#define WSAESOCKTOSUPPORT (WSABASEERR+44)
#define WSAEOPNOTSUPP   (WSABASEERR+45)
#define WSAEPFNOSUPPORT (WSABASEERR+46)
#define WSAEAFNOSUPPORT (WSABASEERR+47)
#define WSAEADDRINUSE   (WSABASEERR+48)
#define WSAEADDRNOTAVAIL (WSABASEERR+49)
#define WSAENETDOWN     (WSABASEERR+50)
#define WSAENETUNREACH  (WSABASEERR+51)
#define WSAENETRESET    (WSABASEERR+52)
#define WSAECONNABORTED (WSABASEERR+53)
#define WSAECONNRESET   (WSABASEERR+54)
#define WSAENOBUFS      (WSABASEERR+55)
#define WSAEISCONN      (WSABASEERR+56)
#define WSAENOTCONN     (WSABASEERR+57)
#define WSAESHUTDOWN    (WSABASEERR+58)
#define WSAETOOMANYREFS (WSABASEERR+59)
#define WSAETIMEDOUT    (WSABASEERR+60)
#define WSAECONNREFUSED (WSABASEERR+61)
#define WSAELOOP        (WSABASEERR+62)
#define WSAENAMETOOLONG (WSABASEERR+63)
#define WSAEHOSTDOWN    (WSABASEERR+64)
#define WSAEHOSTUNREACH (WSABASEERR+65)
#define WSAENOTEMPTY    (WSABASEERR+66)
#define WSAEPROCLIM     (WSABASEERR+67)
#define WSAEUSERS       (WSABASEERR+68)
#define WSAEDQUOT       (WSABASEERR+69)
#define WSAESTALE       (WSABASEERR+70)
#define WSAEREMOTE      (WSABASEERR+71)

/*
 * Extended Windows Sockets error constant definitions
 */
#define WSASYSNOTREADY  (WSABASEERR+91)
#define WSAVERNOTSUPPORTED (WSABASEERR+92)
#define WSANOTINITIALISED (WSABASEERR+93)

/*
 * Error return codes from gethostbyname() and gethostbyaddr()
 * (when using the resolver). Note that these errors are
 * retrieved via WSAGetLastError() and must therefore follow
 * the rules for avoiding clashes with error numbers from
```

Appendix C: Background Information 149

```
* specific implementations or language run-time systems.
* For this reason the codes are based at WSABASEERR+1001.
* Note also that [WSA]NO_ADDRESS is defined only for
* compatibility purposes.
*/

#define h_errno                WSAGetLastError()

/* Authoritative Answer: Host not found */
#define WSAHOST_NOT_FOUND      (WSABASEERR+1001)
#define HOST_NOT_FOUND         WSAHOST_NOT_FOUND

/* Non-Authoritative: Host not found, or SERVERFAIL */
#define WSATRY_AGAIN           (WSABASEERR+1002)
#define TRY_AGAIN              WSATRY_AGAIN

/* Non recoverable errors, FORMERR, REFUSED, NOTIMP */
#define WSANO_RECOVERY         (WSABASEERR+1003)
#define NO_RECOVERY            WSANO_RECOVERY

/* Valid name, no data record of requested type */
#define WSANO_DATA             (WSABASEERR+1004)
#define NO_DATA                WSANO_DATA

/* no address, look for MX record */
#define WSANO_ADDRESS          WSANO_DATA
#define NO_ADDRESS             WSANO_ADDRESS

/*
 * Windows Sockets errors redefined as regular Berkeley error constants
 */
#define EWOULDBLOCK            WSAEWOULDBLOCK
#define EINPROGRESS            WSAEINPROGRESS
#define EALREADY               WSAEALREADY
#define ENOTSOCK               WSAENOTSOCK
#define EDESTADDRREQ           WSAEDESTADDRREQ
#define EMSGSIZE               WSAEMSGSIZE
#define EPROTOTYPE             WSAEPROTOTYPE
#define ENOPROTOOPT            WSAENOPROTOOPT
#define EPROTONOSUPPORT        WSAEPROTONOSUPPORT
#define ESOCKTNOSUPPORT        WSAESOCKTNOSUPPORT
#define EOPNOTSUPP             WSAEOPNOTSUPP
#define EPNOSUPPORT            WSAEPFNOSUPPORT
#define EAFNOSUPPORT           WSAEAFNOSUPPORT
#define EADDRINUSE             WSAEADDRINUSE
#define EADDRNOTAVAIL          WSAEADDRNOTAVAIL
#define ENETDOWN               WSAENETDOWN
#define ENETUNREACH            WSAENETUNREACH
#define ENETRESET              WSAENETRESET
#define ECONNABORTED           WSAECONNABORTED
#define ECONNRESET             WSAECONNRESET
#define ENOBUFS                 WSAENOBUFS
#define EISCONN                 WSAEISCONN
#define ENOTCONN               WSAENOTCONN
#define ESHUTDOWN              WSAESHUTDOWN
#define ETOOMANYREFS           WSAETOOMANYREFS
#define ETIMEDOUT              WSAETIMEDOUT
#define ECONNREFUSED           WSAECONNREFUSED
#define ELOOP                   WSAELOOP
#define ENAMETOOLONG           WSAENAMETOOLONG
#define EHOSTDOWN              WSAEHOSTDOWN
#define EHOSTUNREACH           WSAEHOSTUNREACH
#define ENOTEMPTY              WSAENOTEMPTY
#define EPROCLIM                WSAEPROCLIM
#define EUSERS                  WSAEUSERS
#define EDQUOT                  WSAEDQUOT
#define ESTALE                  WSAESTALE
#define EREMOTE                 WSAEREMOTE

/* Socket function prototypes */
```

150 Appendix C: Background Information

```
SOCKET PASCAL FAR accept (SOCKET s, struct sockaddr FAR *addr,
                          int FAR *addrlen);

int PASCAL FAR bind (SOCKET s, struct sockaddr FAR *addr, int namelen);

int PASCAL FAR closesocket (SOCKET s);

int PASCAL FAR connect (SOCKET s, struct sockaddr FAR *name, int namelen);

int PASCAL FAR ioctlsocket (SOCKET s, long cmd, u_long FAR *argp);

int PASCAL FAR getpeername (SOCKET s, struct sockaddr FAR *name,
                            int FAR * namelen);

int PASCAL FAR getsockname (SOCKET s, struct sockaddr FAR *name,
                            int FAR * namelen);

int PASCAL FAR getsockopt (SOCKET s, int level, int optname,
                           char FAR * optval, int FAR *optlen);

u_long PASCAL FAR htonl (u_long hostlong);

u_short PASCAL FAR htons (u_short hostshort);

struct in_addr PASCAL FAR inet_addr (char FAR * cp);

char FAR * PASCAL FAR inet_ntoa (struct in_addr in);

int PASCAL FAR listen (SOCKET s, int backlog);

u_long PASCAL FAR ntohl (u_long netlong);

u_short PASCAL FAR ntohs (u_short netshort);

int PASCAL FAR recv (SOCKET s, char FAR * buf, int len, int flags);

int PASCAL FAR recvfrom (SOCKET s, char FAR * buf, int len, int flags,
                        struct sockaddr FAR *from, int FAR * fromlen);

long PASCAL FAR select (int nfds, fd_set FAR *readfds, fd_set FAR *writefds,
                       fd_set FAR *exceptfds, struct timeval FAR *timeout);

int PASCAL FAR send (SOCKET s, char FAR * buf, int len, int flags);

int PASCAL FAR sendto (SOCKET s, char FAR * buf, int len, int flags,
                      struct sockaddr FAR *to, int tolen);

int PASCAL FAR setsockopt (SOCKET s, int level, int optname,
                           char FAR * optval, int optlen);

int PASCAL FAR shutdown (SOCKET s, int how);

SOCKET PASCAL FAR socket (int af, int type, int protocol);

/* Database function prototypes */

struct hostent FAR * PASCAL FAR gethostbyaddr(char FAR * addr,
                                              int len, int type);

struct hostent FAR * PASCAL FAR gethostbyname(char FAR * name);

struct servent FAR * PASCAL FAR getservbyport(int port, char FAR * proto);

struct servent FAR * PASCAL FAR getservbyname(char FAR * name,
                                              char FAR * proto);

struct protoent FAR * PASCAL FAR getprotobynumber(int proto);

struct protoent FAR * PASCAL FAR getprotobyname(char FAR * name);

/* Microsoft Windows Extension function prototypes */
```

Appendix C: Background Information 151

```
int PASCAL FAR WSASStartup(WORD wVersionRequired, LPWSADATA lpWSADATA);

int PASCAL FAR WSACleanup(void);

void PASCAL FAR WSASetLastError(int iError);

int PASCAL FAR WSAGetLastError(void);

BOOL PASCAL FAR WSAIsBlocking(void);

int PASCAL FAR WSAUnhookBlockingHook(void);

FARPROC PASCAL FAR WSASetBlockingHook(FARPROC lpBlockFunc);

int PASCAL FAR WSACancelBlockingCall(void);

HANDLE PASCAL FAR WSAAsyncGetServByName(HWND hWnd, u_int wMsg,
                                       char FAR * name, char FAR * proto,
                                       char FAR * buf, int buflen);

HANDLE PASCAL FAR WSAAsyncGetServByPort(HWND hWnd, u_int wMsg, int port,
                                       char FAR * proto, char FAR * buf,
                                       int buflen);

HANDLE PASCAL FAR WSAAsyncGetProtoByName(HWND hWnd, u_int wMsg,
                                       char FAR * name, char FAR * buf,
                                       int buflen);

HANDLE PASCAL FAR WSAAsyncGetProtoByNumber(HWND hWnd, u_int wMsg,
                                       int number, char FAR * buf,
                                       int buflen);

HANDLE PASCAL FAR WSAAsyncGetHostByName(HWND hWnd, u_int wMsg,
                                       char FAR * name, char FAR * buf,
                                       int buflen);

HANDLE PASCAL FAR WSAAsyncGetHostByAddr(HWND hWnd, u_int wMsg,
                                       char FAR * addr, int len, int type,
                                       char FAR * buf, int buflen);

int PASCAL FAR WSACancelAsyncRequest(HANDLE hAsyncTaskHandle);

int PASCAL FAR WSAAsyncSelect(SOCKET s, HWND hWnd, u_int wMsg,
                             long lEvent);

/* Microsoft Windows Extended data types */
typedef struct sockaddr SOCKADDR;
typedef struct sockaddr *PSOCKADDR;
typedef struct sockaddr FAR *LPSOCKADDR;

typedef struct sockaddr_in SOCKADDR_IN;
typedef struct sockaddr_in *PSOCKADDR_IN;
typedef struct sockaddr_in FAR *LPSOCKADDR_IN;

typedef struct linger LINGER;
typedef struct linger *PLINGER;
typedef struct linger FAR *LPLINGER;

typedef struct in_addr IN_ADDR;
typedef struct in_addr *PIN_ADDR;
typedef struct in_addr FAR *LPIN_ADDR;

typedef struct fd_set FD_SET;
typedef struct fd_set *PFD_SET;
typedef struct fd_set FAR *LPFD_SET;

typedef struct hostent HOSTENT;
typedef struct hostent *PHOSTENT;
typedef struct hostent FAR *LPHOSTENT;
```

152 Appendix C: Background Information

```
typedef struct servent SERVENT;
typedef struct servent *PSERVENT;
typedef struct servent FAR *LPSEVENT;

typedef struct protoent PROTOENT;
typedef struct protoent *PPROTOENT;
typedef struct protoent FAR *LPPROTOENT;

/*
 * Windows message parameter composition and decomposition
 * macros.
 *
 * WSAMAKEASYNCREPLY is intended for use by the Windows Sockets implementation
 * when constructing the response to a WSAGetXByY()
 */
#define WSAMAKEASYNCREPLY(buflen,error)          MAKELONG(buflen,error)
/*
 * WSAMAKESELECTREPLY is intended for use by the Windows Sockets implementation
 * when constructing the response to WSAAsyncSelect()
 */
#define WSAMAKESELECTREPLY(event,error)         MAKELONG(event,error)
/*
 * WSAGETASYNCFLEN is intended for use by the Windows Sockets application
 * to extract the buffer length from the lParam in the response
 * to a WSAGetXByY().
 */
#define WSAGETASYNCFLEN(lParam)                LOWORD(lParam)
/*
 * WSAGETASYNCEERROR is intended for use by the Windows Sockets application
 * to extract the error code from the lParam in the response
 * to a WSAGetXByY().
 */
#define WSAGETASYNCEERROR(lParam)              HIWORD(lParam)
/*
 * WSAGETSELECTEVENT is intended for use by the Windows Sockets application
 * to extract the event code from the lParam in the response
 * to a WSAAsyncSelect().
 */
#define WSAGETSELECTEVENT(lParam)             LOWORD(lParam)
/*
 * WSAGETSELECTERROR is intended for use by the Windows Sockets application
 * to extract the error code from the lParam in the response
 * to a WSAAsyncSelect().
 */
#define WSAGETSELECTERROR(lParam)             HIWORD(lParam)

#endif /* _WINSOCKAPI_ */
```


\$³⁵⁴ #³⁵⁵ +³⁵⁶ K³⁵⁷ **Windows Sockets**

Notes for Windows Sockets Suppliers

Introduction

Windows Sockets Components

Multithreadedness and blocking routines.

Database Files

FD_ISSET

Error Codes

DLL Ordinal Numbers

Validation Suite

354\$ Notes for Windows Sockets Suppliers

355# Winsock_NotesForSuppliers

356+ WinSock:0060

357K Notes for Suppliers

154 Appendix C: Background Information

#³⁵⁸ \$³⁵⁹ +³⁶⁰ K³⁶¹ **Notes for Windows Sockets Suppliers**

Introduction

A Windows Sockets implementation must implement ALL the functionality described in the Windows Sockets documentation. Validation of compliance is discussed in Appendix B, Section B.8.

Windows Sockets Version 1.0 implementations must support both TCP and UDP type sockets. An implementation may support raw sockets (of type SOCK_RAW), but their use is deprecated.

Certain APIs documented above have special notes for Windows Sockets implementors. A Windows Sockets implementation should pay special attention to conforming to the API as documented. The Special Notes are provided for assistance and clarification.

358# WinSockNotes_Introduction

359\$ Notes for Windows Sockets Suppliers - Introduction

360+ WinSockN:0010

361^K Notes for Suppliers

#³⁶² \$³⁶³ +³⁶⁴ K³⁶⁵ **Notes for Windows Sockets Suppliers**

Windows Sockets Components

Development Components

The Windows Sockets development components for use by Windows Sockets application developers will be provided by each Windows Sockets supplier. These Windows Sockets development components are:

<u>Component</u>	<u>Description</u>
Windows Sockets Documentation	This document
WINSOCK.LIB file	Windows Sockets API Import Library
WINSOCK.H file	Windows Sockets Header File
NETDB.H file	Berkeley Compatible Header File
ARPA/INET.H file	Berkeley Compatible Header File
SYS/TIME.H file	Berkeley Compatible Header File
SYS/SOCKET.H file	Berkeley Compatible Header File
NETINET/IN.H file	Berkeley Compatible Header File

Run Time Components

The run time component provided by each Windows Sockets supplier is:

<u>Component</u>	<u>Description</u>
WINSOCK.DLL	The Windows Sockets API implementation DLL

362# WinSockNotes_WindowsComponents

363\$ Notes for Windows Sockets Suppliers - Components

364+ WinSockN:0020

365^K Notes for Suppliers

#³⁶⁶ \$³⁶⁷ +³⁶⁸ K³⁶⁹ **Notes for Windows Sockets Suppliers**

Multithreadedness and blocking routines.

Data areas returned by, for example, the getXbyY() routines MUST be on a per thread basis.

Note that an application MUST be prevented from making multiple nested Windows Sockets function calls. Only one outstanding function call will be allowed for a particular task. Any Windows Sockets call performed when an existing blocking call is already outstanding will fail with an error code of WSAEINPROGRESS. There are two exceptions to this restriction: WSACancelBlockingCall() and WSAsIsBlocking() may be called at any time. Windows Sockets suppliers should note that although preliminary drafts of this specification indicated that the restriction only applied to blocking function calls, and that it would be permissible to make non-blocking calls while a blocking call was in progress, this is no longer true.

Regarding the implementation of blocking routines, the solution in Windows Sockets is to simulate the blocking mechanism by having each routine call PeekMessage() as it waits for the completion of its operation. In anticipation of this, the function WSASetBlockingHook() is provided to allow the programmer to define a special routine to be called instead of the default PeekMessage() loop. The blocking hook functions are discussed in more detail in 4.3.13, WSASetBlockingHook().

366# WinSockNotes_Multithreadedness

367\$ Multithreadedness and blocking routines.

368+ WinSockN:0030

369^K Notes for Suppliers

#₃₇₀ \$₃₇₁ +₃₇₂ K₃₇₃ **Notes for Windows Sockets Suppliers**

Database Files

The database routines in the **getXbyY()** family (**gethostbyaddr()**, etc.) were originally designed (in the first Berkeley UNIX releases) as mechanisms for looking up information in text databases. A Windows Sockets supplier may choose to employ local files OR a name service to provide some or all of this information. If local files exist, the format of the files must be identical to that used in BSD UNIX, allowing for the differences in text file formats.

370# WinSockNotes_DatabaseFiles

371\$ Notes for Windows Sockets Suppliers - Database Files

372+ WinSockN:0040

373K Notes for Suppliers

158 Appendix C: Background Information

#³⁷⁴ \$³⁷⁵ +³⁷⁶ K³⁷⁷ Notes for Windows Sockets Suppliers

FD_ISSET

It is necessary to implement the FD_ISSET Berkeley macro using a supporting function: **__WSAFDIsSet()**. It is the responsibility of a Windows Sockets implementation to make this available as part of the Windows Sockets API. Unlike the other functions exported by a Windows Sockets DLL, however, this function is not intended to be invoked directly by Windows Sockets applications: it should be used only to support the FD_ISSET macro. The source code for this function is listed below:

```
int FAR
__WSAFDIsSet(SOCKET fd, fd_set FAR *set)
{
    int i = set->count;

    while (i--)
        if (set->fd_array[i] == fd)
            return 1;

    return 0;
}
```

374# WinSockNotes_FDISSET

375\$ Notes for Windows Sockets Suppliers - FD_ISSET

376+ WinSockN:0050

377K Notes for Suppliers

#₃₇₈ \$₃₇₉ +₃₈₀ K₃₈₁ **Notes for Windows Sockets Suppliers**

Error Codes

In order to avoid conflict between various compiler environments Windows Sockets implementations MUST return the error codes listed in the API specification, using the manifest constants beginning with "WSA". The Berkeley-compatible error code definitions are provided solely for compatibility purposes for applications which are being ported from other platforms.

378# WinSockNotes_ErrorCodes

379\$ Notes for Windows Sockets Suppliers - Error Codes

380+ WinSockN:0060

381^K Notes for Suppliers

160 Appendix C: Background Information

#382 \$383 +384 K385 Notes for Windows Sockets Suppliers

DLL Ordinal Numbers

The **winsock.def** file for use by every Windows Sockets implementation is as follows.

```
;
;       File: winsock.def
;       System: MS-Windows 3.x
;       Summary: Module definition file for Windows Sockets DLL.
;

LIBRARY      WINSOCK      ; Application's module name

DESCRIPTION  'BSD Socket API for Windows'

EXETYPE      WINDOWS      ; required for all windows applications

STUB         'WINSTUB.EXE' ; generates error message if application
                        ; is run without Windows

;CODE can be FIXED in memory because of potential upcalls
CODE         PRELOAD      FIXED

;DATA must be SINGLE and at a FIXED location since this is a DLL
DATA        PRELOAD      FIXED      SINGLE

HEAPSIZE     1024
STACKSIZE    16384

; All functions that will be called by any Windows routine
; must be exported

EXPORTS
    accept                @1
    bind                  @2
    closesocket           @3
    connect               @4
    getpeername           @5
    getsockname           @6
    getsockopt            @7
    htonl                 @8
    htons                 @9
    inet_addr             @10
    inet_ntoa             @11
    ioctlsocket           @12
    listen                @13
    ntohl                 @14
    ntohs                 @15
    recv                  @16
    recvfrom              @17
    select                @18
    send                  @19
    sendto                @20
    setsockopt            @21
    shutdown              @22
    socket                 @23

    gethostbyaddr         @51
```

382# WinSockNotes_DLLOrdinals

383\$ Notes for Windows Sockets Suppliers - DLL Ordinals

384+ WinSockN:0070

385^K Notes for Suppliers

Appendix C: Background Information 161

```
gethostbyname           @52
getprotobyname         @53
getprotobyname         @54
getservbyname          @55
getservbyport         @56

WSAAsyncSelect         @101
WSAAsyncGetHostByAddr @102
WSAAsyncGetHostByName @103
WSAAsyncGetProtoByNumber @104
WSAAsyncGetProtoByName @105
WSAAsyncGetServByPort @106
WSAAsyncGetServByName @107
WSACancelAsyncRequest @108
WSASetBlockingHook    @109
WSAUnhookBlockingHook @110
WSAGetLastError        @111
WSASetLastError        @112
WSACancelBlockingCall @113
WSAIsBlocking         @114
WSAStartup             @115
WSACleanup            @116

__WSAFDIsSet          @151

WEP                    @500    RESIDENTNAME

;eof
```

162 Appendix C: Background Information

#³⁸⁶ \$³⁸⁷ +³⁸⁸ K³⁸⁹ Notes for Windows Sockets Suppliers

Validation Suite

The Windows Sockets Test and Validation suite to ensure Windows Sockets compliance is expected to be available from Microsoft from September 1992. To be made available under the "Windows Sockets compliant" banner, a Windows Sockets implementation must meet the conformance criteria laid down for this suite.

386# WinSockNotes_Validation

387\$ Notes for Windows Sockets Suppliers - Validation Suite

388+ WinSockN:0080

389K Notes for Suppliers

#³⁹⁰ \$³⁹¹ +³⁹² K³⁹³ **Background Information****Origins of Windows Sockets**

The Windows Sockets project had its origins in a Birds Of A Feather session held at Interop '91 in San Jose on October 10, 1991. A committee was established, and an intensive debate via email resulted in the creation of a first draft specification, which was largely based on submissions from JSB and NetManage. This draft, and issues arising from it, were debated at a committee meeting hosted by Microsoft in Redmond, WA on December 9, 1991. Following further email discussions, a working group was established to develop the specification into its current form.

The following people participated in the process as committee members, in working meetings, or in email review. The authors would like to thank everyone who participated in any way, and apologize in advance if we have omitted anyone.

Martin Hall (Moderator)	JSB Corporation	martinh@jsbus.com
Mark Towfiq (Coordinator)	FTP Software	towfiq@ftp.com
Geoff Arnold	Sun Microsystems, Inc.	geoff@east.sun.com
Alistair Banks	Microsoft	alistair@microsoft.com
Carl Beame	Beame & Whiteside	beame@mcmaster.ca
David Beaver	Microsoft	dbeaver@microsoft.com
Amatzia BenArtzi	NetManage, Inc.	amatzia@netmanage.com
Mark Beyer	Ungermann-Bass	mbeyer@ub.com
James Van Bokkelen	FTP Software	jbvb@ftp.com
Nelson Bolyard	Silicon Graphics, Inc.	nelson@sgi.com
Pat Bonner	Hewlett-Packard	p_bonner@cnd.hp.com
Isaac Chan	Microsoft	isaacc@microsoft.com
Nestor Fesas	Hughes LAN Systems	nestor@hls.com
Gary Gere	Gupta	ggere@gupta.com
Bill Hayes	Hewlett-Packard	billh@hpchdpc.cnd.hp.com
Hoek Law	Citicorp	law@dcc.tti.com
Paul Hill	MIT	pbh@athena.mit.edu
Graeme Le Roux	Moresdawn P/L	-
Terry Lister	Hewlett-Packard	tel@cnd.hp.com
Lee Murach	Network Research	lee@nrc.com
David Pool	Spry, Inc.	dave@spry.com
Brad Rice	Age	rice@age.com
Allen Rochkind	3Com	-
Henry Sanders	Microsoft	henrysa@microsoft.com
David Treadwell	Microsoft	davidtr@microsoft.com
Miles Wu	Wollongong	wu@twg.com
Boris Yanovsky	NetManage, Inc.	boris@netmanage.com

390# Winsock_Origins

391\$ Origins of Windows Sockets

392+ WinSock:0070

393^K Background Information

#³⁹⁴ \$³⁹⁵ +³⁹⁶ K³⁹⁷ Background Information

Roadmap

There are two ways to develop a standard specification. One can wait until there are one or two proven implementations in the marketplace, and embody the de facto standard as a formal specification. Alternatively one can develop a largely original specification, publish it, and wait for implementations and applications to emerge. The Windows Sockets effort has followed the second of these approaches. Compared with the first, this approach has a number of drawbacks which must be carefully managed. The principal problem is a classic chicken-and-egg: in the absence of a proven implementation, vendors and developers are concerned that there may be one or more problems within the specification which are not immediately obvious, will only emerge as people start to implement, and will require revisions which will obsolete some of the implementation work. Thus they are tempted to hold off on implementing to the first version of the specification, preferring to wait until a more stable draft emerges. Naturally if everybody follows this cautious approach, the process will never get anywhere.

We are publishing this version of the specification as version 1.0, and will make it widely available. During the summer of 1992, we expect a number of vendors to implement this specification. Those that do so will meet a few days before the Interop show which will take place in San Francisco in October, and will review the results of their work. A revised version of the specification will then be published at the Interop conference. There are three possibilities:

- (1) No change is necessary: the current version is reissued as is, as version 1.0.
- (2) The API is unchanged, but clarifications or corrections to the text of the specification are necessary. The new version will be issued as version 1.1.
- (3) Additions or revisions to the API itself are required. The new version of the specification will be issued as version 2.0.

Our current expectation is that the second of these will occur, and that version 1.1 of the Windows Sockets specification will be published at Interop in October (one year after the process began). This will be the definitive Windows Sockets specification, and we will seek to publish it under the auspices of a standards organization which will allow us to formalize the process of future revision. At the present time, we expect that this publication will take the form of an informational Request For Comments (RFC).

Given that we do not anticipate any significant changes to the API, we expect that commercial implementations based on the present specification, and fully interoperable with versions built to the revised specification, will be commercially available at or soon after Interop.

394# Winsock_Roadmap

395\$ Roadmap

396+ WinSock:0080

397K Background Information