

# MIDI Director Control Panel Index

## Metronome

[Metronome Mode](#)

[Metronome Settings](#)

## Sync Settings

[Sync Mode](#)

[Sync Settings](#)

## Menu Commands

[File Menu](#)

[Options Menu](#)

[Settings Menu](#)

[Help Menu](#)

## Glossary

[Defined Terms](#)

## Procedures

[Selecting metronome modes](#)

[Metronome settings](#)

[Selecting sync modes](#)

[Sync sync settings](#)

[Setting input settings](#)

[Setting Output Mapping](#)

## Keyboard Topics

[Windows Keys](#)

## **File Menu**

The File menu includes commands that let you save the current MIDI Director Setup and Exit the MIDI Director Control Panel.

**Exit** Exits the MIDI Director Control Panel.

**Save Settings** Saves the current Global Settings of the MIDI Director.

## Options Menu

The Options Menu contains commands that let you change different MIDI Director settings and also show the Status and Errors windows.

For more information select the command name from below.

**Show Status ...** Show the Status Window.

**Show Errors ...** Show the Errors Window.

**MIDI Echo** Turn MIDI Echo on or off for all inputs.

**Send MIDI Clocks** Send MIDI Clocks and Song Position Pointer when in play mode.

**Recognize MIDI Start** Control playback in internal Sync Mode from MIDI.

## Settings Menu

The Settings Menu contains selections that let you set options for the Metronome Settings, Sync Settings, Input Setup and Output Mapping.

For more information select one of the following Settings menu commands.

**Metronome Settings**

**Sync Settings**

**Input Setup**

**Output Mapping**

## **Help Menu**

Shows Help commands and the command for showing the About Dialog Box. The About Dialog shows the version number, author name and some other information.

## Metronome Mode

To set the current metronome mode select the Active check box and one of the two radio buttons in the Metronome group on the main MIDI Director Control Panel window.

When Active is checked the metronome is turned on. This setting can be changed by programs, so your sequencer might change this setting once you load a new song. However, programs that change this setting normally allow you to set it with their own commands.

You may select one of two metronome modes, MIDI Notes or PC Speaker.

**MIDI Notes** send MIDI Notes out the MIDI output with the note values selected in the Metronome Settings dialog box.

When the **PC Speaker** is selected, you hear the metronome through your PC's speaker. You can adjust the pitch (note) of the metronome, as well as other settings, from the Metronome Settings dialog box.

## Metronome Settings

The metronome settings are controlled from the Metronome Settings dialog, which is accessed from the [Settings Menu](#). The metronome settings dialog has selections for setting the notes used for the normal and accent metronome sound, the number of count in beats and the MIDI Output and MIDI Channel used to send the metronome to when using the MIDI metronome.

For both the MIDI and PC Speaker [Metronome Mode](#) settings, you can set the note number (pitch), velocity and the duration of the note. You can also specify a Count In value, that is used when in Internal [Sync Mode](#).

**Tick Note** The note used for each metronome tick. It is specified in MIDI note numbers (0-127). The pitch of the PC speaker is also affected by this settings.

**Tick Velocity** The Loudness of the note when using the MIDI metronome, This setting has no effect on the PC Speaker.

**Note Duration** How long the metronome tick is played in metronome ticks (0-239 ticks).

**Count In Beats** How many beats to use as a count in when in MIDI Sync mode.

**Accent** When the accent check box is checked, the first beat of each measure is played with an accent. The accent settings for Note and Velocity are set thew same as those for Tick Note and Velocity.

**Accent Note** The note used for accented metronome ticks. It is specified in MIDI note numbers (0-127). The pitch of the PC speaker is also affected by this setting.

**Accent Velocity** The Loudness of the accented tick note when using the MIDI metronome, This setting has no effect on the PC Speaker.

When using the MIDI [Metronome Mode](#) setting, you also have the following two additional settings.

**MIDI Output** Select the MIDI output you'd like to send the metronome notes to.

**MIDI Channel** Selects the MIDI Channel to send the metronome notes to.

## Sync Mode

To set the current Sync mode select one of the three radio buttons in the Sync group on the main MIDI Director Control Panel window.

The selections are

**Internal Clock** uses the internal timer of the PC to provide timing.

**MIDI Clocks/SPP** lets you sync to external sources such as other sequencers, drum machines or other devices capable of MIDI sync. With this setting the MIDI Director also responds to Song Position Pointer by directing all running sequencers to seek to the new song position. You can also use this setting for devices that use Chase Lock Sync, Smart FSK or other Song Position based tape syncs.

**MIDI Time Code** MIDI time code is used with SMPTE converters to provide SMPTE tape sync. Some high end MIDI interfaces also include SMPTE converters built in. Select this setting for both SMPTE and MTC syncs.

Also see [Sync Settings](#).



## Sync Settings

The Sync Settings dialog box lets you tell the MIDI Director which port to recognize both MIDI and MIDI Time Code syncs from. You can also set the MTC offset used when using MTC sync, and whether to Echo MTC messages received .

**Sync Input Port** The port that MIDI sync with Song Pointer and MIDI Time Code when in these modes. It also controls the port that MIDI Start, Stop and Continue are recognized when in internal sync and Recognize MIDI Start is checked in the Options Menu.

**Echo MTC** When in MTC sync mode, echo MIDI Time Code messages out the MIDI thru port specified for the Sync Input Port specified in the Input Setup for that port.

**MTC Offset** lets you specify the Hours, Minutes, Seconds and Frames to use as a sequence start position when using MTC Sync. You may also be able to set this from within your sequencer. If so, loading a song will probably over-ride any value you might enter. In these cases, set the offset from your sequencer.

## Input Setup

Select Input Settings from the Settings Menu to display the Input Setups dialog box, which lets you change several settings used to control MIDI input filtering, rechannelizing and per-input MIDI Echo.

**MIDI Input** selects the input to change the settings on. Click on the arrow to show more selections.

**Activate Input,** when checked, makes the MIDI input active. When not checked, the input port will be ignored. No MIDI data will be echoed or sent to programs.

### Rechannelizing

**MIDI Channel** lets you rechannel all MIDI data from the input to a new MIDI channel. This parameter's settings are OFF (no channelizing) or between 1-16. When set between 1-16, all MIDI channel data will be rechannelized to the selected channel.

**Echo Output** Allows you to select which output to echo the selected input's MIDI data to. The 'Don't Echo' selection turns off echoing for this input. Note that when the Global MIDI Echo is turned off in the Options Menu that this setting will be suspended.

### Input Enable

**Sets which MIDI Data is recognized from this port.**

## Input Enable

The input enable section of Input Setup dialog box lets you select what kinds of MIDI Data will be received from an input. When an item is checked, the data *will* be received. Your choices are

**Notes** MIDI Note On and Note Off commands are received when checked.

**Bender** Pitch Wheel (Bender) data is received when checked.

**Controllers** Continuous controller messages are received when checked.

**Channel Messages** Channel Messages are passed. These comprise of program changes, control changes and other channel based messages.

**Aftertouch** Both Channel Aftertouch and Key (polyphonic) aftertouch messages are passed when this is checked.

**Common** System Common messages are passed. Common messages include Song Select messages.

**System Exclusive** System exclusive (SYSEX) are passed. These include parameter changes from synthesizers as well as dumps from samplers.

## Output Mapping

Select output mappings from the Settings Menu to display the Output Port Mapping dialog box, which lets you select the mapping mode of each MIDI output port. You can select a Keyboard Map and a Program Change Map for each of the 16 MIDI channels available on each port. You can edit these maps and customize them to your own tastes.

The Output Port Mapping dialog box lets you select the output port and MIDI channel by using the controls at the top of the dialog box. The Output Port combo box lets you select the output to view. The MIDI Channel edit control lets you select the output port channel to see the maps for.

You can select both a Keyboard Map and a Program Change Map for each MIDI channel of each MIDI output. To select a map you would just select the map name from either the Keyboard Map list box or the Program Change Map list box. The No Mapping selection turns off mapping for that channel.

When you select a map, the Edit button will become active. You can then edit the map parameters by clicking on the Edit Button. The appropriate Map Edit dialog will be displayed.

When you are done editing your maps you can select the Save Maps button to store your changes and make your changes permanent. If you don't want your changes to be kept for future sessions, don't select Save Maps, and the MIDI Director will load your old maps the next time it is started. To store your map selections you need to select the Save Current Settings command from the File menu.

## Keyboard Maps

The Keyboard Map remaps note values to new note values. The most common use for Keyboard Maps is to re-arrange notes recorded for one drum machine or drum sound source to be played by another. For instance a Bass Drum might be note number 36 on one sound source and 32 on another. Normally, you would have to remap every note in your sequence for the new sound source. But by using a Keyboard Map, you can leave the sequence data alone and hear the right percussion instruments. Most of the default Keyboard Maps are set to remap different drums machines to the General MIDI Specification. This specification calls for certain drums sounds to be on certain keys. You can create a General MIDI compatible drum part, but play it on any sound source with compatible sounds. But these sounds don't have to be on the normal keys, since you can remap them to new ones with the Keyboard Map. There are eight maps available.

Of course, you can also use the Keyboard Maps to transpose your keyboard, invert your keyboard or even play different sound sources from one keyboard by transmitting on two or more channels at once.

To modify a Keyboard Map, select the map name from the Keyboard Map List Box in the Output Port Mapping dialog. You will notice that the Edit button will then become active. Click on the Edit button to modify the map. The Keyboard Map Edit dialog box will then display.

### Editing the Keyboard Map

The Keyboard Map Name is shown at the top of the dialog. You can select the Key Map Name edit control to change the map's name. In the bottom portion of the dialog box are the key edit fields and the Key list box that shows the values for each key (or note). The list box has values for all 128 notes. You can use the scroll bar to see all of the values.

The Keyboard Map parameters are Source, Key Name, Dest, Chan and Port.

<b>Source</b>	is the source key. You can't change this value. It is a reference to remind you which key you've chosen from the list box.
<b>Key Name</b>	is used to describe the key. For drum sound mapping, you would enter the name of the instrument played by the key.
<b>Dest</b>	(or Destination) is the Destination key. When the source key is played it will be translated to the note value in Dest. The value of this parameter may be between 0 and 127, which is the range of valid MIDI note numbers.
<b>Chan</b>	is the MIDI Channel to use when the note is played. When set to <b>OFF</b> , no channel remapping is used, but values between 1 and 16 will let you rechannel the note. This value takes precedence over the Input Port channel remapping.
<b>Port</b>	The output to send the note to. When set to <b>OFF</b> , no port remapping is used, but values between 1 and the number of the top port will let you send the note to a different output. This value takes precedence over the Input Port Echo setting. By using channel and port remapping you can redirect output to several sound sources at once.

When you are done editing you can select the OK button to return to the Output Port

Mapping dialog box.

## Program Change Maps

The Program Change Map remaps patch changes to new values. The most common use for Program Change Maps is to re-arrange patch changes recorded for one sound module to those of another. For instance a Bass Drum might be note number 36 on one sound source and 32 on another. Normally, you would have to remap every note in your sequence for the new sound source. But by using a Keyboard Map, you can leave the sequence data alone and hear the right percussion instruments. Our default maps are set up for the General MIDI Specification. This specification calls for certain instrument sounds to be at specific patch change numbers. You can create a General MIDI compatible sequence, complete with sound selection, but play it on any sound source with compatible sounds. But these sounds don't have to be at the same locations as your instrument's, since you can remap them to new ones with the Program Change Map. There are eight maps available.

To modify a Program Change Map, select the map name from the Program Change Map List Box in the Output Port Mapping dialog. You will notice that the Edit button will then become active. Click on the Edit button to modify the map. The Program Change Map Edit dialog box will then display.

### Editing the Program Change Map

The Program Change Map Name is shown at the top of the dialog. You can select the Program Change Map Name edit control to change the map's name. In the bottom portion of the dialog box are the program change edit fields and the Program Change list box that shows the mapping values for Program Change. The list box has values for all 128 program changes. You can use the scroll bar to see all of the values.

The Program Change Map parameters are Source, Program Name and Dest.

**Source** is the source program change. You can't change this value. It is a reference to remind you which program change you've chosen from the list box.

**Program Change Name** is used to describe the instrument associated with the program change.

**Dest** (or Destination) is the Destination program change. When the source program change is selected it will be translated to the value in Dest. The value of this parameter may be between 0 and 127, which is the range of valid MIDI program changes.

When you are done editing you can select the OK button to return to the Output Port Mapping dialog box.

## **Error Window**

The error windows provides statistics useful for finding out problems that may be occurring in your setup. You don't really need to keep track of your errors since the MIDI Director is self correcting and will usually recover from most errors. See your owner's manual for more information.



## The Status Window

The Status window has three displays. The Mode display, the Programs count and the Position display.

The **Mode display** shows the current status of the MIDI Director. It is found on the upper left of the status window. When you first start up the Control panel from your program, this will read *Stopped*. When the sequencer is in playback mode, it will read *Playing*. It can also tell you when you are in *Fast Forward* and will also show *Rewind* after a rewind.

The **Programs count** shows how many programs are logged on to the MIDI Director. Since some programs may log on more than once, this may show more programs than are actually running. Currently the MIDI director supports up to sixteen programs at once.

The **Position display** shows the current position the MIDI Director is set to or is playing from. Both the Tick position and the Millisecond positions are displayed. When MIDI Director's Sync Mode is set to MTC (MIDI Time Code) then the Milliseconds position display will show the current HOURS:MINUTES:SECONDS:FRAMES when chasing to start playback. It will then revert to milliseconds when playback has started. The line below the Milliseconds Position display also shows other information about the frame format and MTC status when in MTC sync.



## **Windows Keys**

The MIDI Director uses the keyboard interface that is standard to all Windows programs. Choose from the following list to review the standard keys used in Windows:

[Cursor Movement Keys](#)

[Dialog Box Keys](#)

[Editing Keys](#)

[Help Keys](#)

[Menu Keys](#)

[System Keys](#)

[Text Selection Keys](#)

[Window Keys](#)

### **Cursor Movement Keys**

<b>Key(s)</b>	<b>Function</b>
---------------	-----------------

DIRECTION key	Moves the cursor left, right, up, or down in a field.
---------------	---

End or Ctrl+Right Arrow	Moves to the end of a field.
-------------------------	------------------------------

Home or CTRL+Left Arrow	Moves to the beginning of a field.
-------------------------	------------------------------------

PAGE UP or PAGE DOWN	Moves up or down in a field, one screen at a time.
----------------------	--

## **Dialog Box Keys**

<b>Key(s)</b>	<b>Function</b>
---------------	-----------------

TAB	Moves from field to field (left to right and top to bottom).
SHIFT+TAB	Moves from field to field in reverse order.
ALT+letter	Moves to the option or group whose underlined letter matches the one you type.
DIRECTION key	Moves from option to option within a group of options.
ENTER	Executes a command button. Or, chooses the selected item in a list box and executes the command.
ESC	Closes a dialog box without completing the command. (Same as Cancel)
ALT+DOWN ARROW	Opens a drop-down list box.
ALT+UP or DOWN ARROW	Selects item in a drop-down list box.
SPACEBAR	Cancels a selection in a list box. Selects or clears a check box.
CTRL+SLASH	Selects all the items in a list box.
CTRL+BACKSLASH	Cancels all selections except the current selection.
SHIFT+ DIRECTION key	Extends selection in a text box.
SHIFT+ HOME	Extends selection to first character in a text box.
SHIFT+ END	Extends selection to last character in a text box

**Editing Keys**  
**Key(s)Function**

Backspace	Deletes the character to the left of the cursor. Or, deletes selected text.
Delete	Deletes the character to the right of the cursor. Or, deletes selected text.

**Help Keys**  
**Key(s)Function**

F1

Gets Help and displays the Help Index for the application. If the Help window is already open, pressing F1 displays the "Using Windows Help" topics.

**Menu Keys**  
**Key(s)Function**

Alt	Selects the first menu on the menu bar.
Letter key	Chooses the menu, or menu item, whose underlined letter matches the one you type.
Alt+letter key	Pulls down the menu whose underlined letter matches the one you type.
LEFT or RIGHT ARROW	Moves among menus.
UP or DOWN ARROW	Moves among menu items.
Enter	Chooses the selected menu item.



## **System Keys**

The following keys can be used from any window, regardless of the application you are using.

### **Key(s)Function**

Ctrl+Esc	Switches to the Task List.
Alt+Esc	Switches to the next application window or minimized icon, including full-screen programs.
Alt+TAB	Switches to the next application window, restoring applications that are running as icons.
Alt+PrtSc	Copies the entire screen to Clipboard.
Ctrl+F4	Closes the active window.
F1	Gets Help and displays the Help Index for the application. (See <a href="#">Help Keys</a> )

## **Text Selection Keys**

### **Key(s)Function**

SHIFT+LEFT or RIGHT ARROW	Selects text one character at a time to the left or right.
SHIFT+DOWN or UP	Selects one line of text up or down.
SHIFT+END	Selects text to the end of the line.
SHIFT+HOME	Selects text to the beginning of the line.
SHIFT+PAGE DOWN	Selects text down one window. Or, cancels the selection if the next window is already selected.
SHIFT+PAGE UP	Selects text up one window. Or, cancels the selection if the previous window is already selected.
CTRL+SHIFT+LEFT or RIGHT ARROW	Selects text to the next or previous word.
CTRL+SHIFT+UP or DOWN ARROW	Selects text to the beginning (UP ARROW) or end (DOWN ARROW) of the paragraph.
CTRL+SHIFT+END	Selects text to the end of the document.
CTRL+SHIFT+HOME	Selects text to the beginning of the document.

**Window Keys**  
**Key(s)Function**

ALT+SPACEBAR	Opens the Control menu for an application window.
ALT+Hyphen	Opens the Control menu for a document window.
Alt+F4	Closes a window.
Alt+Esc	Switches to the next application window or minimized icon, including full-screen programs.
Alt+TAB	Switches to the next application window, restoring applications that are running as icons.
Alt+ENTER	Switches a non-Windows application between running in a window and running full screen.
DIRECTION key	Moves a window when you have chosen Move from the Control menu. Or, changes the size of a window when you have chosen Size from the Control menu.



# Glossary

**Accent** is an emphasis placed on a note to make it stand out.

**Aftertouch** A MIDI command that specifies how hard a key is pressed after it has been struck initially. Aftertouch is commonly used for volume swells, filter sweeps and other effects. The MIDI Spec defines two type of Aftertouch, channel and polyphonic. Channel Aftertouch, also called channel pressure, effects all notes on a MIDI Channel. Polyphonic aftertouch, also known as polyphonic key pressure, effects only individual notes on a channel. Of the two, channel aftertouch is the most common.

**Bend** Bend, or Pitch Bend, is the changing of a sounding note up or down in pitch in a smooth fashion. The term pitch bend is taken from the guitar, where the player will stretch the string to produce a bending effect. Synthesizers produce this same effect with the use of a pitch wheel.

**Channel** Channel is a logical path to send MIDI data. MIDI has sixteen channels per port.

**Channel Message** A MIDI command that only affects one MIDI channel. These include note on and note off, program changes, pitch wheel and control change messages.

**Chase Lock Sync** a type of tape sync found in Music Quest™ brand MIDI interfaces, also called smart FSK on other types of interfaces or sync boxes.

**Clock** A Clock is a way of measuring time, that when applied to MIDI usually measures the subdivisions of a beat. MIDI director uses a clock that will time stamp data with either milliseconds or ticks (or 240ths of a beat).

**Common Message** A MIDI command that is sent on a port and affects all MIDI channels, not just one. A good example of common messages are the MIDI start, stop and continue commands.

**Control Change** A MIDI message that affects different MIDI controllers. The most common controllers are Modulation Wheel, Volume and Hold (or sustain) pedal controllers.

**Count In** A count in is used to tell the performer that the music is about to start. A common count in would be a count of one measure.

**Dialog Box** A dialog box is special window that allows the user to enter information. Unlike normal windows, a user cannot switch out of a dialog until he is done.

**Driver** A Driver is special type of program that allows the MIDI Director to communicate with each MIDI interface.

**Duration** The length of time that a note occurs. When used with the MIDI Director's metronome, it specifies how many ticks long a note is.

**Echo** Echo, or MIDI echo, is used to describe the action of passing MIDI data from a MIDI input to an output. Also known as MIDI thru.

## Glossary page 2

**Frames** The frame is the subdivision of a second used by MIDI Time Code and SMPTE sync to mark the passage of time. The most convenient frame rate to use for music applications is 30 non drop frame.

**Keyboard** A music instrument used to play notes.

**MIDI** An that stands for acronym Musical Instrument Digital Interface. MIDI is a standard form of digital communication that is used between electronic music instruments, especially electronic keyboards.

**MIDI Continue** A MIDI Command that tells a sequencer or drums machine to start playing from the position where it was last stopped or positioned to with a Song Position Pointer message.

**MIDI Director** A MIDI multitasking software system, from Big Noise Software, Inc., that allows several MIDI programs to run at once under Microsoft Windows. The MIDI Director allows programs to share a number of MIDI interfaces and lets programs lock to external devices.

**MIDI Start** A MIDI Command that tells a sequencer or drums machine to start playing from the beginning of the song.

**MIDI Stop** A MIDI Command that tells a sequencer or drums machine to stop playing.

**MIDI Sync** A form synchronization specified in the MIDI Specification 1.0 that lets two MIDI devices play together. MIDI sync is based on the musical format of beats and tempo.

**MIDI Time Code** A time based synchronization code that is commonly used when locking MIDI devices to SMPTE based devices.

**Milliseconds** One thousandth of a second. The MIDI Director uses a time base of 1 millisecond to record and playback all MIDI data.

**Module** A module is a synthesizer or sampler that does not have an attached keyboard.

**MTC** Short for MIDI Time Code. See MIDI Time Code above.

**Note On/Off** MIDI Commands that identify the start and stop of notes. A note on is sent from a keyboard when the note is pressed and a note off is sent when the note is released.

**Note Number** A number between 0 and 127 that indicates what note is pressed. Middle C is note number 60. All notes are specified in half steps.

**Notes** Notes are the basic building block of music. A note in MIDI consists of a Note On command and a Note off command.

**Patch Change** A patch change, also known as program change, is a MIDI command that tells a keyboard or module what sound to play.



## Glossary page 3

**Pitch Bend** Pitch Bend, or just Bend, is the changing of a sounding note up or down in pitch in a smooth fashion. The term pitch bend is taken from the guitar, where the player will stretch the string to produce a bending effect. Synthesizers produce this same effect with the use of a pitch wheel.

**Polyphonic Key Pressure** See Aftertouch.

**Port, MIDI** A MIDI port is where the MIDI cable is plugged in. The MIDI Director can control a number of MIDI ports. Each MIDI port can send or receive data on up to sixteen MIDI channels.

**Position** A point in a song, when used with sequencers. A position may be described in the common musical terms of measures and beats, with the beat subdivided into ticks. A song position can also be described in terms of time, as in milliseconds.

**Program Change** A program change, also known as patch change, is a MIDI command that tells a keyboard or module what sound to play.

**Rechannel** The changing of the MIDI channel data is received with to another channel. This is very useful when sequencing.

**Sample** A recorded sound played back through a Sampler.

**Sampler** A special type of keyboard that plays back recorded sounds.

**Save** When used with computers, save means to store to disk.

**Sequence** A recording of a song as performance data, such as MIDI data, instead of as sound.

**Sequencer** A computer program, or hardware device, that records a performance as MIDI data. Cadenza for Windows is a sequencer.

**SMPTE** An acronym that stands for the Society of Motion Picture and Television Engineers, used to describe a form of synchronization code used in the movie and television industry. Originally developed by NASA, SMPTE is also commonly used to sync high end audio equipment such as multitrack tape recorders.

**SMPTE Sync** A form of tape sync commonly used to synchronize MIDI equipment to video equipment and professional recording equipment. Use of SMPTE sync usually requires the use of a SMPTE to MIDI Time Code converter.

**Song Position** The measure, beat and tick position in a song.

**Song Position Pointer** A MIDI command that tells a sequencer what measure, beat and

tick to position to before playback starts or continues.

**Sync** Short for synchronization.

**Glossary** page 4

**Synthesizer** An electronic musical instrument that produces sound electronically.

**System Exclusive** A special MIDI command that is used for instrument specific messages, such as patch programming parameters or sample dumps.

**Tape Sync** A form of sync used to lock recorders and MIDI equipment together. SMPTE, Chase Lock and FSK are three types of tape sync.

**Ticks** Subdivisions of a beat. In the MIDI Director a tick is defined as one 240th of a beat.

**Velocity** Velocity is part of each MIDI Note on message that describes how hard a note was struck.