

SECTION 06414

CABINET DRAWER SLIDES AND CABINET ACCESSORIES

PART GENERAL

SECTION INCLUDES

Drawer Slides.

Television Swivel Pull-Out.

Retracting Door Slides.

RELATED SECTIONS

Section 06410 - Custom Cabinets.

Section 12310 - Manufactured Metal Casework.

Section 12320 - Manufactured Wood Casework.

Section 12350 - Specialty Casework.

SUBMITTALS

Submit under provisions of Section 01300.

Product Data: Manufacturer's descriptive literature for each product specified in this section.

Manufacturer's instructions: Printed installation instructions for each product specified in this section.

DELIVERY, STORAGE, AND HANDLING

Store products of this section in manufacturer's unopened packaging until installation.

PART PRODUCTS

MANUFACTURERS

Acceptable Manufacturer: Accuride International, Inc.; 12311

Shoemaker Avenue, Santa Fe Springs, CA 90670. ASD. Tel: (562) 903-0200.

Requests for substitution will be considered in accordance with provisions of Section 01600.

Substitutions: Not permitted.

Supply all products specified in this section from the same manufacturer.

MANUFACTURED UNITS

Drawer Slides: Light-to-medium capacity, for drawers which extend deeper into cabinet than drawer width:

Acceptable product: Accuride 3832.

Type: Full extension slide, side-mounted, with lever drawer disconnect; silenced slide movement supported by steel ball bearings.

Capacity: 100 pounds (45 kg) per pair for 18-inch (457 mm) slide length.

Finish: Clear zinc.

Finish: Black zinc.

Finish: Epoxy white.

Drawer Slides: Light-to-medium capacity, for drawers 24 inches (609 mm) wide or less:

Acceptable product: Accuride 7434.

Type: Full extension slide, rail-mounted, ball bearing supported progressive slide movement with overtravel.

Capacity: 100 pounds (45 kg) per pair for 18-inch (457 mm) slide length.

Finish: Clear zinc.

Finish: Black zinc.

Drawer Slides: Medium-to-heavy capacity, for drawers 24 inches (609 mm) wide or less:

Acceptable product: Accuride 4034.

Type: Full extension slide, rail-mounted, ball bearing supported progressive slide movement with overtravel.

Capacity: 150 pounds (67 kg) per pair for 18-inch (457 mm) slide length.

Finish: Clear zinc.

Finish: Black zinc.

Drawer Slides: Heavy capacity, for drawers 42 inches (1066 mm)

wide or less:

Acceptable product: Accuride 3640.

Type: Full extension slide, bracket-mounted, ball bearing supported progressive slide movement with overtravel.

Capacity: 200 pounds (90 kg) per pair for 18-inch (457 mm) slide length.

Finish: Clear zinc.

Finish: Black zinc.

Television Swivel Pull-Out:

Acceptable product: Accuride CB3620-258TV.

Type: Ball bearing supported slide movement.

Capacity: 180 pounds (81 kg).

Slide extension: 14 inches (355 mm).

Rotation: 360-degree swivel.

Finish: Black zinc.

Retracting Door Slides:

Acceptable product: Accuride Flipper Door(R) Model 1432.

Type: Retracting hinge assembly for vertical cabinet doors, with provision to prevent racking of door.

Capacity: 75 pounds (34 kg).

Slide extension: For door widths indicated on drawings.

Hinges: Types recommended by manufacturer for indicated door thicknesses, and as follows:

For door height 36 inches (914 mm) and below, supply 2 hinges per door.

For door height above 36 inches (914 mm), supply 3 hinges per door, plus one additional hinge for each 12 inches (304 mm) of door height above 36 inches (914 mm).

Hinge carrier strip: Type recommended by manufacturer for specified hinges.

Finish: Clear zinc.

Supply mounting hardware specified in manufacturer's instructions for cabinet hardware.

PART EXECUTION

INSTALLATION

Install products specified in this section in accordance with requirements of affected sections and manufacturer's instructions.

Do not install products specified in this section before applied finishes on cabinets have dried; allowing foreign substances to foul operating components is prohibited.

Mask or cover products specified in this section before applying finishes on cabinets, removing coverings only after finishes have dried; allowing foreign substances to foul operating components is prohibited.

ADJUSTING

Adjust operating components of products of this section in accordance with manufacturer's instructions; ensure that products operate correctly.

END OF SECTION