

## Contents

# IRC Numeric Codes

The codes included here are taken from:

**Network Working Group  
Request for Comments: 1459  
May 1993**

**J. Oikarinen  
D. Reed**

### **Internet Relay Chat Protocol**

Which is available at: **<http://ds.internic.net/rfc/rfc1459.txt>**

The following Help Topics are available:

[The Help Authors Advisory](#)

[Series 400 codes](#) Error Replies (includes 2 series 500 codes)

[Series 300 codes](#) Command Replies

[Series 200 codes](#) Command Replies

[Reserved Numerics](#) Various Reserved or No-Longer-Used Codes

For Help on Help, Press F1

hlp ver 1.a

## **Numeric Code Advisory:**

This help is not designed as a guide for the use of IRC Numeric Codes, but as a simple reference to the Numeric Code numbers. It is primarily designed for mIRC user's with versions later than 4.5.

Thanks to Hot\_Ice for pointing me to the source document.

S.M. Allen aka Jeepster (DALnet)

## Series 400 Codes: Error Replies

### REPLIES

The following is a list of numeric replies which are generated in response to the commands given above. Each numeric is given with its number, name and reply string.

#### Error Replies.

- 401    ERR\_NOSUCHNICK  
      "<nickname> :No such nick/channel"
- Used to indicate the nickname parameter supplied to a command is currently unused.
- 402    ERR\_NOSUCHSERVER  
      "<server name> :No such server"
- Used to indicate the server name given currently doesn't exist.
- 403    ERR\_NOSUCHCHANNEL  
      "<channel name> :No such channel"
- Used to indicate the given channel name is invalid.
- 404    ERR\_CANNOTSENDOCHAN  
      "<channel name> :Cannot send to channel"
- Sent to a user who is either (a) not on a channel which is mode +n or (b) not a chanop (or mode +v) on a channel which has mode +m set and is trying to send a PRIVMSG message to that channel.
- 405    ERR\_TOOMANYCHANNELS  
      "<channel name> :You have joined too many \ channels"
- Sent to a user when they have joined the maximum number of allowed channels and they try to join another channel.
- 406    ERR\_WASNOSUCHNICK  
      "<nickname> :There was no such nickname"
- Returned by WHOWAS to indicate there is no history information for that nickname.
- 407    ERR\_TOOMANYTARGETS  
      "<target> :Duplicate recipients. No message \ delivered"
- Returned to a client which is attempting to send a PRIVMSG/NOTICE using the user@host destination format and for a user@host which has several occurrences.

- 409 ERR\_NOORIGIN  
":No origin specified"
- PING or PONG message missing the originator parameter which is required since these commands must work without valid prefixes.
- 411 ERR\_NORECIPIENT  
":No recipient given (<command>)"
- 412 ERR\_NOTEXTTOSEND  
":No text to send"
- 413 ERR\_NOTOPLEVEL  
"<mask> :No toplevel domain specified"
- 414 ERR\_WILDTOPLEVEL  
"<mask> :Wildcard in toplevel domain"
- 412 - 414 are returned by PRIVMSG to indicate that the message wasn't delivered for some reason. ERR\_NOTOPLEVEL and ERR\_WILDTOPLEVEL are errors that are returned when an invalid use of "PRIVMSG \$<server>" or "PRIVMSG #<host>" is attempted.
- 421 ERR\_UNKNOWNCOMMAND  
"<command> :Unknown command"
- Returned to a registered client to indicate that the command sent is unknown by the server.
- 422 ERR\_NOMOTD  
":MOTD File is missing"
- Server's MOTD file could not be opened by the server.
- 423 ERR\_NOADMININFO  
"<server> :No administrative info available"
- Returned by a server in response to an ADMIN message when there is an error in finding the appropriate information.
- 424 ERR\_FILEERROR  
":File error doing <file op> on <file>"
- Generic error message used to report a failed file operation during the processing of a message.
- 431 ERR\_NONICKNAMEGIVEN  
":No nickname given"
- Returned when a nickname parameter expected for a command and isn't found.

- 432 ERR\_ERRONEUSNICKNAME  
"<nick> :Erroneus nickname"
- Returned after receiving a NICK message which contains characters which do not fall in the defined set. See section x.x.x for details on valid nicknames.
- 433 ERR\_NICKNAMEINUSE  
"<nick> :Nickname is already in use"
- Returned when a NICK message is processed that results in an attempt to change to a currently existing nickname.
- 436 ERR\_NICKCOLLISION  
"<nick> :Nickname collision KILL"
- Returned by a server to a client when it detects a nickname collision (registered of a NICK that already exists by another server).
- 441 ERR\_USERNOTINCHANNEL  
"<nick> <channel> :They aren't on that channel"
- Returned by the server to indicate that the target user of the command is not on the given channel.
- 442 ERR\_NOTONCHANNEL  
"<channel> :You're not on that channel"
- Returned by the server whenever a client tries to perform a channel effecting command for which the client isn't a member.
- 443 ERR\_USERONCHANNEL  
"<user> <channel> :is already on channel"
- Returned when a client tries to invite a user to a channel they are already on.
- 444 ERR\_NOLOGIN  
"<user> :User not logged in"
- Returned by the summon after a SUMMON command for a user was unable to be performed since they were not logged in.
- 445 ERR\_SUMMONDISABLED  
":SUMMON has been disabled"
- Returned as a response to the SUMMON command. Must be returned by any server which does not implement it.

- 446 ERR\_USERSDISABLED  
":USERS has been disabled"
- Returned as a response to the USERS command. Must be returned by any server which does not implement it.
- 451 ERR\_NOTREGISTERED  
":You have not registered"
- Returned by the server to indicate that the client must be registered before the server will allow it to be parsed in detail.
- 461 ERR\_NEEDMOREPARAMS  
"<command> :Not enough parameters"
- Returned by the server by numerous commands to indicate to the client that it didn't supply enough parameters.
- 462 ERR\_ALREADYREGISTERED  
":You may not reregister"
- Returned by the server to any link which tries to change part of the registered details (such as password or user details from second USER message).
- 463 ERR\_NOPERMFORHOST  
":Your host isn't among the privileged"
- Returned to a client which attempts to register with a server which does not been setup to allow connections from the host the attempted connection is tried.
- 464 ERR\_PASSWDMISMATCH  
":Password incorrect"
- Returned to indicate a failed attempt at registering a connection for which a password was required and was either not given or incorrect.
- 465 ERR\_YOUREBANNEDCREEP  
":You are banned from this server"
- Returned after an attempt to connect and register yourself with a server which has been setup to explicitly deny connections to you.
- 467 ERR\_KEYSET  
"<channel> :Channel key already set"
- 471 ERR\_CHANNELISFULL  
"<channel> :Cannot join channel (+I)"

472 ERR\_UNKNOWNMODE  
"<char> :is unknown mode char to me"  
473 ERR\_INVITEONLYCHAN  
"<channel> :Cannot join channel (+i)"  
474 ERR\_BANNEDFROMCHAN  
"<channel> :Cannot join channel (+b)"  
475 ERR\_BADCHANNELKEY  
"<channel> :Cannot join channel (+k)"  
481 ERR\_NOPRIVILEGES  
":Permission Denied- You're not an IRC operator"

- Any command requiring operator privileges to operate must return this error to indicate the attempt was unsuccessful.

482 ERR\_CHANOPRIVSNEEDED  
"<channel> :You're not channel operator"

- Any command requiring 'chanop' privileges (such as MODE messages) must return this error if the client making the attempt is not a chanop on the specified channel.

483 ERR\_CANTKILLSERVER  
":You cant kill a server!"

- Any attempts to use the KILL command on a server are to be refused and this error returned directly to the client.

491 ERR\_NOOPERHOST  
":No O-lines for your host"

- If a client sends an OPER message and the server has not been configured to allow connections from the client's host as an operator, this error must be returned.

501 ERR\_UMODEUNKNOWNFLAG  
":Unknown MODE flag"

- Returned by the server to indicate that a MODE message was sent with a nickname parameter and that the a mode flag sent was not recognized.

502 ERR\_USERSDONTMATCH  
":Cant change mode for other users"

- Error sent to any user trying to view or change the user mode for a user other than themselves.

## Series 300 Codes: Command Replies

Command responses.

- 300 RPL\_NONE  
Dummy reply number. Not used.
- 302 RPL\_USERHOST  
":[<reply>{<space><reply>}]"
- Reply format used by USERHOST to list replies to the query list. The reply string is composed as follows:
- <reply> ::= <nick>[\*]'=' <'+'|'-><hostname>
- The '\*' indicates whether the client has registered as an Operator. The '-' or '+' characters represent whether the client has set an AWAY message or not respectively.
- 303 RPL\_ISON  
":[<nick> {<space><nick>}]"
- Reply format used by ISON to list replies to the query list.
- 301 RPL\_AWAY  
"<nick> :<away message>"
- 305 RPL\_UNAWAY  
":You are no longer marked as being away"
- 306 RPL\_NOWAWAY  
":You have been marked as being away"
- These replies are used with the AWAY command (if allowed). RPL\_AWAY is sent to any client sending a PRIVMSG to a client which is away. RPL\_AWAY is only sent by the server to which the client is connected. Replies RPL\_UNAWAY and RPL\_NOWAWAY are sent when the client removes and sets an AWAY message.
- 311 RPL\_WHOSUSER  
"<nick> <user> <host> \* :<real name>"
- 312 RPL\_WHOSSEVER  
"<nick> <server> :<server info>"
- 313 RPL\_WHOSOPERATOR  
"<nick> :is an IRC operator"
- 317 RPL\_WHOSIDLE  
"<nick> <integer> :seconds idle"
- 318 RPL\_ENDOFWHOIS  
"<nick> :End of /WHOIS list"
- 319 RPL\_WHOSCHANNELS  
"<nick> :{[@|+]<channel><space>}"



- Replies 311 - 313, 317 - 319 are all replies generated in response to a WHOIS message. Given that there are enough parameters present, the answering server must either formulate a reply out of the above numerics (if the query nick is found) or return an error reply. The '\*' in RPL\_WHOISUSER is there as the literal character and not as a wild card. For each reply set, only RPL\_WHOISCHANNELS may appear more than once (for long lists of channel names). The '@' and '+' characters next to the channel name indicate whether a client is a channel operator or has been granted permission to speak on a moderated channel. The RPL\_ENDOFWHOIS reply is used to mark the end of processing a WHOIS message.

314 RPL\_WHOWASUSER  
 "<nick> <user> <host> \* :<real name>"  
 369 RPL\_ENDOFWHOWAS  
 "<nick> :End of WHOWAS"

- When replying to a WHOWAS message, a server must use the replies RPL\_WHOWASUSER, RPL\_WHOISSERVER or ERR\_WASNOSUCHNICK for each nickname in the presented list. At the end of all reply batches, there must be RPL\_ENDOFWHOWAS (even if there was only one reply and it was an error).

321 RPL\_LISTSTART  
 "Channel :Users Name"  
 322 RPL\_LIST  
 "<channel> <# visible> :<topic>"  
 323 RPL\_LISTEND  
 ":End of /LIST"

- Replies RPL\_LISTSTART, RPL\_LIST, RPL\_LISTEND mark the start, actual replies with data and end of the server's response to a LIST command. If there are no channels available to return, only the start and end reply must be sent.

324 RPL\_CHANNELMODEIS  
 "<channel> <mode> <mode params>"  
 331 RPL\_NOTOPIC  
 "<channel> :No topic is set"  
 332 RPL\_TOPIC  
 "<channel> :<topic>"

- When sending a TOPIC message to determine the channel topic, one of two replies is sent. If the topic is set, RPL\_TOPIC is sent back else RPL\_NOTOPIC.

341 RPL\_INVITING

"<channel> <nick>"

- Returned by the server to indicate that the attempted INVITE message was successful and is being passed onto the end client.

342 RPL\_SUMMONING  
" <user> :Summoning user to IRC"

- Returned by a server answering a SUMMON message to indicate that it is summoning that user.

351 RPL\_VERSION  
" <version>.<debuglevel> <server> :<comments>"

- Reply by the server showing its version details. The <version> is the version of the software being used (including any patchlevel revisions) and the <debuglevel> is used to indicate if the server is running in "debug mode".

The "comments" field may contain any comments about the version or further version details.

352 RPL\_WHOREPLY  
" <channel> <user> <host> <server> <nick> \  
<H|G>[\*][@|+] :<hopcount> <real name>"

315 RPL\_ENDOFWHO  
" <name> :End of /WHO list"

- The RPL\_WHOREPLY and RPL\_ENDOFWHO pair are used to answer a WHO message. The RPL\_WHOREPLY is only sent if there is an appropriate match to the WHO query. If there is a list of parameters supplied with a WHO message, a RPL\_ENDOFWHO must be sent after processing each list item with <name> being the item.

353 RPL\_NAMREPLY  
" <channel> :[[@|+]<nick> [[@|+]<nick> [...]]"

366 RPL\_ENDOFNAMES  
" <channel> :End of /NAMES list"

- To reply to a NAMES message, a reply pair consisting of RPL\_NAMREPLY and RPL\_ENDOFNAMES is sent by the server back to the client. If there is no channel found as in the query, then only RPL\_ENDOFNAMES is returned. The exception to this is when a NAMES message is sent with no parameters and all visible channels and contents are sent back in a series of RPL\_NAMREPLY messages with a RPL\_ENDOFNAMES to mark the end.

364 RPL\_LINKS  
" <mask> <server> :<hopcount> <server info>"

- 365 RPL\_ENDOFLINKS  
"<mask> :End of /LINKS list"
- In replying to the LINKS message, a server must send replies back using the RPL\_LINKS numeric and mark the end of the list using an RPL\_ENDOFLINKS reply.
- 367 RPL\_BANLIST  
"<channel> <banid>"
- 368 RPL\_ENDOFBANLIST  
"<channel> :End of channel ban list"
- When listing the active 'bans' for a given channel, a server is required to send the list back using the RPL\_BANLIST and RPL\_ENDOFBANLIST messages. A separate RPL\_BANLIST is sent for each active banid. After the banids have been listed (or if none present) a RPL\_ENDOFBANLIST must be sent.
- 371 RPL\_INFO  
":<string>"
- 374 RPL\_ENDOFINFO  
":End of /INFO list"
- A server responding to an INFO message is required to send all its 'info' in a series of RPL\_INFO messages with a RPL\_ENDOFINFO reply to indicate the end of the replies.
- 375 RPL\_MOTDSTART  
":- <server> Message of the day - "
- 372 RPL\_MOTD  
":- <text>"
- 376 RPL\_ENDOFMOTD  
":End of /MOTD command"
- When responding to the MOTD message and the MOTD file is found, the file is displayed line by line, with each line no longer than 80 characters, using RPL\_MOTD format replies. These should be surrounded by a RPL\_MOTDSTART (before the RPL\_MOTDs) and an RPL\_ENDOFMOTD (after).
- 381 RPL\_YOUREOPER  
":You are now an IRC operator"
- RPL\_YOUREOPER is sent back to a client which has just successfully issued an OPER message and gained operator status.
- 382 RPL\_REHASHING  
"<config file> :Rehashing"
- If the REHASH option is used and an operator sends a REHASH message, an RPL\_REHASHING is sent back to

the operator.

391 RPL\_TIME  
" <server> :<string showing server's local time>"

- When replying to the TIME message, a server must send the reply using the RPL\_TIME format above. The string showing the time need only contain the correct day and time there. There is no further requirement for the time string.

392 RPL\_USERSSTART  
":UserID Terminal Host"

393 RPL\_USERS  
":%-8s %-9s %-8s"

394 RPL\_ENDOFUSERS  
":End of users"

395 RPL\_NOUSERS  
":Nobody logged in"

- If the USERS message is handled by a server, the replies RPL\_USERSTART, RPL\_USERS, RPL\_ENDOFUSERS and RPL\_NOUSERS are used. RPL\_USERSSTART must be sent first, following by either a sequence of RPL\_USERS or a single RPL\_NOUSER. Following this is RPL\_ENDOFUSERS.

## Series 200 Codes: Command Replies

200	RPL_TRACELINK	"Link <version & debug level> <destination> \ <next server>"
201	RPL_TRACECONNECTING	"Try. <class> <server>"
202	RPL_TRACEHANDSHAKE	"H.S. <class> <server>"
203	RPL_TRACEUNKNOWN	"???? <class> [<client IP address in dot form>]"
204	RPL_TRACEOPERATOR	"Oper <class> <nick>"
205	RPL_TRACEUSER	"User <class> <nick>"
206	RPL_TRACESERVER	"Serv <class> <int>S <int>C <server> \ <nick!user!*!*>@<host server>"
208	RPL_TRACENEWTYPE	"<newtype> 0 <client name>"
261	RPL_TRACELOG	"File <logfile> <debug level>"

- The RPL\_TRACE\* are all returned by the server in response to the TRACE message. How many are returned is dependent on the the TRACE message and whether it was sent by an operator or not. There is no predefined order for which occurs first. Replies RPL\_TRACEUNKNOWN, RPL\_TRACECONNECTING and RPL\_TRACEHANDSHAKE are all used for connections which have not been fully established and are either unknown, still attempting to connect or in the process of completing the 'server handshake'. RPL\_TRACELINK is sent by any server which handles a TRACE message and has to pass it on to another server. The list of RPL\_TRACELINKs sent in response to a TRACE command traversing the IRC network should reflect the actual connectivity of the servers themselves along that path. RPL\_TRACENEWTYPE is to be used for any connection which does not fit in the other categories but is being displayed anyway.

211	RPL_STATSLINKINFO	"<linkname> <sendq> <sent messages> \ <sent bytes> <received messages> \ <received bytes> <time open>"
212	RPL_STATSCOMMANDS	"<command> <count>"
213	RPL_STATSCLINE	"C <host> * <name> <port> <class>"
214	RPL_STATSNLIN	"N <host> * <name> <port> <class>"
215	RPL_STATSLINE	"I <host> * <host> <port> <class>"

216 RPL\_STATSKLINE  
"K <host> \* <username> <port> <class>"

218 RPL\_STATSYLINE  
"Y <class> <ping frequency> <connect \ frequency> <max sendq>"

219 RPL\_ENDOFSTATS  
"<stats letter> :End of /STATS report"

241 RPL\_STATSLINE  
"L <hostmask> \* <servername> <maxdepth>"

242 RPL\_STATSUPTIME  
":Server Up %d days %d:%02d:%02d"

243 RPL\_STATSOLINE  
"O <hostmask> \* <name>"

244 RPL\_STATSHLINE  
"H <hostmask> \* <servername>"

221 RPL\_UMODEIS  
"<user mode string>"

- To answer a query about a client's own mode, RPL\_UMODEIS is sent back.

251 RPL\_LUSERCLIENT  
":There are <integer> users and <integer> \ invisible on <integer> servers"

252 RPL\_LUSEROP  
"<integer> :operator(s) online"

253 RPL\_LUSERUNKNOWN  
"<integer> :unknown connection(s)"

254 RPL\_LUSERCHANNELS  
"<integer> :channels formed"

255 RPL\_LUSERME  
":I have <integer> clients and <integer> \ servers"

- In processing an LUSERS message, the server sends a set of replies from RPL\_LUSERCLIENT, RPL\_LUSEROP, RPL\_USERUNKNOWN, RPL\_LUSERCHANNELS and RPL\_LUSERME. When replying, a server must send back RPL\_LUSERCLIENT and RPL\_LUSERME. The other replies are only sent back if a non-zero count is found for them.

256 RPL\_ADMINME  
"<server> :Administrative info"

257 RPL\_ADMINLOC1  
":<admin info>"

258 RPL\_ADMINLOC2  
":<admin info>"

259 RPL\_ADMINEMAIL  
":<admin info>"

- When replying to an ADMIN message, a server is expected to use replies RLP\_ADMINME

through to RPL\_ADMINEMAIL and provide a text message with each. For RPL\_ADMINLOC1 a description of what city, state and country the server is in is expected, followed by details of the university and department (RPL\_ADMINLOC2) and finally the administrative contact for the server (an email address here is required) in RPL\_ADMINEMAIL.

## Reserved Numerics

Reserved numerics.

These numerics are not described above since they fall into one of the following categories:

1. no longer in use;
2. reserved for future planned use;
3. in current use but are part of a non-generic 'feature' of the current IRC server.

209	RPL_TRACECLASS	217	RPL_STATSQLINE
231	RPL_SERVICEINFO	232	RPL_ENDOFSERVICES
233	RPL_SERVICE	234	RPL_SERVLIST
235	RPL_SERVLISTEND		
316	RPL_WHOISCHANOP	361	RPL_KILLDONE
362	RPL_CLOSING	363	RPL_CLOSEEND
373	RPL_INFOSTART	384	RPL_MYPORTIS
466	ERR_YOUWILLBEBANNED	476	ERR_BADCHANMASK
492	ERR_NOSERVICEHOST		



