# **Sure-loc Aluminum Edging**

A-5482 144th Avenue Holland, MI 49423 Phone (800) 787-3562 (616) 392-3209 Fax (616) 392-6015

# **Specifications and Technical Data**

## ADVANTAGES OF SURE-LOC ALUMINUM EDGING

Landscape Architects have realized the excellent product performance benefits of Alumium Edging. Sure-loc Aluminum Edging makes the decision of which brand of Aluminum Edging to specify easy. Sure-loc is a superior product at a far more affordable price. Most Landscape projects have a budget to work within and a goal of using the best quality products affordable. Sure-loc is sold directly to the Landscape Contractor (or Landscape Architect), there are no middle man mark-ups, saving you upwards of 30%. Allow us to show you the difference by quoting your next project that requires edging. When specifying or inquiring about our products please use our toll free number 1-800-SURE-LOC (1-800-787-3562).

## **PRODUCT APPLICATIONS**

 $1/8" \times 4" (3.2mm \times 102mm)$  - Used primarily for residential or light commercial applications. Used as a planting bed edging, and as a paver restraint for patios or walkways. Works best where flowing curves are needed.

3/16" x 4" (3.2mm x 140mm) - Used primarily for commercial, industrial, and institutional facilities. Used for edging of planting beds, a paver restraint, walking trails, running tracks, asphalt borders, and for maintenance strips. Works well for both long straight runs and curves.

 $1/8" \ge 5.5"$  (4.8mm  $\ge 102$ mm) - Used primarily for residential or light commercial applications where the planting beds may require the additional depth.

3/16" x 5.5" (4.8mm x 140mm) - Used primarily for commercial, industrial, and institutional facilities where the additional depth and strength of a heavy duty product is needed. Excellent for long straight runs. This product is extremely durable yet can form curves with ease.

## **FINISHES**

Sure-loc Aluminum is available in a variety of finishes and can be special ordered in almost any color or finish. If you choose to use a colored finish we strongly recommend using an anodized versus a painted finish, the anodized finish offers far greater durability.

## STANDARD FINISHES

Mill Finish (Natural Aluminum) Anodized Finishes: Black, Green, Bronze Other finishes available by request

#### **ALUMINUM ALLOY**

Edging - Extruded 6063 T6 Hardness Stakes - Extruded 6061 T6 Hardness

#### EDGING SIZES

1/8" x 4" x 16', 12', 8' (3.2mm x 102mm x 4.88m, 3.66m, 2.44m) 3/16" x 4" x 16' (4.8mm x 102mm x 4.88m) 1/8" x 5.5" x 16' (3.2mm x 140mm x 4.88m) 3/16" x 5.5" x 16' (4.8mm x 140mm x 4.88m)

\*8' Lengths can be shipped UPS

#### **STAKES**

1.5" x 11.5" (38mm x 292mm) 1.5" x 18" (38mm x 457mm)

#### **SPECIFIERS CAUTION**

Use caution as to which brand you specify. Sure-loc offers superior function and will cost far less than other aluminum edgings. To take advantage of the upwards of 30% savings be sure to include our toll free number 1-800-SURE-LOC. Sure-loc Aluminum Edging provides the proven performance of Aluminum at a price you can afford. Let us quote you an actual delivered price not a "suggest wholesale".

Note: A competitor is labeling a  $1/8" \times 4"$  product that measures 1/8" only at the very top edge. Sure-loc measures a full 1/8" at six different points. Please take caution when accepting another as equal.

#### **SPECIFICATIONS**

Edging to be Sure-loc Aluminum Edging (1. Specify Edging Size 2. Finish 3. Stake Size) Extruded Aluminum 6063 Alloy T6 Hardness. Edging is to lock together with no offset or overlap at the joints. Install with 5 stakes per 16' (4.88m) Section Stakes are to be Extruded Aluminum 6061 Alloy T6 Hardness. Stakes are to be installed 1/2" (12.7mm) below top edge out of view. At <u>All</u> start points and stop points install End Stake Adaptors to properly secure these critical areas. Please include: 1-800-SURE-LOC (1-800-787-3562).

## EDGE WITH THE BEST FOR LESS

For Additional Assistance Please call 1-800-SURE-LOC (1-800-787-3562) Direct Ph. (616) 392-3209 Fax (616) 392-6015