

MR-MANUFACTURER

TEXTONE® Vinyl-Faced Gypsum Panels are manufactured by United States Gypsum Company, a leader in construction materials and building systems for 90 years.

PP-PRODUCT PRESENTATION

TEXTONE Vinyl-Faced Gypsum Panels and mouldings provide economical, permanent partitions that offer faster room completion and lower in-place cost than field-applied vinyl when used with conventional drywall framing systems or with relocatable wall systems from USG Interiors. There's no mess -- no joint compounds, no taping -- and schedule delays. Routine soapy water cleaning keeps durable finish looking new -- reducing or eliminating redecorating costs.

Regular panels are 1/2" thick, 4' wide and 8', 9' and 10' long. May be special ordered in 3/8" and 5/8" thicknesses, 2' widths and custom lengths from 6' to 14'. FIRECODE Core Panels, 5/8" thick, and FIRECODE Core C Panels, 1/2" thick, 4' wide, are available.

Mouldings

A complete line of surface mouldings for edges, corners and trim around openings are easy to cut and mitre on the job. Included are: inside corner, end cap, snap-on corner, snap-on batten, ceiling/drive-in trim.

Matching Wallcovering

Cotton sheet-backed TEXTONE Vinyl Wallcovering for field installation weighs 1.2-1.4 oz./sq. yd. and comes in 54" x 30 yd. rolls.

UA-USES, APPLICATIONS

TEXTONE Panels may be used with conventional drywall framing systems or in combination with relocatable wall systems from USG Interiors.

AI-ASSEMBLY, INSTALLATION

Over wood or steel studs -- Apply 8" long strip of vinyl foam tape to face of each stud, positioned at midpoint of studs up to 8' long, at third-points on studs up to 12' long and quarter-points on studs over 12'. Where no mechanical fasteners are to be used at top or bottom of stud, apply an 8' long strip of tape on the track or wood plate at each stud. Apply a continuous 3/8" bead of drywall stud adhesive to entire face of studs between vinyl foam tape. Immediately apply TEXTONE Panels vertically, applying sufficient pressure to insure complete contact with both tape and adhesive. Where use of color-matching TEXTONE nails is desired along ends and edges of board and in conjunction with drywall stud adhesive, drive nails with plastic-headed hammer or raw-hide mallet. Space nails at least 3/8" from ends and edges and 8" o.c.

Over gypsum panel base layer -- Apply liquid contact adhesive to back of TEXTONE Panels and face of base layer according to adhesive manufacturer's directions. Allow adhesive to air dry, then bring panels into contact. Apply

pressure to entire surface to assure complete contact.

Over masonry, gypsum panels, wood or mineral fiber board base layer -- For interior masonry walls and gypsum board, apply continuous strips of vinyl foam tape to entire width of TEXTONE Panel back at midpoint and 3/8" from each end. Spread laminating adhesive over entire area of panels between tape using notched metal spreader with 1/4"x1/4" notches spaced 2" o.c. Position panel and immediately apply sufficient pressure to assure complete contact over entire surface. (Mechanical fasteners may be substituted for tape at panel ends.)

Over wood or mineral board -- Pre-bow panels and apply laminating adhesive over entire back surface.

MF-MATERIALS, FINISHES

Materials include TEXTONE Vinyl-Faced Gypsum Panels, Regular, FIRECODE and FIRECODE C Cores, in 38 factory-applied vinyl finishes; precision-extruded rigid plastic Mouldings available plain (RP) in standard Almond or Ash Blue colors or factory laminated with matching TEXTONE Vinyl (RPV); and matching TEXTONE Vinyl Wallcoverings.

CS-COATINGS, SURFACINGS

RP-2 and RPV-2 Inside Corner -- Install first panel so that vertical edge aligns with framing. Apply moulding over first panel, fastening exposed flange to framing. Insert opposite panel into moulding.

RP-4 and RPV-4 End Cap -- Align and fasten end cap to framing. Insert panel into moulding, apply panel to wall.

RP-5 and RPV-5 Snap-on Corner -- Apply panels using adhesive or adhesive/nail-on application. Place retainer strip over corner, fasten with nails or screws driven through holes provided. Snap corner face onto retainer strip.

RP-7 and RPV-7 Snap-on Batten -- Apply panels using adhesive or adhesive/nail-on application. Place retainer strip over joint, fasten with nails or screws driven through holes provided. Snap batten face onto retainer strip.

RP-46 and RPV-46 Ceiling Drive-in Trim -- Install after panels are applied. Insert grooved flange between runner and ceiling; tap trim into place. Adhesive may be required to secure trim.

TS-TECHNICAL SUPPORT

For further information on specifications, design criteria and product performance, order catalog SA-928 *TEXTONE Vinyl-Faced Gypsum Panels* by calling toll-free 1-800-USG-4YOU (874-4968).

CC-CODES, CERTIFICATION

TEXTONE Panels meet ASTM C690.

OM-OPERATION, MAINTENANCE

Contact local U.S. Gypsum Company Sales Office with any questions about maintenance and replacement recommendations.