MR-MANUFACTURER

USG Exterior Textured Finish is manufactured by United States Gypsum Company, a leader in construction materials and building systems for 90 years.

PP-PRODUCT PRESENTATION

USG Exterior Textured Finish is a fade- and weather-resistant 100% acrylic polymer emulsion finish that is available in a dramatic range of standard and custom colors. All colors are lead-free and alkali-resistant. Available in Fine, Medium or Coarse finish. USG Exterior Textured Finish is flexible to accommodate thermal expansion and contraction without delamination under normal conditions. Packaged in 67.5 lb. pail. For a listing of the 33 standard colors, available in your choice of Fine, Medium and Coarse Finish, refer to the table included in this snapshot.

UA-USES, APPLICATIONS

USG Exterior Textured Finish is designed for use in USG Exterior Wall Systems such as USG EIFS, DUROCK[®] EIFS and DUROCK Direct-Applied Exterior Systems. It also can be used over properly prepared conventional stucco (brown coat), monolithic concrete or unit masonry.

AI-ASSEMBLY, INSTALLATION

Over USG Exterior Wall Systems:

- Apply appropriate exterior basecoat as specified by U.S. Gypsum Company.

- Apply USG Exterior Textured Finish according to directions in a continuous operation without cold joints or scaffolding lines.

- Finish as specified with conventional stucco tools such as a plastic float. Over Concrete or Masonry:

- Prepare surfaces according to directions.

- Apply USG Exterior Basecoat over entire surface. Several coats may be required.

- Apply USG Exterior Textured Finish according to directions in a continuous operation without cold joints or scaffolding lines.

- Finish as specified with conventional stucco tools such as a plastic float.

MF-MATERIALS, FINISHES

Materials include USG Exterior Textured Finish, fine, coarse or medium finish; USG Exterior Basecoat; USG Exterior Basecoat -- Fiber-Reinforced; USG Exterior Acrylic Component mixed with portland cement per USG specifications; conventional stucco brown coat mixed, applied and properly cured by ASTM C926-90.

CS-COATINGS, SURFACING

USG Exterior Textured Finish serves as a finish for USG Exterior Wall Systems, conventional stucco (brown coat), monolithic concrete and unit masonry.

TS-TECHNICAL SUPPORT

For further information on specifications, design criteria and product performance, order catalog *SA-700 USG Exterior Products and Systems* by calling toll-free 1-800-USG-4YOU (874-4968).

OM-OPERATION, MAINTENANCE Contact local U.S. Gypsum Company Sales Office with any questions about maintenance and replacement recommendations.