

## **MR-MANUFACTURER** - USG Interiors, Inc.

For specifications on this product, 1.) close this product Snapshot, 2.) click on the Manufacturer's Showcase button, 3.) select the screen, *Specification: Relocatable Partitions* from the drop-down Showcase list that appears in the upper right of your screen.

### **PP-PRODUCT PRESENTATION** - TACKWALL Panel System

- Lower cost than fixed wall systems over the lifetime of the building
- Acoustical, tackable panels integrate with ULTRAWALL® and DONN® High Performance Wall systems
- Flush, full or partial height panels
- Attractive alternative to expensive, unsightly hang-on tackboards
- Economy
- Relocatability
- Superior STC performance
- Superior fire ratings/the best in the industry
- Partitions frame top, side, intersecting and full-height glazing
- Features --

Cavity depth: 1-7/8" (2" if used with High Performance Wall System)

Wall thickness: 3-3/8"

STC rating: 42 or better

Fire rating: 1 hour or better

Flame spread/smoke developed: Class A, vinyl

### **UA-USES, APPLICATIONS**

- Conference rooms
- Training areas
- Schools
- Libraries
- Presentation rooms

### **AI-ASSEMBLY, INSTALLATION**

- Panels are simply substituted for regular relocatable wall panels
- Only four components required for basic wall system
- Fast, easy progressive installation

### **MF-MATERIALS, FINISHES**

#### **Components -**

- Panels

MICORE® mineral fiber board over BLENDEX® gypsum panels (combined thickness 3/4" x 24" or 3/4" x 30" factory kerfed, bevel edge to fit stud)

- Studs

Steel (roll-formed galvanized steel "H" or "T" configuration)

- Ceiling Track

Aluminum (flanged rail ARL-300 or plain rail ARL-301, 3-5/8" width, 1-1/4" return)

- Floor Runner

Steel (galvanized steel, 1-7/8" width, 1-1/8" return)

**Finishes -**

- 36 standard vinyls
- 22 standard fabrics
- Optional flush outside corners
- Optional trimless inside corners
- Call Customer Relations at 1-800-950-3839 for samples.

**Accessories -**

- Door Frames

Aluminum (SMR-Delta, self-mortising, reversible)

Steel (non-handed, reversible)

- Glazing

Aluminum (nonmodular components)

Steel (throated for installation without regard to module)

- Floor Base

Vinyl snap-on base

- Trims

Aluminum

Steel

- Hanging Furniture Studs

Universal studs accept standards for hang-on furniture in nominal 24", 30", 48", 54" and 60" widths.

**CS-COATINGS, SURFACING**

- Aluminum ceiling track, door frames, glazing and trim -- satin anodized, ULTRABRONZE or painted.

**TS-TECHNICAL SUPPORT**

- Call Technical Services at 1-216-722-8773.

**CC-CODES, CERTIFICATION**

- ASTM D2794 (impact resistance)
- ASTM E84 (flame spread)
- ASTM E90 (STC)
- ASTM E119 (fire endurance and hose stream)

**OM-OPERATION, MAINTENANCE**

- Call Technical Services at 1-216-722-8773.