

MR-MANUFACTURER - USG Interiors, Inc.

For specifications on this product, 1.) close this product Snapshot, 2.) click on the Manufacturer's Showcase button, 3.) select the screen, *Specification: Relocatable Partitions* from the drop-down Showcase list that appears in the upper right of your screen.

PP-PRODUCT PRESENTATION - ULTRAWALL® Partition System

- Lower cost than fixed wall systems over the lifetime of your building
- Elegant simplicity
- Economy
- Relocatability
- Superior STC performance
- Superior fire ratings/the best in the industry
- Wiring can run vertically or horizontally in the wall
- Partitions frame top, side, intersecting and full-height glazing
- Features -

Cavity depth: 1-7/8"

Wall thickness: 3-3/8"

STC rating: 42 or better

Fire rating: 1 hour or better

Flame spread/smoke developed: Class A, vinyl

UA-USES, APPLICATIONS

- Offices
- Schools
- Training facilities

AI-ASSEMBLY, INSTALLATION

- Only four components required for basic wall system
- Fast, easy progressive installation

MF-MATERIALS, FINISHES

Components -

- Panels

Gypsum Panels (3/4" x 24" or 3/4" x 30" factory kerfed, bevel edge to fit stud)

- Studs

Steel (roll-formed galvanized steel "H" or "T" configuration)

Aluminum (extruded aluminum "H" or "T" configuration)

- Ceiling Track

Steel (3-5/8" width, 1-1/4" return)

Aluminum (flanged rail ARL-300 or plain rail ARL-301, 3-5/8" width, 1-1/4" return)

- Floor Runner

Steel (galvanized steel, 1-7/8" width, 1-1/8" return)

Finishes -

- 36 standard vinyls
- 22 standard fabrics
- Optional flush outside corners
- Optional trimless inside corners

Call Customer Relations at 1-800-950-3839 for samples.

Accessories -

- Door Frames

Aluminum (SMR-Delta, self mortising, reversible)

Steel (non-handed, reversible)

- Glazing

Aluminum (nonmodular components)

Steel (throated for installation without regard to module)

- Floor Base

Vinyl snap-on base

- Trims

Aluminum

Steel

- Hanging Furniture Studs

Universal studs accept standards for hang-on furniture in nominal 24", 30", 48", 54" and 60" widths.

CS-COATINGS, SURFUCING

- Steel ceiling track, floor runner, door frames, glazing and trim - painted

- Aluminum ceiling track, door frames, glazing and trim - satin anodized, ULTRABRONZE or painted

TS-TECHNICAL SUPPORT

- Call Technical Services at 1-216-722-8773

CC-CODES, CERTIFICATION

- ASTM D2794 (impact resistance)

- ASTM E84 (flame spread)

- ASTM E90 (STC)

- ASTM E119 (fire endurance and hose stream)

OM-OPERATION, MAINTENANCE

- Call Technical Services at 1-216-722-8773.