

MR-MANUFACTURER - USG Interiors, Inc.

For specifications on this product, 1.) close this product Snapshot, 2.) click on the Manufacturer's Showcase button, 3.) select the screen, *Specification: Relocatable Partitions* from the drop-down Showcase list that appears in the upper right of your screen.

PP-PRODUCT PRESENTATION - DONN® High Performance Wall System

- Lower cost than fixed wall systems over the lifetime of your building
- Point accessibility
- Versatility
- Durability
- Special finish options for special performance requirements
- Relocatability
- Superior STC performance
- Superior fire ratings/the best in the industry
- Wiring can run vertically or horizontally in the wall
- Partitions frame top, side, intersecting and full-height glazing
- Features --

Cavity depth: 2"

Wall thickness: 3 - 3-3/4"

STC range: 35-44 (gypsum panels)

40-43 (metal-faced panels)

Fire rating: 1 hour

Flame spread/smoke developed: Class A, vinyl

UA-USES, APPLICATIONS

- Hot, humid or corrosive environments
- Clean rooms
- Laboratories
- Industrial or marine settings

AI-ASSEMBLY, INSTALLATION

- Only five components required for basic wall system
- Fast, easy progressive installation

MF-MATERIALS, FINISHES

Components -

- Panels

Gypsum Panels (1/2" x 48" or 5/8" x 24", 30", or 48", bevel edge)

Metal-Faced Panels (24-ga. steel panel over 1/2" or 5/8" thick gypsum core, 24" or 30" wide, square edge)

- Studs

Steel (roll-formed, 2" depth, holes punched for utility passage)

- Ceiling Track

Steel (3" or 3-3/8" width, 1-3/8" return)

- Floor Runner

Steel (2" width, 1" return)

- Spacer Channels (Optional)
Steel (24" or 30" lengths)

Finishes -

- 36 standard vinyls
- 22 standard fabrics
- Optional flush outside corners
- Optional trimless inside corners
- Call Customer Relations at 1-800-950-3839 for samples.

Accessories -

- Door Frames
Aluminum (SMR-Delta, self-mortising, reversible)
Steel (non-handed, reversible)
- Glazing
Steel (throated for installation without regard to module)
- Floor Base
Vinyl snap-on base
- Trims
Vinyl
Steel

CS-COATINGS, SURFACING

- Steel ceiling track, floor runner, door frames, glazing and trim - painted
- Vinyl floor base and trim - PVC

TS-TECHNICAL SUPPORT

- Call Technical Services at 1-216-722-8773.

CC-CODES, CERTIFICATION

- ASTM D2794 (impact resistance)
- ASTM E84 (flame spread)
- ASTM E90 (STC)
- ASTM E119 (fire endurance and hose stream)

OM-OPERATION, MAINTENANCE

- Call Technical Services at 1-216-722-8773.