

## **MR-MANUFACTURER** - USG Interiors, Inc.

For specifications on this product, 1.) close this product Snapshot, 2.) click on the Manufacturer's Showcase button, 3.) select the screen, *Specification: ACOUSTONE Ceilings* from the drop-down Showcase list that appears in the upper right of your screen.

### **PP-PRODUCT PRESENTATION** - ACOUSTONE® Fine-Textured Ceiling Panels

- \* SANDRIFT™: Richly etched, natural texture with a unique, tactile character.
- \* Frost: Delicate surface texture, for a soft, light look.
- \* Snowcap: Medium and high peaks of texture in a random pattern.
- \* Moraine: Random etched, medium-depth texture with irregular crosshatch pattern.
- \* Class A and FIRECODE® (for fire-rated systems).
- \* Flame spread/smoke developed: 25/15.
- \* Weight:
  - 1.25 lb./sq. ft. (6.10 kg/sq. m.) (Class A).
  - 1.30 lb./sq. ft. (6.35 kg/sq. m.) (FIRECODE).
- \* Thermal resistance: R-2.12.
- \* Maximum backloading: .75 lb./sq. ft. (3.66 kg/sq. m.).
- \* Durability: ACOUSTONE surface resists scrapes commonly caused by accessing ceiling panels.
- \* Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.
- \* Products are available in the following edges:
  - Shadowline (SL), Finesline (FL), Oval (OV), Square (SQ) and Finesline (FL) Bevel. See the "Grid/Edge Selector Guide" in the product Showcase.

### **UA-USES, APPLICATIONS**

- \* Closed-plan offices.
- \* Open-plan offices.
- \* Lobbies.
- \* Retail stores.
- \* Restaurants.
- \* High visibility ceilings.

### **AI-ASSEMBLY, INSTALLATION**

- \* Install panels with Square edge in DONN® DX® or fire-rated DXL™ 15/16" (23 mm) exposed suspension, DXW 1-1/2" (38 mm) exposed suspension, or CENTRICITEE™ or MERIDIAN® 9/16" (14 mm) exposed suspension.
- \* Install panels with Shadowline edge in DONN DX or fire-rated DXL 15/16" (23 mm) exposed suspension.
- \* Install panels with FINELINE or FINELINE Bevel edge in DONN FINELINE® or FINELINE 1/8 9/16" (14 mm) exposed suspension.
- \* Install panels with Oval edge in CENTRICITEE or MERIDIAN 9/16" (14 mm) exposed suspension.

### **MF-MATERIALS, FINISHES**

- \* Materials-

ACOUSTONE molded mineral fiber.

\* Colors-

- White plus 24 standard colors.

- Exclusive clear-through color process masks nicks and scratches.

\* Call Customer Relations at 1-800-950-3839 for samples.

\* Accessory systems-

- DONN DX 15/16" (23 mm) exposed suspension.

- DONN DXL fire-rated 15/16" (23 mm) exposed suspension.

- DONN DXW 1-1/2" (38 mm) exposed suspension.

- DONN CENTRICITEE non-fire-rated or fire-rated 9/16" (14 mm) exposed suspension.

- DONN MERIDIAN 9/16" (14 mm) exposed suspension with rounded reveal.

- DONN FINELINE non-fire-rated or fire-rated slotted 9/16" (14 mm) exposed suspension.

- DONN FINELINE 1/8 slotted 9/16" (14 mm) exposed suspension.

### **CS-COATINGS, SURFACING**

\* ENVIROSENSE™ with INTERSEPT® (new, surface-active, broad spectrum antimicrobial): All products are available with INTERSEPT. To specify, use the standard item number followed by the word "INTERSEPT."

### **TS-TECHNICAL SUPPORT**

\* Call Customer Relations at 1-800-950-3839.

### **CC-CODES, CERTIFICATION**

\* ASTM form/spec. Type 3, Form 1, Class 25.

\* Meets ASTM E1264.

### **OM-OPERATION, MAINTENANCE**

\* Can be cleaned easily with a soft brush or vacuum.