

## **MR-MANUFACTURER** - USG Interiors, Inc.

For specifications on this product, 1.) close this product Snapshot, 2.) click on the Manufacturer's Showcase button, 3.) select the screen, *Specification: ACOUSTONE Ceilings* from the drop-down Showcase list that appears in the upper right of your screen.

### **PP-PRODUCT PRESENTATION** - AURATONE® Fine-Textured Ceiling Panels

- \* Fine Fissured II: Finest fissures and perforations.
- \* Corona: Clean, crisp, nondirectional fissures.
- \* Corona 90: Clean, crisp, nondirectional fissures on panels that are suitable for high temperature and high humidity areas, including areas without air conditioning services.
- \* ARTISAN Colors: Variegated paint finishes give the freshest interpretation of colors in the acoustical marketplace.
- \* ARTISAN 90 Colors: Three-dimensional sculpted texture to variegated finish.
- \* Class A and FIRECODE® (for fire-rated systems).
- \* Flame spread/smoke developed: 25/10.
- \* Weight:
  - .81 lb./sq. ft. (3.95 kg/sq. m) (ARTISAN, ARTISAN 90 Class A panels).
  - 1.00 lb./sq. ft. (4.88 kg/sq. m) (Fine Fissured II, Corona Class A panels).
  - 1.15 lb./sq. ft. (5.61 kg/sq. m) (ARTISAN, ARTISAN 90, Corona FIRECODE).
  - 1.37 lb./sq. ft. (6.69 kg/sq. m) (Fine Fissured II, Corona FIRECODE panels).
  - 1.40 lb./sq. ft. (6.83 kg/sq. m) (Fine Fissured II tile).
- \* Thermal resistance:
  - R-1.85 (ARTISAN, ARTISAN 90)
  - Up to R-2.18 (Fine Fissured II, Corona).
  - R-2.16 (Corona 90).
- \* Maximum backloading: .75 lb./sq. ft. (3.66 kg/sq. m.).
- \* Maximum temperature/humidity: 90°F (32°C)/90% relative humidity (Corona 90).
- \* Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.
- \* Products are available in the following edges:
  - Square (SQ), Shadowline Tapered (SLT), Interline Tapered (ILT), Finline (FL), Bevel Edge/Kerf (BESK), CR (SL) and CR (IL). ARTISAN and ARTISAN 90 are not available in CR (SL) and CR (IL). See the "Grid/Edge Selector Guide" in the Product Showcase.

### **UA-USES, APPLICATIONS**

- \* Open-plan offices.
- \* Closed-plan offices.
- \* Lobbies.
- \* Retail stores (ARTISAN, ARTISAN 90).
- \* High visibility ceilings (ARTISAN, ARTISAN 90).
- \* Restaurants (Fine Fissured II, Corona 90).
- \* High humidity areas (Corona 90).
- \* Schools, health centers, restroom areas (Corona 90).

## **AI-ASSEMBLY, INSTALLATION**

- \* Install panels with Square edge in DONN® DX® or fire-rated DXL™ 15/16" (23 mm) exposed suspension, DXW 1-1/2" (38 mm) exposed suspension, corrosion-resistant ZX, ZXA, or AX 15/16" (23 mm) exposed suspension, or CENTRICITEE™ or MERIDIAN® 9/16" (14 mm) exposed suspension (Fine Fissured II, Corona, Corona 90).
- \* Install panels with Square edge in DONN® DX® or fire-rated DXL™ 15/16" (23 mm) exposed suspension, DXW 1-1/2" (38 mm) exposed suspension, or CENTRICITEE™ or MERIDIAN® 9/16" (14 mm) exposed suspension (ARTISAN, ARTISAN 90).
- \* Install panels with Shadowline Tapered or Crowned (SL) edge in DONN DX or fire-rated DXL 15/16" (23 mm) exposed suspension (Fine Fissured II, Corona, Corona 90).
- \* Install panels with Shadowline Tapered edge in DONN DX or fire-rated DXL 15/16" (23 mm) exposed suspension (ARTISAN, ARTISAN 90).
- \* Install panels with Interline Tapered or Crowned (IL) edge in DONN CENTRICITEE or MERIDIAN 9/16" (14 mm) exposed suspension (Fine Fissured II, Corona, Corona 90).
- \* Install panels with Interline Tapered edge in DONN CENTRICITEE or MERIDIAN 9/16" (14 mm) exposed suspension (ARTISAN, ARTISAN 90).
- \* Install panels with FINELINE edge in DONN FINELINE® or FINELINE 1/8 9/16" (14 mm) exposed suspension.
- \* Install tile with Bevel edge/kerf in DONN Concealed DX suspension.

## **MF-MATERIALS, FINISHES**

- \* Materials-
  - AURATONE water-felted mineral fiber.
- \* Colors-
  - White plus 24 standard colors (Fine Fissured II, Corona, Corona 90).
  - White, Mist, Beige, Black, Teal, Silvertone, Nectar, Dusk, Manila (ARTISAN, ARTISAN 90).
- \* Call Customer Relations at 1-800-950-3839 for samples.
- \* Accessory systems-
  - DONN DX 15/16" (23 mm) exposed suspension.
  - DONN DXL fire-rated 15/16" (23 mm) exposed suspension.
  - DONN DXW 1-1/2" (38 mm) exposed suspension.
  - DONN ZXA corrosion-resistant 15/16" (23 mm) exposed suspension (Fine Fissured II, Corona, Corona 90).
  - DONN ZXLA corrosion-resistant, fire-rated 15/16" (23 mm) exposed suspension (Fine Fissured II, Corona, Corona 90).
  - DONN AX corrosion-resistant, aluminum 15/16" (23 mm) exposed suspension (Fine Fissured II, Corona, Corona 90).
  - DONN CENTRICITEE non-fire-rated or fire-rated 9/16" (14 mm) exposed suspension.
  - DONN MERIDIAN 9/16" (14 mm) exposed suspension with rounded reveal.
  - DONN FINELINE non-fire-rated or fire-rated slotted 9/16" (14 mm) exposed suspension.
  - DONN FINELINE 1/8 slotted 9/16" (14 mm) exposed suspension.
  - DONN Concealed DX non-fire-rated or fire-rated suspension.

**CS-COATINGS, SURFACING**

- \* Optional plastic coating (available only on white Fine Fissured II, Corona, and Corona 90 products) is Gardner-Scrubbability-tested to 3,000 cycles.
- \* ENVIROSENSE™ with INTERSEPT® (new, surface-active, broad spectrum antimicrobial): All products are available with INTERSEPT. To specify, use the standard item number followed by the word "INTERSEPT."

**TS-TECHNICAL SUPPORT**

- \* Call Customer Relations at 1-800-950-3839.

**CC-CODES, CERTIFICATION**

- \* ASTM form/spec. Type 3, Form 2, Class 25 (Fine Fissured II, ARTISAN, ARTISAN 90).
- \* ASTM form/spec. Type 3, Form 2, Class A (Corona 90).
- \* Meets ASTM E1264.

**OM-OPERATION, MAINTENANCE**

- \* Can be cleaned easily with a soft brush or vacuum.