

## **MR-MANUFACTURER** - USG Interiors, Inc.

For specifications on this product, 1.) close this product Snapshot, 2.) click on the Manufacturer's Showcase button, 3.) select the screen, *Specification: ACOUSTONE Ceilings* from the drop-down Showcase list that appears in the upper right of your screen.

### **PP-PRODUCT PRESENTATION** - ECLIPSE™ Fine-Textured Ceiling Panels

- \* ECLIPSE: Technologically advanced, nondirectional fine texture.
- \* High-NRC ECLIPSE: Enhanced noise reduction.
- \* ECLIPSE PREMIER™: 1" (25 mm) thick panel with superior noise reduction and sound attenuation ratings.
- \* ECLIPSE: Class A and FIRECODE® panels (for fire-rated systems).
- \* High-NRC ECLIPSE and ECLIPSE PREMIER: Class A.
- \* Flame spread/smoke developed: 25/25.
- \* Weight: .90 lb./sq. ft. (4.39 kg/sq. m) (ECLIPSE and High-NRC ECLIPSE Class A).
  - 1.1 lb./sq. ft. (5.37 kg/sq. m) (ECLIPSE and High-NRC ECLIPSE FIRECODE).
  - 1.2 lb./sq. ft. (5.86 kg/sq. m) (ECLIPSE PREMIER).
- \* Thermal resistance: R-2.78.
- \* Maximum backloading: .75 lb./sq. ft. (3.66 kg./sq. m).
- \* Maximum temperature: 90°F (32°C).
- \* Maximum humidity: 90% relative humidity.
- \* Water resistance: Less than 0.3 g/sq. m./2 min. per Cobb test.
- \* Sag resistance: 10-year limited warranty.
- \* Class A panels available with hardware compatible cut-outs.
- \* Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.
- \* Products are available in the following edges:
  - Square (SQ), Shadowline Tapered (SLT), Interline Tapered (ILT), Fineline (FL), Bevel Edge/Kerf (BESK). See the "Grid/Edge Selector Guide" in the product Showcase.

### **UA-USSES, APPLICATIONS**

- \* Closed-plan offices.
- \* Open-plan offices.
- \* Lobbies.
- \* Retail stores.
- \* High visibility ceilings.

### **AI-ASSEMBLY, INSTALLATION**

- \* Install panels with Square edge in DONN® DX® or fire-rated DXL™ 15/16" (23 mm) exposed suspension, DXW 1-1/2" (38 mm) exposed suspension, or CENTRICITEE™ or MERIDIAN® 9/16" (14 mm) exposed suspension.
- \* Install panels with Shadowline Tapered edge in DONN DX or fire-rated DXL 15/16" (23 mm) exposed suspension.
- \* Install panels with Interline Tapered edge in DONN CENTRICITEE or MERIDIAN 9/16" (14 mm) exposed suspension.
- \* Install panels with FINELINE edge in DONN FINELINE® or FINELINE 1/8 9/16"

(14 mm) exposed suspension, or CENTRICITEE or MERIDIAN 9/16" (14 mm) exposed suspension.

\* Install tile with Bevel edge/kerf in DONN Concealed DX suspension.

### **MF-MATERIALS, FINISHES**

\* Materials-

- ECLIPSE mineral fiber.

\* Colors-

- White, Manila, Silvertone, Parchment, Taupe, Mist.

- Tile available in White only.

\* Call Customer Relations at 1-800-950-3839 for samples.

\* Accessory systems-

- DONN DX 15/16" (23 mm) exposed suspension.

- DONN DXL fire-rated 15/16" (23 mm) exposed suspension.

- DONN DXW 1-1/2" (38 mm) exposed suspension.

- DONN CENTRICITEE non-fire-rated or fire-rated 9/16" (14 mm) exposed suspension.

- DONN MERIDIAN 9/16" (14 mm) exposed suspension with rounded reveal.

- DONN FINELINE non-fire-rated or fire-rated slotted 9/16" (14 mm) exposed suspension.

- DONN FINELINE 1/8 slotted 9/16" (14 mm) exposed suspension.

- DONN Concealed DX non-fire-rated or fire-rated suspension.

\* Accessory panels-

- Class A panels with hardware compatible cut-outs.

### **CS-COATINGS, SURFACING**

\* ENVIROSENSE™ with INTERSEPT® (new, surface-active, broad spectrum antimicrobial): All products are available with INTERSEPT. To specify, use the standard item number followed by the word "INTERSEPT."

### **TS-TECHNICAL SUPPORT**

\* Call Customer Relations at 1-800-950-3839.

### **CC-CODES, CERTIFICATION**

\* ASTM form/spec. Type 3, Form 1 or 2, Class 25.

\* Meets ASTM E1264.

### **OM-OPERATION, MAINTENANCE-**

\* Can be cleaned easily with a soft brush or vacuum.