

MR-MANUFACTURER - USG Interiors, Inc.

For specifications on this product, 1.) close this product Snapshot, 2.) click on the Manufacturer's Showcase button, 3.) select the screen, *Specification: ACOUSTONE Ceilings* from the drop-down Showcase list that appears in the upper right of your screen.

PP-PRODUCT PRESENTATION - AURATONE® Medium-Textured Ceiling Panels

- * Omni Fissured: Lightly fissured, heavily perforated.
- * High-NRC Omni Fissured: Same surface as Omni Fissured; excellent NRC's combined with optimum density.
- * High-STC Omni Fissured: Same surface as Omni Fissured; excellent CAC ratings for privacy in closed-plan.
- * Natural Fissured II: Deeply fissured, moderately perforated.
- * PREMIER™ Natural Fissured II: Same surface as Natural Fissured II; excellent NRC's combined with optimum density.
- * Fissured: A subtle pattern of fissuring combined with random perforations.
- * Class A and FIRECODE® (for fire-rated systems).
- * Flame spread/smoke developed:
 - 25/10 (Omni Fissured).
 - 15/10 (Natural Fissured II).
- * Weight:
 - .69-.81 lb./sq. ft. (3.37-3.95 kg/sq. m) (Class A 5/8" {16 mm} panels).
 - 1.00 lb./sq. ft. (4.88 kg/sq. m) (Class A and High-NRC 3/4" {19 mm} panels).
 - 1.10 lb./sq. ft. (5.37 kg/sq. m) (Class A 5/8" {16 mm} tile).
 - 1.40 lb./sq. ft. (6.83 kg/sq. m) (Class A 3/4" {19 mm} tile).
 - 1.15 lb./sq. ft. (5.61 kg/sq. m) (FIRECODE 5/8" {16 mm} panels and tile).
 - 1.37 lb./sq. ft. (6.69 kg/sq. m) (FIRECODE 3/4" {19 mm} panels).
 - 1.40 lb./sq. ft. (6.83 kg/sq. m) (FIRECODE 3/4" {19 mm} tile).
 - 1.25 lb./sq. ft. (6.10 kg/sq. m) (PREMIER FIRECODE 7/8" {22 mm} panels).
- * Thermal resistance:
 - R-2.18 (3/4" {19 mm} products).
 - R-1.85 (5/8" {16 mm} products).
- * Maximum backloading: .75 lb./sq. ft. (3.66 kg/sq. m.).
- * Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.
- * Products are available in the following edges:
 - Square (SQ), Shadowline Tapered (SLT), Interline Tapered (ILT), Finline (FL), Bevel Edge/Kerf (BESK) and Tongue & Groove Flange (TGF). See the "Grid/Edge Selector Guide" in the product Showcase.

UA-USES, APPLICATIONS

- * Open-plan offices.
- * Closed-plan offices.
- * Lobbies.
- * Shopping centers and stores.
- * Restaurants.

AI-ASSEMBLY, INSTALLATION

- * Install panels with Square edge in DONN® DX® or fire-rated DXL™ 15/16" (23 mm) exposed suspension, DXW 1-1/2" (38 mm) exposed suspension, or CENTRICITEE™ or MERIDIAN® 9/16" (14 mm) exposed suspension.
- * Install panels with Shadowline Tapered edge in DONN DX or fire-rated DXL 15/16" (23 mm) exposed suspension.
- * Install panels with Interline Tapered edge in DONN CENTRICITEE or MERIDIAN 9/16" (14 mm) exposed suspension.
- * Install panels with FINELINE edge in DONN FINELINE® or FINELINE 1/8 9/16" (14 mm) exposed suspension, or CENTRICITEE or MERIDIAN 9/16" (14 mm) exposed suspension.
- * Install tile with Bevel edge/kerf in DONN Concealed DX suspension.
- * Install tile with Tongue & Groove Flange edge using adhesive or staple-up method.
- * Install tile with Staple Flange edge using staple-up method.

MF-MATERIALS, FINISHES

- * Materials-
 - AURATONE water-felted mineral fiber.
- * Colors-
 - White plus 24 standard colors (Omni Fissured).
 - White (Natural Fissured II).
- * Call Customer Relations at 1-800-950-3839 for samples.
- * Accessory systems-
 - DONN DX 15/16" (23 mm) exposed suspension.
 - DONN DXL fire-rated 15/16" (23 mm) exposed suspension.
 - DONN DXW 1-1/2" (38 mm) exposed suspension.
 - DONN CENTRICITEE non-fire-rated or fire-rated 9/16" (14 mm) exposed suspension.
 - DONN MERIDIAN 9/16" (14 mm) exposed suspension with rounded reveal.
 - DONN FINELINE non-fire-rated or fire-rated slotted 9/16" (14 mm) exposed suspension.
 - DONN FINELINE 1/8 slotted 9/16" (14 mm) exposed suspension.
 - DONN Concealed DX non-fire-rated or fire-rated suspension.

CS-COATINGS, SURFACING

- * Optional plastic coating (available only on white products) is Gardner-Scrubability-tested to 3,000 cycles.
- * ENVIROSENSE™ with INTERSEPT® (new, surface-active, broad spectrum antimicrobial): All products are available with INTERSEPT. To specify, use the standard item number followed by the word "INTERSEPT."

TS-TECHNICAL SUPPORT

- * Call Customer Relations at 1-800-950-3839.

CC-CODES, CERTIFICATION

- * ASTM form/spec. Type 3, Form 2, Class 25.
- * Meets ASTM E1264.

OM-OPERATION, MAINTENANCE

* Can be cleaned easily with a soft brush or vacuum.