

MR-MANUFACTURER - USG Interiors, Inc.

For specifications on this product, 1.) close this product Snapshot, 2.) click on the Manufacturer's Showcase button, 3.) select the screen, *Specification: ACOUSTONE Ceilings* from the drop-down Showcase list that appears in the upper right of your screen.

PP-PRODUCT PRESENTATION - ACOUSTONE® Richly Textured Ceiling Panels

- * GLACIER™: Distinctive rough texture with rich surface detail.
- * Class A and FIRECODE® (for fire-rated systems).
- * Flame spread/smoke developed: 25/15.
- * Weight:
 - 1.25 lb./sq. ft. (6.10 kg/sq. m) (Class A).
 - 1.30 lb./sq. ft. (6.35 kg/sq. m) (FIRECODE).
- * Thermal resistance: R-2.12.
- * Maximum backloading: .75 lb./sq. ft. (3.66 kg/sq. m).
- * Durability: ACOUSTONE surface resists scrapes commonly caused by accessing ceiling panels.
- * Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.
- * Products are available in the following edges:
 - Square (SQ), Shadowline (SL), Finline (FL) and Square Edge/Kerf (SESK).
 - See the "Grid/Edge Selector Guide" in the product Showcase.

UA-USES, APPLICATIONS

- * Closed-plan offices.
- * Open-plan offices.
- * Lobbies.
- * Retail stores.
- * Restaurants.
- * High visibility ceilings.

AI-ASSEMBLY, INSTALLATION

- * Install panels with Square edge in DONN® DX® or fire-rated DXL™ 15/16" (23 mm) exposed suspension, DXW 1-1/2" (38 mm) exposed suspension, or CENTRICITEE™ or MERIDIAN® 9/16" (14 mm) exposed suspension.
- * Install panels with Shadowline edge in DONN DX or fire-rated DXL 15/16" (23 mm) exposed suspension.
- * Install panels with FINELINE edge in DONN FINELINE® or FINELINE 1/8 9/16" (14 mm) exposed suspension, or CENTRICITEE or MERIDIAN 9/16" (14 mm) exposed suspension.
- * Install tile with Square edge/kerf in DONN Concealed DX suspension.

MF-MATERIALS, FINISHES

- * Materials-
 - ACOUSTONE molded mineral fiber.
- * Colors-
 - Panels: White plus 24 standard colors.
 - Tile: White plus Earthtone colors.

- Exclusive clear-through color process masks nicks and scratches.
- * Call Customer Relations at 1-800-950-3839 for samples.
- * Accessory systems-
- DONN DX 15/16" (23 mm) exposed suspension.
- DONN DXL fire-rated 15/16" (23 mm) exposed suspension.
- DONN DXW 1-1/2" (38 mm) exposed suspension.
- DONN CENTRICITEE non-fire-rated or fire-rated 9/16" (14 mm) exposed suspension.
- DONN MERIDIAN 9/16" (14 mm) exposed suspension with rounded reveal.
- DONN FINELINE non-fire-rated or fire-rated slotted 9/16" (14 mm) exposed suspension.
- DONN FINELINE 1/8 slotted 9/16" (14 mm) exposed suspension.
- DONN Concealed DX non-fire-rated or fire-rated suspension.

CS-COATINGS, SURFACING

- * ENVIROSENSE™ with INTERSEPT® (new, surface-active, broad spectrum antimicrobial): All products are available with INTERSEPT. To specify, use the standard item number followed by the word "INTERSEPT."

TS-TECHNICAL SUPPORT

- * Call Customer Relations at 1-800-950-3839.

CC-CODES, CERTIFICATION

- * ASTM form/spec. Type 3, Form 1, Class 25.
- * Meets ASTM E1264.

OM-OPERATION, MAINTENANCE

- * Can be cleaned easily with a soft brush or vacuum.