

## **MR-MANUFACTURER** - USG Interiors, Inc.

For specifications on this product, 1.) close this product Snapshot, 2.) click on the Manufacturer's Showcase button, 3.) select the screen, *Specification: ACOUSTONE Ceilings* from the drop-down Showcase list that appears in the upper right of your screen.

## **PP-PRODUCT PRESENTATION** - AURATONE® Natural Textured Ceiling Panels

- \* Olympia II: The most subtle of the designer surfaces.
- \* Olympia 90: Perforated or unperforated styles; maximum temperature/humidity: 90°F (32°C), 90% R.H. on unperforated panels.
- \* Class A and FIRECODE® (for fire-rated systems).
- \* Flame spread/smoke developed: 25/10 (Olympia II).
- \* Weight: 1.31 lb./sq. ft. (6.40 kg/sq. m) (Olympia II Class A panels).  
1.35 lb./sq. ft. (6.59 kg/sq. m) (Olympia 90 FIRECODE panels).
- \* Thermal resistance: Up to R-2.18.
- \* Maximum backloading: .75 lb./sq. ft. (3.66 kg/sq. m).
- \* Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.
- \* Products are available in the following edges:  
Square (SQ), Shadowline Tapered (SLT), Interline Tapered (ILT) and FINELINE (FL). See the "Grid/Edge Selector Guide" in the product Showcase.

## **UA-USES, APPLICATIONS**

- \* Open-plan offices.
- \* Closed-plan offices.
- \* Lobbies.
- \* Shopping centers and stores.
- \* Restaurants.

## **AI-ASSEMBLY, INSTALLATION**

- \* Install panels with Square edge in DONN® DX® or fire-rated DXL™ 15/16" (23 mm) exposed suspension, DXW 1-1/2" (38 mm) exposed suspension, or CENTRICITEE™ or MERIDIAN® 9/16" (14 mm) exposed suspension.
- \* Install panels with Shadowline Tapered edge in DONN DX or fire-rated DXL 15/16" (23 mm) exposed suspension.
- \* Install panels with Interline Tapered edge in DONN CENTRICITEE or MERIDIAN 9/16" (14 mm) exposed suspension.
- \* Install panels with FINELINE edge in DONN FINELINE® or FINELINE 1/8 9/16" (14 mm) exposed suspension, or CENTRICITEE or MERIDIAN 9/16" (14 mm) exposed suspension.

## **MF-MATERIALS, FINISHES**

- \* Materials-
  - AURATONE water-felted mineral fiber.
- \* Color-
  - White.
- \* Call Customer Relations at 1-800-950-3839 for samples.
- \* Accessory systems-

- DONN DX 15/16" (23 mm) exposed suspension.
- DONN DXL fire-rated 15/16" (23 mm) exposed suspension.
- DONN CENTRICITEE 9/16" (14 mm) exposed suspension.
- DONN MERIDIAN 9/16" (14 mm) exposed suspension with rounded reveal.

### **CS-COATINGS, SURFACING**

- \* Optional plastic coating (available only on white products) is Gardner-Scrubability-tested to 3,000 cycles.
- \* ENVIROSENSE™ with INTERSEPT® (new, surface-active, broad spectrum antimicrobial): All products are available with INTERSEPT. To specify, use the standard item number followed by the word "INTERSEPT."

### **TS-TECHNICAL SUPPORT**

- \* Call Customer Relations at 1-800-950-3839.

### **CC-CODES, CERTIFICATION**

- \* ASTM form/spec. Type 3, Form 2, Class 25.
- \* Meets ASTM E1264.

### **OM-OPERATION, MAINTENANCE**

- \* Can be cleaned easily with a soft brush or vacuum.