

MR-MANUFACTURER - USG Interiors, Inc.

For specifications on this product, 1.) close this product Snapshot, 2.) click on the Manufacturer's Showcase button, 3.) select the screen, *Specification: ACOUSTONE Ceilings* from the drop-down Showcase list that appears in the upper right of your screen.

PP-PRODUCT PRESENTATION - AURATONE® Design Textured Ceiling Panels

- * Allegro: Symmetrical, woven texture on a generous scale.
- * Calypso: Soft, nonrepeating rivulets of texture with minute perforations.
- * Surf: Shading and three-dimensional fissures.
- * Aspen: Random, naturally sculptured appearance.
- * Tahoe: Naturally sculptured, softly rounded texture.
- * Class A and FIRECODE® (for fire-rated systems).
- * Flame spread/smoke developed: 25/10.
 - * Weight: .81 lb./sq. ft. (3.95 kg/sq. m) (Allegro and Calypso panels; Tahoe and Surf Class A panels).
 - 1.00 lb./sq. ft. (4.88 kg/sq. m) (Aspen Class A panels).
 - 1.37 lb./sq. ft. (6.69 kg/sq. m) (Aspen FIRECODE panels).
- * Thermal resistance: R-1.85 (Allegro, Calypso and Surf).
Up to R-2.18 (Aspen and Tahoe).
- * Maximum backloading: .75 lb./sq. ft. (3.66 kg/sq. m).
- * Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.
- * Products are available in the following edges:
Square (SQ), Shadowline Tapered (SLT), Interline Tapered (ILT) and Finline (FL). See the "Grid/Edge Selector Guide" in the product Showcase.

UA-USES, APPLICATIONS

- * Open-plan offices.
- * Closed-plan offices.
- * Lobbies.
- * Shopping centers and stores.
- * Restaurants.

AI-ASSEMBLY, INSTALLATION

- * Install panels with Square edge in DONN® DX® or fire-rated DXL™ 15/16" (23 mm) exposed suspension, DXW 1-1/2" (38 mm) exposed suspension, or CENTRICITEE™ or MERIDIAN® 9/16" (14 mm) exposed suspension.
- * Install panels with Shadowline Tapered edge in DONN DX or fire-rated DXL 15/16" (23 mm) exposed suspension.
- * Install panels with Interline Tapered edge in DONN CENTRICITEE or MERIDIAN 9/16" (14 mm) exposed suspension.
- * Install panels with FINELINE edge in DONN FINELINE® or FINELINE 1/8 9/16" (14 mm) exposed suspension, or CENTRICITEE or MERIDIAN 9/16" (14 mm) exposed suspension.

MF-MATERIALS, FINISHES

- * Materials-

- AURATONE water-felted mineral fiber.
- * Colors-
 - White plus 24 standard colors (Allegro, Calypso, Aspen and Tahoe).
 - Designer White (Surf).
- * Call Customer Relations at 1-800-950-3839 for samples.
- * Accessory systems-
 - DONN DX 15/16" (23 mm) exposed suspension.
 - DONN DXL fire-rated 15/16" (23 mm) exposed suspension.
 - DONN DXW 1-1/2" (38 mm) exposed suspension.
 - DONN CENTRICITEE non-fire-rated or fire-rated 9/16" (14 mm) exposed suspension.
 - DONN MERIDIAN 9/16" (14 mm) exposed suspension with rounded reveal.
 - DONN FINELINE non-fire-rated or fire-rated slotted 9/16" (14 mm) exposed suspension.
 - DONN FINELINE 1/8 slotted 9/16" (14 mm) exposed suspension.
 - DONN Concealed DX non-fire-rated or fire-rated suspension.

CS-COATINGS, SURFACING

- * Optional plastic coating (available only on white products) is Gardner-Scrubability-tested to 3,000 cycles.
- * ENVIROSENSE™ with INTERSEPT® (new, surface-active, broad spectrum antimicrobial): All products are available with INTERSEPT. To specify, use the standard item number followed by the word "INTERSEPT."

TS-TECHNICAL SUPPORT

- * Call Customer Relations at 1-800-950-3839.

CC-CODES, CERTIFICATION

- * ASTM form/spec. Type 3, Form 2, Class 25.
- * Meets ASTM E1264.

OM-OPERATION, MAINTENANCE

- * Can be cleaned easily with a soft brush or vacuum.