

MR-MANUFACTURER - USG Interiors, Inc.

For specifications on this product, 1.) close this product Snapshot, 2.) click on the Manufacturer's Showcase button, 3.) select the screen, *Specification: ACOUSTONE Ceilings* from the drop-down Showcase list that appears in the upper right of your screen.

PP-PRODUCT PRESENTATION - AURATONE® Perforated Ceiling Panels

- * Pin Perforated II Panels: Random fine and coarse perforations.
- * Pin Perforated Tile: Random perforations.
- * Pebbled Panels and Tile: Granular, perforated surface with improved sound ratings.
- * Class A and FIRECODE® (for fire-rated systems).
- * Flame spread/smoke developed: 25/10.
- * Weight:
 - .81 lb./sq. ft. (3.95 kg/sq. m) (Class A panels).
 - 1.15 lb./sq. ft. (5.61 kg/sq. m) (FIRECODE panels).
 - .90 lb./sq. ft. (4.39 kg/sq. m) (Class A tile).
- * Thermal resistance: R-1.85.
- * Maximum backloading: .75 lb./sq. ft. (3.66 kg/sq. m).
- * Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.
- * Products are available in the following edges:
 - Square (SQ), Shadowline Tapered (SLT) and Bevel Edge/Kerf (BESK). See the "Grid/Edge Selector Guide" in the product Showcase.

UA-USES, APPLICATIONS

- * Open-plan offices.
- * Closed-plan offices.
- * Lobbies.
- * Shopping centers and stores.
- * Restaurants.

AI-ASSEMBLY, INSTALLATION

- * Install panels with Square edge in DONN® DX® or fire-rated DXL™ 15/16" (23 mm) exposed suspension, DXW 1-1/2" (38 mm) exposed suspension, or CENTRICITEE™ or MERIDIAN® 9/16" (14 mm) exposed suspension.
- * Install panels with Shadowline Tapered edge in DONN DX or fire-rated DXL 15/16" (23 mm) exposed suspension.
- * Install tile with Bevel edge/kerf in DONN Concealed DX suspension.

MF-MATERIALS, FINISHES

- * Materials-
 - AURATONE water-felted mineral fiber.
- * Color-
 - White.
- * Call Customer Relations at 1-800-950-3839 for samples.
- * Accessory systems-
 - DONN DX 15/16" (23 mm) exposed suspension.

- DONN DXL fire-rated 15/16" (23 mm) exposed suspension.
- DONN DXW 1-1/2" (38 mm) exposed suspension.
- DONN CENTRICITEE non-fire-rated or fire-rated 9/16" (14 mm) exposed suspension.
- DONN MERIDIAN 9/16" (14 mm) exposed suspension with rounded reveal.
- DONN Concealed DX non-fire-rated or fire-rated suspension.

CS-COATINGS, SURFACING

- * Optional plastic coating (available only on white products) is Gardner-Scrubability-tested to 3,000 cycles.
- * ENVIROSENSE™ with INTERSEPT® (new, surface-active, broad spectrum antimicrobial): All products are available with INTERSEPT. To specify, use the standard item number followed by the word "INTERSEPT."

TS-TECHNICAL SUPPORT

- * Call Customer Relations at 1-800-950-3839.

CC-CODES, CERTIFICATION

- * ASTM form/spec. Type 3, Form 2, Class 25.
- * Meets ASTM E1264.

OM-OPERATION, MAINTENANCE

- * Can be cleaned easily with a soft brush or vacuum.