

MR-MANUFACTURER - USG Interiors, Inc.

For specifications on this product, 1.) close this product Snapshot, 2.) click on the Manufacturer's Showcase button, 3.) select the screen, *Specification: ACOUSTONE Ceilings* from the drop-down Showcase list that appears in the upper right of your screen.

PP-PRODUCT PRESENTATION - ACOUSTONE® Scored Ceiling Panels

- * PEDESTALS™ I: Triple step-cut 2' x 2' (600 x 600 mm) modules.
- * PEDESTALS IV: Triple step-cut 12" x 12" (300 x 300 mm) modules.
- * Chex/36: 4" x 4" (100 x 100 mm) squares.
- * Chex/4: 12" x 12" (300 x 300 mm) squares, available with Glacier® or Frost texture.
- * Chex/16: 6" x 6" (150 x 150 mm) squares, embellished with single reveal.
- * Class A.
- * Flame spread/smoke developed: 25/15.
- * Weight: 1.25 lb./sq. ft. (6.10 kg/sq. m).
- * Thermal resistance: R-2.12.
- * Maximum backloading: .75 lb./sq. ft. (3.66 kg/sq. m).
- * Durability: ACOUSTONE surface resists scrapes commonly caused by accessing ceiling panels.
- * Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.
- * Products are available in the following edges:
PEDESTALS Edge (PE), Shadowline (SL), Chex/4 and Chex/16 Edge. See the "Grid/Edge Selector Guide" in the product Showcase.
- * Products are available in the following face styles:
PEDESTALS I, PEDESTALS IV, Chex/4, Chex/16 and Chex/36. See "Face-Cut Configurations" in the product Showcase.

UA-USES, APPLICATIONS

- * Closed-plan offices.
- * Open-plan offices.
- * Lobbies.
- * Retail stores.
- * Restaurants.
- * High visibility ceilings.

AI-ASSEMBLY, INSTALLATION

- * Install PEDESTALS panels in DONN® CENTRICITEE™ or MERIDIAN® 9/16" (14 mm) exposed suspension.
- * Install Chex/36, Chex/4 and Chex/16 panels with Special edge in DONN CENTRICITEE or MERIDIAN® 9/16" (14 mm) exposed suspension.
- * Install Chex/4 panels with Shadowline edge in DONN DX® 15/16" (23 mm) exposed suspension.

MF-MATERIALS, FINISHES

- * Materials-
- ACOUSTONE molded mineral fiber.

* Colors-

- White plus 24 standard colors.
- Exclusive clear-through color process masks nicks and scratches.

* Call Customer Relations at 1-800-950-3839 for samples.

* Accessory systems-

- DONN DX 15/16" (23 mm) exposed suspension.
- DONN CENTRICITEE 9/16" (14 mm) exposed suspension.
- DONN MERIDIAN 9/16" (14 mm) exposed suspension with rounded reveal.

* Accessory panels-

- Panels with hardware compatible cut-outs.

CS-COATINGS, SURFACING

* ENVIROSENSE™ with INTERSEPT® (new, surface-active, broad spectrum antimicrobial): All products are available with INTERSEPT. To specify, use the standard item number followed by the word "INTERSEPT."

TS-TECHNICAL SUPPORT

* Call Customer Relations at 1-800-950-3839.

CC-CODES, CERTIFICATION

- * ASTM form/spec. Type 3, Form 1, Class 25.
- * Meets ASTM E1264.

OM-OPERATION, MAINTENANCE

* Can be cleaned easily with a soft brush or vacuum.