

MR-MANUFACTURER - USG Interiors, Inc.

For specifications on this product, 1.) close this product Snapshot, 2.) click on the Manufacturer's Showcase button, 3.) select the screen, *Specification: ACOUSTONE Ceilings* from the drop-down Showcase list that appears in the upper right of your screen.

PP-PRODUCT PRESENTATION - AURATONE® Scored Ceiling Panels

- * PEDESTALS™ I: Triple step-cut detailing only at panel edges.
- * PEDESTALS IV: Triple step-cut 12" x 12" (300 x 300 mm) modules.
- * PEDESTALS IX: Smaller 8" x 8" (200 x 200 mm) triple step-cut modules.
- * PEDESTALS ILLUSION™ Two/24: Triple step-cut 2' x 2' (600 x 600 mm) panel look with 2' x 4' (600 x 1200 mm) panel economy.
- * PEDESTALS ILLUSION Eight/12: Triple step-cut 12" x 12" (300 x 300 mm) tile look with 2' x 4' (600 x 1200 mm) panel economy.
- * Class A.
- * Flame spread/smoke developed: 25/10.
- * Weight: 1.00 lb./sq. ft. (4.88 kg/sq. m).
- * Thermal resistance: Up to R-2.18.
- * Maximum backloading: .75 lb./sq. ft. (3.66 kg/sq. m).
- * Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.
- * Products are available in the following edge:
PEDESTALS Edge (PE). See the "Grid/Edge Selector Guide" in the product Showcase.
- * Products are available in the following face styles:
PEDESTALS I, PEDESTALS IV, PEDESTALS IX, PEDESTALS Two/24 and PEDESTALS Eight/12. See "Face-Cut Configurations" in the product Showcase.

UA-USES, APPLICATIONS

- * Open-plan offices.
- * Closed-plan offices.
- * Lobbies.
- * Shopping centers and stores.
- * Restaurants.

AI-ASSEMBLY, INSTALLATION

- * Install panels in DONN® CENTRICITEE™ or MERIDIAN® 9/16" (14 mm) exposed suspension.

MF-MATERIALS, FINISHES

- * Materials-
 - AURATONE water-felted mineral fiber.
- * Colors-
 - White, Manila, Silvertone, Parchment, Taupe, Mist.
- * Call Customer Relations at 1-800-950-3839 for samples.
- * Accessory systems-
 - DONN CENTRICITEE 9/16" (14 mm) exposed suspension.

- DONN MERIDIAN 9/16" (14 mm) exposed suspension with rounded reveal.

CS-COATINGS, SURFACING

- * Optional plastic coating (available only on white products) is Gardner-Scrubability-tested to 3,000 cycles.
- * ENVIROSENSE™ with INTERSEPT® (new, surface-active, broad spectrum antimicrobial): All products are available with INTERSEPT. To specify, use the standard item number followed by the word "INTERSEPT."

TS-TECHNICAL SUPPORT

- * Call Customer Relations at 1-800-950-3839.

CC-CODES, CERTIFICATION

- * ASTM form/spec. Type 3, Form 2, Class 25.
- * Meets ASTM E1264.

OM-OPERATION, MAINTENANCE

- * Can be cleaned easily with a soft brush or vacuum.