

MR-MANUFACTURER - USG Interiors, Inc.

For specifications on this product, 1.) close this product Snapshot, 2.) click on the Manufacturer's Showcase button, 3.) select the screen, *Specification: ACOUSTONE Ceilings* from the drop-down Showcase list that appears in the upper right of your screen.

PP-PRODUCT PRESENTATION - AURATONE® Designer Ceiling Series

- * DESIGNER SQUARES™ I: Thirty-six 3" x 3" (75 x 75 mm) squares.
- * DESIGNER SQUARES III: Twenty-five 4" x 4" (100 x 100 mm) squares.
- * Class A.
- * Flame spread/smoke developed: 25/10.
- * Thermal resistance: Up to R-1.52.
- * Maximum backloading: .75 lb./sq. ft. (3.66 kg/sq. m).
- * Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.
- * Products are available in the following edges:
Shadowline (SL) and FINELINE (FL). See the "Grid/Edge Selector Guide" in the product Showcase.
- * Products are available in the following face styles:
DESIGNER SQUARES I and DESIGNER SQUARES III. See "Face-Cut Configurations" in the product Showcase.

UA-USES, APPLICATIONS

- * Open-plan offices.
- * Closed-plan offices.
- * Lobbies.
- * Shopping centers and stores.
- * Restaurants.

AI-ASSEMBLY, INSTALLATION

- * Install panels with Shadowline edge in DONN® DX® or fire-rated DXL™ 15/16" (23 mm) exposed suspension.
- * Install panels with FINELINE edge in DONN FINELINE® or FINELINE 1/8 9/16" (14 mm) exposed suspension, or CENTRICITEE™ or MERIDIAN® 9/16" (14 mm) exposed suspension.

MF-MATERIALS, FINISHES

- * Materials-
 - AURATONE water-felted mineral fiber.
- * Colors-
 - White, Manila, Silvertone, Parchment, Taupe, Mist.
- * Call Customer Relations at 1-800-950-3839 for samples.
- * Accessory systems-
 - DONN DX 15/16" (23 mm) exposed suspension.
 - DONN DXL fire-rated 15/16" (23 mm) exposed suspension.
 - DONN CENTRICITEE 9/16" (14 mm) exposed suspension.
 - DONN MERIDIAN 9/16" (14 mm) exposed suspension with rounded reveal.
 - DONN FINELINE non-fire-rated or fire-rated, slotted 9/16" (14 mm) exposed

suspension.

- DONN FINELINE 1/8 slotted 9/16" (14 mm) exposed suspension.

CS-COATINGS, SURFACING

* Optional plastic coating (available only on white products) is Gardner-Scrubability-tested to 3,000 cycles.

* ENVIROSENSE™ with INTERSEPT® (new, surface-active, broad spectrum antimicrobial): All products are available with INTERSEPT. To specify, use the standard item number followed by the word "INTERSEPT."

TS-TECHNICAL SUPPORT

* Call Customer Relations at 1-800-950-3839.

CC-CODES, CERTIFICATION

* ASTM form/spec. Type 3, Form 2, Class 25.

* Meets ASTM E1264.

OM-OPERATION, MAINTENANCE

* Can be cleaned easily with a soft brush or vacuum.