

MR-MANUFACTURER - USG Interiors, Inc.

For specifications on this product, 1.) close this product Snapshot, 2.) click on the Manufacturer's Showcase button, 3.) select the screen, *Specification: ACOUSTONE Ceilings* from the drop-down Showcase list that appears in the upper right of your screen.

PP-PRODUCT PRESENTATION - Face-Cut ECLIPSE™ Ceiling Panels

- * ECLIPSE ILLUSION™ Two-24: The look of 2' x 2' (600 x 600 mm) panels.
- * ECLIPSE ILLUSION Eight-12: The look of 12" x 12" (300 x 300 mm) tile.
- * ECLIPSE Chex/4: Classic 12" x 12" (300 x 300 mm) squares.
- * ECLIPSE Chex/16: 6" x 6" (150 x 150 mm) squares, embellished with single reveal.
- * ECLIPSE PEDESTALS™ I: Triple-step scoring at the perimeter.
- * ECLIPSE PEDESTALS IV: Triple-step-cut 12" x 12" (300 x 300 mm) modules.
- * Class A.
- * Flame spread/smoke developed: 25/25.
- * Weight: .90 lb./sq. ft. (4.39 kg/sq. m).
- * Thermal resistance: R-2.78.
- * Maximum backloading: .75 lb./sq. ft. (3.66 kg/sq. m).
- * Maximum temperature: 90°F (32°C).
- * Maximum humidity: 90% relative humidity.
- * Water resistance: Less than 0.3 g/sq. m/2 min. per Cobb test.
- * Sag resistance: 10-year limited warranty.
- * Panels available with hardware compatible cut-outs.
- * Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.
- * Products are available in the following edges:
Shadowline Tapered (SLT), Interline Tapered (ILT), Fineline (FL) and PEDESTALS (PE). See the "Grid/Edge Selector Guide" in the product Showcase.
- * Products are available in the following face styles:
ILLUSION Two-24, ILLUSION Eight-12, Chex/4, Chex/16, PEDESTALS I and PEDESTALS IV. See "Face-Cut Configurations" in the product Showcase.

UA-USSES, APPLICATIONS

- * Closed-plan offices.
- * Open-plan offices.
- * Lobbies.
- * Retail stores.
- * High visibility ceilings.

AI-ASSEMBLY, INSTALLATION

- * Install panels with Shadowline Tapered edge in DONN® DX® 15/16" (23 mm) exposed suspension.
- * Install panels with Interline Tapered edge in DONN CENTRICITEE™ or MERIDIAN® 9/16" (14 mm) exposed suspension.
- * Install panels with FINELINE edge in DONN FINELINE® or FINELINE 1/8 9/16" (14 mm) exposed suspension, or CENTRICITEE or MERIDIAN 9/16" (14 mm)

exposed suspension.

* Install panels with PEDESTALS edge in DONN CENTRICITEE 9/16" (14 mm) exposed suspension.

MF-MATERIALS, FINISHES

* Materials-

- ECLIPSE mineral fiber.

* Color-

- White.

* Call Customer Relations at 1-800-950-3839 for samples.

* Accessory systems-

- DONN DX 15/16" (23 mm) exposed suspension.

- DONN CENTRICITEE non-fire-rated or fire-rated 9/16" (14 mm) exposed suspension.

- DONN MERIDIAN 9/16" (14 mm) exposed suspension with rounded reveal.

- DONN FINELINE non-fire-rated or fire-rated slotted 9/16" (14 mm) exposed suspension.

- DONN FINELINE 1/8 slotted 9/16" (14 mm) exposed suspension.

* Accessory panels-

- Panels with hardware compatible cut-outs.

CS-COATINGS, SURFACING

* ENVIROSENSE™ with INTERSEPT® (new, surface-active, broad spectrum antimicrobial): All products are available with INTERSEPT. To specify, use the standard item number followed by the word "INTERSEPT."

TS-TECHNICAL SUPPORT

* Call Customer Relations at 1-800-950-3839.

CC-CODES, CERTIFICATION

* ASTM form/spec. Type 3, Form 1 or 2, Class 25.

* Meets ASTM E1264.

OM-OPERATION, MAINTENANCE

* Can be cleaned easily with a soft brush or vacuum.