

MR-MANUFACTURER - USG Interiors, Inc.

PP-PRODUCT PRESENTATION - ACOUSTONE® Linear-Scored Ceiling Panels

- * LINEAR EXPRESSIONS™ Random and Wide: Surfaces inspired by linear patterns in nature.
- * Checkmate: Ideal for expansive ceilings.
- * Checkline: Linear scored.
- * LINEAR EXPRESSIONS: Class A and FIRECODE® (for fire-rated systems).
- * Checkmate and Checkline: Class A panels.
- * Flame spread/smoke developed: 25/15.
- * Weight: 1.25 lb./sq. ft. (6.10 kg/sq. m) (Class A).
1.30 lb./sq. ft.(6.35 kg/sq. m) (FIRECODE).
- * Thermal resistance: R-2.12.
- * Maximum backloading: .75 lb./sq. ft. (3.66 kg/sq. m).
- * Durability: ACOUSTONE surface resists scrapes commonly caused by accessing ceiling panels.
- * Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.
- * Products are available in the following edges:
Special, Checkmate and Checkline. See the "Grid/Edge Selector Guide" in Showcase Screen.
- * Products are available in the following face styles:
Checkmate and Checkline. See "Face-Cut Configurations" in Corporate Showcase Screen.

UA-USES, APPLICATIONS

- * Closed-plan offices.
- * Open-plan offices.
- * Lobbies.
- * Retail stores.
- * Restaurants.
- * High visibility ceilings.

AI-ASSEMBLY, INSTALLATION

- * Install Checkmate and Checkline panels with Special edge in DONN CENTRICITEE™ or MERIDIAN® 9/16" (14 mm) exposed suspension.

MF-MATERIALS, FINISHES

- * Materials-
 - ACOUSTONE molded mineral fiber.
- * Colors-
 - White plus 24 standard colors.
 - Exclusive clear-through color process masks nicks and scratches.
- * Call Customer Relations at 1-800-950-3839 for samples.
- * Accessory systems-
 - DONN DX 15/16" (23 mm) exposed suspension.
 - DONN DXL fire-rated 15/16" (23 mm) exposed suspension.
 - DONN CENTRICITEE 9/16" (14 mm) exposed suspension.
 - DONN MERIDIAN 9/16" (14 mm) exposed suspension with rounded reveal.

- DONN FINELINE slotted 9/16" (14 mm) exposed suspension.
- DONN FINELINE 1/8 slotted 9/16" (14 mm) exposed suspension.

CS-COATINGS, SURFACING

* ENVIROSENSE™ with INTERSEPT® (new, surface-active, broad spectrum antimicrobial): All products are available with INTERSEPT. To specify, use the standard item number followed by the word "INTERSEPT".

TS-TECHNICAL SUPPORT

* Call Customer Relations at 1-800-950-3839.

CC-CODES, CERTIFICATION

- * ASTM form/spec. Type 3, Form 1, Class 25.
- * Meets ASTM E1264.

OM-OPERATION, MAINTENANCE

* Can be cleaned easily with a soft brush or vacuum.