

## **MR-MANUFACTURER** - USG Interiors, Inc.

For specifications on this product, 1.) close this product Snapshot, 2.) click on the Manufacturer's Showcase button, 3.) select the screen, *Specification: ACOUSTONE Ceilings* from the drop-down Showcase list that appears in the upper right of your screen.

### **PP-PRODUCT PRESENTATION** - AURATONE® Linear-Scored Ceiling Panels

- \* PEDESTALS™ II: Narrow proportioned, triple step-cut 12" x 4" (300 x 600 mm) modules.
- \* PEDESTALS ILLUSION™ Four/48: Triple step-cut 6" x 48" (150 x 1200 mm) linear strips.
- \* PROFILE™ Nine/Two-24: Nine linear bars, 24" (600 mm) long and 2" (50 mm) wide.
- \* DESIGNER SQUARES™ II: Six 3" x 24" (75 x 600 mm) linear bars.
- \* DESIGNER SQUARES™ IV: Eleven 1" x 24" (25 x 600 mm) linear bars.
- \* ILLUSION Four/48: 6" x 48" (150 x 1200 mm) linear strips.
- \* Class A and FIRECODE® (for fire-rated systems).
- \* Flame spread/smoke developed: 25/10 (Natural Fissured II, Omni Fissured and Aspen texture).
- \* Weight: 1.00 lb./sq. ft. (4.88 kg/sq. m) (PEDESTALS panels).  
.69-.81 lb./sq. ft. (3.37-3.95 kg/sq. m) (PROFILE panels).  
1.37 lb./sq. ft. (6.69 kg/sq. m) (ILLUSION panels).
- \* Thermal resistance: Up to R-2.18 (PEDESTALS panels).  
R-1.52 to R-1.85 (PROFILE panels).  
Up to R-1.52 (DESIGNER SQUARES panels).  
R-2.18 (ILLUSION panels with Omni Fissured and Aspen texture).
- \* Maximum backloading: .75 lb./sq. ft. (3.66 kg/sq. m).
- \* Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.
- \* Products are available in the following edges:  
PEDESTALS (PE), Interline Tapered (ILT), Shadowline (SL), Fineline (FL) and Shadowline Tapered (SLT). See the "Grid/Edge Selector Guide" in the product Showcase.
- \* Products are available in the following face styles:  
PEDESTALS II, PEDESTALS ILLUSION Four/48, PROFILE Nine/Two-24, DESIGNER SQUARES II, DESIGNER SQUARES IV and ILLUSION Four/48. See "Face-Cut Configurations" in the product Showcase.

### **UA-USES, APPLICATIONS**

- \* Open-plan offices.
- \* Lobbies.
- \* Shopping centers and stores.
- \* Restaurants.
- \* Expansive ceiling areas.

### **AI-ASSEMBLY, INSTALLATION**

- \* Install PEDESTALS panels in Donn® CENTRICITEE™ or MERIDIAN® 9/16" (14 mm) exposed suspension.

- \* Install panels with Shadowline Tapered edge in Donn DX® or fire-rated DXL™ 15/16" (23 mm) exposed suspension.
- \* Install panels with Interline Tapered edge in Donn CENTRICITEE or MERIDIAN 9/16" (14 mm) exposed suspension.
- \* Install panels with Fineline edge in Donn FINELINE® or FINELINE 1/8 9/16" (14 mm) exposed suspension, or CENTRICITEE or MERIDIAN 9/16" (14 mm) exposed suspension.

### **MF-MATERIALS, FINISHES**

- \* Materials-
  - AURATONE water-felted mineral fiber.
- \* Colors-
  - White, Manila, Silvertone, Parchment, Taupe, Mist.
- \* Call Customer Relations at 1-800-950-3839 for samples.
- \* Accessory systems-
  - Donn DX 15/16" (23 mm) exposed suspension.
  - Donn DXL fire-rated 15/16" (23 mm) exposed suspension.
  - Donn CENTRICITEE non-fire-rated or fire-rated 9/16" (14 mm) exposed suspension.
  - Donn MERIDIAN 9/16" (14 mm) exposed suspension with rounded reveal.
  - Donn FINELINE non-fire-rated or fire-rated slotted 9/16" (14 mm) exposed suspension.
  - Donn FINELINE 1/8 slotted 9/16" (14 mm) exposed suspension.

### **CS-COATINGS, SURFACING**

- \* Optional plastic coating (available only on white products) is Gardner-Scrubability-tested to 3,000 cycles.
- \* ENVIROSENSE™ with INTERSEPT® (new, surface-active, broad spectrum antimicrobial): All products are available with INTERSEPT. To specify, use the standard item number followed by the word "INTERSEPT."

### **TS-TECHNICAL SUPPORT**

- \* Call Customer Relations at 1-800-950-3839.

### **CC-CODES, CERTIFICATION**

- \* ASTM form/spec. Type 3, Form 2, Class 25.
- \* Meets ASTM E1264.

### **OM-OPERATION, MAINTENANCE**

- \* Can be cleaned easily with a soft brush or vacuum.