

MR-MANUFACTURER - USG Interiors, Inc.

For specifications on this product, 1.) close this product Snapshot, 2.) click on the Manufacturer's Showcase button, 3.) select the screen, *Specification: ACOUSTONE Ceilings* from the drop-down Showcase list that appears in the upper right of your screen.

PP-PRODUCT PRESENTATION - ECLIPSE™ Scored Ceiling Panels

- * ECLIPSE Crystal: Overlapping chiseled figures.
- * ECLIPSE Sketch: Woven scored lines.
- * ECLIPSE Dots: Small, evenly repeating dots.
- * ECLIPSE Regiment: Ultra-symmetrical miniature squares.
- * ECLIPSE Square-to-Square: A window of tiny squares.
- * Class A.
- * Flame spread/smoke developed: 25/25.
- * Weight: .90 lb./sq. ft. (4.39 kg/sq. m).
- * Thermal resistance: R-2.78.
- * Maximum backloading: .75 lb./sq. ft. (3.66 kg/sq. m).
- * Maximum temperature: 90°F (32°C).
- * Maximum humidity: 90% relative humidity.
- * Water resistance: Less than 0.3 g/sq. m/2 min. per Cobb test.
- * Sag resistance: 10-year limited warranty.
- * Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.
- * Products are available in the following edges:
Shadowline Tapered (SLT) and Fineline (FL). See the "Grid/Edge Selector Guide" in the product Showcase.
- * Products are available in the following face styles:
Crystal, Sketch, Square-to-Square, Regiment and Dots. See "Face-Cut Configurations" in the product Showcase.

UA-USES, APPLICATIONS

- * Closed-plan offices.
- * Open-plan offices.
- * Lobbies.
- * Retail stores.
- * High visibility ceilings.

AI-ASSEMBLY, INSTALLATION

- * Install panels with Shadowline Tapered edge in DONN® DX® 15/16" (23 mm) exposed suspension.
- * Install panels with FINELINE edge in DONN FINELINE® or FINELINE 1/8 9/16" (14 mm) exposed suspension, or CENTRICITEE™ or MERIDIAN® 9/16" (14 mm) exposed suspension.

MF-MATERIALS, FINISHES

- * Materials-
 - ECLIPSE mineral fiber.
- * Color-

- White.
- * Call Customer Relations at 1-800-950-3839 for samples.
- * Accessory systems-
- DONN DX 15/16" (23 mm) exposed suspension.
- DONN FINELINE non-fire-rated or fire-rated slotted 9/16" (14 mm) exposed suspension.
- DONN FINELINE 1/8 slotted 9/16" (14 mm) exposed suspension.
- DONN CENTRICITEE 9/16" (14 mm) exposed suspension.
- DONN MERIDIAN 9/16" (14 mm) exposed suspension with rounded reveal.

CS-COATINGS, SURFACING

* ENVIROSENSE™ with INTERSEPT® (new, surface-active, broad spectrum antimicrobial): All products are available with INTERSEPT. To specify, use the standard item number followed by the word "INTERSEPT."

TS-TECHNICAL SUPPORT

* Call Customer Relations at 1-800-950-3839.

CC-CODES, CERTIFICATION

- * ASTM form/spec. Type 3, Form 1 or 2, Class 25.
- * Meets ASTM E1264.

OM-OPERATION, MAINTENANCE

* Can be cleaned easily with a soft brush or vacuum.