

## **MR-MANUFACTURER** - USG Interiors, Inc.

For specifications on this product, 1.) close this product Snapshot, 2.) click on the Manufacturer's Showcase button, 3.) select the screen, *Specification: ACOUSTONE Ceilings* from the drop-down Showcase list that appears in the upper right of your screen.

### **PP-PRODUCT PRESENTATION** - AURATONE® CLEAN ROOM™ Ceiling Panels

- \* Tough, fire-resistant panels for high-tech clean rooms.
- \* Sealed edges and special back coating control airborne particles to meet stringent requirements.
- \* Meets Federal Standard 209D and high standards for hospitals, laboratories and computer rooms.
- \* Humidity resistance tested by 48 hour cycles of 90% and 25% relative humidity repeated continuously for 24 days; no delamination occurred.
- \* Freeze/thaw resistance tested by 10 repeated cycles of 16 hours freezing (-30°F {-34°C}) and 8 hours thaw; no delamination occurred.
- \* CLEAN ROOM Class 100: Impervious surface of white vinyl-coated aluminum foil. USDA-approved for food preparation areas.
- \* CLEAN ROOM Class 10M-100M: Perforated, white-vinyl coated aluminum foil surface.
- \* FIRECODE® (for fire-rated systems).
- \* Flame spread/smoke developed: 25/45.
- \* Weight: 1.11 lb./sq. ft. (5.42 kg/sq. m).
- \* Thermal resistance: R-1.85.
- \* Maximum backloading: .75 lb./sq. ft. (3.66 kg/sq. m).
- \* Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.
- \* Products are available in the following edge:
  - Square (SQ). See the "Grid/Edge Selector Guide" in the product Showcase.

### **UA-USES, APPLICATIONS**

- \* Hospitals.
- \* Laboratories.
- \* Computer rooms.
- \* Food preparation areas (CLEAN ROOM Class 100).

### **AI-ASSEMBLY, INSTALLATION**

- \* Install panels with Square edge in DONN® DX® or fire-rated DXL™ 15/16" (23 mm) exposed suspension, DXW 1-1/2" (38 mm) exposed suspension, or corrosion-resistant ZX, ZXA, or AX 15/16" (23 mm) exposed suspension, or CENTRICITEE™ or MERIDIAN® 9/16" (14 mm) exposed suspension.

### **MF-MATERIALS, FINISHES**

- \* Materials-
  - AURATONE water-felted mineral fiber.
- \* Color-
  - White.
- \* Call Customer Relations at 1-800-950-3839 for samples.
- \* Accessory systems-

- DONN DX 15/16" (23 mm) exposed suspension.
- DONN DXL fire-rated 15/16" (23 mm) exposed suspension.
- DONN DXW 1-1/2" (38 mm) exposed suspension.
- DONN ZXA corrosion-resistant 15/16" (23 mm) exposed suspension.
- DONN ZXLA corrosion-resistant, fire-rated 15/16" (23 mm) exposed suspension.
- DONN AX corrosion-resistant, aluminum 15/16" (23 mm) exposed suspension.
- DONN CENTRICITEE 9/16" (14 mm) exposed suspension.
- DONN MERIDIAN 9/16" (14 mm) exposed suspension with rounded reveal.

### **CS-COATINGS, SURFACING**

- \* Plastic coating on face is Gardner-Scrubbability-tested to 5,000 cycles.
- \* Vinyl latex seal on edges and back controls airborne particles.

### **TS-TECHNICAL SUPPORT**

- \* Call Customer Relations at 1-800-950-3839.

### **CC-CODES, CERTIFICATION**

- \* ASTM form/spec. Type 3, Form 2, Class 25.
- \* Meets ASTM E1264.

### **OM-OPERATION, MAINTENANCE**

- \* Can be cleaned easily with a damp sponge.