MR-MANUFACTURER - USG Interiors, Inc.

For specifications on this product, 1.) close this product Snapshot, 2.) click on the Manufacturer's Showcase button, 3.) select the screen, *Specification: ACOUSTONE Ceilings* from the drop-down Showcase list that appears in the upper right of your screen.

PP-PRODUCT PRESENTATION - DONN® CENTRICITEE™ suspension grid

- * Subtle, narrow-line alternative to 15/16" (23 mm) exposed grid.
- * Patented, automatic panel-centering devices built into each grid member.
- * High tensile steel connection clips on cross tee ends provide plug-in positive lock insertion for quick installation.
- * Exceptional tension and compression connection values without additional wires, clips, fasteners or pins.
- * Cross tees with override ends resist twisting and give a professionally finished appearance.
- * Meets or exceeds all national code requirements, including seismic.
- * Fire-rated assemblies available up to 2 hours.
- * Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.

UA-USES, APPLICATIONS

DONN CENTRICITEE for interior use only. See Ceiling Systems catalog *SA-905* and DONN Suspension Systems catalog *SA-904* for specific applications.

AI-ASSEMBLY, INSTALLATION

Designed for use with Square, Fineline, Fineline Bevel and Interline Tapered edge panels in exposed suspension. Level components and tie to structural members with hanger wire max. 48" (1200 mm) o.c. Install in accordance with ASTM C636 and manufacturer's instructions.

MF-MATERIALS, FINISHES

- * Materials-
- Double web intermediate-duty steel tees.
- Panel centering device.
- * Finishes-
- 29 standard finishes.
- Call Customer Relations at 1-800-950-3839 for samples.

CS-COATINGS, SURFACING

Proven corrosion-resistant coating.

TS-TECHNICAL SUPPORT

Call Customer Relations at 1-800-950-3839.

CC-CODES, CERTIFICATION

ASTM C635.

OM-OPERATION, MAINTENANCE

Can be cleaned easily with a soft cloth.