

MR-MANUFACTURER - USG Interiors, Inc.

For specifications on this product, 1.) close this product Snapshot, 2.) click on the Manufacturer's Showcase button, 3.) select the screen, *Specification: ACOUSTONE Ceilings* from the drop-down Showcase list that appears in the upper right of your screen.

PP-PRODUCT PRESENTATION - DONN® FINELINE® and Finline 1/8 suspension grids

- * Innovative, narrow-profile, slotted ceiling grid.
- * Mitered intersections offer a clean, tailored appearance.
- * High tensile steel connection clips on cross tee ends provide plug-in positive lock insertion for quick installation.
- * Exceptional tension and compression connection values without additional wires, clips, fasteners or pins.
- * Cross tees with override ends resist twisting and give a professionally finished appearance.
- * Finline offers a 1/4" (6 mm) reveal, Finline 1/8 a 1/8" (3 mm) reveal.
- * Choice of module sizes.
- * Cost savings from fast assembly.
- * Integrates with DONN air diffuser assemblies for a clean, uninterrupted ceiling plane.
- * Finline is available in fire-rated assemblies.
- * Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.

UA-USES, APPLICATIONS

FINELINE and Finline 1/8 for interior use only. See Ceiling Systems catalog SA-905 and DONN Suspension Systems catalog SA-904 for specific applications.

AI-ASSEMBLY, INSTALLATION

DONN FINELINE and Finline 1/8 are designed for use with Finline and Finline Bevel edge panels in exposed suspension. Level components and tie to structural members with hanger wire max. 48" (1200 mm) o.c. Install in accordance with ASTM C636 and manufacturer's instructions.

MF-MATERIALS, FINISHES

- * Material-
 - Double web intermediate- and heavy-duty steel.
- * Finishes-
 - Standard in Flat White, White with Black reveal and available in 24 standard colors.
 - Outside color of Black or Flat White with contrasting reveal of Red, Yellow, Royal Blue or Turquoise.
 - Call Customer Relations at 1-800-950-3839 for samples.

CS-COATINGS, SURFACING

Proven corrosion-resistant coating.

TS-TECHNICAL SUPPORT

Call Customer Relations at 1-800-950-3839.

CC-CODES, CERTIFICATION

ASTM C635.

OM-OPERATION, MAINTENANCE

Can be cleaned easily with a soft cloth.