

MR-MANUFACTURER - USG Interiors, Inc.

For specifications on this product, 1.) close this product Snapshot, 2.) click on the Manufacturer's Showcase button, 3.) select the screen, *Specification: ACOUSTONE Ceilings* from the drop-down Showcase list that appears in the upper right of your screen.

PP-PRODUCT PRESENTATION - DONN® DXW suspension grid

- * Maximum economy, design simplicity and access in an exposed grid system.
- * Plug-in positive-lock insertion for quick installation without tools.
- * High tensile steel connection clips on cross tee ends provide plug-in positive-lock insertion for quick installation.
- * Exceptional tension and compression connection values without additional wires, clips, fasteners or pins.
- * Cross tees with override ends resist twisting and give a professionally finished appearance.
- * Meets or exceeds all national code requirements, including seismic.
- * 1-1/2" (38 mm) wide exposed face.
- * Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.

UA-USES, APPLICATIONS

DXW for interior use only. See Ceiling Systems catalog SA-905 and DONN Suspension Systems catalog SA-904 for specific applications.

AI-ASSEMBLY, INSTALLATION

DXW grids are designed for use with Square edge panels in exposed suspension. Level components and tie to structural members with hanger wire max. 48" (1200 mm) o.c. Install in accordance with ASTM C636 and manufacturer's instructions.

MF-MATERIALS, FINISHES

- * Material-
 - Steel
- * Finishes-
 - Flat White
- Call Customer Relations at 1-800-950-3839 for a sample.

CS-COATINGS, SURFACING

Proven corrosion-resistant coating.

TS-TECHNICAL SUPPORT

Call Customer Relations at 1-800-950-3839.

CC-CODES, CERTIFICATION

ASTM C635.

OM-OPERATION, MAINTENANCE

Can be easily cleaned with a soft cloth.