#### MR-MANUFACTURER - USG Interiors, Inc.

For specifications on this product, 1.) close this product Snapshot, 2.) click on the Manufacturer's Showcase button, 3.) select the screen, *Specification: ACOUSTONE Ceilings* from the drop-down Showcase list that appears in the upper right of your screen.

# PP-PRODUCT PRESENTATION - DONN® CONCEALED DX® suspension grid

- \* Allows supporting grid to be completely concealed, resulting in a monolithic, uninterrupted ceiling plane.
- \* Can accommodate a variety of upward or downward access requirements.
- \* Light fixtures, air diffusers and plenum access points can be arranged with great flexibility.
- \* High tensile steel connection clips on cross tee ends provide plug-in positive-lock insertion for quick installation.
- \* Exceptional tension and compression connection values without additional wires, clips, fasteners or pins.
- \* Cross tees with override ends resist twisting and give a professionally finished appearance.
- \* Fire-rated assemblies are available.
- \* Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.

## **UA-USES, APPLICATIONS**

CONCEALED DX for interior use only. See Ceiling Systems catalog *SA-905* and DONN Suspension Systems catalog *SA-904* for specific applications.

## AI-ASSEMBLY, INSTALLATION

DONN CONCEALED DX grids are designed for use with Square and Bevel edge panels in concealed suspension. Level components and tie to structural members with hanger wire max. 48" (1200 mm) c.o. Install in accordance with ASTM C636 and manufacturer's instructions.

## **MF-MATERIALS, FINISHES**

- \* Materials-
- Double web steel tees and stabilizer bars.

#### **CS-COATINGS. SURFACING**

Proven corrosion-resistant coating.

## **TS-TECHNICAL SUPPORT**

Call Customer Relations at 1-800-950-3839.

## **CC-CODES, CERTIFICATION**

ASTM C635.

## **OM-OPERATION, MAINTENANCE**

Can be cleaned easily with a soft cloth.