

MR-MANUFACTURER - USG Interiors, Inc.

For specifications on this product, 1.) close this product Snapshot, 2.) click on the Manufacturer's Showcase button, 3.) select the screen, *Specification: ACOUSTONE Ceilings* from the drop-down Showcase list that appears in the upper right of your screen.

PP-PRODUCT PRESENTATION - DONN® RIGID X® suspension grid

- * Ideal for screw-attaching drywall to a direct hung suspension.
- * Combines the installation speed of grid and the durability of black iron furring channel systems into one unique system.
- * Accepts standard lay-in light fixtures and air diffusers.
- * Knurled face on furring cross channels and furring cross tees for faster screw installation.
- * Quickly installed with modular components.
- * Many fire-rated designs.
- * Metric sizes: All products are available in metric sizes. To specify, add "ME" before the standard item number.

UA-USES, APPLICATIONS

RIGID X for interior use only. See Ceiling Systems catalog *SA-905* and DONN Suspension Systems catalog *SA-904* for specific applications.

AI-ASSEMBLY, INSTALLATION

DONN RIGID X is designed for use with U.S. Gypsum Company SHEETROCK® brand Gypsum Panels in drywall suspension. Level components and tie to structural members with hanger wire max. 48" (1200 mm) o.c. Screw-attach drywall to components. Install in accordance with ASTM C636 and manufacturer's instructions.

MF-MATERIALS, FINISHES

- * Material-
- Direct-hung heavy-duty single web steel.

CS-COATINGS, SURFACING

Proven corrosion-resistant coating.

TS-TECHNICAL SUPPORT

Call Customer Relations at 1-800-950-3839.

CC-CODES, CERTIFICATION

ASTM C635.

OM-OPERATION, MAINTENANCE

Can be cleaned easily with a soft cloth.