

FairWeather™

Site Furnishings and Accessories

Urban Systems, Inc.

P.O. Box 487

Tacoma, WA 98401

Toll Free: (800) 323-1798

Tel: (206) 627-2811

Fax: (206) 627-2830

FairWeather™

For over fifteen years Urban Systems, Inc. has been manufacturing FairWeather site furnishings to meet the needs of our customers worldwide. We provide beauty, craftsmanship, and durability with our site furnishings. Whether you order from our standard product line or you have a custom project, you know it will be done with pride and attention to detail.

OLYMPIC SERIES, Model OL-1 (shown)

Backless bench finished with carefully matched wood plugs for the look of fine furniture.

OPTIONS:

LENGTH: 4 to 12 ft.

Special woods

Surface mount or embed

OL-1 H: 16-1/2" W: 21"

TRADITION SERIES

Featuring the timeless appeal of wood and cast iron. The TD-3 uses 1-1/2" x 2-1/2" wood elements while the TD-4 and TD-5 benches use 1-1/2" x 1-5/8" wood.

OPTIONS:

LENGTH: 4 to 8 ft.

Special woods

TD-3 H: 29-1/2" W: 20-1/2"

TD-4 & TD-5 H: 34-1/2" W: 28"

VILLAGE SERIES

Classic full slat design popular in "old town" settings.

OPTIONS:

LENGTH: 4 to 12 ft.

Special woods

Surface mount

V-2 H: 37" W: 31"

V-3 H: 37" W: 31"

TRASH RECEPTACLES, Model TR-1

Elegant, full slat receptacle with spun aluminum tops for either trash or ash urn use. It can be used with 30 gallon plastic bags.

OPTIONS:

Ash urn top

Trash-ash combination top
20 gallon liner
TR-1 H: 30" W: 21"
TR-1 H: 37" W: 21" (trash ash)

SPECIFICATIONS

METAL

All steel support straps, pipe, etc., shall be wheel abraded, drilled and formed for quick assembly. All steel shall conform to ASTM A36 hot rolled steel. Trash receptacle and planter top rims shall be spun steel. Dome tops shall be spun steel or galvanized steel. Cast end frames shall be ductile cast iron.

WOOD

Wood elements may be fabricated from any of the many available species. The woods most often specified and recommended for FairWeather furnishings are vertical grain Douglas Fir, clear heart Redwood and Red Oak. Red Oak is for interior use only. We also recommend Ipe or Purple Heart, hard woods that work well for either interior or exterior use.

PROTECTIVE COATINGS

WOOD

All wood elements for exterior use are to be treated with a clear wood preservative unless otherwise specified. Special stain colors are available as an option.

METAL

All metal elements, following fabrication shall be cleaned and treated with a five stage iron phosphate process prior to the coating application. This process shall include a non-chromated alkaline cleaner and an iron phosphate treatment followed with an acidic sealer for maximum adhesion.

The protective coatings shall be either polyester or TGIC powder. This material shall be applied by the dry electrostatic process. Following application, the metal parts shall be baked at 400° and maintained at that temperature until properly cured. The resultant coating shall be three to four mils thick on all surfaces.

WARRANTY

If any product fails due to defects in workmanship or materials within one year from date of delivery, we will repair or replace all parts found defective.