

## **Exposed Tee Systems – *Prelude 15/16"***

ECONOMICAL WITH LASTING PERFORMANCE

### **PRELUDE 15/16" SYSTEMS:**

### **PRELUDE XL, PRELUDE XL FIRE GUARD, PRELUDE FIRE GUARD**

#### **DESIGN VERSATILITY**

- 15/16" reveal
- White and colors to match Armstrong ceilings
- Metallic and aluminum finishes available
- Variety of cross tee heights and lengths to suit budget needs
- Hardened steel staked-on end detail provides secure connection and removability **(a)**
- Hanger wire holes every two inches on main runners and every eight to 12 inches on cross tees for easy installation **(b)**
- For environmentally demanding applications, see Prelude Plus options

#### **SAFETY**

- State-of-the-art prenotched expansion relief on Fire Guard options
- Seismic performance up to, and including, Zone 4
- ICBO Evaluation Report Numbers 3350 and 5173 (for XL grid)

#### **DURABILITY**

- Electrogalvanized zinc finish inhibits red rusting better than painted grid systems **(c)**
- Rotary-stitched XL cross tees for extra stability **(d)**
- Steel- or aluminum-capped intermediate- and heavy-duty steel

#### **AVOID HASSLES**

- Additional system load and light fixture load data available from TechLine 1 800 448-1405:
  - Prelude XL Submittal Sheet, CS-2384
  - Prelude XL Fire Guard Submittal Sheet, CS-2451
  - Prelude Fire Guard Submittal Sheet, CS-1792
  - Suspension System Colors Chart, CS-1565

#### **PHYSICAL DATA – FOR PRELUDE SYSTEMS**

**MATERIAL:** Double-web electrogalvanized steel

**FACE DIMENSION:** 15/16"

**PROFILE:** Exposed tee

**COLOR:** White, colors, metallics and aluminum finishes

**SURFACE FINISH:** Baked polyester paint or anodized

**FIRE RESISTANCE RATING:** Prelude Fire Guard is resistive when used in applicable UL fire resistive designs

**CROSS TEE/MAIN BEAM INTERFACE:** Override

**END DETAIL:** Prelude XL, Prelude XL Fire Guard: Staked-on end detail, Prelude Fire Guard: Stab-type end detail

**DUTY CLASSIFICATION:** Intermediate- or Heavy-duty

*See table on this screen.*

**SEISMIC PERFORMANCE:** Components available for use in Seismic Zones 0 (lowest) through 4 (highest).

In areas of ICBO jurisdiction, see ICBO Evaluation Report Number 5173 (for XL grid) or 3350 for allowable values and/or conditions of use concerning the suspension system components listed on this screen. The report is subject to reexamination, revisions and possible cancellation.

## **Exposed Tee Systems – *Suprafine 9/16"***

NARROW FACE GRID WITH REFINED LOOK

### **SUPRAFINE 9/16" SYSTEMS: SUPRAFINE XL, SUPRAFINE, SUPRAFINE FIRE GUARD**

#### **DESIGN VERSATILITY**

- 9/16" reveal
- For square-cut and beveled tegular ceiling panels
- Suited to a wide variety of modular configurations
- Colors, metallics, aluminum finishes
- Staked-on or stab-type end detail
- Removable and reusable cross tees
- Custom sizes, finishes and performance features

#### **SAFETY**

- Fire Guard options for UL Designs A202, D216, G229, G243, G244, G256, L210, P225, P251, P253
- Seismic performance up to, and including, Zone 4
- ICBO Evaluation Report Numbers 3350 and 5173 (for XL grid)

#### **DURABILITY**

- Rotary-stitched XL cross tees insure excellent handling and stability
- Steel-capped or aluminum-capped double-web intermediate-duty steel
- Electrogalvanized zinc finish resists rust more than painted systems

#### **AVOID HASSLES**

- Additional system load and light fixture load data available from TechLine 1 800 448-1405:
  - Suprafine XL Submittal Sheet, CS-2450
  - Suprafine Submittal Sheet, CS-1754
  - Suprafine Fire Guard Submittal Sheet, CS-2159
  - Suspension System Colors Chart, CS-1565

#### **PHYSICAL DATA – FOR SUPRAFINE SYSTEMS**

**MATERIAL:** Double-web electrogalvanized steel

**FACE DIMENSION:** 9/16"

**PROFILE:** Exposed tee

**COLOR:** Colors, metallics and aluminum finishes (Suprafine Fire Guard – colors only)

**SURFACE FINISH:** Baked polyester paint or anodized

**FIRE RESISTANCE RATING:** Suprafine Fire Guard is resistive when used in applicable fire resistive designs.

**CROSS TEE/MAIN BEAM INTERFACE:** Override

**END DETAIL:** Suprafine XL: Staked-on end detail Suprafine, Suprafine Fire Guard: Stab-type

end detail

**DUTY CLASSIFICATION:** Intermediate-duty

*See table on this screen.*

**SEISMIC PERFORMANCE:** Components available for use in Seismic Zones 0 (lowest) through 4 (highest).

In areas of ICBO jurisdiction, see ICBO Evaluation Report Number 5173 (for XL grid) or 3350 for allowable values and/or conditions of use concerning the suspension system components listed on this screen. The report is subject to reexamination, revisions and possible cancellation.

### **Armstrong Ceilings, Walls or Grid**

**TechLine: 1 800 448-1405**

**Fax: 717 396-6282**