

CONNECTION STRENGTH (SEISMIC)			
MAIN BEAMS	CROSS TEES	LBS. TO PULL OUT	
		COMPRESSION	TENSION
SUPRAFINE XL			
7500	-	390.7	340.6
7503	-	506.3	234.8
All Suprafine XL cross tees exceed 300 lbs. in both compression and tension.			
SUPRAFINE			
7500	-	390.7	340.6
7503	-	506.3	234.8
-	7510, 7530, 7540, 7550 7555, 7556, 7560, 7570 7590	325.3	305.7
-	7511, 7521, 7531, 7541 7557, 7558, 7559, 7561 7571, 7591	473.3	388.3
-	7520	202.5	168.7
SUPRAFINE FIRE GUARD			
8500		506.3	234.8
-	8520	325.3	305.7
-	8540	473.3	388.3
PRELUDE XL			
7300	-	375.0	329.0
7301	-	509.3	446.7
7302	-	375.0	329.0
PRELUDE XL FIRE GUARD			
8300	-	390.7	340.6
8301	-	509.3	446.7
All Prelude XL cross tees exceed 300 lbs. in both compression and tension.			
PRELUDE FIRE GUARD			
8300	-	390.7	340.6
8301	-	509.3	446.7
	8310, 8320, 8330, 8340 8355, 8357, 8358, 8360 8370, 8390	500+	291.0