

AMICO®

METAL LATH ACCESSORIES

ZINC CONTROL JOINTS

(N-380 – N-500 – N-750 – N-1000)

Flexible control joints for plaster membrane stress relief. Single “V” profile in 3/8", 1/2", 3/4" and 1" grounds with amply perforated solid wings for plaster keying square shoulders. Lips of “V” provide surface for removable tape strip to keep “V” clean during plastering. Made of zinc alloy for greater corrosion resistance and flexibility during expansion and contraction.

N-093 Drywall and Veneer Expansion Joint

Same as other “N” series but with a 0.093" ground for veneer coat plaster and drywall.

SMOOTHEDGE CORNALATH

An angle lath with smooth edges formed like regular Small Mesh Diamond Lath. Cornalath should always be used in corners where walls meet walls and walls meet ceiling. This reinforcing of interior corners helps to prevent cracks. Galvanized only.

X-1 CORNER BEAD

Standard accessory for providing exterior corner protection and providing a reliably straight ground for screeding. 3" expanded mesh wings are easily flexed to adapt to framing irregularities. Furnished in galvanized steel or zinc alloy.

X-2 CORNER BEAD

Similar to X-1 but with stiffening rib in 3-1/4" expanded wings for allowing greater compensation for “out-of-plumb” framing or base support surfaces. Provided in galvanized steel or zinc alloy.

Note: It is recommended that only zinc alloy or vinyl accessories be used for all exterior exposures.

Metal Lath Products Meet the following specifications:

- All paper meets Federal specification UU-B-790a.
- All Cornalath, Channel and Bead accessories meet specifications ASTM C841 and ASTM C1063.
- All wire products meet ASTM A641.
- Standard Metal Lath meets American Society for Testing and Materials – ASTM C847.

Alabama Metal Industries Corporation

3245 Fayette Avenue
Birmingham, AL 35208
205/787-2611
WATS: 800/366-2642
FAX: 205/780-3303