

PRODUCT NO.	DIMENSIONS	GROUND	PCS PER BOX
-------------	------------	--------	-------------

3" SOFFIT VENTS - 3-PIECE

3" WIDE VENT			
AMSV380-300	With removable	3/8"	15
AMSV500-300	V-300 vent.	1/2"	13
AMSV750-300	7-1/8" overall width,	3/4"	11
AMSV780-300	perforated flanges 10' LENGTHS	7/8"	10

SOFFIT SCREED

AMSVS300-500	4-3/4"	1/2"	15
AMSVS300-750	4-3/4"	3/4"	15
AMSVS300-780	4-3/4"	7/8"	13
10' LENGTHS			

FOUNDATION WEEP SCREED

AMFWSP-238-50 (punched)	2-3/8"	1/2"	60
AMFWS-425-50 (unpunched)	4-1/4"	1/2"	30
AMFWSP-238-75 (punched)	2-3/8"	3/4"	60
AMFWS-425-75 (unpunched)	4-1/4"	3/4"	30
AMFWSP-238-780 (punched)	2-3/8"	7/8"	60
AMFWS-425-780 (unpunched)	4-1/4"	7/8"	30
10' LENGTHS			

Note: Foundation Weep Screed is now required to be used at the bottom of all framed walls by ASTM C 1063 and U.B.C.

ROOF DRIP EDGE

AMRDE-200	1-7/8" 10' LENGTHS	-	100
-----------	-----------------------	---	-----

NOTE: AMICO recommends that you caulk all butt joints, intersections and ends.

NOTE: All Stucco and EIFS Products: ASTM C1063, C841, ASTM D1784

Cell Class 13244C and D4216 Cell Class 144234330100.

AMICO