

PRODUCT NO.	DIMENSIONS	GROUND	BOARD THICKNESS	PCS PER BOX
-------------	------------	--------	-----------------	-------------

STARTER STRIP (with drip edge) For 1/16" finish

Used to provide support or a shelf for foam board. Dispenses with the necessity to back wrap and finish the bottom edge of the board. The bottom leg and lip serve as a drip edge to funnel moisture away from the wall. Excellent adhesion of EIFS finishes and paint can be expected.

AMSS100-16	2" x 1" 10' LENGTHS	-	1"	40
------------	------------------------	---	----	----

STARTER CASING STRIP (no drip edge) For 1/16" finish

Same as above but without the drip edge. To be used at termination points where moisture is not expected to be a problem, such as wall intersections. Excellent adhesion of EIFS and paint can be expected.

AMSCS100-16	2" x 1" 10' LENGTHS	-	1"	40
-------------	------------------------	---	----	----

EIFS CORNER BEAD X-4

This product produces straight and durable corners while allowing for most thicknesses and also eliminate the need for time consuming rasping of corners.

AMX4	2-1/2" x 2-1/2" 10' LENGTHS	ANY	-	50
------	--------------------------------	-----	---	----

EXPANSION JOINT (Deep "V") with removable tape.

1/16" and 1/4" systems

The deep leg groove allows for more expansion and contraction than would be possible with 1/16" or 1/4" regular expansion joints. Excellent adhesion of EIFS and paint can be expected.

AMCJV160	2-1/4" WIDTH	-	1/16"	60
AMCJV250	10' LENGTHS		1/4"	35

ALL AMICO EIFS Products are manufactured with prime exterior grade PVC that meet ASTM D-4216 Cell Class 144234330100 and ASTM D 1784 Cell Class 13244C.

NOTE: AMICO recommends that you caulk all butt joints, intersections and ends.

NOTE: All Stucco and EIFS Products: ASTM C1063, C841, ASTM D1784

Cell Class 13244C and D4216 Cell Class 144234330100.

AMICO