Textures

G-P Gypsum Textures are compatible with G-P Gypsum Joint System products and are formulated to offer a variety of attractive finishes for walls and ceilings.

Finish Surface Preparation – For Best Results

If the final surface is to be textured, a quality vinyl primer should be applied and allowed to dry before texturing. This will minimize joint show-through.

G-P Wall Texture

G-P Gypsum Wall Texture is a non-aggregated compound formulated for either hand tool or spray application. When applied by hand, stipple, swirl or brocade appearance may be produced. When spray applied, a spatter or orange peel effect is formed. G-P Gypsum Wall Texture may be applied immediately following the wipedown of the ceiling overspray.

Coverage: Up to 1000 sq. ft. per 25 lbs. for spatter application; approximately 200 sq. ft. per 25 lbs. for other applications.

Available in 25 lb. bags.

G-P Ceiling Textures

G-P Gypsum Ceiling Texture products are formulated for spray application to gypsum board or concrete ceilings. Not recommended for high-moisture areas such as bathrooms. The finished appearance is dependent on the size and type of aggregate used. For best results use a primer before spraying the texture.

Vermiculite: There are 2 versions of vermiculite ceiling texture (medium and coarse) depending upon the surface effect desired. These textures are for spray application only.

Coverage: Varies from 300 to 400 sq. ft. per bag. Texture samples are available on request.

Available in 40 lb. bags.

Polystyrene - This is a relatively coarse finish white texture. It applies easily with good coverage and hiding properties. This product is for spray application only and is especially designed for large volume application where an economical high quality finish is desired.

Surface burning characteristics applied to gypsum and plaster board: Flame spread - 5, smoke developed - 0.

Coverage: 250 sq. ft. per bag.

Available in 32 lb. bags.

G-P Premixed Ceiling Texture

G-P Gypsum Premixed Ceiling Texture is designed for roll-on application to interior ceilings. It contains a medium perlite aggregate and provides a hard, white textured surface.

Coverage: 60 to 120 sq. ft. per 2 gallon pail.

Available in 2 gallon pails. (Available in most markets.)