

Rt. click on col. to freeze.	DIMENSIONS			EDGE						TESTING AGENCY			STANDARDS		
PRODUCT	LENGTH	WIDTH	THICKNESS	T	S	RE	B	T&G	DB	UL/ULC	TPI	CTC	ASTM	FEDERAL	CSA
GyProc® Gypsum Board															
Regular Gypsum Wall Board For interior walls and ceilings. Accommodates wide range of decorative treatments. Level of fire resistance and sound isolation depends on product thickness and assembly construction.	8' to 12' 8' to 12' 8' to 16'	4' 4' 4'	1/4" 3/8" 1/2"	• • •									C36	SS-L-30d Type III Grade R	A 82.27 M
5/8" Fireguard® Gypsum Board Type X Noncombustible gypsum core. Interior wall, floor and ceiling applications. Can be used in fire-rated assemblies. Meets basic Type X requirements.	8' to 16'	4'	5/8"	•	•	•	•			•			C 36 Type X	SS-L-30d Type III Grade X	A 82.27 M
Fireguard® C Gypsum Board Use as described above. Appropriate for commercial applications requiring extended fire endurance ratings.	8' to 16' 8' to 16'	4' 4'	1/2" 5/8"	• •	• •	• •	• •			• •			C 36 Type X	SS-L-30d Type III Grade X	A 82.27 M
Moisture-Guard® (Greenboard) Water-resistant gypsum core. Use as backing for ceramic, plastic or metal tile in tub, bathroom or shower areas. Not for continuous high moisture or wet areas.	8', 10', 12'	4'	1/2"	•									C 630	SS-L-30d Type VII Grade W	A 82.27 M
Fireguard® Moisture-Guard® Use as described above. Available in 1/2" and 5/8" fire-resistant type X core containing glass fibers.	8' to 12' 8' to 12'	4' 4'	1/2" 5/8"	• •						•			C 630 Type X	SS-L-30d Type VII Grade W, X	A 82.27 M
Fireguard® Backer Board (Special Order) Use as described above. Can be used in fire-rated assemblies.	8' std. 8' std.	4' 4'	1/2" 5/8"	• •						•			C 442	SS-L-30d Type IV Grade X	A 82.27 M
Fireguard® Shaft Liner™ Type X For use with metal stud shaftwall, stairwell or area separation systems. Type X fire-resistant core. Beveled edges facilitate fit into metal components.	8' to 14'	23-7/8"	1"						•		*		C 442	SS-L-30d Type IV Grade X	—
54" Wide Board For interior walls and ceilings. Accommodates wide range of decorative treatments. Level of fire resistance and sound isolation depends on product thickness and assembly construction.	4' 8" 4' 8" 8' to 16'	54" 54" 54"	1/4" 1/2" 5/8"	• • •		•							C 36	SS-L-30d Type III Grade R	A82.27 M
Specialty Products															
GyProc® CD® Ceiling Board Specially formulated core and paper ceiling board designed for water-based, textured ceiling applications. Sag resistant.	8' to 12'	4'	1/2"	•									C 36	SS-L-30d Type III Grade R	A 82.27 M
GyProc® PreDec® Designed to receive decorative finish by other manufacturers. For use in manufactured housing.	Cut-to-size	4'	5/16"		•					•	•		C 36	SS-L-30d Type III Grade R	A 82.27 M
GyProc® Exterior Soffit Board Noncombustible soffit board with treated paper face bonded to specially formulated core designed to resist sag and moisture. For exterior use such as outdoor building soffits, carports and outdoor applications where there is no direct exposure to weather.	8', 9', 10' 8', 9', 10'	4' 4'	1/2" 5/8"	• •									C 931		A 82.27 M
GyProc® Sound Deadening Gypsum Board Use with 1/2" or 5/8" GyProc® Fireguard® to meet requirements for sound and fire resistance. Noncombustible.	8'	4'	1/4"		•					•			C 442	SS-L-30d Type IV Grade R	A82.27 M
GyProc® Fire-Halt® Sealant A noncombustible fast setting compound to use as a firestop sealant for penetrations such as pipes, conduit and telephone cables in fire-resistive assemblies; as filler for the flutes and steel decks. 33.1 lbs. (30 lbs. fills approximately 1,000 inches) and 15 lbs. pails.										•			C 475		
Glass Mat Gypsum Boards															
DENS-SHIELD® Flooring Underlayment **	4'	4'	1/4"										C 1178	—	—
DENS-SHIELD® Tile Backer **	5', 8'	4' 32"	1/2"										C 1178	—	—
DENS-SHIELD® Fireguard® Type X **	8'	4'	5/8"									•	C 1178 Type X	—	—
DENS-DECK® Overlayment ***	8'	4'	1/4"							•	•		C 1177	—	—
DENS-DECK® Gypsum Roof Board ***	8'	4'	1/2"							•	•		C 1177	—	—
DENS-DECK® Fireguard® Type X ***	8'	4'	5/8"							•			C 1177 Type X	—	—
DENS-GLASS® GOLD Gypsum Sheathing ** ***	8', 9', 10'	4'	1/2"										C 1177	—	—
DENS-GLASS® GOLD 5/8" Fireguard® Type X ** ***	8', 9', 10'	4'	5/8"							•			C 1177 Type X	—	—
Sheathing															
GyProc Sheathing	8', 9" 8' std.	4' 2'	1/2" 1/2"										C 79	SS-L-30d Type II Grade W	A 82.27 M

Fireguard® 5/8" Type X Gypsum Sheathing - Treated Core	8' std.	4'	5/8"								•			C 79 Type X	SS-L-30d Grade W, X	A 82.27 M
DENS-GLASS® GOLD Gypsum Sheathing ** ***	8', 9', 10'	4'	1/2"											C 1177	NONE	N/A
DENS-GLASS® GOLD 5/8" Fireguard® Type X ** ***	8', 9', 10'	4'	5/8"								•			C 1177 Type X	NONE	N/A

Veneer Board														
Cameo® Plaster Base	8' to 12'	4'	1/2"									C 588	SS-L-30d Type VI Grade R	A 82.22 M
Fireguard® Cameo® Plaster Base	8' to 12'	4'	5/8"								•	C 588 Type X	SS-L-30d Type VI Grade X	A 82.27 M

T- Tapered Edge

S - Square Edge

RE - Tapered w/Round Edge

B - Modified Beveled Edge

T&G - Tongue and Groove Edge

DB - Double Beveled Edge

* Warnock Hersey

** 20-year limited warranty.

*** Six-month exposure warranty plus five-year limited warranty.